

Product Overview

06.06.2024 English EUR



BeyondHumanVision

All prices are Manufacturer's suggested retail prices, net, ex works. Information subject to change without notice.
HS = Harmonized System Code DG = Discount Group
MOBOTIX • 06.06.2024 • MOBOTIX accepts no liability arising from printing errors, mistakes and changes. • Revision 06.06.2024

MOBOTIX

Professional Video Systems Outdoor


BeyondHumanVision

MOBOTIX




M73A

MOBOTIX 7 Solution Platform

Weatherproof (IP66) Fixed Network Camera (Body) in two color variants, modular design with separately orderable optical 4K UHD image sensor modules (optimized for day, night or day & night use) and separately orderable function modules for easy insertion in the front panel (3 module openings, can be assigned as required), module connection via MOBOTIX sensor cables pre-positioned in the camera

	Article No. / Name / Description	EAN / HS / weight	dimen.
	<p>Mx-M73A-LSA</p> <p>M73 Body with LSA Connector Box (white)</p> <p>M73A IP camera module (body) for connecting up to three additional functional and optical sensor modules (to be ordered individually) • ONVIF-compliant MOBOTIX 7 system platform (Profile S, T) with H.264 (Triple Streaming), H.265, MxPEG+ and M-JPEG • Max. image size (per image sensor): 4K UHD (3840 x 2160 pixels), 16:9 • WDR: up to 120 dB • Functional extensions (via optional MOBOTIX modules): Audio (Microphone & Speaker), MultiSense (PIR, temperature, brightness sensor, Microphone), IR Light (supports 15°, 45°, 95° lenses), 1x miniUSB • Operating conditions: IP66/IK07, -40 to 65°C (-40 to 149 °F) • Internal DVR: 8 GB microSD (for MxPEG+ recordings) • Max. Power consumption: 25 W, supply via network cable, PoE Class 4 (IEEE 802.3af/at) • Connections: 1x LSA terminal for weatherproof network connection via laying cable (Ethernet 1000BaseT), 3x MOBOTIX module connection (optical/functional), I/O (1x input, 1x output), 1x line in, 1x line out, 1x miniUSB • Software interface for MOBOTIX Certified Apps (based on Deep Learning, approx. 20 different 30-day demo versions pre-installed) • Housing: Aluminium, PBT-30GF • Color: white • Warranty: 5 years (optionally extendable up to 8 years)</p>	<p>4047438036825</p> <p>85258900</p> <p>2.500 g</p>	<p>29,6 cm</p> <p>26,8 cm</p> <p>18,0 cm</p> <p>14,3 l</p>
	<p>Mx-M73A-RJ45</p> <p>M73 Body with RJ45 Connector Box (white)</p> <p>M73A IP camera module (body) for connecting up to three additional functional and optical sensor modules (to be ordered individually) • ONVIF-compliant MOBOTIX 7 system platform (Profile S, T) with H.264 (Triple Streaming), H.265, MxPEG+ and M-JPEG • Max. image size (per image sensor): 4K UHD (3840 x 2160 pixels), 16:9 • WDR: up to 120 dB • Functional extensions (via optional MOBOTIX modules): Audio (Microphone & Speaker), MultiSense (PIR, temperature, brightness sensor, Microphone), IR Light (supports 15°, 45°, 95° lenses), 1x miniUSB • Operating conditions: IP66/IK07, -40 to 65°C (-40 to 149 °F) • Internal DVR: 8 GB microSD (for MxPEG+ recordings) • Max. Power consumption: 25 W, supply via network cable, PoE Class 4 (IEEE 802.3af/at) • Connections: 1x RJ45 jack for weatherproof network connection via MOBOTIX patch cable (Ethernet 1000BaseT), 3x MOBOTIX module connection (optical/functional), I/O (1x input, 1x output), 1x line in, 1x line out, 1x miniUSB • Software interface for MOBOTIX Certified Apps (based on Deep Learning, approx. 20 different 30-day demo versions pre-installed) • Housing: Aluminium, PBT-30GF • Color: white • Warranty: 5 years (optionally extendable up to 8 years)</p>	<p>4047438034982</p> <p>85258900</p> <p>2.500 g</p>	<p>29,6 cm</p> <p>26,8 cm</p> <p>18,0 cm</p> <p>14,3 l</p>

ONE M1A Single IP Camera

	Article No. / Name / Description	EAN / HS / weight	dimen.
	<p>Mx-ONE-M1A-S-8DN040 M1A-S with 4K DN040 (Day/Night), 120°x60° M1A-Single IP camera equipped with one premium wide-angle lens B040 and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 120°x60° • Max. image size: 4K UHD (3840 x 2160 pixels), 16:9 • max. frame rate: 30 fps @ 4K • ONVIF-S-compliant (Profile G, S, T) MOBOTIX ONE system platform with H.264 (Triple Streaming), H.265, MxPEG+ and M-JPEG • WDR: up to 120dB, IR LEDs (up to 30m) • HD Audio with integrated microphone and speaker • Temperature sensor, MxActivitySensor, shock detector • Functional extensions (via optional MOBOTIX modules): 1x USB-C compatible with P7 extension boxes • Operating conditions: IP66/IK10, -40 to 65°C (-40 to 149 °F) • Internal DVR: 64 GB microSD (for MxPEG+ recordings) • Max. Power consumption: 12.95 W, supply via network cable, PoE Class 3 (IEEE 802.3af) or 12/24VDC external power supply • Connections: 1x RJ45 jack for weatherproof network connection via MOBOTIX patch cable (Ethernet 1000BaseT), I/O (1x input, 2x outputs), 1x audio out, 1x 12/24VDC input, 1x USB-C • Software interface for MOBOTIX Camera Apps (based on Deep Learning) • Housing: PBT-30GF • Color: white • Warranty: 5 years (optionally extendable up to 8 years)</p>	<p>4047438048446 85258900 1.500 g</p>	<p>29,6 cm 19,6 cm 18,0 cm 10,4 l</p>
	<p>Mx-ONE-M1A-S-8DN050 M1A-S with 4K DN050 (Day/Night), 95°x50° M1A-Single IP camera equipped with one premium wide-angle lens B050 and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 95°x50° • Max. image size: 4K UHD (3840 x 2160 pixels), 16:9 • max. frame rate: 30 fps @ 4K • ONVIF-S-compliant (Profile G, S, T) MOBOTIX ONE system platform with H.264 (Triple Streaming), H.265, MxPEG+ and M-JPEG • WDR: up to 120dB, IR LEDs (up to 30m) • HD Audio with integrated microphone and speaker • Temperature sensor, MxActivitySensor, shock detector • Functional extensions (via optional MOBOTIX modules): 1x USB-C compatible with P7 extension boxes • Operating conditions: IP66/IK10, -40 to 65°C (-40 to 149 °F) • Internal DVR: 64 GB microSD (for MxPEG+ recordings) • Max. Power consumption: 12.95 W, supply via network cable, PoE Class 3 (IEEE 802.3af) or 12/24VDC external power supply • Connections: 1x RJ45 jack for weatherproof network connection via MOBOTIX patch cable (Ethernet 1000BaseT), I/O (1x input, 2x outputs), 1x audio out, 1x 12/24VDC input, 1x USB-C • Software interface for MOBOTIX Camera Apps (based on Deep Learning) • Housing: PBT-30GF • Color: white • Warranty: 5 years (optionally extendable up to 8 years)</p>	<p>4047438048453 85258900 1.500 g</p>	<p>29,6 cm 19,6 cm 18,0 cm 10,4 l</p>
	<p>Mx-ONE-M1A-S-8DN080 M1A-S with 4K DN080 (Day/Night), 60°x33° M1A-Single IP camera equipped with one premium wide-angle lens B080 and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 60°x33° • Max. image size: 4K UHD (3840 x 2160 pixels), 16:9 • max. frame rate: 30 fps @ 4K • ONVIF-S-compliant (Profile G, S, T) MOBOTIX ONE system platform with H.264 (Triple Streaming), H.265, MxPEG+ and M-JPEG • WDR: up to 120dB, IR LEDs (up to 30m) • HD Audio with integrated microphone and speaker • Temperature sensor, MxActivitySensor, shock detector • Functional extensions (via optional MOBOTIX modules): 1x USB-C compatible with P7 extension boxes • Operating conditions: IP66/IK10, -40 to 65°C (-40 to 149 °F) • Internal DVR: 64 GB microSD (for MxPEG+ recordings) • Max. Power consumption: 12.95 W, supply via network cable, PoE Class 3 (IEEE 802.3af) or 12/24VDC external power supply • Connections: 1x RJ45 jack for weatherproof network connection via MOBOTIX patch cable (Ethernet 1000BaseT), I/O (1x input, 2x outputs), 1x audio out, 1x 12/24VDC input, 1x USB-C • Software interface for MOBOTIX Camera Apps (based on Deep Learning) • Housing: PBT-30GF • Color: white • Warranty: 5 years (optionally extendable up to 8 years)</p>	<p>4047438048460 85258900 1.500 g</p>	<p>29,6 cm 19,6 cm 18,0 cm 10,4 l</p>

**Mx-ONE-M1A-S-8DN100****M1A-S with 4K DN100 (Day/Night), 45°x25°**

M1A-Single IP camera equipped with one premium normal lens B100 and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 45°x25° • Max. image size: 4K UHD (3840 x 2160 pixels), 16:9 • max. frame rate: 30 fps @ 4K • ONVIF-S-compliant (Profile G, S, T) MOBOTIX ONE system platform with H.264 (Triple Streaming), H.265, MxPEG+ and M-JPEG • WDR: up to 120dB, IR LEDs (up to 30m) • HD Audio with integrated microphone and speaker • Temperature sensor, MxActivitySensor, shock detector • Functional extensions (via optional MOBOTIX modules): 1x USB-C compatible with P7 extension boxes • Operating conditions: IP66/IK10, -40 to 65°C (-40 to 149 °F) • Internal DVR: 64 GB microSD (for MxPEG+ recordings) • Max. Power consumption: 12.95 W, supply via network cable, PoE Class 3 (IEEE 802.3af) or 12/24VDC external power supply • Connections: 1x RJ45 jack for weatherproof network connection via MOBOTIX patch cable (Ethernet 1000BaseT), I/O (1x input, 2x outputs), 1x audio out, 1x 12/24VDC input, 1x USB-C • Software interface for MOBOTIX Camera Apps (based on Deep Learning) • Housing: PBT-30GF • Color: white • Warranty: 5 years (optionally extendable up to 8 years)

4047438048477 29,6 cm
85258900 19,6 cm
1.500 G 18,0 cm
10,4 l

**Mx-ONE-M1A-S-8DN150****M1A-S with 4K DN150 (Day/Night), 30°x17°**

M1A-Single IP camera equipped with one premium tele lens B150 and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 30°x17° • Max. image size: 4K UHD (3840 x 2160 pixels), 16:9 • max. frame rate: 30 fps @ 4K • ONVIF-S-compliant (Profile G, S, T) MOBOTIX ONE system platform with H.264 (Triple Streaming), H.265, MxPEG+ and M-JPEG • WDR: up to 120dB, IR LEDs (up to 30m) • HD Audio with integrated microphone and speaker • Temperature sensor, MxActivitySensor, shock detector • Functional extensions (via optional MOBOTIX modules): 1x USB-C compatible with P7 extension boxes • Operating conditions: IP66/IK10, -40 to 65°C (-40 to 149 °F) • Internal DVR: 64 GB microSD (for MxPEG+ recordings) • Max. Power consumption: 12.95 W, supply via network cable, PoE Class 3 (IEEE 802.3af) or 12/24VDC external power supply • Connections: 1x RJ45 jack for weatherproof network connection via MOBOTIX patch cable (Ethernet 1000BaseT), I/O (1x input, 2x outputs), 1x audio out, 1x 12/24VDC input, 1x USB-C • Software interface for MOBOTIX Camera Apps (based on Deep Learning) • Housing: PBT-30GF • Color: white • Warranty: 5 years (optionally extendable up to 8 years)

4047438048484 29,6 cm
85258900 19,6 cm
1.500 G 18,0 cm
10,4 l

**Mx-ONE-M1A-S-8DN280****M1A-S with 4K DN280 (Day/Night), 15°x8,5°**

M1A-Single IP camera equipped with one premium tele lens B280 and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 15°x8,5° • Max. image size: 4K UHD (3840 x 2160 pixels), 16:9 • max. frame rate: 30 fps @ 4K • ONVIF-S-compliant (Profile G, S, T) MOBOTIX ONE system platform with H.264 (Triple Streaming), H.265, MxPEG+ and M-JPEG • WDR: up to 120dB, IR LEDs (up to 30m) • HD Audio with integrated microphone and speaker • Temperature sensor, MxActivitySensor, shock detector • Functional extensions (via optional MOBOTIX modules): 1x USB-C compatible with P7 extension boxes • Operating conditions: IP66/IK10, -40 to 65°C (-40 to 149 °F) • Internal DVR: 64 GB microSD (for MxPEG+ recordings) • Max. Power consumption: 12.95 W, supply via network cable, PoE Class 3 (IEEE 802.3af) or 12/24VDC external power supply • Connections: 1x RJ45 jack for weatherproof network connection via MOBOTIX patch cable (Ethernet 1000BaseT), I/O (1x input, 2x outputs), 1x audio out, 1x 12/24VDC input, 1x USB-C • Software interface for MOBOTIX Camera Apps (based on Deep Learning) • Housing: PBT-30GF • Color: white • Warranty: 5 years (optionally extendable up to 8 years)

4047438048491 29,6 cm
85258900 19,6 cm
1.500 G 18,0 cm
10,4 l

**Mx-ONE-M1A-S-8DNTELE****M1A-S with 4K DN Tele Varifocal (Day/Night), 42° - 15°**

M1A-Single IP camera equipped with one premium motorized tele varifocal lens and IR cut filter for day and night use, aperture: f/1,7, image angle H: 42°-15°, V: 22,8°-8,4° • focal length: 11-29 mm • Max. image size: 4K UHD (3840 x 2160 pixels), 16:9 • max. frame rate: 30 fps @ 4K • ONVIF-S-compliant (Profile G, S, T) MOBOTIX ONE system platform with H.264 (Triple Streaming), H.265, MxPEG+ and M-JPEG • WDR: up to 120dB, IR LEDs (up to 30m) • HD Audio with integrated microphone and speaker • Temperature sensor, MxActivitySensor, shock detector • Functional extensions (via optional MOBOTIX modules): 1x USB-C compatible with P7 extension boxes • Operating conditions: IP66/IK10, -40 to 65°C (-40 to 149 °F) • Internal DVR: 64 GB microSD (for MxPEG+ recordings) • Max. Power consumption: 12.95 W, supply via network cable, PoE Class 3 (IEEE 802.3af) or 12/24VDC external power supply • Connections: 1x RJ45 jack for weatherproof network connection via MOBOTIX patch cable (Ethernet 1000BaseT), I/O (1x input, 2x outputs), 1x audio out, 1x 12/24VDC input, 1x USB-C • Software interface for MOBOTIX Camera Apps (based on Deep Learning) • Housing: PBT-30GF • Color: white • Warranty: 5 years (optionally extendable up to 8 years)

4047438048422 29,6 cm
85258900 19,6 cm
1.550 G 18,0 cm
10,4 l

**Mx-ONE-M1A-S-8DNWIDE****M1A-S with 4K DN Wide Varifocal (Day/Night), 112° - 47,5°**

M1A-Single IP camera equipped with one premium motorized wide varifocal lens and IR cut filter for day and night use, aperture: f/1.3, image angle H: 112°-47,5°, V:58°-26,6° • focal length: 4.3-9.3 mm • Max. image size: 4K UHD (3840 x 2160 pixels), 16:9 • max. frame rate: 30 fps @ 4K • ONVIF-S-compliant (Profile G, S, T) MOBOTIX ONE system platform with H.264 (Triple Streaming), H.265, MxPEG+ and M-JPEG • WDR: up to 120dB, IR LEDs (up to 30m) • HD Audio with integrated microphone and speaker • Temperature sensor, MxActivitySensor, shock detector • Functional extensions (via optional MOBOTIX modules): 1x USB-C compatible with P7 extension boxes • Operating conditions: IP66/IK10, -40 to 65°C (-40 to 149 °F) • Internal DVR: 64 GB microSD (for MxPEG+ recordings) • Max. Power consumption: 12.95 W, supply via network cable, PoE Class 3 (IEEE 802.3af) or 12/24VDC external power supply • Connections: 1x RJ45 jack for weatherproof network connection via MOBOTIX patch cable (Ethernet 1000BaseT), I/O (1x input, 2x outputs), 1x audio out, 1x 12/24VDC input, 1x USB-C • Software interface for MOBOTIX Camera Apps (based on Deep Learning) • Housing: PBT-30GF • Color: white • Warranty: 5 years (optionally extendable up to 8 years)

4047438048439 29,6 cm
85258900 19,6 cm
1.500 9 18,0 cm
10,4 l

**Mx-ONE-M1A-S-8N040****M1A-S with 4K Night sensor, 120°x60°**

M1A-Single IP camera equipped with one premium wide-angle lens B040 and B/W sensor for night use, aperture: f/1.8, max. image angle (HxV): 120°x60° • Max. image size: 4K UHD (3840 x 2160 pixels), 16:9 • max. frame rate: 30 fps @ 4K • ONVIF-S-compliant (Profile G, S, T) MOBOTIX ONE system platform with H.264 (Triple Streaming), H.265, MxPEG+ and M-JPEG • WDR: up to 120dB, IR LEDs (up to 30m) • HD Audio with integrated microphone and speaker • Temperature sensor, MxActivitySensor, shock detector • Functional extensions (via optional MOBOTIX modules): 1x USB-C compatible with P7 extension boxes • Operating conditions: IP66/IK10, -40 to 65°C (-40 to 149 °F) • Internal DVR: 64 GB microSD (for MxPEG+ recordings) • Max. Power consumption: 12.95 W, supply via network cable, PoE Class 3 (IEEE 802.3af) or 12/24VDC external power supply • Connections: 1x RJ45 jack for weatherproof network connection via MOBOTIX patch cable (Ethernet 1000BaseT), I/O (1x input, 2x outputs), 1x audio out, 1x 12/24VDC input, 1x USB-C • Software interface for MOBOTIX Camera Apps (based on Deep Learning) • Housing: PBT-30GF • Color: white • Warranty: 5 years (optionally extendable up to 8 years)

4047438048521 29,6 cm
85258900 19,6 cm
1.500 9 18,0 cm
10,4 l

**Mx-ONE-M1A-S-8N050****M1A-S with 4K Night sensor, 95°x50°**

M1A-Single IP camera equipped with one premium wide-angle lens B050 and B/W sensor for night use, aperture: f/1.8, max. image angle (HxV): 95°x50° • Max. image size: 4K UHD (3840 x 2160 pixels), 16:9 • max. frame rate: 30 fps @ 4K • ONVIF-S-compliant (Profile G, S, T) MOBOTIX ONE system platform with H.264 (Triple Streaming), H.265, MxPEG+ and M-JPEG • WDR: up to 120dB, IR LEDs (up to 30m) • HD Audio with integrated microphone and speaker • Temperature sensor, MxActivitySensor, shock detector • Functional extensions (via optional MOBOTIX modules): 1x USB-C compatible with P7 extension boxes • Operating conditions: IP66/IK10, -40 to 65°C (-40 to 149 °F) • Internal DVR: 64 GB microSD (for MxPEG+ recordings) • Max. Power consumption: 12.95 W, supply via network cable, PoE Class 3 (IEEE 802.3af) or 12/24VDC external power supply • Connections: 1x RJ45 jack for weatherproof network connection via MOBOTIX patch cable (Ethernet 1000BaseT), I/O (1x input, 2x outputs), 1x audio out, 1x 12/24VDC input, 1x USB-C • Software interface for MOBOTIX Camera Apps (based on Deep Learning) • Housing: PBT-30GF • Color: white • Warranty: 5 years (optionally extendable up to 8 years)

4047438048538 29,6 cm
85258900 19,6 cm
1.500 9 18,0 cm
10,4 l

**Mx-ONE-M1A-S-8N080****M1A-S with 4K Night sensor, 60°x33°**

M1A-Single IP camera equipped with one premium wide-angle lens B080 and B/W sensor for night use, aperture: f/1.8, max. image angle (HxV): 60°x33° • Max. image size: 4K UHD (3840 x 2160 pixels), 16:9 • max. frame rate: 30 fps @ 4K • ONVIF-S-compliant (Profile G, S, T) MOBOTIX ONE system platform with H.264 (Triple Streaming), H.265, MxPEG+ and M-JPEG • WDR: up to 120dB, IR LEDs (up to 30m) • HD Audio with integrated microphone and speaker • Temperature sensor, MxActivitySensor, shock detector • Functional extensions (via optional MOBOTIX modules): 1x USB-C compatible with P7 extension boxes • Operating conditions: IP66/IK10, -40 to 65°C (-40 to 149 °F) • Internal DVR: 64 GB microSD (for MxPEG+ recordings) • Max. Power consumption: 12.95 W, supply via network cable, PoE Class 3 (IEEE 802.3af) or 12/24VDC external power supply • Connections: 1x RJ45 jack for weatherproof network connection via MOBOTIX patch cable (Ethernet 1000BaseT), I/O (1x input, 2x outputs), 1x audio out, 1x 12/24VDC input, 1x USB-C • Software interface for MOBOTIX Camera Apps (based on Deep Learning) • Housing: PBT-30GF • Color: white • Warranty: 5 years (optionally extendable up to 8 years)

4047438048545 29,6 cm
85258900 19,6 cm
1.500 9 18,0 cm
10,4 l

**Mx-ONE-M1A-S-8N100****M1A-S with 4K Night sensor, 45°x25°**

M1A-Single IP camera equipped with one premium normal lens B100 and B/W sensor for night use, aperture: f/1.8, max. image angle (HxV): 45°x25° • Max. image size: 4K UHD (3840 x 2160 pixels), 16:9 • max. frame rate: 30 fps @ 4K • ONVIF-S-compliant (Profile G, S, T) MOBOTIX ONE system platform with H.264 (Triple Streaming), H.265, MxPEG+ and M-JPEG • WDR: up to 120dB, IR LEDs (up to 30m) • HD Audio with integrated microphone and speaker • Temperature sensor, MxActivitySensor, shock detector • Functional extensions (via optional MOBOTIX modules): 1x USB-C compatible with P7 extension boxes • Operating conditions: IP66/IK10, -40 to 65°C (-40 to 149 °F) • Internal DVR: 64 GB microSD (for MxPEG+ recordings) • Max. Power consumption: 12.95 W, supply via network cable, PoE Class 3 (IEEE 802.3af) or 12/24VDC external power supply • Connections: 1x RJ45 jack for weatherproof network connection via MOBOTIX patch cable (Ethernet 1000BaseT), I/O (1x input, 2x outputs), 1x Audio Out, 1x 12/24VDC input, 1x USB-C • Software interface for MOBOTIX Camera Apps (based on Deep Learning) • Housing: PBT-30GF • Color: white • Warranty: 5 years (optionally extendable up to 8 years)

4047438048552	29,6 cm
85258900	19,6 cm
1.500 9	18,0 cm
	10,4 l

**Mx-ONE-M1A-S-8N150****M1A-S with 4K Night sensor, 30°x17°**

M1A-Single IP camera equipped with one premium tele lens B150 and B/W sensor for night use, aperture: f/1.8, max. image angle (HxV): 30°x17° • Max. image size: 4K UHD (3840 x 2160 pixels), 16:9 • max. frame rate: 30 fps @ 4K • ONVIF-S-compliant (Profile G, S, T) MOBOTIX ONE system platform with H.264 (Triple Streaming), H.265, MxPEG+ and M-JPEG • WDR: up to 120dB, IR LEDs (up to 30m) • HD Audio with integrated microphone and speaker • Temperature sensor, MxActivitySensor, shock detector • Functional extensions (via optional MOBOTIX modules): 1x USB-C compatible with P7 extension boxes • Operating conditions: IP66/IK10, -40 to 65°C (-40 to 149 °F) • Internal DVR: 64 GB microSD (for MxPEG+ recordings) • Max. Power consumption: 12.95 W, supply via network cable, PoE Class 3 (IEEE 802.3af) or 12/24VDC external power supply • Connections: 1x RJ45 jack for weatherproof network connection via MOBOTIX patch cable (Ethernet 1000BaseT), I/O (1x input, 2x outputs), 1x mic In, 1x audio out, 1x 12/24VDC input, 1x USB-C • Software interface for MOBOTIX Camera Apps (based on Deep Learning) • Housing: Aluminium, PBT-30GF • Color: white • Warranty: 5 years (optionally extendable up to 8 years)






4047438048569	29,6 cm
85258900	19,6 cm
1.500 9	18,0 cm
	10,4 l

**Mx-ONE-M1A-S-8N280****M1A-S with 4K Night sensor, 15°x8,5°**

M1A-Single IP camera equipped with one premium tele lens B280 and B/W sensor for night use, aperture: f/1.8, max. image angle (HxV): 15°x8,5° • Max. image size: 4K UHD (3840 x 2160 pixels), 16:9 • max. frame rate: 30 fps @ 4K • ONVIF-S-compliant (Profile G, S, T) MOBOTIX ONE system platform with H.264 (Triple Streaming), H.265, MxPEG+ and M-JPEG • WDR: up to 120dB, IR LEDs (up to 30m) • HD Audio with integrated microphone and speaker • Temperature sensor, MxActivitySensor, shock detector • Functional extensions (via optional MOBOTIX modules): 1x USB-C compatible with P7 extension boxes • Operating conditions: IP66/IK10, -40 to 65°C (-40 to 149 °F) • Internal DVR: 64 GB microSD (for MxPEG+ recordings) • Max. Power consumption: 12.95 W, supply via network cable, PoE Class 3 (IEEE 802.3af) or 12/24VDC external power supply • Connections: 1x RJ45 jack for weatherproof network connection via MOBOTIX patch cable (Ethernet 1000BaseT), I/O (1x input, 2x outputs), 1x audio out, 1x 12/24VDC input, 1x USB-C • Software interface for MOBOTIX Camera Apps (based on Deep Learning) • Housing: PBT-30GF • Color: white • Warranty: 5 years (optionally extendable up to 8 years)

4047438048576	29,6 cm
85258900	19,6 cm
1.500 9	18,0 cm
	10,4 l

D71 Dome Camera

	Article No. / Name / Description	EAN / HS / weight	dimen.
	Mx-D71A-4DN050	4047438039741	19,6 cm
	D71 Complete Camera 4MP Ultra LowLight DN050 (Day)	85258900	18,0 cm
	D71 4MP camera with premium wide-angle lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 95°x50°, max. resolution: 4MP Ultra LowLight Sensor (2688x1512) • Integrated IR LED illuminators • WDR: Wide Dynamic Range 120 dB - Day and night sensors • 3-axis mechanical pan/tilt head • IP66 • IK10 • Operating temperature range: -40 to +65 °C - Built-in speaker and microphone • Line In & Out • Input & Output • USB-C • 8GB memory card included	1.180 g	14,8 cm
			5,2 l
	Mx-D71A-4DN080	4047438039758	19,6 cm
	D71 Complete Camera 4MP Ultra LowLight DN080 (Day)	85258900	18,0 cm
	D71 4MP camera with premium wide-angle lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 60°x33°, max. resolution: 4MP Ultra LowLight Sensor (2688x1512) • Integrated IR LED illuminators • WDR: Wide Dynamic Range 120 dB - Day and night sensors • 3-axis mechanical pan/tilt head • IP66 • IK10 • Operating temperature range: -40 to +65 °C - Built-in speaker and microphone • Line In & Out • Input & Output • USB-C • 8GB memory card included	1.180 g	14,8 cm
			5,2 l
	Mx-D71A-4DN100	4047438039765	19,6 cm
	D71 Complete Camera 4MP Ultra LowLight DN100 (Day)	85258900	18,0 cm
	D71 4MP camera with premium wide-angle lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 45°x25°, max. resolution: 4MP Ultra LowLight Sensor (2688x1512) • Integrated IR LED illuminators • WDR: Wide Dynamic Range 120 dB - Day and night sensors • 3-axis mechanical pan/tilt head • IP66 • IK10 • Operating temperature range: -40 to +65 °C - Built-in speaker and microphone • Line In & Out • Input & Output • USB-C • 8GB memory card included	1.180 g	14,8 cm
			5,2 l
	Mx-D71A-4DN150	4047438039772	19,6 cm
	D71 Complete Camera 4MP Ultra LowLight DN150 (Day)	85258900	18,0 cm
	D71 4MP camera with premium wide-angle lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 30°x17°, max. resolution: 4MP Ultra LowLight Sensor (2688x1512) • Integrated IR LED illuminators • WDR: Wide Dynamic Range 120 dB - Day and night sensors • 3-axis mechanical pan/tilt head • IP66 • IK10 • Operating temperature range: -40 to +65 °C - Built-in speaker and microphone • Line In & Out • Input & Output • USB-C • 8GB memory card included	1.180 g	14,8 cm
			5,2 l
	Mx-D71A-4DN280	4047438039789	19,6 cm
	D71 Complete Camera 4MP Ultra LowLight DN280 (Day)	85258900	18,0 cm
	D71 4MP camera with premium wide-angle lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 15°x8,5°, max. resolution: 4MP Ultra LowLight Sensor (2688x1512) • Integrated IR LED illuminators • WDR: Wide Dynamic Range 120 dB - Day and night sensors • 3-axis mechanical pan/tilt head • IP66 • IK10 • Operating temperature range: -40 to +65 °C - Built-in speaker and microphone • Line In & Out • Input & Output • USB-C • 8GB memory card included	1.180 g	14,8 cm
			5,2 l

**Mx-D71A-8DN050****D71 Complete Camera 4K DN050 (Day(Night), 95°x50°)**

D71 4K camera with premium wide-angle lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 95°x50°, max. resolution: 4K UHD (3840x2160) • Integrated IR LED illuminators • WDR: Wide Dynamic Range 120 dB - Day and night sensors • 3-axis mechanical pan/tilt head • IP66 • IK10 • Operating temperature range: -40 to +65 °C - Built-in speaker and microphone • Line In & Out • Input & Output • USB-C • 8GB memory card included

4047438039697	19,6 cm
85258900	18,0 cm
1.180 9	14,8 cm
	5,2 l

**Mx-D71A-8DN080****D71 Complete Camera 4K DN080 (Day(Night), 60°x33°)**

D71 4K camera with premium wide-angle lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 60°x33°, max. resolution: 4K UHD (3840x2160) • Integrated IR LED illuminators • WDR: Wide Dynamic Range 120 dB - Day and night sensors • 3-axis mechanical pan/tilt head • IP66 • IK10 • Operating temperature range: -40 to +65 °C - Built-in speaker and microphone • Line In & Out • Input & Output • USB-C • 8GB memory card included

4047438039703	19,6 cm
85258900	18,0 cm
1.180 9	14,8 cm
	5,2 l

**Mx-D71A-8DN100****D71 Complete Camera 4K DN100 (Day(Night), 45°x25°)**

D71 4K camera with premium wide-angle lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 45°x25°, max. resolution: 4K UHD (3840x2160) • Integrated IR LED illuminators • WDR: Wide Dynamic Range 120 dB - Day and night sensors • 3-axis mechanical pan/tilt head • IP66 • IK10 • Operating temperature range: -40 to +65 °C - Built-in speaker and microphone • Line In & Out • Input & Output • USB-C • 8GB memory card included

4047438039710	19,6 cm
85258900	18,0 cm
1.180 9	14,8 cm
	5,2 l

**Mx-D71A-8DN150****D71 Complete Camera 4K DN150 (Day(Night), 30°x17°)**

D71 4K camera with premium wide-angle lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 30°x17°, max. resolution: 4K UHD (3840x2160) • Integrated IR LED illuminators • WDR: Wide Dynamic Range 120 dB - Day and night sensors • 3-axis mechanical pan/tilt head • IP66 • IK10 • Operating temperature range: -40 to +65 °C - Built-in speaker and microphone • Line In & Out • Input & Output • USB-C • 8GB memory card included


4047438039727	19,6 cm
85258900	18,0 cm
1.180 9	14,8 cm
	5,2 l

**Mx-D71A-8DN280****D71 Complete Camera 4K DN280 (Day(Night), 15°x8,5°)**

D71 4K camera with premium wide-angle lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 15°x8,5°, max. resolution: 4K UHD (3840x2160) • Integrated IR LED illuminators • WDR: Wide Dynamic Range 120 dB - Day and night sensors • 3-axis mechanical pan/tilt head • IP66 • IK10 • Operating temperature range: -40 to +65 °C - Built-in speaker and microphone • Line In & Out • Input & Output • USB-C • 8GB memory card included

4047438039734	19,6 cm
85258900	18,0 cm
1.180 9	14,8 cm
	5,2 l

Q71A Hemispheric Camera

	Article No. / Name / Description	EAN / HS / weight	dimen.
	Mx-Q71A-12DN016	4047438039796	19,6 cm
	Q71 Complete Camera 12MP, DN016 (Day/Night), 360°	85258900	18,0 cm
	Q71 camera with Hemispheric lens and IR cut filter for day and night use • f/1.8 •	1.050 g	14,8 cm
	12MP image sensor • 4K effective resolution: 2880x2880 (hemispheric original image) • Max. Frame rate (4K): 20 fps@MxPEG, 30 fps@H.264/H.265 • Integrated IR and white light LED illuminator • WDR: Wide Dynamic Range 120 dB • Combined day/night sensor with IR cut filter • IP66 • IK10 except on the lens • Operating temperature range: -40 to +65 °C • Built-in speaker and microphone - Line In & Out - Input & Output • USB-C • 8GB memory card included		5,2 l

M16B AllroundDual Camera „Mx6B“

Second Mx6 generation – with MxBus functionality and enhanced performance.

	Article No. / Name / Description	EAN / HS / weight	dimen.
	Mx-M16B M16B Body, For M16 Sensor Modules (Day/Night) M16 camera module for connecting one or two M16/M15 sensor modules (to be ordered individually) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Image sensor options (via sensor module): 5 or 6 megapixels, color (day) and/or B/W (night) • Lens options (via sensor module): horizontal image angle from 180° to 8° • Max. image size (per image sensor): 6MP (3072 x 2048 pixels) • Operating conditions: IP66/IK07, -40 to 60°C (-40 to 140°F) • Internal DVR: 4 GB microSD • System components: speaker and microphone (inside housing), PIR sensor, temperature sensor, MxActivitySensor, shock detector • VarioFlex wall mount (can be used with additional ceiling mount MX-DH-M24-SecureFlex and pole mount MX-MH-SecureFlex-ESWS), ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; IO and RS232 via additional MX Interface Box • Incl. 1 Blind Module (MX-SM-Blind-PW)	4047438030915 85258900 1.764 g	29,6 cm 19,6 cm 18,0 cm 10,4 l
	Mx-M16B-6D6N036 M16B Complete Cam 6MP, 2x B036 (Day & Night) IP camera set with two installed sensor modules • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Image sensors (via sensor module): 1/1.8" CMOS, 6 megapixels, 1x day and 1x night • HD premium lenses (via sensor module): 2x B036 ultra wide-angle (f/1.8, horizontal image angle 103°) • Max. image size (per image sensor): 6MP (3072 x 2048 pixels) • IP66/IK07, -40 to 60°C (-40 to 140°F) • Internal DVR: 4 GB microSD • Camera components: speaker and microphone (inside housing), PIR sensor, temperature sensor, MxActivitySensor, shock detector • VarioFlex wall mount (can be used with additional ceiling mount MX-DH-M24-SecureFlex and pole mount MX-MH-SecureFlex-ESWS), ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; IO and RS232 via additional MX Interface Box	4047438030922 85258900 1.981 g	29,6 cm 19,6 cm 18,0 cm 10,4 l
	Mx-M16B-6D6N041 M16B Complete Cam 6MP, 2x B041 (Day & Night) IP camera set with two installed sensor modules • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Image sensors (via sensor module): 1/1.8" CMOS, 6 megapixels, 1x day and 1x night • HD premium lenses (via sensor module): 2x B041 super wide-angle (f/1.8, horizontal image angle 90°) • Max. image size (per image sensor): 6MP (3072 x 2048 pixels) • IP66/IK07, -40 to 60°C (-40 to 140°F) • Internal DVR: 4 GB microSD • Camera components: speaker and microphone (inside housing), PIR sensor, temperature sensor, MxActivitySensor, shock detector • VarioFlex wall mount (can be used with additional ceiling mount MX-DH-M24-SecureFlex and pole mount MX-MH-SecureFlex-ESWS), ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; IO and RS232 via additional MX Interface Box	4047438030939 85258900 1.974 g	29,6 cm 19,6 cm 18,0 cm 10,4 l
	Mx-M16B-6D6N061 M16B Complete Cam 6MP, 2x B061 (Day & Night) IP camera set with two installed sensor modules • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Image sensors (via sensor module): 1/1.8" CMOS, 6 megapixels, 1x day and 1x night • HD premium lenses (via sensor module): 2x B061 wide-angle (f/1.8, horizontal image angle 60°) • Max. image size (per image sensor): 6MP (3072 x 2048 pixels) • IP66/IK07, -40 to 60°C (-40 to 140°F) • Internal DVR: 4 GB microSD • Camera components: speaker and microphone (inside housing), PIR sensor, temperature sensor, MxActivitySensor, shock detector • VarioFlex wall mount (can be used with additional ceiling mount MX-DH-M24-SecureFlex and pole mount MX-MH-SecureFlex-ESWS), ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; IO and RS232 via additional MX Interface Box	4047438030946 85258900 1.980 g	29,6 cm 19,6 cm 18,0 cm 10,4 l

**Mx-M16B-6D6N079****M16B Complete Cam 6MP, 2x B079 (Day & Night)**

IP camera set with two installed sensor modules • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Image sensors (via sensor module): 1/1.8" CMOS, 6 megapixels, 1x day and 1x night • HD premium lenses (via sensor module): 2x B079 standard (f/1.8, horizontal image angle 45°) • Max. image size (per image sensor): 6MP (3072 x 2048 pixels) • IP66/IK07, -40 to 60°C (-40 to 140°F) • Internal DVR: 4 GB microSD • Camera components: speaker and microphone (inside housing), PIR sensor, temperature sensor, MxActivitySensor, shock detector • VarioFlex wall mount (can be used with additional ceiling mount MX-DH-M24-SecureFlex and pole mount MX-MH-SecureFlex-ESWS), ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; IO and RS232 via additional MX Interface Box

4047438030953	29,6 cm
85258900	19,6 cm
1.971 9	18,0 cm
	10,4 l

**Mx-M16B-6D6N119****M16B Complete Cam 6MP, 2x B119 (Day & Night)**

IP camera set with two installed sensor modules • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Image sensors (via sensor module): 1/1.8" CMOS, 6 megapixels, 1x day and 1x night • HD premium lenses (via sensor module): 2x B119 tele (f/1.8, horizontal image angle 31°) • Max. image size (per image sensor): 6MP (3072 x 2048 pixels) • IP66/IK07, -40 to 60°C (-40 to 140°F) • Internal DVR: 4 GB microSD • Camera components: speaker and microphone (inside housing), PIR sensor, temperature sensor, MxActivitySensor, shock detector • VarioFlex wall mount (can be used with additional ceiling mount MX-DH-M24-SecureFlex and pole mount MX-MH-SecureFlex-ESWS), ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; IO and RS232 via additional MX Interface Box

4047438030960	29,6 cm
85258900	19,6 cm
1.970 9	18,0 cm
	10,4 l






**Mx-M16B-6D6N237****M16B Complete Cam 6MP, 2x B237 (Day & Night)**

IP camera set with two installed sensor modules • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Image sensors (via sensor module): 1/1.8" CMOS, 6 megapixels, 1x day and 1x night • HD premium lenses (via sensor module): 2x B237 distant tele (f/1.8, horizontal image angle 15°) • Max. image size (per image sensor): 6MP (3072 x 2048 pixels) • IP66/IK07, -40 to 60°C (-40 to 140°F) • Internal DVR: 4 GB microSD • Camera components: speaker and microphone (inside housing), PIR sensor, temperature sensor, MxActivitySensor, shock detector • VarioFlex wall mount (can be used with additional ceiling mount MX-DH-M24-SecureFlex and pole mount MX-MH-SecureFlex-ESWS), ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; IO and RS232 via additional MX Interface Box

4047438030977	29,6 cm
85258900	19,6 cm
1.981 9	18,0 cm
	10,4 l

D16B DualDome Camera „Mx6B“

Second Mx6 generation – with MxBus functionality and enhanced performance.

	Article No. / Name / Description	EAN / HS / weight	dimen.
	Mx-D16B D16B Body, For D16B/D15 Sensor Modules (Day/Night) IP camera module for connecting one or two D16/D15 sensor modules or a D16/D15 lens bridge FIX/PAN (to be ordered individually) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Image sensor options (via sensor module/bridge): 6 megapixels, color (day) and/or B/W (night) • Lens options (via lens unit): horizontal image angle from 103° to 31° • Max. image size (per image sensor): 6MP (3072 x 2048 pixels) • Operating conditions: IP54 without accessories, IP65/IK10 with Outdoor Wall Mount or IP66/IK10+ with Vandalism Set, each -40 to 60°C (-40 to 140°F) • Internal DVR: 4 GB MicroSD • Camera components: speaker, microphone, PIR sensor, temperature sensor, MxActivitySensor, shock detector • Ethernet patch cable 0.5 m/1.65 ft • Incl. 1x standard lens cover • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; IO and RS232 via additional MX Interface Box	4047438030588 85258900 1.277 g	39,5 cm 29,6 cm 9,0 cm 10,5 l
		Mx-D16B-F-6D6N036 D16B Complete Cam 6MP, 2x B036 (Day & Night) IP camera with two parallel aligned lenses • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 6 megapixel Moonlight sensors, 1x day and 1x night • HD premium lenses: 2x B036 ultra wide-angle (f/1.8, horizontal image angle 103°) • Max. image size (per image sensor): 6MP (3072 x 2048 pixels) • IP54 without accessories, IP65/IK10 with Outdoor Wall Mount or IP66/IK10+ with Vandalism Set, each -40 to 60°C (-40 to 140°F) • Internal DVR: 4 GB MicroSD • Camera components: speaker, PIR sensor, temperature sensor, MxActivitySensor, shock detector • Ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; IO and RS232 via additional MX-232-IO-Box	4047438030595 85258900 1.646 g
	Mx-D16B-F-6D6N041 D16B Complete Cam 6MP, 2x B041 (Day & Night) IP camera with two parallel aligned lenses • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 6 megapixel Moonlight sensors, 1x day and 1x night • HD premium lenses: 2x B041 super wide-angle (f/1.8, horizontal image angle 90°) • Max. image size (per image sensor): 6MP (3072 x 2048 pixels) • IP54 without accessories, IP65/IK10 with Outdoor Wall Mount or IP66/IK10+ with Vandalism Set, each -40 to 60°C (-40 to 140°F) • Internal DVR: 4 GB MicroSD • Camera components: speaker, PIR sensor, temperature sensor, MxActivitySensor, shock detector • Ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; IO and RS232 via additional MX-232-IO-Box	4047438030601 85258900 1.627 g	39,5 cm 29,6 cm 18,0 cm 21,0 l
	Mx-D16B-F-6D6N061 D16B Complete Cam 6MP, 2x B061 (Day & Night) IP camera with two parallel aligned lenses • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 6 megapixel Moonlight sensors, 1x day and 1x night • HD premium lenses: 2x B061 wide-angle (f/1.8, horizontal image angle 60°) • Max. image size (per image sensor): 6MP (3072 x 2048 pixels) • IP54 without accessories, IP65/IK10 with Outdoor Wall Mount or IP66/IK10+ with Vandalism Set, each -40 to 60°C (-40 to 140°F) • Internal DVR: 4 GB MicroSD • Camera components: speaker, PIR sensor, temperature sensor, MxActivitySensor, shock detector • Ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; IO and RS232 via additional MX-232-IO-Box	4047438030618 85258900 1.642 g	39,5 cm 29,6 cm 18,0 cm 21,0 l
	Mx-D16B-F-6D6N079 D16B Complete Cam 6MP, 2x B079 (Day & Night) IP camera with two parallel aligned lenses • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 6 megapixel Moonlight sensors, 1x day and 1x night • HD premium lenses: 2x B079 wide-angle (f/1.8, horizontal image angle 45°) • Max. image size (per image sensor): 6MP (3072 x 2048 pixels) • IP54 without accessories, IP65/IK10 with Outdoor Wall Mount or IP66/IK10+ with Vandalism Set, each -40 to 60°C (-40 to 140°F) • Internal DVR: 4 GB MicroSD • Camera components: speaker, PIR sensor, temperature sensor, MxActivitySensor, shock detector • Ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; IO and RS232 via additional MX-232-IO-Box	4047438030625 85258900 1.645 g	39,5 cm 29,6 cm 18,0 cm 21,0 l

**Mx-D16B-F-6D6N119****D16B Complete Cam 6MP, 2x B119 (Day & Night)**

IP camera with two parallel aligned lenses • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 6 megapixel Moonlight sensors, 1x day and 1x night • HD premium lenses: 2x B119 tele (f/1.8, horizontal image angle 31°) • Max. image size (per image sensor): 6MP (3072 x 2048 pixels) • IP54 without accessories, IP65/IK10 with Outdoor Wall Mount or IP66/IK10+ with Vandalism Set, each -40 to 60°C (-40 to 140°F) • Internal DVR: 4 GB MicroSD • Camera components: speaker, PIR sensor, temperature sensor, MxActivitySensor, shock detector • Ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; IO and RS232 via additional MX-232-IO-Box

4047438030632	39,5 cm
85258900	29,6 cm
1.630 ₧	18,0 cm
	21,0 l

**Mx-D16B-P-6D6D041****D16B Complete Cam 2x 6MP, Panorama 180° (Day)**

IP camera with PAN lens bridge • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 2 Moonlight sensors day, 6MP (3072 x 2048) • HD premium lenses: 2x B041 super wide-angle (horiz. image angle 180°) • Max. image size: 2x 6MP (6144 x 2048 Pixel) • IP54 without accessories, IP65/IK10 with Outdoor Wall Mount, IP66/IK10+ with Vandalism Set, each -40 bis 60 °C (-40 to 140°F) • Internal DVR: 4 GB microSD • Speaker, microphone, PIR sensor, temperature sensor, MxActivitySensor, shock detector • Ethernet patch cable 0,5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via Interface Box (MOBOTIX accessory)

4047438030656	39,5 cm
85258900	29,6 cm
1.650 ₧	18,0 cm
	21,0 l






**Mx-D16B-P-6N6N041****D16B Complete Cam 2x 6MP, Panorama 180° (Night)**

IP camera with PAN sensor bridge • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 2 Moonlight sensors night, 6MP (3072 x 2048) • HD premium lenses: 2x B041 super wide-angle (horiz. image angle 180°) • Max. image size: 2x 6MP (6144 x 2048 Pixel) • IP54 without accessories, IP65/IK10 with Outdoor Wall Mount, IP66/IK10+ with Vandalism Set, each -40 bis 60 °C (-40 to 140°F) • Internal DVR: 4 GB microSD • Speaker, microphone, PIR sensor, temperature sensor, MxActivitySensor, shock detector • Ethernet patch cable 0,5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via Interface Box (MOBOTIX accessory)

4047438030663	39,5 cm
85258900	29,6 cm
1.642 ₧	18,0 cm
	21,0 l

V16B Vandalism Camera „Mx6B“

Second Mx6 generation – with MxBus functionality and enhanced performance.

	Article No. / Name / Description	EAN / HS / weight	dimen.
	Mx-V16B-6D041	4047438031462	26,0 cm
	V16B Complete Cam 6MP, 1x B041 (Day) V16 Vandalism with one 6MP Moonlight sensor day (3072 x 2048), HD premium lens B041 (f/1.8, horiz. image angle 90°) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 3-5 mm stainless steel casing • IK10+ /IP66 • Functional range like S16B (incl. MxBus) • HD Audio: Microphone and speaker integrated in the housing	85258900 4.600 g	26,0 cm 26,0 cm 17,6 l
	Mx-V16B-6D079	4047438031479	26,0 cm
	V16B Complete Cam 6MP, 1x B079 (Day) V16 Vandalism with one 6MP Moonlight sensor day (3072 x 2048), HD premium lens B079 (f/1.8, horiz. image angle 45°) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 3-5 mm stainless steel casing • IK10+ /IP66 • Functional range like S16B (incl. MxBus) • HD Audio: Microphone and speaker integrated in the housing	85258900 4.600 g	26,0 cm 26,0 cm 17,6 l
	Mx-V16B-6D6D041	4047438031486	26,0 cm
	V16B Complete Cam 6MP, 2x B041 (Day) V16 Vandalism with two 6MP Moonlight sensors (3072 x 2048): 2x Color (day), two HD premium lenses B041 (f/1.8, horiz. image angle 90°) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 3-5 mm stainless steel casing • IK10+/IP66 • Functional range like S16B (incl. MxBus) • HD Audio: Microphone and speaker integrated in the housing	85258900 4.700 g	26,0 cm 26,0 cm 17,6 l
	Mx-V16B-6D6D079	4047438031493	26,0 cm
	V16B Complete Cam 2x 6MP, 2x B079 (Day) V16 Vandalism with two 6MP Moonlight sensors (3072 x 2048): 2x color (day), two HD premium lenses B079 (f/1.8, horiz. image angle 45°) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 3-5 mm stainless steel casing • IK10+/IP66 • Functional range like S16B (incl. MxBus) • HD Audio: Microphone and speaker integrated in the housing	85258900 4.700 g	26,0 cm 26,0 cm 17,6 l
	Mx-V16B-6D6N041	4047438031509	26,0 cm
	V16B Complete Cam 2x 6MP, 2x B041 (Day & Night) V16 Vandalism with two 6MP Moonlight sensors (3072 x 2048): 1x color (day), 1x B/W (night), two HD premium lenses B041 (f/1.8, horiz. image angle 90°) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 3-5 mm stainless steel casing • IK10+/IP66 • Functional range like S16B (incl. MxBus) • HD Audio: Microphone and speaker integrated in the housing	85258900 4.700 g	26,0 cm 26,0 cm 17,6 l

**Mx-V16B-6D6N079****V16B Complete Cam 2x 6MP, 2x B079 (Day & Night)**

V16 Vandalism with two 6MP Moonlight sensors (3072 x 2048): 1x color (day), 1x B/W (night), two HD premium lenses B079 (f/1.8, horiz. image angle 45°) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 3-5 mm stainless steel casing • IK10+/IP66 • Functional range like S16B (incl. MxBus) • HD Audio: Microphone and speaker integrated in the housing

4047438031516	26,0 cm
85258900	26,0 cm
4.700 g	26,0 cm
	17,6 l

**Mx-V16B-6N6N041****V16B Complete Cam 2x 6MP, 2x B041 (Night)**

V16 Vandalism with two 6MP Moonlight sensors (3072 x 2048): 2x B/W (night), two HD premium lenses B041 (f/1.8, horiz. image angle 90°) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 3-5 mm stainless steel casing • IK10+/IP66 • Functional range like S16B (incl. MxBus) • HD Audio: Microphone and speaker integrated in the housing

4047438031523	26,0 cm
85258900	26,0 cm
4.700 g	26,0 cm
	17,6 l

**Mx-V16B-6N6N079****V16B Complete Cam 2x 6MP, 2x B079 (Night)**

V16 Vandalism with two 6MP Moonlight sensors (3072 x 2048): 2x B/W (night), two HD premium lenses B079 (f/1.8, horiz. image angle 45°) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 3-5 mm stainless steel casing • IK10+/IP66 • Functional range like S16B (incl. MxBus) • HD Audio: Microphone and speaker integrated in the housing

4047438031530	26,0 cm
85258900	26,0 cm
4.700 g	26,0 cm
	17,6 l

S74A

Article No. / Name / Description

EAN / HS / weight dimen.

**Mx-S74A****S74 Body for 4 Sensor- and Functional Modules**

S74A IP camera module (body) for connecting up to four additional functional and optical sensor modules (to be ordered individually) • ONVIF-S/T-compliant MOBOTIX 7 system platform with H.264/H.265 (Triple Streaming), MxPEG+ and M-JPEG • Image sensor options (via sensor module): 4K (8 megapixels), color (day) and/or B/W (night) and/or color (day/night with IR cut) • Lens options (via sensor module): horizontal image angle from 95° to 15° • Max. image size (per image sensor): 4K UHD (3840 x 2160 pixels), 16:9 • WDR: up to 120 dB • Functional extensions (via optional MOBOTIX modules): MultiSense (PIR, temperature, brightness sensor, Microphone), IR Light (supports 15°, 45°, 95° lenses), USB-C • Operating conditions: IP66/IK10 (housing), -40 to 65°C (-40 to 149 °F) • Internal DVR: 8 GB microSD (for MxPEG+ recordings) • Max. Power consumption: 25 W, supply via network cable, PoE Class 4 (IEEE 802.3af/at) • Connections: 1x RJ45 or 1x LSA board for weatherproof network connection via MOBOTIX patch cable (Ethernet 1000BaseT), 4x MOBOTIX module connection (2x optical/2x functional), USB-C, further connections via interface board • Software interface for MOBOTIX Certified Apps (based on Deep Learning, approx. 20 different 30-day demo versions pre-installed) • Housing: Aluminium, PBT-30GF • Color: white • Warranty: 5 years (optionally extendable up to 8 years)

4047438035552 29,6 cm
85258900 19,6 cm
1.400 g 9,0 cm
5,2 l

**Mx-S74A-LSA****S74 Body for 4 Sensor- and Functional Modules with LSA**

S74A IP camera module (body) for connecting up to four additional functional and optical sensor modules (to be ordered individually) • ONVIF-S/T-compliant MOBOTIX 7 system platform with H.264/H.265 (Triple Streaming), MxPEG+ and M-JPEG • Image sensor options (via sensor module): 4K (8 megapixels), color (day) and/or B/W (night) and/or color (day/night with IR cut) • Lens options (via sensor module): horizontal image angle from 95° to 15° • Max. image size (per image sensor): 4K UHD (3840 x 2160 pixels), 16:9 • WDR: up to 120 dB • Functional extensions (via optional MOBOTIX modules): MultiSense (PIR, temperature, brightness sensor, Microphone), IR Light (supports 15°, 45°, 95° lenses), USB-C • Operating conditions: IP66/IK10 (housing), -40 to 65°C (-40 to 149 °F) • Internal DVR: 8 GB microSD (for MxPEG+ recordings) • Max. Power consumption: 25 W, supply via network cable, PoE Class 4 (IEEE 802.3af/at) • Connections: 1x LSA board for weatherproof network connection via MOBOTIX patch cable (Ethernet 1000BaseT), 4x MOBOTIX module connection (2x optical/2x functional), USB-C, further connections via interface board • Software interface for MOBOTIX Certified Apps (based on Deep Learning, approx. 20 different 30-day demo versions pre-installed) • Housing: Aluminium, PBT-30GF • Color: white • Warranty: 5 years (optionally extendable up to 8 years)

4047438047814 29,6 cm
85258900 19,6 cm
1.525 g 9,0 cm
5,2 l

**Mx-S74A-RJ45****S74 Body for 4 Sensor- and Functional Modules with RJ45**

S74A IP camera module (body) for connecting up to four additional functional and optical sensor modules (to be ordered individually) • ONVIF-S/T-compliant MOBOTIX 7 system platform with H.264/H.265 (Triple Streaming), MxPEG+ and M-JPEG • Image sensor options (via sensor module): 4K (8 megapixels), color (day) and/or B/W (night) and/or color (day/night with IR cut) • Lens options (via sensor module): horizontal image angle from 95° to 15° • Max. image size (per image sensor): 4K UHD (3840 x 2160 pixels), 16:9 • WDR: up to 120 dB • Functional extensions (via optional MOBOTIX modules): MultiSense (PIR, temperature, brightness sensor, Microphone), IR Light (supports 15°, 45°, 95° lenses), USB-C • Operating conditions: IP66/IK10 (housing), -40 to 65°C (-40 to 149 °F) • Internal DVR: 8 GB microSD (for MxPEG+ recordings) • Max. Power consumption: 25 W, supply via network cable, PoE Class 4 (IEEE 802.3af/at) • Connections: 1x RJ45 board for weatherproof network connection via MOBOTIX patch cable (Ethernet 1000BaseT), 4x MOBOTIX module connection (2x optical/2x functional), USB-C, further connections via interface board • Software interface for MOBOTIX Certified Apps (based on Deep Learning, approx. 20 different 30-day demo versions pre-installed) • Housing: Aluminium, PBT-30GF • Color: white • Warranty: 5 years (optionally extendable up to 8 years)

4047438047807 29,6 cm
85258900 19,6 cm
1.520 g 9,0 cm
5,2 l

**Mx-S74A-SET****S74 Set with 2x 12DN016 sensor modules**

S74A IP camera (set) incl. built-in AudioIO and RJ45 plug-in board + 2x 3m sensor cable (Mx-A-S7A-CBL03) + 2x 12DN016 sensor module (12MP, Day/Night, Hemispheric, white, Mx-O-M7SA-12DN016) • for connecting up to two additional functional and optical sensor modules (to be ordered individually) • ONVIF-S/T-compliant MOBOTIX 7 system platform with H.264/H.265 (Triple Streaming), MxPEG+ and M-JPEG • Image sensor options (via sensor module): 4K (8 megapixels), color (day) and/or B/W (night) and/or color (day/night with IR cut) • Lens options (via sensor module): horizontal image angle from 95° to 15° • Max. image size (per image sensor): 4K UHD (3840 x 2160 pixels), 16:9 • WDR: up to 120 dB • Functional extensions (via optional MOBOTIX modules): MultiSense (PIR, temperature, brightness sensor, Microphone), IR Light (supports 15°, 45°, 95° lenses), USB-C • Operating conditions: IP66/IK10 (housing), -40 to 65°C (-40 to 149 °F) • Internal DVR: 8 GB microSD (for MxPEG+ recordings) • Max. Power consumption: 25 W, supply via network cable, PoE Class 4 (IEEE 802.3af/at) • Connections: 1x RJ45 board (with 12/24 VDC Power Supply) for weatherproof network connection via MOBOTIX patch cable (Ethernet 1000BaseT), 4x MOBOTIX module connection (2x optical/2x functional), USB-C, further connections via interface board • Software interface for MOBOTIX Certified Apps (based on Deep Learning, approx. 20 different 30-day demo versions pre-installed) • Housing: Aluminium, PBT-30GF • Color: white • Warranty: 5 years (optionally extendable up to 8 years)

4047438047999	29,6 cm
85258900	19,6 cm
1.980 G	18,0 cm
	10,4 l


**Mx-S74A-VDC****S74 Body for 4 Sensor- and Functional Modules with RJ45**

S74A IP camera module (body) for connecting up to four additional functional and optical sensor modules (to be ordered individually) • ONVIF-S/T-compliant MOBOTIX 7 system platform with H.264/H.265 (Triple Streaming), MxPEG+ and M-JPEG • Image sensor options (via sensor module): 4K (8 megapixels), color (day) and/or B/W (night) and/or color (day/night with IR cut) • Lens options (via sensor module): horizontal image angle from 95° to 15° • Max. image size (per image sensor): 4K UHD (3840 x 2160 pixels), 16:9 • WDR: up to 120 dB • Functional extensions (via optional MOBOTIX modules): MultiSense (PIR, temperature, brightness sensor, Microphone), IR Light (supports 15°, 45°, 95° lenses), USB-C • Operating conditions: IP66/IK10 (housing), -40 to 65°C (-40 to 149 °F) • Internal DVR: 8 GB microSD (for MxPEG+ recordings) • Max. Power consumption: 25 W, supply via network cable, PoE Class 4 (IEEE 802.3af/at) • Connections: 1x RJ45 board (with 12/24 VDC Power Supply) for weatherproof network connection via MOBOTIX patch cable (Ethernet 1000BaseT), 4x MOBOTIX module connection (2x optical/2x functional), USB-C, further connections via interface board • Software interface for MOBOTIX Certified Apps (based on Deep Learning, approx. 20 different 30-day demo versions pre-installed) • Housing: Aluminium, PBT-30GF • Color: white • Warranty: 5 years (optionally extendable up to 8 years)

4047438047821	29,6 cm
85258900	19,6 cm
1.510 G	9,0 cm
	5,2 l






S16B DualFlex Camera „Mx6B“

Second Mx6 generation – with MxBus functionality and enhanced performance.

	Article No. / Name / Description	EAN / HS / weight	dimen.
	Mx-S16B	4047438031400	19,6 cm
	S16B Body, For S16B/S15 Sensor Modules	85258900	14,8 cm
	<p>S16 camera module (body) for connecting one or two S16/S15 sensor modules (to be ordered individually) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Image sensor options (via sensor module): 6 megapixels, color (day) and/or B/W (night) and/or thermal • Lens options (via optical sensor module): horizontal image angle from 180° to 8° • IP66/IK06, -40 to 60°C (-40 to 140°F) • Internal DVR: 4 GB microSD • System components: temperature sensor, MxActivitySensor, shock detector • Ethernet patch cable 0.5 m/1.65 ft • Interfaces: 2x connection for MOBOTIX sensor module (Cam1/Cam2), Ethernet 10/100 (RJ45 and LSA), MxBus, USB, Audio (I/O); RS232 via MX Interface Box</p>	660 g	9,0 cm
			2,6 l

M26B Allround Camera „Mx6B“

Second Mx6 generation – with MxBus functionality and enhanced performance.

	Article No. / Name / Description	EAN / HS / weight	dimen.
	Mx-M26B-6D M26B Body 6MP (Day) IP camera module (body) with 6 Megapixel Moonlight Sensor, color (day) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Lens to be ordered individually (B036 to B500) • For mounting the Super Tele Lens MX-B500, the Extended Replacement Lens Cover is needed (MOBOTIX accessory: MX-M24M-OPT-LCGL) • Max. image size: 6MP (3072 x 2048) • IP66/IK10, -40 to 50°C (-40 to 122°F) • Internal DVR: 4 GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, MxActivitySensor, MxAnalytics, shock detector • VarioFlex wall mount (can be used with additional ceiling mount MX-DH-M24-SecureFlex and pole mount MX-MH-SecureFlex-ESWS) • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via MX-232-IO-Box (MX-OPT-RS1-EXT)	4047438031042 85258900 1.337 g	29,6 cm 19,6 cm 18,0 cm 10,4 l
		Mx-M26B-6D016 M26B Complete Cam 6MP, B016 (Day) Hemispheric IP camera with 6 Megapixel Moonlight Sensor, color (day) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • HD premium fisheye lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • Max. image size: 6MP (3072 x 2048) • IP66/IK10, -40 to 50°C (-40 to 122°F) • Internal DVR: 4 GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, MxActivitySensor, MxAnalytics, shock detector • VarioFlex wall mount (can be used with additional ceiling mount MX-DH-M24-SecureFlex and pole mount MX-MH-SecureFlex-ESWS) • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via MX-232-IO-Box (MX-OPT-RS1-EXT)	4047438031059 85258900 1.342 g
	Mx-M26B-6D036 M26B Complete Cam 6MP, B036 (Day) IP camera with 6 Megapixel Moonlight Sensor, color (day) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Ultra Wide Lens B036 (focal length 3.6 mm, f/1.8, 103° x 77°) • Max. image size: 6MP (3072 x 2048) • IP66/IK10, -40 to 50°C (-40 to 122°F) • Internal DVR: 4 GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, MxActivitySensor, MxAnalytics, shock detector • VarioFlex wall mount (can be used with additional ceiling mount MX-DH-M24-SecureFlex and pole mount MX-MH-SecureFlex-ESWS) • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via MX-232-IO-Box (MX-OPT-RS1-EXT)	4047438031066 85258900 1.365 g	29,6 cm 19,6 cm 18,0 cm 10,4 l
		Mx-M26B-6D041 M26B Complete Cam 6MP, B041 (Day) IP camera with 6 Megapixel Moonlight Sensor, color (day) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Super Wide Lens B041 (focal length 4.1 mm, f/1.8, 90° x 67°) • Max. image size: 6MP (3072 x 2048) • IP66/IK10, -40 to 50°C (-40 to 122°F) • Internal DVR: 4 GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, MxActivitySensor, MxAnalytics, shock detector • VarioFlex wall mount (can be used with additional ceiling mount MX-DH-M24-SecureFlex and pole mount MX-MH-SecureFlex-ESWS) • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via MX-232-IO-Box (MX-OPT-RS1-EXT)	4047438031073 85258900 1.354 g
	Mx-M26B-6D061 M26B Complete Cam 6MP, B061 (Day) IP camera with 6 Megapixel Moonlight Sensor, color (day) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Wide Lens B061 (focal length 6.1 mm, f/1.8, 60° x 45°) • Max. image size: 6MP (3072 x 2048) • IP66/IK10, -40 to 50°C (-40 to 122°F) • Internal DVR: 4 GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, MxActivitySensor, MxAnalytics, shock detector • VarioFlex wall mount (can be used with additional ceiling mount MX-DH-M24-SecureFlex and pole mount MX-MH-SecureFlex-ESWS) • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via MX-232-IO-Box (MX-OPT-RS1-EXT)	4047438031080 85258900 1.361 g	29,6 cm 19,6 cm 18,0 cm 10,4 l

**Mx-M26B-6D079****M26B Complete Cam 6MP, B079 (Day)**

IP camera with 6 Megapixel Moonlight Sensor, color (day) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Standard Lens B079 (focal length 7.9 mm, f/1.8, 45° x 34°) • Max. image size: 6MP (3072 x 2048) • IP66/IK10, -40 to 50°C (-40 to 122°F) • Internal DVR: 4 GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, MxActivitySensor, MxAnalytics, shock detector • VarioFlex wall mount (can be used with additional ceiling mount MX-DH-M24-SecureFlex and pole mount MX-MH-SecureFlex-ESWS) • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via MX-232-IO-Box (MX-OPT-RS1-EXT)

4047438031097 29,6 cm
85258900 19,6 cm
1.359 G 18,0 cm
10,4 l

**Mx-M26B-6D119****M26B Complete Cam 6MP, B119 (Day)**

IP camera with 6 Megapixel Moonlight Sensor, color (day) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Tele Lens B119 (focal length 11.9 mm, f/1.8, 31° x 23°) • Max. image size: 6MP (3072 x 2048) • IP66/IK10, -40 to 50°C (-40 to 122°F) • Internal DVR: 4 GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, MxActivitySensor, MxAnalytics, shock detector • VarioFlex wall mount (can be used with additional ceiling mount MX-DH-M24-SecureFlex and pole mount MX-MH-SecureFlex-ESWS) • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via MX-232-IO-Box (MX-OPT-RS1-EXT)

4047438031103 29,6 cm
85258900 19,6 cm
1.359 G 18,0 cm
10,4 l

**Mx-M26B-6D237****M26B Complete Cam 6MP, B237 (Day)**

IP camera with 6 Megapixel Moonlight Sensor, color (day) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Distant Tele Lens B237 (focal length 23.7 mm, f/1.8, 15° x 11°) • Max. image size: 6MP (3072 x 2048) • IP66/IK10, -40 to 50°C (-40 to 122°F) • Internal DVR: 4 GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, MxActivitySensor, MxAnalytics, shock detector • VarioFlex wall mount (can be used with additional ceiling mount MX-DH-M24-SecureFlex and pole mount MX-MH-SecureFlex-ESWS) • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via MX-232-IO-Box (MX-OPT-RS1-EXT)

4047438031110 29,6 cm
85258900 19,6 cm
1.359 G 18,0 cm
10,4 l

**Mx-M26B-6D500****M26B Complete Cam 6MP, B500 (Day)**

IP camera with 6 Megapixel Moonlight Sensor, color (day) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Super Tele Lens B500 (focal length 50 mm, f/2.5, 8° x 6°) • Max. image size: 6MP (3072 x 2048) • IP66/IK10, -40 to 50°C (-40 to 122°F) • Internal DVR: 4 GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, MxActivitySensor, MxAnalytics, shock detector • VarioFlex wall mount (can be used with additional ceiling mount MX-DH-M24-SecureFlex and pole mount MX-MH-SecureFlex-ESWS) • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via MX-232-IO-Box (MX-OPT-RS1-EXT)

4047438031127 29,6 cm
85258900 19,6 cm
2.000 G 18,0 cm
10,4 l

**Mx-M26B-6N****M26B Body 6MP (Night)**

IP camera module (body) with 6 Megapixel Moonlight Sensor, B/W (night) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Lens to be ordered individually (B036 to B500) • For mounting the Super Tele Lens B500, the Extended Replacement Lens Cover is needed (MOBOTIX accessory: MX-M24M-OPT-LCGL) • Max. image size: 6MP (3072 x 2048) • IP66/IK10, -40 to 50°C (-40 to 122°F) • Internal DVR: 4 GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, MxActivitySensor, MxAnalytics, shock detector • VarioFlex wall mount (can be used with additional ceiling mount MX-DH-M24-SecureFlex and pole mount MX-MH-SecureFlex-ESWS) • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via MX-232-IO-Box (MX-OPT-RS1-EXT)

4047438031134 29,6 cm
85258900 19,6 cm
1.344 G 18,0 cm
10,4 l

**Mx-M26B-6N016****M26B Complete Cam 6MP, B016 (Night)**

Hemispheric IP camera with 6 Megapixel Moonlight Sensor, B/W (night) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • HD premium fisheye lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • Max. image size: 6MP (3072 x 2048) • IP66/IK10, -40 to 50°C (-40 to 122°F) • Internal DVR: 4 GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, MxActivitySensor, MxAnalytics, shock detector • VarioFlex wall mount (can be used with additional ceiling mount MX-DH-M24-SecureFlex and pole mount MX-MH-SecureFlex-ESWS) • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via MX-232-IO-Box (MX-OPT-RS1-EXT)

4047438031141 29,6 cm
85258900 19,6 cm
1.342 G 18,0 cm
10,4 l

**Mx-M26B-6N036****M26B Complete Cam 6MP, B036 (Night)**

IP camera with 6 Megapixel Moonlight Sensor, B/W (night) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Ultra Wide Lens B036 (focal length 3.6 mm, f/1.8, 103° x 77°) • Max. image size: 6MP (3072 x 2048) • IP66/IK10, -40 to 50°C (-40 to 122°F) • Internal DVR: 4 GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, MxActivitySensor, MxAnalytics, shock detector • VarioFlex wall mount (can be used with additional ceiling mount MX-DH-M24-SecureFlex and pole mount MX-MH-SecureFlex-ESWS) • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via MX-232-IO-Box (MX-OPT-RS1-EXT)

4047438031158 29,6 cm
85258900 19,6 cm
1.365 G 18,0 cm
10,4 l

**Mx-M26B-6N041****M26B Complete Cam 6MP, B041 (Night)**

IP camera with 6 Megapixel Moonlight Sensor, B/W (night) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Super Wide Lens B041 (focal length 4.1 mm, f/1.8, 90° x 67°) • Max. image size: 6MP (3072 x 2048) • IP66/IK10, -40 to 50°C (-40 to 122°F) • Internal DVR: 4 GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, MxActivitySensor, MxAnalytics, shock detector • VarioFlex wall mount (can be used with additional ceiling mount MX-DH-M24-SecureFlex and pole mount MX-MH-SecureFlex-ESWS) • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via MX-232-IO-Box (MX-OPT-RS1-EXT)

4047438031165 29,6 cm
85258900 19,6 cm
1.354 G 18,0 cm
10,4 l

**Mx-M26B-6N061****M26B Complete Cam 6MP, B061 (Night)**

IP camera with 6 Megapixel Moonlight Sensor, B/W (night) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Wide Lens B061 (focal length 6.1 mm, f/1.8, 60° x 45°) • Max. image size: 6MP (3072 x 2048) • IP66/IK10, -40 to 50°C (-40 to 122°F) • Internal DVR: 4 GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, MxActivitySensor, MxAnalytics, shock detector • VarioFlex wall mount (can be used with additional ceiling mount MX-DH-M24-SecureFlex and pole mount MX-MH-SecureFlex-ESWS) • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via MX-232-IO-Box (MX-OPT-RS1-EXT)

4047438031172 29,6 cm
85258900 19,6 cm
1.361 G 18,0 cm
10,4 l

**Mx-M26B-6N079****M26B Complete Cam 6MP, B079 (Night)**

IP camera with 6 Megapixel Moonlight Sensor, B/W (night) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Standard Lens B079 (focal length 7.9 mm, f/1.8, 45° x 34°) • Max. image size: 6MP (3072 x 2048) • IP66/IK10, -40 to 50°C (-40 to 122°F) • Internal DVR: 4 GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, MxActivitySensor, MxAnalytics, shock detector • VarioFlex wall mount (can be used with additional ceiling mount MX-DH-M24-SecureFlex and pole mount MX-MH-SecureFlex-ESWS) • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via MX-232-IO-Box (MX-OPT-RS1-EXT)

4047438031189 29,6 cm
85258900 19,6 cm
1.359 G 18,0 cm
10,4 l

**Mx-M26B-6N119****M26B Complete Cam 6MP, B119 (Night)**

IP camera with 6 Megapixel Moonlight Sensor, B/W (night) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Tele Lens B119 (focal length 11.9 mm, f/1.8, 31° x 23°) • Max. image size: 6MP (3072 x 2048) • IP66/IK10, -40 to 50°C (-40 to 122°F) • Internal DVR: 4 GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, MxActivitySensor, MxAnalytics, shock detector • VarioFlex wall mount (can be used with additional ceiling mount MX-DH-M24-SecureFlex and pole mount MX-MH-SecureFlex-ESWS) • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via MX-232-IO-Box (MX-OPT-RS1-EXT)

4047438031196	29,6 cm
85258900	19,6 cm
1.359 G	18,0 cm
	10,4 l

**Mx-M26B-6N237****M26B Complete Cam 6MP, B237 (Night)**

IP camera with 6 Megapixel Moonlight Sensor, B/W (night) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Distant Tele Lens B237 (focal length 23.7 mm, f/1.8, 15° x 11°) • Max. image size: 6MP (3072 x 2048) • IP66/IK10, -40 to 50°C (-40 to 122°F) • Internal DVR: 4 GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, MxActivitySensor, MxAnalytics, shock detector • VarioFlex wall mount (can be used with additional ceiling mount MX-DH-M24-SecureFlex and pole mount MX-MH-SecureFlex-ESWS) • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via MX-232-IO-Box (MX-OPT-RS1-EXT)

4047438031202	29,6 cm
85258900	19,6 cm
1.359 G	18,0 cm
	10,4 l




**Mx-M26B-6N500****M26B Complete Cam 6MP, B500 (Night)**

IP camera with 6 Megapixel Moonlight Sensor, B/W (night) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Super Tele Lens B500 (focal length 50 mm, f/2.5, 8° x 6°) • Max. image size: 6MP (3072 x 2048) • IP66/IK10, -40 to 50°C (-40 to 122°F) • Internal DVR: 4 GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, MxActivitySensor, MxAnalytics, shock detector • VarioFlex wall mount (can be used with additional ceiling mount MX-DH-M24-SecureFlex and pole mount MX-MH-SecureFlex-ESWS) • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via MX-232-IO-Box (MX-OPT-RS1-EXT)

4047438031219	29,6 cm
85258900	19,6 cm
1.366 G	18,0 cm
	10,4 l

D26B Allround Camera „Mx6B“

Second Mx6 generation – with MxBus functionality and enhanced performance.

	Article No. / Name / Description	EAN / HS / weight	dimen.
	Mx-D26B-6D D26B Body 6MP (Day) D26 camera module (body) with 6 Megapixel Moonlight Sensor, color (day) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Lens to be ordered individually (B036 to B237) • Max. image size: 6MP (3072 x 2048) • IP66/IK10, -40 to 50°C (-40 to 122°F) • Internal DVR: 4 GB microSD • Temperature sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet cable 0.5 m/1.6 ft • Lens cover with sealing ring (polycarbonate, 1.5 mm) • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via MX-232-IO-Box (MX-OPT-RS1-EXT)	4047438030670 85258900 799 g	19,6 cm 18,0 cm 14,8 cm 5,2 l
	Mx-D26B-6D036 D26B Complete Cam 6MP, B036 (Day) IP camera with 6 Megapixel Moonlight Sensor, color (day) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Ultra wide lens B036 (f/1.8, 103° x 77°) • Max. image size: 6MP (3072 x 2048) • IP66/IK10, -40 to 50°C (-40 to 122°F) • Internal DVR: 4 GB microSD • Temperature sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft, lens cover with sealing ring • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via MX-232-IO-Box (MX-OPT-RS1-EXT)	4047438030687 85258900 814 g	19,6 cm 18,0 cm 14,8 cm 5,2 l
	Mx-D26B-6D041 D26B Complete Cam 6MP, B041 (Day) IP camera with 6 Megapixel Moonlight Sensor, color (day) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Super wide lens B041 (f/1.8, 90° x 67°) • Max. image size: 6MP (3072 x 2048) • IP66/IK10, -40 to 50°C (-40 to 122°F) • Internal DVR: 4 GB microSD • Temperature sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft, lens cover with sealing ring • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via MX-232-IO-Box (MX-OPT-RS1-EXT)	4047438030694 85258900 762 g	19,6 cm 18,0 cm 14,8 cm 5,2 l
	Mx-D26B-6D061 D26B Complete Cam 6MP, B061 (Day) IP camera with 6 Megapixel Moonlight Sensor, color (day) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Wide lens B061 (f/1.8, 60° x 45°) • Max. image size: 6MP (3072 x 2048) • IP66/IK10, -40 to 50°C (-40 to 122°F) • Internal DVR: 4 GB microSD • Temperature sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft, lens cover with sealing ring • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via MX-232-IO-Box (MX-OPT-RS1-EXT)	4047438030700 85258900 814 g	19,6 cm 18,0 cm 14,8 cm 5,2 l
	Mx-D26B-6D079 D26B Complete Cam 6MP, B079 (Day) IP camera with 6 Megapixel Moonlight Sensor, color (day) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Standard lens B079 (f/1.8, 45° x 34°) • Max. image size: 6MP (3072 x 2048) • IP66/IK10, -40 to 50°C (-40 to 122°F) • Internal DVR: 4 GB microSD • Temperature sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft, lens cover with sealing ring • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via Interface Box (MOBOTIX accessor)	4047438030717 85258900 1.580 g	19,6 cm 18,0 cm 14,8 cm 5,2 l

**Mx-D26B-6D119****D26B Complete Cam 6MP, B119 (Day)**

IP camera with 6 Megapixel Moonlight Sensor, color (day) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Tele lens B119 (f/1.8, 31° x 23°) • Max. image size: 6MP (3072 x 2048) • IP66/IK10, -40 to 50°C (-40 to 122°F) • Internal DVR: 4 GB microSD • Temperature sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft, lens cover with sealing ring • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via MX-232-IO-Box (MX-OPT-RS1-EXT)

4047438030724 19,6 cm
85258900 18,0 cm
1.580 9 14,8 cm
5,2 l

**Mx-D26B-6D237****D26B Complete Cam 6MP, B237 (Day)**

IP camera with 6 Megapixel Moonlight Sensor, color (day) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Distance tele lens B237 (f/1.8, 15° x 11°) • Max. image size: 6MP (3072 x 2048) • IP66/IK10, -40 to 50° C (-40 to 122°F) • Internal DVR: 4 GB microSD • Temperature sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft, lens cover with sealing ring • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via MX-232-IO-Box (MX-OPT-RS1-EXT)

4047438030731 19,6 cm
85258900 18,0 cm
815 9 14,8 cm
5,2 l

**Mx-D26B-6N****D26B Body 6MP (Night)**

D26 camera module (body) with 6 Megapixel Moonlight Sensor, B/W (night) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Lens to be ordered individually (B036 to B237) • Max. image size: 6MP (3072 x 2048) • IP66/IK10, -40 to 50°C (-40 to 122°F) • Internal DVR: 4 GB microSD • Temperature sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft • Lens cover with sealing ring (polycarbonate, 1.5 mm) • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via MX-232-IO-Box (MX-OPT-RS1-EXT)

4047438030748 19,6 cm
85258900 18,0 cm
799 9 14,8 cm
5,2 l

**Mx-D26B-6N036****D26B Complete Cam 6MP, B036 (Night)**

IP camera with 6 Megapixel Moonlight Sensor, B/W (night) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Ultra wide lens B036 (f/1.8, 103° x 77°) • Max. image size: 6MP (3072 x 2048) • IP66/IK10, -40 to 50°C (-40 to 122°F) • Internal DVR: 4 GB microSD • Temperature sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft, lens cover with sealing ring • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via MX-232-IO-Box (MX-OPT-RS1-EXT)

4047438030755 19,6 cm
85258900 18,0 cm
814 9 14,8 cm
5,2 l

**Mx-D26B-6N041****D26B Complete Cam 6MP, B041 (Night)**

IP camera with 6 Megapixel Moonlight Sensor, B/W (night) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Super wide lens B041 (f/1.8, 90° x 67°) • Max. image size: 6MP (3072 x 2048) • IP66/IK10, -40 to 50°C (-40 to 122°F) • Internal DVR: 4 GB microSD • Temperature sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft, lens cover with sealing ring • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via MX-232-IO-Box (MX-OPT-RS1-EXT)

4047438030762 19,6 cm
85258900 18,0 cm
1.580 9 14,8 cm
5,2 l

**Mx-D26B-6N061****D26B Complete Cam 6MP, B061 (Night)**

IP camera with 6 Megapixel Moonlight Sensor, B/W (night) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Wide lens B061 (f/1.8, 60° x 45°) • Max. image size: 6MP (3072 x 2048) • IP66/IK10, -40 to 50°C (-40 to 122°F) • Internal DVR: 4 GB microSD • Temperature sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft, lens cover with sealing ring • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via MX-232-IO-Box (MX-OPT-RS1-EXT)

4047438030779 19,6 cm
85258900 18,0 cm
1.580 9 14,8 cm
5,2 l

**Mx-D26B-6N079****D26B Complete Cam 6MP, B079 (Night)**

IP camera with 6 Megapixel Moonlight Sensor, B/W (night) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Standard lens B079 (f/1.8, 45° x 34°) • Max. image size: 6MP (3072 x 2048) • IP66/IK10, -40 to 50°C (-40 to 122°F) • Internal DVR: 4 GB microSD • Temperature sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft, lens cover with sealing ring • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via MX-232-IO-Box (MX-OPT-RS1-EXT)

4047438030786	19,6 cm
85258900	18,0 cm
1.580 G	14,8 cm
	5,2 l

**Mx-D26B-6N119****D26B Complete Cam 6MP, B119 (Night)**

IP camera with 6 Megapixel Moonlight Sensor, B/W (night) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Tele lens B119 (f/1.8, 31° x 23°) • Max. image size: 6MP (3072 x 2048) • IP66/IK10, -40 to 50°C (-40 to 122°F) • Internal DVR: 4 GB microSD • Temperature sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft, lens cover with sealing ring • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via MX-232-IO-Box (MX-OPT-RS1-EXT)

4047438030793	19,6 cm
85258900	18,0 cm
1.580 G	14,8 cm
	5,2 l



**Mx-D26B-6N237****D26B Complete Cam 6MP, B237 (Night)**

IP camera with 6 Megapixel Moonlight Sensor, B/W (night) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Distance tele lens B237 (f/1.8, 15° x 11°) • Max. image size: 6MP (3072 x 2048) • IP66/IK10, -40 to 50°C (-40 to 122°F) • Internal DVR: 4 GB microSD • Temperature sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft, lens cover with sealing ring • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via MX-232-IO-Box (MX-OPT-RS1-EXT)

4047438030809	19,6 cm
85258900	18,0 cm
1.580 G	14,8 cm
	5,2 l

Q26B Hemispheric Camera „Mx6B“

Second Mx6 generation – with MxBus functionality and enhanced performance.



	Article No. / Name / Description	EAN / HS / weight	dimen.
	Mx-Q26B-6D016	4047438031387	29,6 cm
	Q26B Complete Cam 6MP, B016 (Day) Hemispheric IP camera with 6 Megapixel Moonlight Sensor, color (day) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • HD premium fisheye lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • Max. image size: 6MP (3072 x 2048) • IP66/IK06, -40 to 50°C (-40 to 122°F) • Internal DVR: 4 GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, MxActivitySensor, MxAnalytics (incl. behavioral detection), shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via MX-232-IO-Box (MX-OPT-RS1-EXT)	85258900 853 9	19,6 cm 9,0 cm 5,2 l
	Mx-Q26B-6N016	4047438031394	29,6 cm
	Q26B Complete Cam 6MP, B016 (Night) Hemispheric IP camera with 6 Megapixel Moonlight Sensor, B/W (night) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • HD premium fisheye lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • Max. image size: 6MP (3072 x 2048) • IP66/IK06, -40 to 50°C (-40 to 122°F) • Internal DVR: 4 GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, MxActivitySensor, MxAnalytics (incl. behavioral detection), shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via MX-232-IO-Box (MX-OPT-RS1-EXT)	85258900 855 9	19,6 cm 9,0 cm 5,2 l

Professional Video Systems Indoor



BeyondHumanVision

MOBOTIX

c71A Indoor Camera

	Article No. / Name / Description	EAN / HS / weight	dimen.
	Mx-c71A-8DN016	4047438041027	19,6 cm
	c71 Indoor Complete Camera 4k, DN016 (Day/Night) c71 Indoor camera with Hemispheric lens and IR cut filter for day and night use • f/1.8 • 4k image sensor • 4MP effective resolution: 2160x2160 (hemispheric original image) • Max. Frame rate (4MP): 30 fps@MxPEG, 30 fps@H.264/H.265 • Integrated IR LED illuminator • WDR: Wide Dynamic Range 120 dB • Combined day/night sensor with IR cut filter • Operating temperature range: -10 to +50 °C • Built-in speaker and microphone • USB-C • 8GB memory card included • MTBF 80,000 hours • 5 years warranty	85258900 1.040 g	18,0 cm 14,8 cm 5,2 l
	Mx-c71A-NurseAssist	4047438048293	19,6 cm
	MOBOTIX c71 NurseAssist powered by Kepler Vision MOBOTIX c71 NurseAssist powered by Kepler Vision Technologies including the following features: • monitoring of the well-being of patients in private rooms, corridors and common areas of Healthcare facilities • minimization of reaction times due to decentralized state-of-the-art fall detection • prevention of accidents through: person down, person in bed and person out of bed event • simple and decent installation • GDPR compliant operation through event-controlled obscuring of live and recorded images • Currently not available for USA, Canada & Latam.	85258900 1.040 g	18,0 cm 14,8 cm 5,2 l

p71A Indoor Camera

	Article No. / Name / Description	EAN / HS / weight	dimen.		
	Mx-p71A-4DN040 p71 Indoor Complete Camera 4MP Ultra LowLight DN040 p71 4MP Indoor camera with premium wide-angle lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 120°x60°, max. resolution: 4MP Ultra LowLight Sensor (2688x1512) • Integrated IR LED illuminators • WDR: Wide Dynamic Range 120 dB - Day and night sensors • 3-axis mechanical pan/tilt head • Operating temperature range: -10 to +50°C • Built-in speaker and microphone • USB-C • 8GB memory card included • MTBF 80,000 hours • 5 years warranty	4047438041164 85258900 1.175 g	19,6 cm 18,0 cm 14,8 cm 5,2 l		
		Mx-p71A-4DN050 p71 Indoor Complete Camera 4MP Ultra LowLight DN050 p71 4MP Indoor camera with premium wide-angle lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 95°x50°, max. resolution: 4MP Ultra LowLight Sensor (2688x1512) • Integrated IR LED illuminators • WDR: Wide Dynamic Range 120 dB - Day and night sensors • 3-axis mechanical pan/tilt head • Operating temperature range: -10 to +50°C • Built-in speaker and microphone • USB-C • 8GB memory card included • MTBF 80,000 hours • 5 years warranty	4047438041171 85258900 1.175 g	19,6 cm 18,0 cm 14,8 cm 5,2 l	
			Mx-p71A-4DN080 p71 Indoor Complete Camera 4MP Ultra LowLight DN080 p71 4MP Indoor camera with premium wide-angle lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 60°x33°, max. resolution: 4MP Ultra LowLight Sensor (2688x1512) • Integrated IR LED illuminators • WDR: Wide Dynamic Range 120 dB - Day and night sensors • 3-axis mechanical pan/tilt head • Operating temperature range: -10 to +50°C • Built-in speaker and microphone • USB-C • 8GB memory card included • MTBF 80,000 hours • 5 years warranty	4047438041188 85258900 1.175 g	19,6 cm 18,0 cm 14,8 cm 5,2 l
				Mx-p71A-4DN100 p71 Indoor Complete Camera 4MP Ultra LowLight DN100 p71 4MP Indoor camera with premium wide-angle lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 45°x25°, max. resolution: 4MP Ultra LowLight Sensor (2688x1512) • Integrated IR LED illuminators • WDR: Wide Dynamic Range 120 dB - Day and night sensors • 3-axis mechanical pan/tilt head • Operating temperature range: -10 to +50 °C • Built-in speaker and microphone • USB-C • 8GB memory card included • MTBF 80,000 hours • 5 years warranty	4047438041195 85258900 1.175 g
				Mx-p71A-4DN150 p71 Indoor Complete Camera 4MP Ultra LowLight DN150 p71 4MP Indoor camera with premium wide-angle lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 30°x17°, max. resolution: 4MP Ultra LowLight Sensor (2688x1512) • Integrated IR LED illuminators • WDR: Wide Dynamic Range 120 dB - Day and night sensors • 3-axis mechanical pan/tilt head • Operating temperature range: -10 to +50°C • Built-in speaker and microphone • USB-C • 8GB memory card included • MTBF 80,000 hours • 5 years warranty	4047438041201 85258900 1.175 g

**Mx-p71A-4DN280****p71 Indoor Complete Camera 4MP Ultra LowLight DN280**

p71 4MP Indoor camera with premium wide-angle lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 15°x8,5°, max. resolution: 4MP Ultra LowLight Sensor (2688x1512) • Integrated IR LED illuminators • WDR: Wide Dynamic Range 120 dB - Day and night sensors • 3-axis mechanical pan/tilt head • Operating temperature range: -10 to +50°C • Built-in speaker and microphone • USB-C • 8GB memory card included • MTBF 80,000 hours • 5 years warranty

4047438041218	19,6 cm
85258900	18,0 cm
1.175 G	14,8 cm
	5,2 l

**Mx-p71A-8DN040****p71 Indoor Complete Camera 4K DN040 (Day/Night), 120°**

p71 4K Indoor camera with premium wide-angle lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 120°x60°, max. resolution: 4K UHD (3840x2160) • Integrated IR LED illuminators • WDR: Wide Dynamic Range 120 dB - Day and night sensors • 3-axis mechanical pan/tilt head • Operating temperature range: -10 to +50 °C • Built-in speaker and microphone • USB-C • 8GB memory card included • MTBF 80,000 hours • 5 years warranty

4047438041041	19,6 cm
85258900	18,0 cm
1.175 G	14,8 cm
	5,2 l

**Mx-p71A-8DN050****p71 Indoor Complete Camera 4K DN050 (Day/Night), 95°**

p71 4K Indoor camera with premium wide-angle lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 95°x50°, max. resolution: 4K UHD (3840x2160) • Integrated IR LED illuminators • WDR: Wide Dynamic Range 120 dB - Day and night sensors • 3-axis mechanical pan/tilt head • Operating temperature range: -10 to +50 °C • Built-in speaker and microphone • USB-C • 8GB memory card included • MTBF 80,000 hours • 5 years warranty

4047438041058	19,6 cm
85258900	18,0 cm
1.175 G	14,8 cm
	5,2 l

**Mx-p71A-8DN080****p71 Indoor Complete Camera 4K DN080 (Day(Night), 60°**

p71 4K Indoor camera with premium wide-angle lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 60°x33°, max. resolution: 4K UHD (3840x2160) • Integrated IR LED illuminators • WDR: Wide Dynamic Range 120 dB - Day and night sensors • 3-axis mechanical pan/tilt head • Operating temperature range: -10 to +50 °C • Built-in speaker and microphone • USB-C • 8GB memory card included • MTBF 80,000 hours • 5 years warranty

4047438041065	19,6 cm
85258900	18,0 cm
1.175 G	14,8 cm
	5,2 l

**Mx-p71A-8DN100****p71 Indoor Complete Camera 4K DN100 (Day(Night), 45°**

p71 4K Indoor camera with premium wide-angle lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 45°x25°, max. resolution: 4K UHD (3840x2160) • Integrated IR LED illuminators • WDR: Wide Dynamic Range 120 dB - Day and night sensors • 3-axis mechanical pan/tilt head • Operating temperature range: -10 to +50 °C • Built-in speaker and microphone • USB-C • 8GB memory card included • MTBF 80,000 hours • 5 years warranty

4047438041072	19,6 cm
85258900	18,0 cm
1.175 G	14,8 cm
	5,2 l

**Mx-p71A-8DN150****p71 Indoor Complete Camera 4K DN150 (Day(Night), 30°**

p71 4K Indoor camera with premium wide-angle lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 30°x17°, max. resolution: 4K UHD (3840x2160) • Integrated IR LED illuminators • WDR: Wide Dynamic Range 120 dB - Day and night sensors • 3-axis mechanical pan/tilt head • Operating temperature range: -10 to +50 °C • Built-in speaker and microphone • USB-C • 8GB memory card included • MTBF 80,000 hours • 5 years warranty

4047438041089	19,6 cm
85258900	18,0 cm
1.175 G	14,8 cm
	5,2 l

**Mx-p71A-8DN280****p71 Indoor Complete Camera 4K DN280 (Day(Night), 15°**

p71 4K Indoor camera with premium wide-angle lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 15°x8,5°, max. resolution: 4K UHD (3840x2160) • Integrated IR LED illuminators • WDR: Wide Dynamic Range 120 dB - Day and night sensors • 3-axis mechanical pan/tilt head • Operating temperature range: -10 to +50 °C • Built-in speaker and microphone • USB-C • 8GB memory card included • MTBF 80,000 hours • 5 years warranty





4047438041096 19,6 cm

85258900 18,0 cm

1.175 9 14,8 cm

5,2 l

v71A Indoor Camera

	Article No. / Name / Description	EAN / HS / weight	dimen.
	Mx-v71A-4DN050	4047438040921	19,6 cm
	v71 Indoor Complete Camera 4MP Ultra LowLight DN050 -	85258900	18,0 cm
	v71 4MP Indoor camera with premium wide-angle lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 95°x50°, max. resolution: 4MP Ultra LowLight Sensor (2688x1512) • Integrated IR LED illuminators • WDR: Wide Dynamic Range 120 dB - Day and night sensors • 3-axis mechanical pan/tilt head • IK10 with standard dome • Operating temperature range: -10 to +50 °C • Built-in speaker and microphone • USB-C • 8GB memory card included • MTBF 80,000 hours • 5 years warranty	1.050 g	14,8 cm
			5,2 l
	Mx-v71A-4DN080	4047438040938	19,6 cm
	v71 Indoor Complete Camera 4MP Ultra LowLight DN080 -	85258900	18,0 cm
	v71 4MP Indoor camera with premium wide-angle lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 60°x33°, max. resolution: 4MP Ultra LowLight Sensor (2688x1512) • Integrated IR LED illuminators • WDR: Wide Dynamic Range 120 dB - Day and night sensors • 3-axis mechanical pan/tilt head • IK10 with standard dome • Operating temperature range: -10 to +50 °C • Built-in speaker and microphone • USB-C • 8GB memory card included • MTBF 80,000 hours • 5 years warranty	1.050 g	14,8 cm
			5,2 l
	Mx-v71A-4DN100	4047438040945	19,6 cm
	v71 Indoor Complete Camera 4MP Ultra LowLight DN100 -	85258900	18,0 cm
	v71 4MP Indoor camera with premium wide-angle lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 45°x25°, max. resolution: 4MP Ultra LowLight Sensor (2688x1512) • Integrated IR LED illuminators • WDR: Wide Dynamic Range 120 dB - Day and night sensors • 3-axis mechanical pan/tilt head • IK10 with standard dome • Operating temperature range: -10 to +50 °C • Built-in speaker and microphone • USB-C • 8GB memory card included • MTBF 80,000 hours • 5 years warranty	1.050 g	14,8 cm
			5,2 l
	Mx-v71A-4DN150	4047438040952	19,6 cm
	v71 Indoor Complete Camera 4MP Ultra LowLight DN150 -	85258900	18,0 cm
	v71 4MP Indoor camera with premium wide-angle lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 30°x17°, max. resolution: 4MP Ultra LowLight Sensor (2688x1512) • Integrated IR LED illuminators • WDR: Wide Dynamic Range 120 dB - Day and night sensors • 3-axis mechanical pan/tilt head • IK10 with standard dome • Operating temperature range: -10 to +50 °C • Built-in speaker and microphone • USB-C • 8GB memory card included • MTBF 80,000 hours • 5 years warranty	1.050 g	14,8 cm
			5,2 l
	Mx-v71A-4DN280	4047438040969	19,6 cm
	v71 Indoor Complete Camera 4MP Ultra LowLight DN280 -	85258900	18,0 cm
	v71 4MP Indoor camera with premium wide-angle lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 15°x8,5°, max. resolution: 4MP Ultra LowLight Sensor (2688x1512) • Integrated IR LED illuminators • WDR: Wide Dynamic Range 120 dB - Day and night sensors • 3-axis mechanical pan/tilt head • IK10 with standard dome • Operating temperature range: -10 to +50 °C • Built-in speaker and microphone • USB-C • 8GB memory card included • MTBF 80,000 hours • 5 years warranty	1.050 g	14,8 cm
			5,2 l

**Mx-v71A-8DN050****v71 Indoor Complete Camera 4K DN050 - 95°x50°**

v71 4K Indoor camera with premium wide-angle lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 95°x50°, max. resolution: 4K UHD (3840x2160) • Integrated IR LED illuminators • WDR: Wide Dynamic Range 120 dB - Day and night sensors • 3-axis mechanical pan/tilt head • IK10 with standard dome • Operating temperature range: -10 to +50 °C • Built-in speaker and microphone • USB-C • 8GB memory card included • MTBF 80,000 hours • 5 years warranty

4047438040822	19,6 cm
85258900	18,0 cm
1.050 9	14,8 cm
	5,2 l

**Mx-v71A-8DN080****v71 Indoor Complete Camera 4K DN080 - 60°x33° (Day)**

v71 4K Indoor camera with premium wide-angle lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 60°x33°, max. resolution: 4K UHD (3840x2160) • Integrated IR LED illuminators • WDR: Wide Dynamic Range 120 dB - Day and night sensors • 3-axis mechanical pan/tilt head • IK10 with standard dome • Operating temperature range: -10 to +50 °C • Built-in speaker and microphone • USB-C • 8GB memory card included • MTBF 80,000 hours • 5 years warranty

4047438040839	19,6 cm
85258900	18,0 cm
1.050 9	14,8 cm
	5,2 l

**Mx-v71A-8DN100****v71 Indoor Complete Camera 4K DN100 - 45°x25° (Day)**

v71 4K Indoor camera with premium wide-angle lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 45°x25°, max. resolution: 4K UHD (3840x2160) • Integrated IR LED illuminators • WDR: Wide Dynamic Range 120 dB - Day and night sensors • 3-axis mechanical pan/tilt head • IK10 with standard dome • Operating temperature range: -10 to +50 °C • Built-in speaker and microphone • USB-C • 8GB memory card included • MTBF 80,000 hours • 5 years warranty

4047438040846	19,6 cm
85258900	18,0 cm
1.050 9	14,8 cm
	5,2 l

**Mx-v71A-8DN150****v71 Indoor Complete Camera 4K DN150 - 30°x17° (Day)**

v71 4K Indoor camera with premium wide-angle lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 30°x17°, max. resolution: 4K UHD (3840x2160) • Integrated IR LED illuminators • WDR: Wide Dynamic Range 120 dB - Day and night sensors • 3-axis mechanical pan/tilt head • IK10 with standard dome • Operating temperature range: -10 to +50 °C • Built-in speaker and microphone • USB-C • 8GB memory card included • MTBF 80,000 hours • 5 years warranty

4047438040853	19,6 cm
85258900	18,0 cm
1.050 9	14,8 cm
	5,2 l




**Mx-v71A-8DN280****v71 Indoor Complete Camera 4K DN280 - 15°x8,5° (Day)**

v71 4K Indoor camera with premium wide-angle lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 15°x8,5°, max. resolution: 4K UHD (3840x2160) • Integrated IR LED illuminators • WDR: Wide Dynamic Range 120 dB - Day and night sensors • 3-axis mechanical pan/tilt head • IK10 with standard dome • Operating temperature range: -10 to +50 °C • Built-in speaker and microphone • USB-C • 8GB memory card included • MTBF 80,000 hours • 5 years warranty

4047438040860	19,6 cm
85258900	18,0 cm
1.050 9	14,8 cm
	5,2 l

c26B Indoor Camera „Mx6B“

Second Mx6 generation – with MxBus functionality and enhanced performance.

	Article No. / Name / Description	EAN / HS / weight	dimen.
	Mx-c26B-6D c26B Body 6MP (Day) c26 camera module (body) with 6 Megapixel Moonlight Sensor, color (day) and lens mount • Lens to be ordered individually (B036 to B237, focal length 3.6 to 23.7 mm, f/1.8) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 6 Megapixel Moonlight Sensor, color (day) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • 4-GB microSD • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics, shock detector • 0.5 m/1.6 ft Ethernet patch cable • Interfaces: Ethernet 10/100 (RJ45), MxBus (via Mx-A-IOA-IC), USB, slot for MxIOBoard-IC (Mx-A-IOA-IC) • Color: white	4047438030489 85258900 431 g	19,6 cm 15,0 cm 9,0 cm 2,6 l
	Mx-c26B-6D016 c26B Complete Cam 6MP, B016, Day Hemispheric IP indoor camera for ceiling mounting • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 6 Megapixel Moonlight Sensor, color (day) • HD premium fisheye lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • 4-GB microSD • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics (incl. behavioral detection), shock detector • 0.5 m/1.6 ft Ethernet patch cable • Interfaces: Ethernet 10/100 (RJ45), MxBus (via Mx-A-IOA-IC), USB, slot for MxIOBoard-IC (Mx-A-IOA-IC) • Color: white	4047438030496 85258900 433 g	19,6 cm 15,0 cm 9,0 cm 2,6 l
	Mx-c26B-6N c26B Body 6MP (Night) c26 camera module (body) with 6 Megapixel Moonlight Sensor, B/W (night) and lens mount • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Lens to be ordered individually (B036 to B237, focal length 3.6 to 23.7 mm, f/1.8) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • 4-GB microSD • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics, shock detector • 0.5 m/1.6 ft Ethernet patch cable • Interfaces: Ethernet 10/100 (RJ45), MxBus (via Mx-A-IOA-IC), USB, slot for MxIOBoard-IC (Mx-A-IOA-IC) • Color: white	4047438030519 85258900 431 g	19,6 cm 15,0 cm 9,0 cm 2,6 l
	Mx-c26B-6N016 c26B Complete Cam 6MP, B016, Night Hemispheric IP indoor camera for ceiling mounting • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 6 Megapixel Moonlight Sensor, B/W (night) • HD premium fisheye lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • 4-GB microSD • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics (incl. behavioral detection), shock detector • 0.5 m/1.6 ft Ethernet patch cable • Interfaces: Ethernet 10/100 (RJ45), MxBus (via Mx-A-IOA-IC), USB, slot for MxIOBoard-IC (Mx-A-IOA-IC) • Color: white	4047438030526 85258900 433 g	19,6 cm 15,0 cm 9,0 cm 2,6 l
	Mx-c26B-AU-6D016 c26B Complete Cam 6MP, B016, Day, Audio Package Hemispheric IP indoor camera for ceiling mounting • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 6 Megapixel Moonlight Sensor, color (day) • HD premium fisheye lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • 4-GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics (incl. behavioral detection), shock detector • 0.5 m/1.6 ft Ethernet patch cable • Interfaces: Ethernet 10/100 (RJ45), MxBus (via Mx-A-IOA-IC), USB, slot for MxIOBoard-IC (Mx-A-IOA-IC) • Color: white	4047438030540 85258900 442 g	19,6 cm 15,0 cm 9,0 cm 2,6 l

**Mx-c26B-AU-6N016****c26B Complete Cam 6MP, B016, Night, Audio Package**

Hemispheric IP indoor camera for ceiling mounting • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 6 Megapixel Moonlight Sensor, B/W (night) • HD premium fisheye lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • 4-GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics (incl. behavioral detection), shock detector • 0.5 m/1.6 ft Ethernet patch cable • Interfaces: Ethernet 10/100 (RJ45), MxBus (via Mx-A-IOA-IC), USB, slot for MxIOBoard-IC (Mx-A-IOA-IC) • Color: white

4047438030564 19,6 cm






85258900 15,0 cm

452 9 9,0 cm

2,6 l

i26B Indoor Camera „Mx6B“

Second Mx6 generation – with MxBus functionality and enhanced performance.

	Article No. / Name / Description	EAN / HS / weight	dimen.
	Mx-i26B-6D	4047438030816	19,6 cm
	i26B Body 6MP (Day)	85258900	14,8 cm
	i26 camera module (body) with 6 Megapixel Moonlight Sensor, color (day) and lens mount • Lens to be ordered individually (B036 to B237, focal length 3.6 to 23.7 mm, f/1.8) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 6 Megapixel Moonlight Sensor, color (day) • Max. image size: 6MP (3072 x 2048) • IP30, 0 to 40°C (32 to 104°F) • 4-GB microSD • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus (via Mx-A-IOA-IC), USB, slot for MxIOBoard-IC (Mx-A-IOA-IC) • Color: white	420 g	9,0 cm 2,6 l
	Mx-i26B-6D016	4047438030823	19,6 cm
	i26B Complete Cam 6MP, B016, Day	85258900	15,0 cm
	Hemispheric IP indoor camera for wall mounting • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 6 Megapixel Moonlight Sensor, color (day) • HD premium fisheye lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • Max. image size: 6MP (3072 x 2048) • IP30, 0 to 40°C (32 to 104°F) • 4-GB microSD • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus (via Mx-A-IOA-IC), USB, slot for MxIOBoard-IC (Mx-A-IOA-IC) • Color: white	423 g	9,0 cm 2,6 l
	Mx-i26B-6N	4047438030847	19,6 cm
	i26B Body 6MP (Night)	85258900	14,8 cm
	i26 camera module (body) with 6 Megapixel Moonlight Sensor, B/W (night) and lens mount • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Lens to be ordered individually (B036 to B237, focal length 3.6 to 23.7 mm, f/1.8) • Max. image size: 6MP (3072 x 2048) • IP30, 0 to 40°C (32 to 104°F) • 4-GB microSD • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus (via Mx-A-IOA-IC), USB, slot for MxIOBoard-IC (Mx-A-IOA-IC) • Color: white	420 g	9,0 cm 2,6 l
	Mx-i26B-6N016	4047438030854	19,6 cm
	i26B Complete Cam 6MP, B016, Night	85258900	15,0 cm
	Hemispheric IP indoor camera for wall mounting • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 6 Megapixel Moonlight Sensor, B/W (night) • HD premium fisheye lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • Max. image size: 6MP (3072 x 2048) • IP30, 0 to 40°C (32 to 104°F) • 4-GB microSD • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus (via Mx-A-IOA-IC), USB, slot for MxIOBoard-IC (Mx-A-IOA-IC) • Color: white	423 g	9,0 cm 2,6 l
	Mx-i26B-AU-6D016	4047438030878	19,6 cm
	i26B Complete Cam 6MP, B016, Day, Audio Package	85258900	15,0 cm
	Hemispheric IP indoor camera for wall mounting • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 6 Megapixel Moonlight Sensor, color (day) • HD premium fisheye lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • Max. image size: 6MP (3072 x 2048) • IP30, 0 to 40°C (32 to 104°F) • 4-GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus (via Mx-A-IOA-IC), USB, slot for MxIOBoard-IC (Mx-A-IOA-IC) • Color: white	429 g	9,0 cm 2,6 l

**Mx-i26B-AU-6N016****i26B Complete Cam 6MP, B016, Night, Audio Package**

Hemispheric IP indoor camera for wall mounting • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 6 Megapixel Moonlight Sensor, B/W (night) • HD premium fisheye lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • Max. image size: 6MP (3072 x 2048) • IP30, 0 to 40°C (32 to 104°F) • 4-GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus (via Mx-A-IOA-IC), USB, slot for MxIOBoard-IC (Mx-A-IOA-IC) • Color: white

4047438030892 19,6 cm




85258900 15,0 cm

429 g 9,0 cm

2,6 l

p26B Indoor Camera „Mx6B“

Second Mx6 generation – with MxBus functionality and enhanced performance.

	Article No. / Name / Description	EAN / HS / weight	dimen.
	Mx-p26B-6D p26B Body 6MP, Day p26 camera module (body) with image sensor and lens mount • Lens to be ordered individually (B036 to B237, focal length 3.6 to 23.7 mm, f/1.8) • Manually adjustable lens tilt angle -5° to -45° • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 6 Megapixel Moonlight Sensor, color (day) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • Internal DVR: 4-GB MicroSD • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus (via Mx-A-IOA-IC), USB, slot for MxIOBoard-IC (Mx-A-IOA-IC) • Color: white	4047438031226 85258900 582 g	19,6 cm 18,0 cm 14,8 cm 5,2 l
	Mx-p26B-6D016 p26B Complete Cam 6MP, B016, Day Hemispheric IP indoor camera for ceiling mounting • Manually adjustable lens tilt angle -5° to -45° • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 6 Megapixel Moonlight Sensor, color (day) • HD premium fisheye lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • Internal DVR: 4-GB MicroSD • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus (via Mx-A-IOA-IC), USB, slot for MxIOBoard-IC (Mx-A-IOA-IC) • Color: white	4047438031233 85258900 574 g	19,6 cm 18,0 cm 14,8 cm 5,2 l
	Mx-p26B-6N p26B Body 6MP, Night p26 camera module (body) with image sensor and lens mount • Lens to be ordered individually (B036 to B237, focal length 3.6 to 23.7 mm, f/1.8) • Manually adjustable lens tilt angle -5° to -45° • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 6 Megapixel Moonlight Sensor, B/W (night) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • Internal DVR: 4-GB MicroSD • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus (via Mx-A-IOA-IC), USB, slot for MxIOBoard-IC (Mx-A-IOA-IC) • Color: white	4047438031295 85258900 582 g	19,6 cm 18,0 cm 14,8 cm 5,2 l
	Mx-p26B-6N016 p26B Complete Cam 6MP, B016, Night Hemispheric IP indoor camera for ceiling mounting • Manually adjustable lens tilt angle -5° to -45° • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 6 Megapixel Moonlight Sensor, B/W (night) • HD premium fisheye lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • Internal DVR: 4-GB MicroSD • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus (via Mx-A-IOA-IC), USB, slot for MxIOBoard-IC (Mx-A-IOA-IC) • Color: white	4047438031301 85258900 574 g	19,6 cm 18,0 cm 14,8 cm 5,2 l
	Mx-p26B-AU-6D p26B Body 6MP, Day, Audio Package p26 camera module (body) with 6 Megapixel Moonlight Sensor, color (day) and lens mount • Lens to be ordered individually (B036 to B237, focal length 3.6 to 23.7 mm, f/1.8) • Manually adjustable lens tilt angle -5° to -45° • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 6 Megapixel Moonlight Sensor, color (day) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • 4-GB microSD • HD-Audio with integrated microphone and speaker • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus (via Mx-A-IOA-IC), USB, slot for MxIOBoard-IC (Mx-A-IOA-IC) • Color: white	4047438031325 85258900 591 g	19,6 cm 18,0 cm 14,8 cm 5,2 l

**Mx-p26B-AU-6D016****p26B Complete Cam 6MP, B016, Day, Audio Package**

Hemispheric IP indoor camera for ceiling mounting • Manually adjustable lens tilt angle -5° to -45° • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 6 Megapixel Moonlight Sensor, color (day) • HD premium fisheye lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • 4-GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus (via Mx-A-IOA-IC), USB, slot for MxIOBoard-IC (Mx-A-IOA-IC) • Color: white

4047438031332 19,6 cm
85258900 18,0 cm
480 g 14,8 cm
5,2 l

**Mx-p26B-AU-6N****p26B Body 6MP, Night, Audio Package**

p26 camera module (body) with 6 Megapixel Moonlight Sensor, B/W (night) and lens mount • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Lens to be ordered individually (B036 to B237, focal length 3.6 to 23.7 mm, f/1.8) • Manually adjustable lens tilt angle -5° to -45° • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • 4-GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus (via Mx-A-IOA-IC), USB, slot for MxIOBoard-IC (Mx-A-IOA-IC) • Color: white

4047438031356 19,6 cm
85258900 18,0 cm
480 g 14,8 cm
5,2 l



**Mx-p26B-AU-6N016****p26B Complete Cam 6MP, B016, Night, Audio Package**

Hemispheric IP indoor camera for ceiling mounting • Manually adjustable lens tilt angle -5° to -45° • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 6 Megapixel Moonlight Sensor, B/W (night) • HD premium fisheye lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • 4-GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus (via Mx-A-IOA-IC), USB, slot for MxIOBoard-IC (Mx-A-IOA-IC) • Color: white

4047438031363 19,6 cm
85258900 18,0 cm
480 g 14,8 cm
5,2 l

v26B Indoor Dome Camera „Mx6B“

Second Mx6 generation – with MxBus functionality and enhanced performance.

	Article No. / Name / Description	EAN / HS / weight	dimen.
	Mx-v26B-6D	4047438031547	19,6 cm
	v26B Body 6MP, Day, White	85258900	18,0 cm
	v26 camera module (body) with image sensor and lens mount • Lens to be ordered individually (B036 to B237, focal length 3.6 to 23.7 mm, f/1.8) • Manually adjustable lens tilt angle 0° to -90° • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 6 Megapixel Moonlight Sensor, color (day) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • Lens cover with sealing ring (polycarbonate, 1.5 mm) • Internal DVR: 4 GB microSD • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus (via Mx-A-IOA-IC), USB, slot for MxIOBoard-IC (Mx-A-IOA-IC) • Housing color: white	726 g	14,8 cm
	Mx-v26B-6N	4047438031578	19,6 cm
	v26B Body 6MP, Night, White	85258900	18,0 cm
	v26 camera module (body) with image sensor and lens mount • Lens to be ordered individually (B036 to B237, focal length 3.6 to 23.7 mm, f/1.8) • Manually adjustable lens tilt angle 0° to -90° • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • 6 Megapixel Moonlight Sensor, B/W (night) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • Lens cover with sealing ring (polycarbonate, 1.5 mm) • Internal DVR: 4 GB microSD • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus (via Mx-A-IOA-IC), USB, slot for MxIOBoard-IC (Mx-A-IOA-IC) • Housing color: white	726 g	14,8 cm





Professional Video Systems Thermal

BeyondHumanVision

MOBOTIX

M16B Thermal Camera „Mx6B“

Second Mx6 generation – with MxBus functionality and enhanced performance.

	Article No. / Name / Description	EAN / HS / weight	dimen.
	Mx-M16TB-R079-EN54-V2	4047438048330	29,6 cm
	M16B Thermographic Camera TR, 50 mK, R079 (45°) - EN54 EN54 V2 Bundle incl. EN54 compliant default configuration, MX-OPT-RS1-EXT RS232 module + MX-Overvoltage-Protection-Box-LSA + MX-OPT-NPA1-EXT PoE Outdoor Box • IP thermographic camera TR with Germanium Lens: B079 equivalent, horizontal/vertical image angle 45°/35° • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Thermal radiometry (TR): calibrated thermal sensor for temperature events from -40 to 550°C (-40 to 1022°F) • NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second, 336 x 252 pixels (can be scaled up to 6MP) • Optional optical 6MP sensor module (to be ordered individually) • IP66/IK07, -40 to 60°C (-40 to 140°F) • Internal DVR: 4 GB microSD • System components: speaker and microphone (inside housing), PIR sensor, temperature sensor, MxActivitySensor, shock detector • VarioFlex wall mount (can be used with additional ceiling mount MX-DH-M24-SecureFlex and pole mount MX-MH-SecureFlex-ESWS), ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45) • Incl. 1 Blind Module (MX-SM-Blind-PW)	90251900 2.170 g	26,8 cm 18,0 cm 14,3 l
	Mx-M16TB-R119-EN54-V2	4047438048347	29,6 cm
	M16B Thermographic Camera TR, 50 mK, R119 (25°) - EN54 EN54 Bundle incl. EN54 compliant default configuration, MX-OPT-RS1-EXT RS232 module + MX-Overvoltage-Protection-Box-LSA + MX-OPT-NPA1-EXT PoE Outdoor Box • IP thermographic camera TR with Germanium Lens: B119 equivalent, horizontal/vertical image angle 25°/19° • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Thermal radiometry (TR): calibrated thermal sensor for temperature events from -40 to 550°C (-40 to 1022°F) • NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second, 336 x 252 pixels (can be scaled up to 6MP) • Optional optical 6MP sensor module (to be ordered individually) • IP66/IK07, -40 to 60°C (-40 to 140°F) • Internal DVR: 4 GB microSD • System components: speaker and microphone (inside housing), PIR sensor, temperature sensor, MxActivitySensor, shock detector • VarioFlex wall mount (can be used with additional ceiling mount MX-DH-M24-SecureFlex and pole mount MX-MH-SecureFlex-ESWS), ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45) • Incl. 1 Blind Module (MX-SM-Blind-PW)	90251900 2.170 g	26,8 cm 18,0 cm 14,3 l
	Mx-M16TB-R237-EN54-V2	4047438048354	29,6 cm
	M16B Thermographic Camera TR, 50 mK, R237 (17°) - EN54 EN54 Bundle incl. EN54 compliant default configuration, MX-OPT-RS1-EXT RS232 module + MX-Overvoltage-Protection-Box-LSA + MX-OPT-NPA1-EXT PoE Outdoor Box • IP thermographic camera TR with Germanium Lens: B237 equivalent, horizontal/vertical image angle 17°/13° • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Thermal radiometry (TR): calibrated thermal sensor for temperature events from -40 to 550°C (-40 to 1022°F) • NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second, 336 x 252 pixels (can be scaled up to 6MP) • Optional optical 6MP sensor module (to be ordered individually) • IP66/IK07, -40 to 60°C (-40 to 140°F) • Internal DVR: 4 GB microSD • System components: speaker and microphone (inside housing), PIR sensor, temperature sensor, MxActivitySensor, shock detector • VarioFlex wall mount (can be used with additional ceiling mount MX-DH-M24-SecureFlex and pole mount MX-MH-SecureFlex-ESWS), ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45) • Incl. 1 Blind Module (MX-SM-Blind-PW)	90251900 2.170 g	26,8 cm 18,0 cm 14,3 l
	Mx-M16TB-R079	4047438030984	29,6 cm
	M16B Thermographic Camera TR, 50 mK, R079 (45°) IP thermographic camera TR with Germanium Lens: B079 equivalent, horizontal/vertical image angle 45°/35° • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Thermal radiometry (TR): calibrated thermal sensor for temperature events from -40 to 550°C (-40 to 1022°F) • NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second, 336 x 252 pixels (can be scaled up to 6MP) • Optional optical 6MP sensor module (to be ordered individually) • IP66/IK07, -40 to 60°C (-40 to 140°F) • Internal DVR: 4 GB microSD • System components: speaker and microphone (inside housing), PIR sensor, temperature sensor, MxActivitySensor, shock detector • VarioFlex wall mount (can be used with additional ceiling mount MX-DH-M24-SecureFlex and pole mount MX-MH-SecureFlex-ESWS), ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; IO and RS232 via additional MX Interface Box • Incl. 1 Blind Module (MX-SM-Blind-PW)	90251900 2.480 g	19,6 cm 18,0 cm 10,4 l

**Mx-M16TB-R090****M16B Thermographic Camera TR, 50 mK, R090 (35°)**

IP thermographic camera TR with Germanium Lens: B090 equivalent, horizontal/vertical image angle 35°/27° • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Thermal radiometry (TR): calibrated thermal sensor for temperature events from -40 to 550°C (-40 to 1022°F) • NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second, 336 x 252 pixels (can be scaled up to 6MP) • Optional optical 6MP sensor module (to be ordered individually) • IP66/IK07, -40 to 60°C (-40 to 140°F) • Internal DVR: 4 GB microSD • System components: speaker and microphone (inside housing), PIR sensor, temperature sensor, MxActivitySensor, shock detector • VarioFlex wall mount (can be used with additional ceiling mount MX-DH-M24-SecureFlex and pole mount MX-MH-SecureFlex-ESWS), ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; IO and RS232 via additional MX Interface Box • Incl. 1 Blind Module (MX-SM-Blind-PW)

4047438036795	29,6 cm
90251900	19,6 cm
2.480 g	18,0 cm
	10,4 l

**Mx-M16TB-R119****M16B Thermographic Camera TR, 50 mK, R119 (25°)**

IP thermographic camera TR with Germanium Lens: B119 equivalent, horizontal/vertical image angle 25°/19° • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Thermal radiometry (TR): calibrated thermal sensor for temperature events from -40 to 550°C (-40 to 1022°F) • NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second, 336 x 252 pixels (can be scaled up to 6MP) • Optional optical 6MP sensor module (to be ordered individually) • IP66/IK07, -40 to 60°C (-40 to 140°F) • Internal DVR: 4 GB microSD • System components: speaker and microphone (inside housing), PIR sensor, temperature sensor, MxActivitySensor, shock detector • VarioFlex wall mount (can be used with additional ceiling mount MX-DH-M24-SecureFlex and pole mount MX-MH-SecureFlex-ESWS), ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; IO and RS232 via additional MX Interface Box • Incl. 1 Blind Module (MX-SM-Blind-PW)

4047438030991	29,6 cm
90251900	19,6 cm
1.936 g	18,0 cm
	10,4 l

**Mx-M16TB-R237****M16B Thermographic Camera TR, 50 mK, R237 (17°)**

IP thermographic camera TR with Germanium Lens: B237 equivalent, horizontal/vertical image angle 17°/13° • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Thermal radiometry (TR): calibrated thermal sensor for temperature events from -40 to 550°C (-40 to 1022°F) • NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second, 336 x 252 pixels (can be scaled up to 6MP) • Optional optical 6MP sensor module (to be ordered individually) • IP66/IK07, -40 to 60°C (-40 to 140°F) • Internal DVR: 4 GB microSD • System components: speaker and microphone (inside housing), PIR sensor, temperature sensor, MxActivitySensor, shock detector • VarioFlex wall mount (can be used with additional ceiling mount MX-DH-M24-SecureFlex and pole mount MX-MH-SecureFlex-ESWS), ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; IO and RS232 via additional MX Interface Box • Incl. 1 Blind Module (MX-SM-Blind-PW)

4047438031004	29,6 cm
90251900	19,6 cm
1.942 g	18,0 cm
	10,4 l

**Mx-M16TB-R079-VDS****M16B Thermographic Camera TR, 50 mK, R079 (45°) - VDS**

VdS-Bundle • IP thermographic camera TR with Germanium Lens: B079 equivalent, horizontal/vertical image angle 45°/35° • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Thermal radiometry (TR): calibrated thermal sensor, detects critical temperature thresholds in the measuring range between 50° and 200° C (122° to 392°F) • NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second, 336 x 252 pixels (can be scaled up to 6MP) • IP66/IK07, -40 to 60°C (-40 to 140°F) • Internal DVR: 4 GB microSD • System components: speaker and microphone (inside housing), PIR sensor, temperature sensor, MxActivitySensor, shock detector • VarioFlex wall mount (can be used with additional ceiling mount MX-DH-M24-SecureFlex and pole mount MX-MH-SecureFlex-ESWS), ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; IO and RS232 via additional MX Interface Box • Incl. 1 Blind Module (MX-SM-Blind-PW) • Bundle content: Thermal camera, Mx-OPT-RS1-EXT, Mx-Overvoltage-Protection-Box-LSA, Mx-OPT-NPA1-EXT, Firmware Mx-FW-VDS-UP • Price on request

4047438041607	29,6 cm
90251900	26,8 cm
2.170 g	18,0 cm
	14,3 l

**Mx-M16TB-R119-VDS****M16B Thermographic Camera TR, 50 mK, R119 (25°) - VDS**

VdS Bundle • IP thermographic camera TR with Germanium Lens: B119 equivalent, horizontal/vertical image angle 25°/19° • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Thermal radiometry (TR): calibrated thermal sensor, detects critical temperature thresholds in the measuring range between 50° and 200° C (122° to 392°F) • NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second, 336 x 252 pixels (can be scaled up to 6MP) • IP66/IK07, -40 to 60°C (-40 to 140°F) • Internal DVR: 4 GB microSD • System components: speaker and microphone (inside housing), PIR sensor, temperature sensor, MxActivitySensor, shock detector • VarioFlex wall mount (can be used with additional ceiling mount MX-DH-M24-SecureFlex and pole mount MX-MH-SecureFlex-ESWS), ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; IO and RS232 via additional MX Interface Box • Incl. 1 Blind Module (MX-SM-Blind-PW) • Bundle content: Thermal camera, Mx-OPT-RS1-EXT, Mx-Overvoltage-Protection-Box-LSA, Mx-OPT-NPA1-EXT, Firmware Mx-FW-VDS-UP • Price on request

4047438041614	29,6 cm
90251900	26,8 cm
2.170 G	18,0 cm
	14,3 l

**Mx-M16TB-R237-VDS****M16B Thermographic Camera TR, 50 mK, R237 (17°) - VDS**

VdS Bundle • IP thermographic camera TR with Germanium Lens: B237 equivalent, horizontal/vertical image angle 17°/13° • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Thermal radiometry (TR): calibrated thermal sensor, detects critical temperature thresholds in the measuring range between 50° and 200° C (122° to 392°F) • NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second, 336 x 252 pixels (can be scaled up to 6MP) • IP66/IK07, -40 to 60°C (-40 to 140°F) • Internal DVR: 4 GB microSD • System components: speaker and microphone (inside housing), PIR sensor, temperature sensor, MxActivitySensor, shock detector • VarioFlex wall mount (can be used with additional ceiling mount MX-DH-M24-SecureFlex and pole mount MX-MH-SecureFlex-ESWS), ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; IO and RS232 via additional MX Interface Box • Incl. 1 Blind Module (MX-SM-Blind-PW) • Bundle content: Thermal camera, Mx-OPT-RS1-EXT, Mx-Overvoltage-Protection-Box-LSA, Mx-OPT-NPA1-EXT, Firmware Mx-FW-VDS-UP • Price on request

4047438041621	29,6 cm
90251900	26,8 cm
2.170 G	18,0 cm
	14,3 l

**Mx-M16TB-T079****M16B Thermographic Camera 50 mK, T079 (45°)**

IP thermographic camera with T079 thermal lens, horizontal/vertical image angle 45°/35°, optional connection of an additional optical 6MP sensor module (to be ordered individually) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Highly sensitive thermal image sensor: NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second • Image size (thermal): 336 x 252 pixels (can be scaled up) • IP66/IK07, -40 to 60°C (-40 to 140°F) • Internal DVR: 4 GB microSD • System components: speaker and microphone (inside housing), PIR sensor, temperature sensor, MxActivitySensor, shock detector • VarioFlex wall mount (can be used with additional ceiling mount MX-DH-M24-SecureFlex and pole mount MX-MH-SecureFlex-ESWS), ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; IO and RS232 via additional MX Interface Box • Incl. 1 Blind Module (MX-SM-Blind-PW)

4047438031011	29,6 cm
90251900	19,6 cm
2.460 G	18,0 cm
	10,4 l

**Mx-M16TB-T119****M16B Thermographic Camera 50 mK, T119 (25°)**

IP thermographic camera with T119 thermal lens, horizontal/vertical image angle 25°/19°, optional connection of an additional optical 6MP sensor module (to be ordered individually) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Highly sensitive thermal image sensor: NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second • Image size (thermal): 336 x 252 pixels (can be scaled up) • IP66/IK07, -40 to 60°C (-40 to 140°F) • Internal DVR: 4 GB microSD • System components: speaker and microphone (inside housing), PIR sensor, temperature sensor, MxActivitySensor, shock detector • VarioFlex wall mount (can be used with additional ceiling mount MX-DH-M24-SecureFlex and pole mount MX-MH-SecureFlex-ESWS), ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; IO and RS232 via additional MX Interface Box • Incl. 1 Blind Module (MX-SM-Blind-PW)

4047438031028	29,6 cm
90251900	19,6 cm
2.460 G	18,0 cm
	10,4 l



**Mx-M16TB-T237****M16B Thermographic Camera 50 mK, T237 (17°)**

IP thermographic camera with T237 thermal lens, horizontal/vertical image angle 17°/13°, optional connection of an additional optical 6MP sensor module (to be ordered individually) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Highly sensitive thermal image sensor: NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second • Image size (thermal): 336 x 252 pixels (can be scaled up) • IP66/IK07, -40 to 60°C (-40 to 140°F) • Internal DVR: 4 GB MicroSD • System components: speaker and microphone (inside housing), PIR sensor, temperature sensor, MxActivitySensor, shock detector • VarioFlex wall mount (can be used with additional ceiling mount MX-DH-M24-SecureFlex and pole mount MX-MH-SecureFlex-ESWS), ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; IO and RS232 via additional MX Interface Box • Incl. 1 Blind Module (MX-SM-Blind-PW)






4047438031035	29,6 cm
90251900	19,6 cm
1.946 9	18,0 cm
	10,4 l

M16B Thermal Camera „Mx6B“

Second Mx6 generation – with MxBus functionality and enhanced performance.

	Article No. / Name / Description	EAN / HS / weight	dimen.
	Mx-M16TB-R500	4047438035514	29,6 cm
	M16B Thermographic Camera 35 mK, R500 (9.3°)	90251900	19,6 cm
	IP thermographic camera with R500 thermal lens, horizontal/vertical image angle 9.3°/7.1°, optional connection of an additional optical 6MP sensor module (to be ordered individually) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Thermal radiometry (TR): calibrated thermal sensor for temperature events from -40 to 550°C (-40 to 1022°F): NETD typ. 35 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second • Image size (thermal): 336 x 252 pixels (can be scaled up) • IP66/IK07, -40 to 60°C (-40 to 140° F) • Internal DVR: 4 GB MicroSD • System components: speaker and microphone (inside housing), PIR sensor, temperature sensor, MxActivitySensor, shock detector • VarioFlex wall mount (can be used with additional ceiling mount MX-DH-M24-SecureFlex and pole mount MX-MH-SecureFlex-ESWS), ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; IO and RS232 via additional MX Interface Box • Incl. 1 Blind Module (MX-SM-Blind-PW)	1.946 g	18,0 cm 10,4 l
	Mx-M16TB-T500	4047438047500	29,6 cm
	M16B Thermographic Camera 50 mK, T500 (9.3°)	90251900	19,6 cm
	IP thermographic camera with T500 thermal lens, horizontal/vertical image angle 9.3°/7.1°, optional connection of an additional optical 6MP sensor module (to be ordered individually) • ONVIF-compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • Highly sensitive thermal image sensor: NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second • Image size (thermal): 336 x 252 pixels (can be scaled up) • IP66/IK07, -40 to 60°C (-40 to 140°F) • Internal DVR: 4 GB MicroSD • System components: speaker and microphone (inside housing), PIR sensor, temperature sensor, MxActivitySensor, shock detector • VarioFlex wall mount (can be used with additional ceiling mount MX-DH-M24-SecureFlex and pole mount MX-MH-SecureFlex-ESWS), ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; IO and RS232 via additional MX Interface Box • Incl. 1 Blind Module (MX-SM-Blind-PW)	1.946 g	18,0 cm 10,4 l

Sensor Module Thermal for MOBOTIX 7

	Article No. / Name / Description	EAN / HS / weight	dimen.
	Mx-O-M73TB-336R100 Thermal module 336-R100 with front plate for M73 (B) CIF (336 x 256 Pixel) • with Thermal Radiometry • 45° x 35° • incl. M73 replacement front plate	4047438040198 19,6 cm 90275000 18,0 cm 450 g 14,8 cm	5,2 l
	Mx-O-M73TB-336R150 Thermal module 336-R150 with front plate for M73 (B) CIF (336 x 256 Pixel) • with Thermal Radiometry • 25° x 19° • incl. M73 replacement front plate	4047438040204 19,6 cm 90275000 18,0 cm 450 g 14,8 cm	5,2 l
	Mx-O-M73TB-336R280 Thermal module 336-R280 with front plate for M73 (B) CIF (336 x 256 Pixel) • with Thermal Radiometry • 17° x 13° • incl. M73 replacement front plate	4047438040211 19,6 cm 90275000 18,0 cm 450 g 14,8 cm	5,2 l
	Mx-O-M73TB-336R500 Thermal module 336-R500 with front plate for M73 (B) CIF (336 x 256 Pixel) • with Thermal Radiometry • 9,3° x 7,1° • incl. M73 replacement front plate	4047438043557 19,6 cm 90275000 18,0 cm 450 g 14,8 cm	5,2 l
	Mx-O-M73TB-336T100 Thermal module 336-T100 with front plate for M73 (B) CIF (336 x 256 Pixel) • w/o Thermal Radiometry • 45° x 35° • incl. M73 replacement front plate	4047438040129 19,6 cm 90275000 18,0 cm 450 g 14,8 cm	5,2 l

**Mx-O-M73TB-336T150****Thermal module 336-T150 with front plate for M73 (B)**

CIF (336 x 256 Pixel) • w/o Thermal Radiometry • 25° x 19° • incl. M73 replacement front plate

4047438040136	19,6 cm
90275000	18,0 cm
450 g	14,8 cm
	5,2 l

**Mx-O-M73TB-336T280****Thermal module 336-T280 with front plate for M73 (B)**

CIF (336 x 256 Pixel) • w/o Thermal Radiometry • 17° x 13° • incl. M73 replacement front plate

4047438040143	19,6 cm
90275000	18,0 cm
450 g	14,8 cm
	5,2 l

**Mx-O-M73TB-336T500****Thermal module 336-T500 with front plate for M73 (B)**

CIF (336 x 256 Pixel) • w/o Thermal Radiometry • 9° x 7° • incl. M73 replacement front plate

4047438041287	19,6 cm
90275000	18,0 cm
450 g	14,8 cm
	5,2 l

**Mx-O-M73TB-640R050****Thermal module 640-R050 with front plate for M73 (B)**

VGA (640 x 480 Pixel) • with Thermal Radiometry • 90° x 69° • incl. M73 replacement front plate

4047438040228	19,6 cm
90275000	18,0 cm
450 g	14,8 cm
	5,2 l

**Mx-O-M73TB-640R080****Thermal module 640-R080 with front plate for M73 (B)**

VGA (640 x 480 Pixel) • with Thermal Radiometry • 69° x 56° • incl. M73 replacement front plate

4047438040235	19,6 cm
90275000	18,0 cm
450 g	14,8 cm
	5,2 l

**Mx-O-M73TB-640R100****Thermal module 640-R100 with front plate for M73 (B)**

VGA (640 x 480 Pixel) • with Thermal Radiometry • 45° x 37° • incl. M73 replacement front plate

4047438040242	19,6 cm
90275000	18,0 cm
450 g	14,8 cm
	5,2 l

**Mx-O-M73TB-640R150****Thermal module 640-R150 with front plate for M73 (B)**

VGA (640 x 480 Pixel) • with Thermal Radiometry • 32° x 26° • incl. M73 replacement front plate

4047438040259	19,6 cm
90275000	18,0 cm
450 g	14,8 cm
	5,2 l

**Mx-O-M73TB-640R280****Thermal module 640-R280 with front plate for M73 (B)**

VGA (640 x 480 Pixel) • with Thermal Radiometry • 18° x 14° • incl. M73 replacement front plate

4047438042598	19,6 cm
90275000	18,0 cm
450 g	14,8 cm
	5,2 l

**Mx-O-M73TB-640T050****Thermal module 640-T050 with front plate for M73 (B)**

VGA (640 x 480 Pixel) • w/o Thermal Radiometry • 90° x 69° • incl. M73 replacement front plate

4047438040150	19,6 cm
90275000	18,0 cm
450 g	14,8 cm
	5,2 l

**Mx-O-M73TB-640T080****Thermal module 640-T080 with front plate für M73 (B)**

VGA (640 x 480 Pixel) • w/o Thermal Radiometry • 69° x 56° • incl. M73 replacement front plate

4047438040167	19,6 cm
90275000	18,0 cm
450 g	14,8 cm
	5,2 l

**Mx-O-M73TB-640T100****Thermal module 640-T100 with front plate for M73 (B)**

VGA (640 x 480 Pixel) • w/o Thermal Radiometry • 45° x 37° • incl. M73 replacement front plate

4047438040174	19,6 cm
90275000	18,0 cm
450 g	14,8 cm
	5,2 l

**Mx-O-M73TB-640T150****Thermal module 640-T150 with front plate for M73 (B)**

VGA (640 x 480 Pixel) • w/o Thermal Radiometry • 32° x 26° • incl. M73 replacement front plate

4047438040181	19,6 cm
90275000	18,0 cm
450 g	14,8 cm
	5,2 l

**Mx-O-M73TB-640T280****Thermal module 640-T280 with front plate for M73 (B)**

VGA (640 x 480 Pixel) • w/o Thermal Radiometry • 18° x 14° • incl. M73 replacement front plate

4047438041294	19,6 cm
90275000	18,0 cm
450 g	14,8 cm
	5,2 l

**Mx-O-M7SA-320T040****Thermal Module ECO 320 - T040**

MOBOTIX 7 Thermal Module 320-T040 for M73/S74, CIF 320x240 • 9fps • 105° x 75°; 3,23mr • NETD: 65mK (typ); < 100mK (max) • IR Range 7,8 to 14µm • -40° to +65°C / 40° to 149°F • 5% to 95% non-condensing • IP66 • IK04

4047438040648	9,8 cm
90275000	7,5 cm
106 g	9,0 cm
	0,7 l

**Mx-O-M7SA-320T080****Thermal Module ECO 320 - T080**

MOBOTIX 7 Thermal Module 320-T080 for M73/S74, CIF 320x240 • 9fps • 56° x 42°; 3,00mr • NETD: 65mK (typ); < 100mK (max) • IR Range 7,8 to 14µm • -40° to +65°C / 40° to 149°F • 5% to 95% non-condensing • IP66 • IK04

4047438040655	9,8 cm
90275000	7,5 cm
106 g	9,0 cm
	0,7 l

**Mx-O-M7SB-336RP100****S7x PTMount Thermal 336-R100 (B model)**

CIF (336 x 256 Pixel) • with Thermal Radiometry • 45° x 35° • Equipped with a 2 meter connection cable

4047438040051	19,6 cm
90275000	18,0 cm
890 g	14,8 cm
	5,2 l

**Mx-O-M7SB-336RP150****S7x PTMount Thermal 336-R150 (B model)**


CIF (336 x 256 Pixel) • with Thermal Radiometry • 25° x 19° • Equipped with a 2 meter connection cable

4047438040068	19,6 cm
90275000	18,0 cm
890 g	14,8 cm
	5,2 l

**Mx-O-M7SB-336RP280****S7x PTMount Thermal 336-R280 (B model)**


CIF (336 x 256 Pixel) • with Thermal Radiometry • 17° x 13° • Equipped with a 2 meter connection cable

4047438040075	19,6 cm
90275000	18,0 cm
890 g	14,8 cm
	5,2 l




Mx-O-M7SB-336RS100
S7x Thermal Module 336-R100 (B model)
 CIF (336 x 256 Pixel) • with Thermal Radiometry • 45° x 35°

4047438039918	14,8 cm
90275000	9,8 cm
380 g	9,0 cm
	1,3 l



Mx-O-M7SB-336RS150
S7x Thermal module 336-R150 (B model)
 CIF (336 x 256 Pixel) • with Thermal Radiometry • 25° x 19°

4047438039925	14,8 cm
90275000	9,8 cm
380 g	9,0 cm
	1,3 l



Mx-O-M7SB-336RS280
S7x Thermal Module 336-R280 (B model)
 CIF (336 x 256 Pixel) • with Thermal Radiometry • 17° x 13°

4047438039932	14,8 cm
90275000	9,8 cm
380 g	9,0 cm
	1,3 l



Mx-O-M7SB-336TP100
S7x PTMount Thermal 336-T100 (B model)
 CIF (336 x 256 Pixel) • w/o Thermal Radiometry • 45° x 35° • Equipped with a 2 meter connection cable

4047438039987	19,6 cm
90275000	18,0 cm
890 g	14,8 cm
	5,2 l



Mx-O-M7SB-336TP150
S7x PTMount Thermal 336-T150 (B model)
 CIF (336 x 256 Pixel) • w/o Thermal Radiometry • 25° x 19° • Equipped with a 2 meter connection cable

4047438039994	19,6 cm
90275000	18,0 cm
890 g	14,8 cm
	5,2 l



Mx-O-M7SB-336TP280
S7x PTMount Thermal 336-T280 (B model)
 CIF (336 x 256 Pixel) • w/o Thermal Radiometry • 17° x 13° • Equipped with a 2 meter connection cable

4047438040006	19,6 cm
90275000	18,0 cm
890 g	14,8 cm
	5,2 l



Mx-O-M7SB-336TS100
S7x Thermal Module 336-T100 (B model)

CIF (336 x 256 Pixel) • w/o Thermal Radiometry • 45° x 35°

4047438039840	14,8 cm
90275000	9,8 cm
380 g	9,0 cm
	1,3 l



Mx-O-M7SB-336TS150
S7x Thermal module 336-T150 (B model)

CIF (336 x 256 Pixel) • w/o Thermal Radiometry • 25° x 19°

4047438039857	14,8 cm
90275000	9,8 cm
380 g	9,0 cm
	1,3 l



Mx-O-M7SB-336TS280
S7x Thermal Module 336-T280 (B model)

CIF (336 x 256 Pixel) • w/o Thermal Radiometry • 17° x 13°

4047438039864	14,8 cm
90275000	9,8 cm
380 g	9,0 cm
	1,3 l



Mx-O-M7SB-640RP050
S7x PTMount Thermal 640-R050 (B model)

VGA (640 x 480 Pixel) • with Thermal Radiometry • 90° x 69° Equipped with a 2 meter connection cable

4047438040082	19,6 cm
90275000	18,0 cm
890 g	14,8 cm
	5,2 l



Mx-O-M7SB-640RP080
S7x PTMount Thermal 640-R080 (B model)

VGA (640 x 480 Pixel) • with Thermal Radiometry • 69° x 56° Equipped with a 2 meter connection cable

4047438040099	19,6 cm
90275000	18,0 cm
890 g	14,8 cm
	5,2 l



Mx-O-M7SB-640RP100
S7x PTMount Thermal 640-R100 (B model)

VGA (640 x 480 Pixel) • with Thermal Radiometry • 45° x 37° Equipped with a 2 meter connection cable

4047438040105	19,6 cm
90275000	18,0 cm
890 g	14,8 cm
	5,2 l

**Mx-O-M7SB-640RP150****S7x PTMount Thermal 640-R150 (B model)**


VGA (640 x 480 Pixel) • with Thermal Radiometry • 30° x 26° • Equipped with a 2 meter connection cable

4047438040112	19,6 cm
90275000	18,0 cm
890 g	14,8 cm
	5,2 l

**Mx-O-M7SB-640RS050****S7x Thermal Module 640-R050 (B model)**


VGA (640 x 480 Pixel) • with Thermal Radiometry • 90° x 69°

4047438039949	14,8 cm
90275000	9,8 cm
380 g	9,0 cm
	1,3 l

**Mx-O-M7SB-640RS080****S7x Thermal Module 640-R080 (B model)**

VGA (640 x 480 Pixel) • with Thermal Radiometry • 90° x 56°

4047438039956	14,8 cm
90275000	9,8 cm
380 g	9,0 cm
	1,3 l

**Mx-O-M7SB-640RS100****S7x Thermal Module 640-R100 (B model)**

VGA (640 x 480 Pixel) • with Thermal Radiometry • 45° x 37°

4047438039963	14,8 cm
90275000	9,8 cm
380 g	9,0 cm
	1,3 l

**Mx-O-M7SB-640RS150****S7x Thermal module 640-R150 (B model)**

VGA (640 x 480 Pixel) • with Thermal Radiometry • 30° x 26°

4047438039970	14,8 cm
90275000	9,8 cm
380 g	9,0 cm
	1,3 l

**Mx-O-M7SB-640TP050****S7x PTMount Thermal 640-T050 (B model)**

VGA (640 x 480 Pixel) • w/o Thermal Radiometry • 90° x 69° • Equipped with a 2 meter connection cable

4047438040013	19,6 cm
90275000	18,0 cm
890 g	14,8 cm
	5,2 l

**Mx-O-M7SB-640TP080****S7x PTMount Thermal 640-T080 (B model)**

VGA (640 x 480 Pixel) • w/o Thermal Radiometry • 69° x 56° • Equipped with a 2 meter connection cable

4047438040020	19,6 cm
90275000	18,0 cm
890 g	14,8 cm
	5,2 l

**Mx-O-M7SB-640TP100****S7x PTMount Thermal 640-T100 (B model)**


VGA (640 x 480 Pixel) • w/o Thermal Radiometry • 45° x 37° • Equipped with a 2 meter connection cable

4047438040037	19,6 cm
90275000	18,0 cm
890 g	14,8 cm
	5,2 l

**Mx-O-M7SB-640TP150****S7x PTMount Thermal 640-T150 (B model)**


VGA (640 x 480 Pixel) • w/o Thermal Radiometry • 30° x 26° • Equipped with a 2 meter connection cable

4047438040044	19,6 cm
90275000	18,0 cm
890 g	14,8 cm
	5,2 l

**Mx-O-M7SB-640TS050****S7x Thermal Module 640-T050 (B model)**


VGA (640 x 480 Pixel) • w/o Thermal Radiometry • 90° x 69°

4047438039871	14,8 cm
90275000	9,8 cm
380 g	9,0 cm
	1,3 l

**Mx-O-M7SB-640TS080****S7x Thermal Module 640-T080 (B model)**

VGA (640 x 480 Pixel) • w/o Thermal Radiometry • 69° x 56°

4047438039888	14,8 cm
90275000	9,8 cm
380 g	9,0 cm
	1,3 l

**Mx-O-M7SB-640TS100****S7x Thermal module 640-T100 (B model)**

VGA (640 x 480 Pixel) • w/o Thermal Radiometry • 45° x 37°

4047438039895	14,8 cm
90275000	9,8 cm
380 g	9,0 cm
	1,3 l

**Mx-O-M7SB-640TS150****S7x Thermal module 640-T150 (B model)**

VGA (640 x 480 Pixel) • w/o Thermal Radiometry • 30° x 26°

4047438039901	14,8 cm
90275000	9,8 cm
380 g	9,0 cm
	1,3 l

M73A Thermal Camera

	Article No. / Name / Description	EAN / HS / weight	dimen.
	<p>Mx-M73TA-B336R100-EN54</p> <p>M73A Thermographic Camera TR(B), CIF, R100 (45°) - EN54</p> <p>EN54 bundle • M73A IP camera module (body) for connecting up to 1 additional optical sensor module (to be ordered individually) • ONVIF-S-compliant MOBOTIX 7 system platform with H.264 (Triple Streaming), H.265, MxPEG+ and M-JPEG • CIF Thermal sensor (336 x 256 Pixel), with Thermal Radiometry, 45° x 35° • Image sensor options (via sensor module): 4K (8 megapixels), color (day) and/or B/W (night) and/or color (day/night with IR cut) • Lens options (via sensor module): horizontal image angle from 95° to 15° • Max. image size (per image sensor): 4K UHD (3840 x 2160 pixels), 16:9 • WDR: 120 dB Tripple Shutter • Functional module: MultiSense (PIR, temperature, brightness sensor, Microphone), 1x miniUSB • Operating conditions: IP66/IK07, -40 to 65°C (-40 to 149 °F) • Internal DVR: 8 GB microSD (for MxPEG+ recordings) • Max. Power consumption: 25 W, supply via network cable, PoE Class 4 (IEEE 802.3af/at) • Connections: 1x RJ45 jack for weatherproof network connection via MOBOTIX patch cable (Ethernet 1000BaseT), 1x MOBOTIX module connection (optical), I/O (1x input, 1x output), 1x line in, 1x line out, 1x miniUSB • Software interface for MOBOTIX Certified Apps (based on Deep Learning, approx. 20 different 30-day demo versions pre-installed) • Housing: Aluminium, PBT-30GF • Color: white • Warranty: 5 years (optionally extendable up to 8 years) • Bundle content: Mx-M73A-RJ45, Mx-O-M73TB-336R100, Mx-F-MSA, Mx-O-M7SA-Blind</p>	<p>4047438043410</p> <p>90251900</p> <p>2.814 g</p>	<p>29,6 cm</p> <p>26,8 cm</p> <p>18,0 cm</p> <p>14,3 l</p>
	<p>Mx-M73TA-B336R150-EN54</p> <p>M73A Thermographic Camera TR(B), CIF, R150 (25°) - EN54</p> <p>EN54 bundle • M73A IP camera module (body) for connecting up to 1 additional optical sensor module (to be ordered individually) • ONVIF-S-compliant MOBOTIX 7 system platform with H.264 (Triple Streaming), H.265, MxPEG+ and M-JPEG • CIF Thermal sensor (336 x 256 Pixel), with Thermal Radiometry, 25° x 19° • Image sensor options (via sensor module): 4K (8 megapixels), color (day) and/or B/W (night) and/or color (day/night with IR cut) • Lens options (via sensor module): horizontal image angle from 95° to 15° • Max. image size (per image sensor): 4K UHD (3840 x 2160 pixels), 16:9 • WDR: 120 dB Tripple Shutter • Functional module: MultiSense (PIR, temperature, brightness sensor, Microphone), 1x miniUSB • Operating conditions: IP66/IK07, -40 to 65°C (-40 to 149 °F) • Internal DVR: 8 GB microSD (for MxPEG+ recordings) • Max. Power consumption: 25 W, supply via network cable, PoE Class 4 (IEEE 802.3af/at) • Connections: 1x RJ45 jack for weatherproof network connection via MOBOTIX patch cable (Ethernet 1000BaseT), 1x MOBOTIX module connection (optical), I/O (1x input, 1x output), 1x line in, 1x line out, 1x miniUSB • Software interface for MOBOTIX Certified Apps (based on Deep Learning, approx. 20 different 30-day demo versions pre-installed) • Housing: Aluminium, PBT-30GF • Color: white • Warranty: 5 years (optionally extendable up to 8 years) • Bundle content: Mx-M73A-RJ45, Mx-O-M73TB-336R150, Mx-F-MSA, Mx-O-M7SA-Blind</p>	<p>4047438043427</p> <p>90251900</p> <p>2.814 g</p>	<p>29,6 cm</p> <p>26,8 cm</p> <p>18,0 cm</p> <p>14,3 l</p>
	<p>Mx-M73TA-B336R280-EN54</p> <p>M73A Thermographic Camera TR(B), CIF, R280 (17°) - EN54</p> <p>EN54 bundle • M73A IP camera module (body) for connecting up to 1 additional optical sensor module (to be ordered individually) • ONVIF-S-compliant MOBOTIX 7 system platform with H.264 (Triple Streaming), H.265, MxPEG+ and M-JPEG • CIF Thermal sensor (336 x 256 Pixel), with Thermal Radiometry, 17° x 13° • Image sensor options (via sensor module): 4K (8 megapixels), color (day) and/or B/W (night) and/or color (day/night with IR cut) • Lens options (via sensor module): horizontal image angle from 95° to 15° • Max. image size (per image sensor): 4K UHD (3840 x 2160 pixels), 16:9 • WDR: 120 dB Tripple Shutter • Functional module: MultiSense (PIR, temperature, brightness sensor, Microphone), 1x miniUSB • Operating conditions: IP66/IK07, -40 to 65°C (-40 to 149 °F) • Internal DVR: 8 GB microSD (for MxPEG+ recordings) • Max. Power consumption: 25 W, supply via network cable, PoE Class 4 (IEEE 802.3af/at) • Connections: 1x RJ45 jack for weatherproof network connection via MOBOTIX patch cable (Ethernet 1000BaseT), 1x MOBOTIX module connection (optical), I/O (1x input, 1x output), 1x line in, 1x line out, 1x miniUSB • Software interface for MOBOTIX Certified Apps (based on Deep Learning, approx. 20 different 30-day demo versions pre-installed) • Housing: Aluminium, PBT-30GF • Color: white • Warranty: 5 years (optionally extendable up to 8 years) • Bundle content: Mx-M73A-RJ45, Mx-O-M73TB-336R280, Mx-F-MSA, Mx-O-M7SA-Blind</p>	<p>4047438043434</p> <p>90251900</p> <p>2.814 g</p>	<p>29,6 cm</p> <p>26,8 cm</p> <p>18,0 cm</p> <p>14,3 l</p>

**Mx-M73TA-B640R050-EN54****M73A Thermographic Camera TR(B), VGA, R050 (90°) - EN54**

EN54 bundle • M73A IP camera module (body) for connecting up to 1 additional optical sensor module (to be ordered individually) • ONVIF-S-compliant MOBOTIX 7 system platform with H.264 (Triple Streaming), H.265, MxPEG+ and M-JPEG • VGA Thermal sensor (640 x 480 Pixel), with Thermal Radiometry, 90° x 69° • Image sensor options (via sensor module): 4K (8 megapixels), color (day) and/or B/W (night) and/or color (day/night with IR cut) • Lens options (via sensor module): horizontal image angle from 95° to 15° • Max. image size (per image sensor): 4K UHD (3840 x 2160 pixels), 16:9 • WDR: 120 dB Tripple Shutter • Functional module: MultiSense (PIR, temperature, brightness sensor, Microphone), 1x miniUSB • Operating conditions: IP66/IK07, -40 to 65°C (-40 to 149 °F) • Internal DVR: 8 GB microSD (for MxPEG+ recordings) • Max. Power consumption: 25 W, supply via network cable, PoE Class 4 (IEEE 802.3af/at) • Connections: 1x RJ45 jack for weatherproof network connection via MOBOTIX patch cable (Ethernet 1000BaseT), 1x MOBOTIX module connection (optical), I/O (1x input, 1x output), 1x line in, 1x line out, 1x miniUSB • Software interface for MOBOTIX Certified Apps (based on Deep Learning, approx. 20 different 30-day demo versions pre-installed) • Housing: Aluminium, PBT-30GF • Color: white • Warranty: 5 years (optionally extendable up to 8 years) • Bundle content: Mx-M73A-RJ45, Mx-O-M73TB-640R050, Mx-F-MSA, Mx-O-M7SA-Blind

4047438043441	29,6 cm
90251900	26,8 cm
2.814 G	18,0 cm
	14,3 l

**Mx-M73TA-B640R080-EN54****M73A Thermographic Camera TR(B), VGA, R080 (69°) - EN54**

EN54 bundle • M73A IP camera module (body) for connecting up to 1 additional optical sensor module (to be ordered individually) • ONVIF-S-compliant MOBOTIX 7 system platform with H.264 (Triple Streaming), H.265, MxPEG+ and M-JPEG • VGA Thermal sensor (640 x 480 Pixel), with Thermal Radiometry, 69° x 56° • Image sensor options (via sensor module): 4K (8 megapixels), color (day) and/or B/W (night) and/or color (day/night with IR cut) • Lens options (via sensor module): horizontal image angle from 95° to 15° • Max. image size (per image sensor): 4K UHD (3840 x 2160 pixels), 16:9 • WDR: 120 dB Tripple Shutter • Functional module: MultiSense (PIR, temperature, brightness sensor, Microphone), 1x miniUSB • Operating conditions: IP66/IK07, -40 to 65°C (-40 to 149 °F) • Internal DVR: 8 GB microSD (for MxPEG+ recordings) • Max. Power consumption: 25 W, supply via network cable, PoE Class 4 (IEEE 802.3af/at) • Connections: 1x RJ45 jack for weatherproof network connection via MOBOTIX patch cable (Ethernet 1000BaseT), 1x MOBOTIX module connection (optical), I/O (1x input, 1x output), 1x line in, 1x line out, 1x miniUSB • Software interface for MOBOTIX Certified Apps (based on Deep Learning, approx. 20 different 30-day demo versions pre-installed) • Housing: Aluminium, PBT-30GF • Color: white • Warranty: 5 years (optionally extendable up to 8 years) • Bundle content: Mx-M73A-RJ45, Mx-O-M73TB-640R080, Mx-F-MSA, Mx-O-M7SA-Blind

4047438043458	29,6 cm
90251900	26,8 cm
2.814 G	18,0 cm
	14,3 l

**Mx-M73TA-B640R100-EN54****M73A Thermographic Camera TR(B), VGA, R100 (45°) - EN54**

EN54 bundle • M73A IP camera module (body) for connecting up to 1 additional optical sensor module (to be ordered individually) • ONVIF-S-compliant MOBOTIX 7 system platform with H.264 (Triple Streaming), H.265, MxPEG+ and M-JPEG • VGA Thermal sensor (640 x 480 Pixel), with Thermal Radiometry, 45° x 37° • Image sensor options (via sensor module): 4K (8 megapixels), color (day) and/or B/W (night) and/or color (day/night with IR cut) • Lens options (via sensor module): horizontal image angle from 95° to 15° • Max. image size (per image sensor): 4K UHD (3840 x 2160 pixels), 16:9 • WDR: 120 dB Tripple Shutter • Functional module: MultiSense (PIR, temperature, brightness sensor, Microphone), 1x miniUSB • Operating conditions: IP66/IK07, -40 to 65°C (-40 to 149 °F) • Internal DVR: 8 GB microSD (for MxPEG+ recordings) • Max. Power consumption: 25 W, supply via network cable, PoE Class 4 (IEEE 802.3af/at) • Connections: 1x RJ45 jack for weatherproof network connection via MOBOTIX patch cable (Ethernet 1000BaseT), 1x MOBOTIX module connection (optical), I/O (1x input, 1x output), 1x line in, 1x line out, 1x miniUSB • Software interface for MOBOTIX Certified Apps (based on Deep Learning, approx. 20 different 30-day demo versions pre-installed) • Housing: Aluminium, PBT-30GF • Color: white • Warranty: 5 years (optionally extendable up to 8 years) • Bundle content: Mx-M73A-RJ45, Mx-O-M73TB-640R100, Mx-F-MSA, Mx-O-M7SA-Blind

4047438043465	29,6 cm
90251900	26,8 cm
2.814 G	18,0 cm
	14,3 l

**Mx-M73TA-B640R150-EN54****M73A Thermographic Camera TR(B), VGA, R150 (32°) - EN54**

EN54 bundle • M73A IP camera module (body) for connecting up to 1 additional optical sensor module (to be ordered individually) • ONVIF-S-compliant MOBOTIX 7 system platform with H.264 (Triple Streaming), H.265, MxPEG+ and M-JPEG • VGA Thermal sensor (640 x 480 Pixel), with Thermal Radiometry, 32° x 26° • Image sensor options (via sensor module): 4K (8 megapixels), color (day) and/or B/W (night) and/or color (day/night with IR cut) • Lens options (via sensor module): horizontal image angle from 95° to 15° • Max. image size (per image sensor): 4K UHD (3840 x 2160 pixels), 16:9 • WDR: 120 dB Tripple Shutter • Functional module: MultiSense (PIR, temperature, brightness sensor, Microphone), 1x miniUSB • Operating conditions: IP66/IK07, -40 to 65°C (-40 to 149 °F) • Internal DVR: 8 GB microSD (for MxPEG+ recordings) • Max. Power consumption: 25 W, supply via network cable, PoE Class 4 (IEEE 802.3af/at) • Connections: 1x RJ45 jack for weatherproof network connection via MOBOTIX patch cable (Ethernet 1000BaseT), 1x MOBOTIX module connection (optical), I/O (1x input, 1x output), 1x line in, 1x line out, 1x miniUSB • Software interface for MOBOTIX Certified Apps (based on Deep Learning, approx. 20 different 30-day demo versions pre-installed) • Housing: Aluminium, PBT-30GF • Color: white • Warranty: 5 years (optionally extendable up to 8 years) • Bundle content: Mx-M73A-RJ45, Mx-O-M73TB-640R150, Mx-F-MSA, Mx-O-M73A-Blind

4047438043472 29,6 cm

90251900 26,8 cm

2.814 9 18,0 cm

14,3 l

Sensor Modules Thermal For S16A/S16B

	Article No. / Name / Description	EAN / HS / weight	dimen.
	Mx-O-SMA-TS-R090	4047438048408	17,5 cm
	Thermal Sensor Module TR for S16/S15, 50 mK, B090 (35°)	90275000	14,0 cm
	Thermal Sensor Module TR for the S16/S15 • Thermal radiometry (TR): calibrated thermal sensor for temperature events from -40 to 550°C (-40 to 1022°F) • NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second • Germanium Lens (included): B090 equivalent, horizontal/vertical image angle 35°/27° • Image size: 336 x 252 pixels (can be scaled up to 6MP) • IP66, -30 to 60°C (-22 to 140°F) • Housing: Black anodized aluminum • Camera connection via MOBOTIX sensor cable (max. 3 m/9.8 ft, to be ordered individually)	650 g	13,5 cm 3,3 l
	Mx-O-SMA-TS-R079	4047438030090	17,5 cm
	Thermal Sensor Module TR For S16/S15, 50 mK, B079 (45°)	90275000	14,0 cm
	Thermal Sensor Module TR for the S16/S15 • Thermal radiometry (TR): calibrated thermal sensor for temperature events from -40 to 550°C (-40 to 1022°F) • NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second • Germanium Lens (included): B079 equivalent, horizontal/vertical image angle 45°/35° • Image size: 336 x 252 pixels (can be scaled up to 6MP) • IP66, -30 to 60°C (-22 to 140°F) • Housing: Black anodized aluminum • Camera connection via MOBOTIX sensor cable (max. 3 m/9.8 ft, to be ordered individually)	650 g	13,5 cm 3,3 l
	Mx-O-SMA-TS-R119	4047438030106	17,5 cm
	Thermal Sensor Module TR For S16/S15, 50 mK, B119 (25°)	90275000	14,0 cm
	Thermal Sensor Module TR for the S16/S15 • Thermal radiometry (TR): calibrated thermal sensor for temperature events from -40 to 550°C (-40 to 1022°F) • NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second • Germanium Lens (included): B119 equivalent, horizontal/vertical image angle 25°/19° • Image size: 336 x 252 pixels (can be scaled up to 6MP) • IP66, -30 to 60°C (-22 to 140°F) • Housing: Black anodized aluminum • Camera connection via MOBOTIX sensor cable (max. 3 m/9.8 ft, to be ordered individually)	650 g	13,5 cm 3,3 l
	Mx-O-SMA-TS-R237	4047438030113	17,5 cm
	Thermal Sensor Module TR For S16/S15, 50 mK, B237 (17°)	90275000	14,0 cm
	Thermal Sensor Module TR for the S16/S15 • Thermal radiometry (TR): calibrated thermal sensor for temperature events from -40 to 550°C (-40 to 1022°F) • NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second • Germanium Lens (included): B237 equivalent, horizontal/vertical image angle 17°/13° • Image size: 336 x 252 pixels (can be scaled up to 6MP) • IP66, -30 to 60°C (-22 to 140°F) • Housing: Black anodized aluminum • Camera connection via MOBOTIX sensor cable (max. 3 m/9.8 ft, to be ordered individually)	650 g	13,5 cm 3,3 l
	Mx-O-SMA-TP-R079	4047438030120	19,6 cm
	PTMount-Thermal TR For S16/S15, 50 mK, B079 (45°), White	90275000	18,0 cm
	PTMount-Thermal TR for the S16/S15 • Thermal radiometry (TR): calibrated thermal sensor for temperature events from -40 to 550°C (-40 to 1022°F) • NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second • Germanium Lens (2 m/6.6 ft, included): B079 equivalent, horizontal/vertical image angle 45°/35° • Image size: 336 x 252 pixels (can be scaled up to 6MP) • IP66, -30 to 60°C (-22 to 140°F) • Camera connection via MOBOTIX sensor cable (2 m/6.6 ft, included) • Color: White	890 g	14,8 cm 5,2 l

**Mx-O-SMA-TP-R119****PTMount-Thermal TR For S16/S15, 50 mK, B119 (25°), White**

PTMount-Thermal TR for the S16/S15 • Thermal radiometry (TR): calibrated thermal sensor for temperature events from -40 to 550 °C (-40 to 1022°F) • NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second • Germanium Lens (2 m/6.6 ft, included): B119 equivalent, horizontal/vertical image angle 25°/19° • Image size: 336 x 252 pixels (can be scaled up to 6MP) • IP66, -30 to 60°C (-22 to 140°F) • Camera connection via MOBOTIX sensor cable (2 m/6.6 ft, included) • Color: White

4047438030137	19,6 cm
90275000	18,0 cm
890 G	14,8 cm
	5,2 l

**Mx-O-SMA-TP-R237****PTMount-Thermal TR For S16/S15, 50 mK, B237 (17°), White**

PTMount-Thermal TR for the S16/S15 • Thermal radiometry (TR): calibrated thermal sensor for temperature events from -40 to 550 °C (-40 to 1022°F) • NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second • Germanium Lens (2 m/6.6 ft, included): B237 equivalent, horizontal/vertical image angle 17°/13° • Image size: 336 x 252 pixels (can be scaled up to 6MP) • IP66, -30 to 60°C (-22 to 140°F) • Camera connection via MOBOTIX sensor cable (2 m/6.6 ft, included) • Color: White

4047438030144	19,6 cm
90275000	18,0 cm
890 G	14,8 cm
	5,2 l

**Mx-O-SMA-TP-R079-b****PTMount-Thermal TR For S16/S15, 50 mK, B079 (45°), Black**

PTMount-Thermal TR for the S16/S15 • Thermal radiometry (TR): calibrated thermal sensor for temperature events from -40 to 550 °C (-40 to 1022°F) • NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second • Germanium Lens (2 m/6.6 ft, included): B079 equivalent, horizontal/vertical image angle 45°/35° • Image size: 336 x 252 pixels (can be scaled up to 6MP) • IP66, -30 to 60°C (-22 to 140°F) • Camera connection via MOBOTIX sensor cable (2 m/6.6 ft, included) • Color: Black

4047438030151	19,6 cm
90275000	18,0 cm
890 G	14,8 cm
	5,2 l

**Mx-O-SMA-TP-R119-b****PTMount-Thermal TR For S16/S15, 50 mK, B119 (25°), Black**

PTMount-Thermal TR for the S16/S15 • Thermal radiometry (TR): calibrated thermal sensor for temperature events from -40 to 550 °C (-40 to 1022°F) • NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second • Germanium Lens (2 m/6.6 ft, included): B119 equivalent, horizontal/vertical image angle 25°/19° • Image size: 336 x 252 pixels (can be scaled up to 6MP) • IP66, -30 to 60°C (-22 to 140°F) • Camera connection via MOBOTIX sensor cable (2 m/6.6 ft, included) • Color: Black

4047438030168	19,6 cm
90275000	18,0 cm
890 G	14,8 cm
	5,2 l

**Mx-O-SMA-TP-R237-b****PTMount-Thermal TR For S16/S15, 50 mK, B237 (17°), Black**

PTMount-Thermal TR for the S16/S15 • Thermal radiometry (TR): calibrated thermal sensor for temperature events from -40 to 550 °C (-40 to 1022°F) • NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second • Germanium Lens (2 m/6.6 ft, included): B237 equivalent, horizontal/vertical image angle 17°/13° • Image size: 336 x 252 pixels (can be scaled up to 6MP) • IP66, -30 to 60°C (-22 to 140°F) • Camera connection via MOBOTIX sensor cable (2 m/6.6 ft, included) • Color: Black

4047438030175	19,6 cm
90275000	18,0 cm
890 G	14,8 cm
	5,2 l

**Mx-O-SMA-TS-T079****Thermal Sensor Module For S16/S15, 50 mK, B079 (45°)**

Suitable for: S16/S15 (to be ordered individually) • Highly sensitive thermal image sensor: NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second • Germanium Lens (included): B079, horizontal/vertical image angle 45°/35° • Image size: 336 x 252 pixels (can be scaled up to 6MP) • IP66, -30 to 60°C (-22 to 140°F) • Housing: Black anodized aluminum • Camera connection via MOBOTIX sensor cable (max. 3 m/9.8 ft, to be ordered individually)

4047438029049	17,5 cm
90275000	14,0 cm
650 G	13,5 cm
	3,3 l

**Mx-O-SMA-TS-T119****Thermal Sensor Module For S16/S15, 50 mK, B119 (25°)**

Suitable for: S16/S15 (to be ordered individually) • Highly sensitive thermal image sensor: NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second • Germanium Lens (included): B119, horizontal/vertical image angle 25°/19° • Image size: 336 x 252 pixels (can be scaled up to 6MP) • IP66, -30 to 60°C (-22 to 140°F) • Housing: black anodized aluminum • Camera connection via MOBOTIX sensor cable (max. 3 m/9.8 ft, to be ordered individually)

4047438029056	17,5 cm
90275000	14,0 cm
650 9	13,5 cm
	3,3 l

**Mx-O-SMA-TS-T237****Thermal Sensor Module For S16/S15, 50 mK, B237 (17°)**

Suitable for: S16/S15 (to be ordered individually) • Highly sensitive thermal image sensor: NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second • Germanium Lens (included): B237, horizontal/vertical image angle 17°/13° • Image size: 336 x 252 pixels (can be scaled up to 6MP) • IP66, -30 to 60°C (-22 to 140°F) • Housing: black anodized aluminum • Camera connection via MOBOTIX sensor cable (max. 3 m/9,8 ft, to be ordered individually)

4047438029063	17,5 cm
90275000	14,0 cm
650 9	13,5 cm
	3,3 l

**Mx-O-SMA-TP-T079****PTMount-Thermal For S16/S15, 50 mK, B079 (45°), White**

PTMount-Thermal with integrated highly sensitive thermal image sensor for the S16/S15 • NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second • Germanium Lens (included): B079, horizontal/vertical image angle 45°/35° • Image size: 336 x 252 pixels (can be scaled up to 6MP) • Operating conditions: IP66, -30 to 60°C (-22 to 140°F) • Camera connection via MOBOTIX sensor cable (2 m/6.6 ft, included) • Color: White

4047438029070	19,6 cm
90275000	18,0 cm
890 9	14,8 cm
	5,2 l

**Mx-O-SMA-TP-T119****PTMount-Thermal For S16/S15, 50 mK, B119 (25°), White**

PTMount-Thermal with integrated highly sensitive thermal image sensor for the S16/S15 • NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second • Germanium Lens (included): B119, horizontal/vertical image angle 25°/19° • Image size: 336 x 252 pixels (can be scaled up to 6MP) • Operating conditions: IP66, -30 to 60°C (-22 to 140°F) • Camera connection via MOBOTIX sensor cable (2 m/6.6 ft, included) • Color: White

4047438029087	19,6 cm
90275000	18,0 cm
890 9	14,8 cm
	5,2 l

**Mx-O-SMA-TP-T237****PTMount Thermal For S16/S15, 50 mK, B237 (17°), White**

PTMount-Thermal with integrated highly sensitive thermal image sensor for the S16/S15 • NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second • Germanium Lens (included): B237, horizontal/vertical image angle 17°/13° • Image size: 336 x 252 pixels (can be scaled up to 6MP) • Operating conditions: IP66, -30 to 60°C (-22 to 140°F) • Camera connection via MOBOTIX sensor cable (2 m/6.6 ft, included) • Color: White

4047438029094	19,6 cm
90275000	18,0 cm
890 9	14,8 cm
	5,2 l

**Mx-O-SMA-TP-T079-b****PTMount-Thermal For S16, S15, 50 mK, B079 (45°), Black**

PTMount-Thermal with integrated highly sensitive thermal image sensor for the S16, S15 • NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second • Germanium Lens (included): B079, horizontal/vertical image angle 45°/35° • Image size: 336 x 252 pixels (can be scaled up to 6MP) • Operating conditions: IP66, -30 to 60°C (-22 to 140°F) • Camera connection via MOBOTIX sensor cable (2 m/6.6 ft, included) • Color: Black

4047438030021	19,6 cm
90275000	18,0 cm
890 9	14,8 cm
	5,2 l

**Mx-O-SMA-TP-T119-b****PTMount-Thermal For S16, S15, 50 mK, B119 (25°), Black**

PTMount-Thermal with integrated highly sensitive thermal image sensor for the S16, S15 • NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second • Germanium Lens (included): B119, horizontal/vertical image angle 25°/19° • Image size: 336 x 252 pixels (can be scaled up to 6MP) • Operating conditions: IP66, -30 to 60°C (-22 to 140°F) • Camera connection via MOBOTIX sensor cable (2 m/6.6 ft, included) • Color: Black

4047438030038	19,6 cm
90275000	18,0 cm
890 9	14,8 cm
	5,2 l

**Mx-O-SMA-TP-T237-b****PTMount Thermal For S16, S15, 50 mK, B237 (17°), Black**

PTMount-Thermal with integrated highly sensitive thermal image sensor for the S16, S15 • NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second • Germanium Lens (included): B237, horizontal/vertical image angle 17°/13° • Image size: 336 x 252 pixels (can be scaled up to 6MP) • Operating conditions: IP66, -30 to 60°C (-22 to 140°F) • Camera connection via MOBOTIX sensor cable (2 m/6.6 ft, included) • Color: black

4047438030045	19,6 cm
90275000	18,0 cm
890 9	14,8 cm
	5,2 l

S74 Thermal Bundle

	Article No. / Name / Description	EAN / HS / weight	dimen.
	<p>Mx-S74TA-B336R100-EN54</p> <p>S74A Thermographic Camera TR(B), CIF, R100 (45°) - EN54</p> <p>EN54 bundle • S74A IP camera module (body) for connecting up to two additional functional and optical sensor modules (to be ordered individually) • ONVIF-S/T-compliant MOBOTIX 7 system platform with H.264/H.265 (Triple Streaming), MxPEG+ and M-JPEG • CIF Thermal sensor (336x256 Pixel), with Thermal Radiometry, 45° x 35° • Image sensor options (via sensor module): 4K (8 megapixels), color (day) and/or B/W (night) and/or color (day/night with IR cut) • Lens options (via sensor module): horizontal image angle from 95° to 15° • Max. image size (per image sensor): 4K UHD (3840 x 2160 pixels), 16:9 • WDR: up to 120 dB • Functional extensions (via optional MOBOTIX modules): IR Light (supports 15°, 45°, 95° lenses), USB-C • Operating conditions: IP66/IK010 (housing), -40 to 65°C (-40 to 149 °F) • Internal DVR: 8 GB microSD (for MxPEG+ recordings) • Max. Power consumption: 25 W, supply via network cable, PoE Class 4 (IEEE 802.3af/at) • Connections: 1x RJ45 jack for weatherproof network connection via MOBOTIX patch cable (Ethernet 1000BaseT), 2x MOBOTIX module connection (1x optical/1x functional), USB-C, further connections via interface board • Software interface for MOBOTIX Certified Apps (based on Deep Learning, approx. 20 different 30-day demo versions pre-installed) • Housing: Aluminium, PBT-30GF • Color: white • Warranty: 5 years (optionally extendable up to 8 years) • Bundle content: Mx-S74A, Mx-F-S7A-RJ45-VDC, Mx-O-M7SB-336RP100, Mx-F-MSA, Mx-M-PTMA, 2xMx-A-S7A-CBL03-AN</p>	<p>4047438043489</p> <p>90251900</p> <p>3.520 g</p>	<p>40,8 cm</p> <p>31,2 cm</p> <p>20,2 cm</p> <p>25,7 l</p>
	<p>Mx-S74TA-B336R150-EN54</p> <p>S74A Thermographic Camera TR(B), CIF, R150 (25°) - EN54</p> <p>EN54 bundle • S74A IP camera module (body) for connecting up to two additional functional and optical sensor modules (to be ordered individually) • ONVIF-S/T-compliant MOBOTIX 7 system platform with H.264/H.265 (Triple Streaming), MxPEG+ and M-JPEG • CIF Thermal sensor (336x256 Pixel), with Thermal Radiometry, 25° x 19° • Image sensor options (via sensor module): 4K (8 megapixels), color (day) and/or B/W (night) and/or color (day/night with IR cut) • Lens options (via sensor module): horizontal image angle from 95° to 15° • Max. image size (per image sensor): 4K UHD (3840 x 2160 pixels), 16:9 • WDR: up to 120 dB • Functional extensions (via optional MOBOTIX modules): IR Light (supports 15°, 45°, 95° lenses), USB-C • Operating conditions: IP66/IK010 (housing), -40 to 65°C (-40 to 149 °F) • Internal DVR: 8 GB microSD (for MxPEG+ recordings) • Max. Power consumption: 25 W, supply via network cable, PoE Class 4 (IEEE 802.3af/at) • Connections: 1x RJ45 jack for weatherproof network connection via MOBOTIX patch cable (Ethernet 1000BaseT), 2x MOBOTIX module connection (1x optical/1x functional), USB-C, further connections via interface board • Software interface for MOBOTIX Certified Apps (based on Deep Learning, approx. 20 different 30-day demo versions pre-installed) • Housing: Aluminium, PBT-30GF • Color: white • Warranty: 5 years (optionally extendable up to 8 years) • Bundle content: Mx-S74A, Mx-F-S7A-RJ45-VDC, Mx-O-M7SB-336RP150, Mx-F-MSA, Mx-M-PTMA, 2xMx-A-S7A-CBL03-AN</p>	<p>4047438043496</p> <p>90251900</p> <p>3.520 g</p>	<p>40,8 cm</p> <p>31,2 cm</p> <p>20,2 cm</p> <p>25,7 l</p>
	<p>Mx-S74TA-B336R280-EN54</p> <p>S74A Thermographic Camera TR(B), CIF, R280 (17°) - EN54</p> <p>EN54 bundle • S74A IP camera module (body) for connecting up to two additional functional and optical sensor modules (to be ordered individually) • ONVIF-S/T-compliant MOBOTIX 7 system platform with H.264/H.265 (Triple Streaming), MxPEG+ and M-JPEG • CIF Thermal sensor (336x256 Pixel), with Thermal Radiometry, 17° x 13° • Image sensor options (via sensor module): 4K (8 megapixels), color (day) and/or B/W (night) and/or color (day/night with IR cut) • Lens options (via sensor module): horizontal image angle from 95° to 15° • Max. image size (per image sensor): 4K UHD (3840 x 2160 pixels), 16:9 • WDR: up to 120 dB • Functional extensions (via optional MOBOTIX modules): IR Light (supports 15°, 45°, 95° lenses), USB-C • Operating conditions: IP66/IK010 (housing), -40 to 65°C (-40 to 149 °F) • Internal DVR: 8 GB microSD (for MxPEG+ recordings) • Max. Power consumption: 25 W, supply via network cable, PoE Class 4 (IEEE 802.3af/at) • Connections: 1x RJ45 jack for weatherproof network connection via MOBOTIX patch cable (Ethernet 1000BaseT), 2x MOBOTIX module connection (1x optical/1x functional), USB-C, further connections via interface board • Software interface for MOBOTIX Certified Apps (based on Deep Learning, approx. 20 different 30-day demo versions pre-installed) • Housing: Aluminium, PBT-30GF • Color: white • Warranty: 5 years (optionally extendable up to 8 years) • Bundle content: Mx-S74A, Mx-F-S7A-RJ45-VDC, Mx-O-M7SB-336RP280, Mx-F-MSA, Mx-M-PTMA, 2xMx-A-S7A-CBL03-AN</p>	<p>4047438043502</p> <p>90251900</p> <p>3.520 g</p>	<p>40,8 cm</p> <p>31,2 cm</p> <p>20,2 cm</p> <p>25,7 l</p>

**Mx-S74TA-B640R050-EN54****S74A Thermographic Camera TR(B), VGA, R050 (90°) - EN54**

EN54 bundle • S74A IP camera module (body) for connecting up to two additional functional and optical sensor modules (to be ordered individually) • ONVIF-S/T-compliant MOBOTIX 7 system platform with H.264/H.265 (Triple Streaming), MxPEG+ and M-JPEG • VGA Thermal sensor (640x480 Pixel), with Thermal Radiometry, 90° x 69° • Image sensor options (via sensor module): 4K (8 megapixels), color (day) and/or B/W (night) and/or color (day/night with IR cut) • Lens options (via sensor module): horizontal image angle from 95° to 15° • Max. image size (per image sensor): 4K UHD (3840 x 2160 pixels), 16:9 • WDR: up to 120 dB • Functional extensions (via optional MOBOTIX modules): IR Light (supports 15°, 45°, 95° lenses), USB-C • Operating conditions: IP66/IK010 (housing), -40 to 65°C (-40 to 149 °F) • Internal DVR: 8 GB microSD (for MxPEG+ recordings) • Max. Power consumption: 25 W, supply via network cable, PoE Class 4 (IEEE 802.3af/at) • Connections: 1x RJ45 jack for weatherproof network connection via MOBOTIX patch cable (Ethernet 1000BaseT), 2x MOBOTIX module connection (1x optical/1x functional), USB-C, further connections via interface board • Software interface for MOBOTIX Certified Apps (based on Deep Learning, approx. 20 different 30-day demo versions pre-installed) • Housing: Aluminium, PBT-30GF • Color: white • Warranty: 5 years (optionally extendable up to 8 years) • Bundle content: Mx-S74A, Mx-F-S7A-RJ45-VDC, Mx-O-M7SB-640RP050, Mx-F-MSA, Mx-M-PTMA, 2xMx-A-S7A-CBL03-AN

4047438043519	40,8 cm
90251900	31,2 cm
3.520 9	20,2 cm
	25,7 l

**Mx-S74TA-B640R080-EN54****S74A Thermographic Camera TR(B), VGA, R080 (69°) - EN54**

EN54 bundle • S74A IP camera module (body) for connecting up to two additional functional and optical sensor modules (to be ordered individually) • ONVIF-S/T-compliant MOBOTIX 7 system platform with H.264/H.265 (Triple Streaming), MxPEG+ and M-JPEG • VGA Thermal sensor (640x480 Pixel), with Thermal Radiometry, 69° x 56° • Image sensor options (via sensor module): 4K (8 megapixels), color (day) and/or B/W (night) and/or color (day/night with IR cut) • Lens options (via sensor module): horizontal image angle from 95° to 15° • Max. image size (per image sensor): 4K UHD (3840 x 2160 pixels), 16:9 • WDR: up to 120 dB • Functional extensions (via optional MOBOTIX modules): IR Light (supports 15°, 45°, 95° lenses), USB-C • Operating conditions: IP66/IK010 (housing), -40 to 65°C (-40 to 149 °F) • Internal DVR: 8 GB microSD (for MxPEG+ recordings) • Max. Power consumption: 25 W, supply via network cable, PoE Class 4 (IEEE 802.3af/at) • Connections: 1x RJ45 jack for weatherproof network connection via MOBOTIX patch cable (Ethernet 1000BaseT), 2x MOBOTIX module connection (1x optical/1x functional), USB-C, further connections via interface board • Software interface for MOBOTIX Certified Apps (based on Deep Learning, approx. 20 different 30-day demo versions pre-installed) • Housing: Aluminium, PBT-30GF • Color: white • Warranty: 5 years (optionally extendable up to 8 years) • Bundle content: Mx-S74A, Mx-F-S7A-RJ45-VDC, Mx-O-M7SB-640RP080, Mx-F-MSA, Mx-M-PTMA, 2xMx-A-S7A-CBL03-AN

4047438043526	40,8 cm
90251900	31,2 cm
3.520 9	20,2 cm
	25,7 l

**Mx-S74TA-B640R100-EN54****S74A Thermographic Camera TR(B), VGA, R100 (45°) - EN54**

EN54 bundle • S74A IP camera module (body) for connecting up to two additional functional and optical sensor modules (to be ordered individually) • ONVIF-S/T-compliant MOBOTIX 7 system platform with H.264/H.265 (Triple Streaming), MxPEG+ and M-JPEG • VGA Thermal sensor (640x480 Pixel), with Thermal Radiometry, 45° x 37° • Image sensor options (via sensor module): 4K (8 megapixels), color (day) and/or B/W (night) and/or color (day/night with IR cut) • Lens options (via sensor module): horizontal image angle from 95° to 15° • Max. image size (per image sensor): 4K UHD (3840 x 2160 pixels), 16:9 • WDR: up to 120 dB • Functional extensions (via optional MOBOTIX modules): IR Light (supports 15°, 45°, 95° lenses), USB-C • Operating conditions: IP66/IK010 (housing), -40 to 65°C (-40 to 149 °F) • Internal DVR: 8 GB microSD (for MxPEG+ recordings) • Max. Power consumption: 25 W, supply via network cable, PoE Class 4 (IEEE 802.3af/at) • Connections: 1x RJ45 jack for weatherproof network connection via MOBOTIX patch cable (Ethernet 1000BaseT), 2x MOBOTIX module connection (1x optical/1x functional), USB-C, further connections via interface board • Software interface for MOBOTIX Certified Apps (based on Deep Learning, approx. 20 different 30-day demo versions pre-installed) • Housing: Aluminium, PBT-30GF • Color: white • Warranty: 5 years (optionally extendable up to 8 years) • Bundle content: Mx-S74A, Mx-F-S7A-RJ45-VDC, Mx-O-M7SB-640RP100, Mx-F-MSA, Mx-M-PTMA, 2xMx-A-S7A-CBL03-AN



4047438043533	40,8 cm
90251900	31,2 cm
3.520 9	20,2 cm
	25,7 l

**Mx-S74TA-B640R150-EN54****S74A Thermographic Camera TR(B), VGA, R150 (32°) - EN54**

EN54 bundle • S74A IP camera module (body) for connecting up to two additional functional and optical sensor modules (to be ordered individually) • ONVIF-S/T-compliant MOBOTIX 7 system platform with H.264/H.265 (Triple Streaming), MxPEG+ and M-JPEG • VGA Thermal sensor (640x480 Pixel), with Thermal Radiometry, 32° x 26° • Image sensor options (via sensor module): 4K (8 megapixels), color (day) and/or B/W (night) and/or color (day/night with IR cut) • Lens options (via sensor module): horizontal image angle from 95° to 15° • Max. image size (per image sensor): 4K UHD (3840 x 2160 pixels), 16:9 • WDR: up to 120 dB • Functional extensions (via optional MOBOTIX modules): IR Light (supports 15°, 45°, 95° lenses), USB-C • Operating conditions: IP66/IK010 (housing), -40 to 65°C (-40 to 149 °F) • Internal DVR: 8 GB microSD (for MxPEG+ recordings) • Max. Power consumption: 25 W, supply via network cable, PoE Class 4 (IEEE 802.3af/at) • Connections: 1x RJ45 jack for weatherproof network connection via MOBOTIX patch cable (Ethernet 1000BaseT), 2x MOBOTIX module connection (1x optical/1x functional), USB-C, further connections via interface board • Software interface for MOBOTIX Certified Apps (based on Deep Learning, approx. 20 different 30-day demo versions pre-installed) • Housing: Aluminium, PBT-30GF • Color: white • Warranty: 5 years (optionally extendable up to 8 years) • Bundle content: Mx-S74A, Mx-F-S7A-RJ45-VDC, Mx-O-M7SB-640RP150, Mx-F-MSA, Mx-M-PTMA, 2xMx-A-S7A-CBL03-AN

4047438043540	40,8 cm
90251900	31,2 cm
3.520 9	20,2 cm
	25,7 l

p71A ECO Thermal Camera

	Article No. / Name / Description	EAN / HS / weight	dimen.
	<p>Mx-p71TA-320T040</p> <p>p71 Thermal ECO 320 - T040</p> <p>p71 Indoor camera with Thermal ECO module 320-T040. CIF 320x240 • 9fps • 105 x 75°; 5,23mr • NETD: 65mK (typ); < 100mK (max) • build in ambient temperature sensor • IR Range 7,8 to 14µm • 3-axis mechanical pan/tilt head • Operating temperature range: -10 to +50 °C - Built-in speaker and microphone • USB-C • 8GB memory card included</p>	<p>4047438042499</p> <p>90251900</p> <p>1.175 g</p>	<p>19,6 cm</p> <p>18,0 cm</p> <p>14,8 cm</p> <p>5,2 l</p>
	<p>Mx-p71TA-320T080</p> <p>p71 Thermal ECO 320 - T080</p> <p>p71 Indoor camera with Thermal ECO 320-T080. CIF 320x240 • 9fps • 56 x 42°; 3mr • NETD: 65mK (typ); < 100mK (max) • IR Range 7,8 to 14µm • 3-axis mechanical pan/tilt head • Operating temperature range: -10 to +50 °C - Built-in speaker and microphone • USB-C • 8GB memory card included</p>	<p>4047438042505</p> <p>90251900</p> <p>1.175 g</p>	<p>19,6 cm</p> <p>18,0 cm</p> <p>14,8 cm</p> <p>5,2 l</p>



MOBOTIX MOVE Cameras

BeyondHumanVision

MOBOTIX

MOBOTIX MOVE Speed Dome Cameras

MOBOTIX MOVE Speed Dome Cameras

	Article No. / Name / Description	EAN / HS / weight	dimen.
	Mx-SD1A-540-IR-VA MOBOTIX MOVE SpeedDome SD-540-IR-VA (DNN Analytics) MOBOTIX MOVE SpeedDome Network Camera SD-540-IR-VA •Weatherproof motor-driven ONVIF S / G / T/M Dome PTZ camera • 10 Integrated Video Analytic Function incl. DNN Face- and License-Plate Recognition, linkable to PTZ Presets • Up to 40x optical zoom • Image sensor: 5MP SONY STARVIS II IMX675 (2608 x 1964), 1/2.8" Progressive CMOS • Automatic switching from color to B / W image (mechanical IR cut filter) • Motor-controlled Zoom lens (F1.6-F4.95: 4.3 to 170 mm, viewing angle HxV: 62,6 ° - 1,9 ° x 48,8 ° -1.4 °) with autofocus and P-Iris with automatic adaptation to changing light situations • Auto Object Tracking, DNN based (Humans, Vehicles) • 2D & 3D Motion Compensated Noise Reduction (MCTF) • IR LEDs (working distance up to 300m) • IP66 • Ambient temperature -40 to 55°C, humidity 10 to 90% • Video codecs: H.264, H.265, MJPEG (up to 4 streams simultaneously) • Wide Dynamic Range (130 dB) • Max. Frame rate: 5MP @ 30 fps (H.264, with and without WDR enabled); MJPEG: 1080p @ 30 fps • Power supply: PoE++ IEEE802.3bt, max. 51 W, AC24V max. 59.05 W / 87.12 VA • Hardened and "self-cleaning" anti-reflex camera front glass coating by MOBOTIX EverClear • MTBF: 50.000h • Warranty: 5 years	4047438045049 85258900 5.950 g	40,2 cm 25,0 cm 37,0 cm 37,2 l
	Mx-SD1A-831-LIR-VA MOBOTIX MOVE SpeedDome SD-831-LIR-VA LIDAR (DNN) MOBOTIX MOVE SpeedDome Network Camera SD-831-LIR-VA •Weatherproof motor-driven ONVIF S / G / T/M Dome PTZ camera • 10 Integrated Video Analytic Function incl. DNN Face- and License-Plate Recognition, linkable to PTZ Presets • Up to 31x optical zoom • Precise LiDAR Focusing System • Image sensor: 8MP SONY STARVIS II IMX678 (3856 x 2180) 4K, 1/1.8" Progressive CMOS • Automatic switching from color to B / W image (mechanical IR cut filter) • Motor-controlled Zoom lens (F1.35-F4.6: 6.9 to 214.6 mm, viewing angle HxV: 61.8 ° - 2.2 ° x 35.9 ° -1.3 °) with autofocus and P-Iris with automatic adaptation to changing light situations • Auto Object Tracking, DNN based (Humans, Vehicles) • IR LEDs (working distance up to 300m) • 2D & 3D Motion Compensated Noise Reduction (MCTF) • IR LEDs (working distance up to 200m) • IP66 • Ambient temperature -40 to 55°C, humidity 10 to 90% • Video codecs: H.264, H.265, MJPEG (up to 4 streams simultaneously) • Wide Dynamic Range (130 dB) • Max. Frame rate: 8MP @ 30 fps (H.264, with and without WDR enabled); MJPEG: 1080p @ 30 fps • Power supply: PoE++ IEEE802.3bt, max. 51 W, AC24V max. 53,10 W / 74,80 VA • Hardened and "self-cleaning" anti-reflex camera front glass coating by MOBOTIX EverClear • MTBF: 50.000h • Warranty: 5 years	4047438045056 85258900 7.640 g	33,0 cm 33,0 cm 54,0 cm 58,8 l
	Mx-SD2A-230-LL-FM-VA MOBOTIX MOVE SpeedDome SD-230-LL-FM-VA Low Light MOBOTIX MOVE SpeedDome Network Camera SD-230-LL-FM-VA •Weatherproof motor-driven ONVIF S / G / T/M Indoor Dome PTZ camera for ceiling flush mount • 10 Integrated Video Analytic Function incl. DNN Face- and License-Plate Recognition, linkable to PTZ Presets • Up to 30x optical zoom • Image sensor: 2MP SONY STARVIS II IMX662 (1936 x 1100), 1/2.8" Progressive CMOS • Automatic switching from color to B / W image (mechanical IR cut filter) • Motor-controlled Zoom lens (F1.6-F4.7: 4.3 to 129 mm, viewing angle HxV: 59.3 ° - 2.3 ° x 34.9 ° -1.4 °) with autofocus and P-Iris with automatic adaptation to changing light situations • Auto Object Tracking, DNN based (Humans, Vehicles) • 2D & 3D Motion Compensated Noise Reduction (MCTF) • Ambient temperature -40 to 55°C, humidity 10 to 90% • Video codecs: H.264, H.265, MJPEG (up to 3 streams simultaneously) • Wide Dynamic Range (130 dB) • Max. Frame rate: 2MP @ 30 fps (H.264, with and without WDR enabled); MJPEG: 1080p @ 30 fps • Power supply: PoE+ IEEE802.3at, max. 17.71 W, AC24V max. 17.10 W / 32.76 VA • Hardened and "self-cleaning" anti-reflex dome bubble coating by MOBOTIX EverClear • MTBF: 50.000h • Warranty: 5 years	4047438045032 85258900 3.970 g	31,0 cm 31,0 cm 38,0 cm 36,5 l





**Mx-SD2A-230-LL-VA****MOBOTIX MOVE SpeedDome SD-230-LL-VA Low Light (DNN**

MOBOTIX MOVE SpeedDome Network Camera SD-230-LL-VA • Weatherproof motor-driven ONVIF S / G / T / M Dome PTZ camera • 10 Integrated Video Analytic Function incl. DNN Face- and License-Plate Recognition, linkable to PTZ Presets • Up to 30x optical zoom • Image sensor: 2MP SONY STARVIS II IMX662 (1936 x 1100), 1/2.8" Progressive CMOS • Automatic switching from color to B / W image (mechanical IR cut filter) • Motor-controlled Zoom lens (F1.6-F4.7: 4.3 to 129 mm, viewing angle HxV: 59.3° - 2.3° x 34.9° - 1.4°) with autofocus and P-Iris with automatic adaptation to changing light situations • Auto Object Tracking, DNN based (Human, Vehicles) • 2D & 3D Motion Compensated Noise Reduction (MCTF) • IP66, IK10 • Ambient temperature -40 to 55°C, humidity 10 to 90% • Video codecs: H.264, H.265, MJPEG (up to 3 streams simultaneously) • Wide Dynamic Range (130 dB) • Max. Frame rate: 2MP @ 30 fps (H.264, with and without WDR enabled); MJPEG: 1080p @ 30 fps • Power supply: PoE + IEEE802.3at, max. 25.5 W, AC24V max. 29.04 W / 53.24 VA • Hardened and "self-cleaning" anti-reflex dome bubble coating by MOBOTIX EverClear • MTBF: 50.000h • Warranty: 5 years

4047438045025	42,5 cm
85258900	26,2 cm
5.150 9	35,0 cm
	39,0 l

MOBOTIX MOVE Vandal Dome Cameras

MOBOTIX MOVE Vandal Dome Cameras

	Article No. / Name / Description	EAN / HS / weight	dimen.
	Mx-VT1A-2-IR	4047438048200	16,5 cm
	MOBOTIX MOVE Vandal Turret Mx-VT-2-IR MOBOTIX MOVE Vandal Turret Network Camera Mx-VT-2-IR • Max. Image Resolution: 2MP (1920x1080), 1/2.8" Progressive CMOS • ONVIF S/G/T/M camera with integrated IR LEDs (up to 30 m) for day and night operation • Automatic changeover from color to B/W image (mechanical IR cut filter) • Fixed lens (F1.6: 2.8 mm), viewing angle H: 105°, V: 56° • 3-axis adjustment(Pan/Tilt/Rotation) • IP67/IK10 • Ambient temperature -30 to 60°C, humidity 10 to 90% non-condensing • Video codecs: H.264, H.265, MJPEG (up to 3 video-streams simultaneously) • Built-in Microphone • True WDR (120 dB) • Max. Frame rate: 2MP H.264, H.265 @ 30 fps; MJPEG: 1080p @ 30 fps • Power supply: PoE IEEE802.3af Class 3, 12V DC max. 10 W • MTBF: 95.000h • Warranty: 5 years	85258900 950 g	16,5 cm 15,4 cm 4,2 l
	Mx-VT1A-203-IR	4047438048262	16,5 cm
	MOBOTIX MOVE Vandal Turret Mx-VT-203-IR MOBOTIX MOVE Vandal Turret Network Camera Mx-VT-203-IR • Max. Image Resolution: 2MP (1920x1080), 1/2.8" Progressive CMOS • ONVIF S/G/T/M camera with integrated IR LEDs (up to 30 m) for day and night operation • Automatic changeover from color to B/W image (mechanical IR cut filter) • Motor-controlled varifocal lens (F1.4-2.8: 2.7 to 13.5 mm, viewing angle H: 111°-34°, V: 61°-19°) • 3-axis adjustment (Pan/Tilt/Rotation) • IP67/IK10 • Ambient temperature -30 to 60°C, humidity 10 to 90% non-condensing • Video codecs: H.264, H.265, MJPEG (up to 3 video-streams simultaneously) • Built-in Microphone • True WDR (120 dB) • Max. Frame rate: 2MP H.264, H.265 @ 30 fps; MJPEG: 1080p @ 30 fps • Power supply: PoE IEEE802.3af Class 3, 12V DC max. 10 W • MTBF: 95.000h • Warranty: 5 years	85258900 980 g	16,5 cm 15,4 cm 4,2 l
	Mx-VT1A-5-IR	4047438048255	16,5 cm
	MOBOTIX MOVE Vandal Turret Mx-VT-5-IR MOBOTIX MOVE Vandal Turret Network Camera Mx-VT-5-IR • Max. Image Resolution: 5MP (2592x1944), 1/2.8" Progressive CMOS • ONVIF S/G/T/M camera with integrated IR LEDs (up to 30 m) for day and night operation • Automatic changeover from color to B/W image (mechanical IR cut filter) • Fixed lens (F1.6: 2.8 mm), viewing angle H: 97°, V: 70.5° • 3-axis adjustment(Pan/Tilt/Rotation) • IP67/IK10 • Ambient temperature -30 to 60°C, humidity 10 to 90% non-condensing • Video codecs: H.264, H.265, MJPEG (up to 3 video-streams simultaneously) • Built-in Microphone • True WDR (120 dB) • Max. Frame rate: 5MP H.264, H.265 @ 30 fps; MJPEG: 1080p @ 30 fps • Power supply: PoE IEEE802.3af Class 3, 12V DC max. 10 W • MTBF: 95.000h • Warranty: 5 years	85258900 950 g	16,5 cm 15,4 cm 4,2 l
	Mx-VT1A-503-IR	4047438048279	16,5 cm
	MOBOTIX MOVE Vandal Turret Mx-VT-503-IR MOBOTIX MOVE Vandal Turret Network Camera Mx-VT-503-IR • Max. Image Resolution: 5MP (2592x1944), 1/2.8" Progressive CMOS • ONVIF S/G/T/M camera with integrated IR LEDs (up to 30 m) for day and night operation • Automatic changeover from color to B/W image (mechanical IR cut filter) • Motor-controlled varifocal lens (F1.4-2.8: 2.7 to 13.5 mm, viewing angle H: 103°-31°, V: 76°-23.5°) • 3-axis adjustment(Pan/Tilt/Rotation) • IP67/IK10 • Ambient temperature -30 to 60°C, humidity 10 to 90% non-condensing • Video codecs: H.264, H.265, MJPEG (up to 3 video-streams simultaneously) • Built-in Microphone • True WDR (120 dB) • Max. Frame rate: 5MP H.264, H.265 @ 30 fps; MJPEG: 1080p @ 30 fps • Power supply: PoE IEEE802.3af Class 3, 12V DC max. 10 W • MTBF: 95.000h • Warranty: 5 years	85258900 980 g	16,5 cm 15,4 cm 4,2 l

**Mx-VD1A-8-IR-VA****MOBOTIX MOVE VandalDome VD-8-IR-VA (DNN Analytics)**

MOBOTIX MOVE Vandal Dome Network Camera VD-8-IR-VA (DNN Video Analytics) • 10 Integrated Video Analytic Function incl. DNN Face- and License-Plate Recognition • Max. Image Resolution: 4K/8MP (3864x2180), 1/1.8" Progressive CMOS • Weatherproof ONVIF S/G/T dome camera with integrated IR LEDs (up to 40 m) for day and night operation • Automatic changeover from color to B/W image (mechanical IR cut filter) • Remote Zoom / Focus • Motor-controlled Varifocal lens (F1.5-F2.0: 3.6 to 11 mm, viewing angle H: 115.0°-47.5°, V: 61.2°-27.0°) with Auto Iris with automatic adaptation to changing light situations • 3-axis lens adjustment • IP66, IK10 • Ambient temperature -55 to 60°C, (heater switched on) humidity 10 to 90% non-condensing • Video codecs: H.264, H.265, MJPEG (up to 4 video-streams simultaneously) • True WDR (130 dB) • Max. Frame rate: 4K/8MP H.264, H.265 @ 30 fps; MJPEG: 1080p @ 30 fps • Power supply: PoE IEEE802.3af, max. 11.67 W, DC12V max. 12.14 W, AC24V max. 11.99 W / 20.02 VA • Optic hardened and "selfcleaning" Anti-Reflex coating by MOBOTIX ClearView • MTBF: 95.000h • Warranty: 5 years

4047438040341 17,3 cm
85258900 17,3 cm
1.081 9 16,6 cm
5,0 l

**Mx-VD2A-5-IR-VA****MOBOTIX MOVE VandalDome VD2-5-IR-VA (Video Analytics)**

MOBOTIX MOVE Vandal Dome Network Camera VD2-5-IR-VA (Video Analytics) • Weatherproof ONVIF S/G/T dome camera with integrated IR LEDs (up to 40 m) for day and night operation • Max. Image Resolution: 5MP (2720 x 1976), 1/2.7" Progressive CMOS • Automatic changeover from color to B / W image (mechanical IR cut filter) • Remote Zoom • Motor-controlled Varifocal lens (F1.6-F2.9: 2.7 to 12 mm, viewing angle H: 102.1°-31.5°, V: 70.3°-22.7°) with Auto Iris with automatic adaptation to changing light situations • 3-axis lens adjustment • IP66, IK10 • Ambient temperature -55 to 60°C, (heater switched on) humidity 10 to 90% non-condensing • Video codecs: H.264, H.265, MJPEG (up to 4 video-streams simultaneously) • True WDR (130 dB) • Max. Frame rate: 5MP H.264, H.265 30 fps • WDR on: H.265 / H.264: 2688x1944 @ 30 fps + 1024x768 @ 30 fps; MJPEG: 1080p @ 30 fps • WDR off: H.265 / H.264: 2688x1944 @ 30 fps + 1024x768 @ 30 fps; H.265 / H.264: 1920x1080 @ 60 fps + 1280x720 @ 60 fps; MJPEG: 1080p @ 60 fps • Power supply: PoE IEEE 802.3af or DC 12V (13W) or AC 24V; max 14 W • Hardened and "self-cleaning" anti-reflex dome bubble coating by MOBOTIX EverClear • MTBF: 95.000h • Warranty: 5 years

4047438040457 17,5 cm
85258900 17,5 cm
1.210 9 17,0 cm
5,2 l

**Mx-VD3A-2-IR-VA****MOBOTIX MOVE VandalDome VD3-2-IR-VA (Video Analytics)**

MOBOTIX MOVE Vandal Dome Network Camera VD3-2-IR-VA (Video Analytics) • Weatherproof ONVIF S/G/T dome camera with integrated IR LEDs (up to 40 m) for day and night operation • Max. Image Resolution: 2MP (1920 x 1080), 1/2.7" Progressive CMOS • Automatic changeover from color to B / W image (mechanical IR cut filter) • Remote Zoom • Motor-controlled Varifocal lens (F1.6-F2.9: 2.7 to 12 mm, viewing angle H: 99°-31°, V: 53°-18°) with Auto Iris with automatic adaptation to changing light situations • 3-axis lens adjustment • IP66, IK10 • Ambient temperature -55 to 60°C, (heater on) humidity 10 to 90% non-condensing • Video codecs: H.264, H.265, MJPEG (up to 4 video-streams simultaneously) • True WDR (130 dB) • Max. Frame rate: H.265 / H.264: 1920x1080 @ 30 fps + 720x480 @ 30 fps; MJPEG: 1080p @ 30 fps • Power supply: PoE IEEE 802.3af or DC 12V (13W) or AC 24V; max 14 W • Hardened and "self-cleaning" anti-reflex dome bubble coating by MOBOTIX EverClear • MTBF: 95.000h • Warranty: 5 years

4047438040433 17,5 cm
85258900 17,5 cm
1.210 9 17,0 cm
5,2 l




**Mx-VD2A-2-IR****MOBOTIX MOVE VandalDome VD2-2-IR**

MOBOTIX MOVE VandalDome Network Camera VD2-2-IR • Image sensor: 2MP (1920x1080), 1/3" Progressive CMOS • Weatherproof ONVIF S/G/T vandal dome camera with built-in IR LEDs (up to 40 m) for use with day and night • Automatic changeover from color to B / W image (mechanical IR cut filter) • Manually adjustable vario lens (F1.4: 2.8 to 12 mm, viewing angle H: 91°-34°) • IP66 • IK10 • Ambient temperature -30 to 60°C (-22° to 140° F), humidity 10 to 90% • Video codecs: H.264, MJPEG (up to 4 streams simultaneously) • WDR (up to 130 dB) • Max. Frame rate: 2MP @ 60B / s (H.264, H.265 with and without WDR enabled); MJPEG: 1080p @ 30 B / s • Power supply: PoE IEEE 802.3af • Warranty: 5 years

4047438038959 17,5 cm
85258900 17,5 cm
1.010 9 17,0 cm
5,2 l

MOBOTIX MOVE Bullet Cameras

MOBOTIX MOVE Bullet Cameras

	Article No. / Name / Description	EAN / HS / weight	dimen.
	Mx-BC2A-2-IR	4047438038966	29,6 cm
	MOBOTIX MOVE BulletCamera BC2-2-IR MOBOTIX MOVE Bullet Network Camera BC2-2-IR • Image Resolution: 2MP (1920x1080), 1/2.7" Progressive CMOS • Weatherproof ONVIF S/G/T bullet camera with built-in IR LEDs (up to 15 m) for day and night operation • Automatic changeover from color to B / W image (mechanical IR cut filter) • Manually adjustable vario lens (F1.4: 2.8 to 12 mm, viewing angle H: 96.67° - 34.13° - V: 52.21° - 19.24°) • IP66 • Ambient temperature -30 to 60°C (-22° to 140° F), humidity 10 to 95% • Video codecs: H.264, MJPEG (up to 4 streams simultaneously) • WDR (up to 130 dB) • Max. Frame rate: 2MP @ 30 fps (H.264, H.265 with and without WDR enabled); MJPEG: 1080p @ 30 fps • Power supply: PoE IEEE 802.3af • MTBF: 95.000h • Warranty: 5 years	85258900 580 g	20,0 cm 17,5 cm 10,4 l
	Mx-VB1A-2-IR-ALPR	4047438044295	28,5 cm
	MOBOTIX MOVE ALPR Vandal Bullet Network Camera VB-2-IR-ALPR (License Plate Recognition) • Integrated professional international Automatic License Plate Recognition for stopped and slow moving vehicles up to 18m distance • incl. MMC (Make, Model, Color Detection) • ALPR Activation License Key pre-installed • Max. Image Resolution: 2 MP / 1080p (Full-HD), 1/2.8" Progressive CMOS (SONY) • Weatherproof ONVIF S/G/T/M bullet camera with integrated IR LEDs (up to 60m) for day and night operation • Automatic changeover from color to B/W image (mechanical IR cut filter) • Light-Sensitivity: Color: 0.02lx, B/W: 0.001lx, IR: 0lx • Remote Zoom / Focus • Motor-controlled Varifocal lens (F1.6-F2.9: 2.7 to 12 mm, viewing angle H: 102.1°-31.5°, V: 70.3°-22.7°), Auto Iris with automatic adaptation to changing light situations • Video codecs: H.264, H.265, MJPEG (up to 4 video-streams simultaneously) • True WDR (130 dB) • Max. Frame rate: 2 MP H.264, H.265 @ 30 fps; MJPEG: 1080p @ 30 fps • Bi-directional Audio (Line In/Out) • Alarm I/O • 64 GB SD-Karte pre-installed • Power supply: PoE IEEE802.3af, class 0, max 12.95 watt, DC12V, 15.59 watt, AC24V, max 13.31 watt, max 25.08 VA • IP67, IK10 • Ambient temperature -55 to 60°C, (heater switched on), Rel. humidity 10 to 90% non-condensing • Hardened and "self-cleaning" anti-reflex Bullet front glass coating by MOBOTIX EverClear • MTBF: 95.000h • Warranty: 5 years	85258900 1.740 g	19,6 cm 17,8 cm 9,9 l
	Mx-VB1A-2-IR-D-ALPR	4047438044318	28,5 cm
	MOBOTIX MOVE ALPR Vandal Bullet Network Camera VB-2-IR-D-ALPR (License Plate Recognition) • Integrated professional international Automatic License Plate Recognition for slow and fast moving vehicles up to 35m distance • incl. MMC (Make, Model, Color Detection) • ALPR Activation License Key pre-installed • Max. Image Resolution: 2 MP / 1080p (Full-HD), 1/2.8" Progressive CMOS (SONY) • Weatherproof ONVIF S/G/T/M bullet camera with integrated IR LEDs (up to 60m) for day and night operation • Automatic changeover from color to B/W image (mechanical IR cut filter) • Light-Sensitivity: Color: 0.02lx, B/W: 0.001lx, IR: 0lx • Remote Zoom / Focus • Motor-controlled Zoom lens (F1.6-F2.4: 9 to 22 mm, viewing angle H: 36.1°-15.4°, V: 19.8°-8.8°), Auto Iris with automatic adaptation to changing light situations • Video codecs: H.264, H.265, MJPEG (up to 4 video-streams simultaneously) • True WDR (130 dB) • Max. Frame rate: 2 MP H.264, H.265 @ 30 fps; MJPEG: 1080p @ 30 fps • Bi-directional Audio (Line In/Out) • Alarm I/O • 64 GB SD-Karte pre-installed • Power supply: PoE IEEE802.3af, class 0, max 12.95 watt, DC12V, 15.59 watt, AC24V, max 13.31 watt, max 25.08 VA • IP67, IK10 • Ambient temperature -55 to 60°C, (heater switched on), Rel. humidity 10 to 90% non-condensing • Hardened and "self-cleaning" anti-reflex Bullet front glass coating by MOBOTIX EverClear • MTBF: 95.000h • Warranty: 5 years	85258900 1.740 g	19,6 cm 17,8 cm 9,9 l

**Mx-VB1A-8-IR-VA****MOBOTIX MOVE VandalBullet VB-8-IR-VA (DNN Analytics)**

MOBOTIX MOVE Vandal Bullet Network Camera VB-8-IR-VA (DNN Video Analytics) • 10 Integrated Video Analytic Function incl. DNN Face- and License-Plate Recognition • Max. Image Resolution: 4K/8MP (3864x2180), 1/1.8" Progressive CMOS • Weatherproof ONVIF S/G/T/M bullet camera with integrated IR LEDs (up to 40 m) for day and night operation • Automatic changeover from color to B/W image (mechanical IR cut filter) • Remote Zoom / Focus • Motor-controlled Varifocal lens (F1.5-F2.0: 3.6 to 11 mm, viewing angle H: 115.0°-47.5°, V: 61.2°-27.0°) with Auto Iris with automatic adaptation to changing light situations • IP67, IK10 • Ambient temperature -55 to 60°C, (heater switched on) humidity 10 to 90% non-condensing • Video codecs: H.264, H.265, MJPEG (up to 4 video-streams simultaneously) • True WDR (130 dB) • Max. Frame rate: 4K/8MP H.264, H.265 @ 30 fps; MJPEG: 1080p @ 30 fps • Power supply: PoE IEEE802.3af, max 12.95 W, DC12V, 15.59 W, AC24V, max 13.31 W, max 25.08 VA • Hardened and "self-cleaning" anti-reflex Bullet front glass coating by MOBOTIX EverClear • MTBF: 95.000h • Warranty: 5 years

4047438040358	28,5 cm
85258900	19,6 cm
1.793 9	17,4 cm
	9,7 l

**Mx-VB2A-5-IR-VA****MOBOTIX MOVE VandalBullet VB2-5-IR-VA (Video Analytics)**

MOBOTIX MOVE Vandal Bullet Network Camera VB2-5-IR-VA (Video Analytics) • Weatherproof ONVIF S / G / T dome camera with integrated IR LEDs (up to 40 m) for day and night operation • Max. Image Resolution: 5MP (2720 x 1976), 1/2.7" Progressive CMOS • Automatic changeover from color to B / W image (mechanical IR cut filter) • Remote Zoom • Motor-controlled Varifocal lens (F1.6-F2.9: 2.7 to 12 mm, viewing angle H: 102.1°-31.5°, V: 70.3°-22.7°) with Auto Iris with automatic adaptation to changing light situations • IP67, IK10 • Ambient temperature -55 to 60°C (heater on), humidity 10 to 90% non-condensing • Video codecs: H.264, H.265, MJPEG (up to 4 video-streams simultaneously) • True WDR (130 dB) • WDR on: H.265 / H.264: 2688x1944 @ 30 fps + 1024x768 @ 30 fps; MJPEG: 1080p @ 30 fps • WDR off: H.265 / H.264: 2688x1944 @ 30 fps + 1024x768 @ 30 fps; H.265 / H.264: 1920x1080 @ 60 fps + 1280x720 @ 60 fps; MJPEG: 1080p @ 60 fps • Power supply: PoE IEEE 802.3af or DC 12V (13W) or AC 24V; max 14 W • Hardened and "self-cleaning" anti-reflex Bullet front glass coating by MOBOTIX EverClear • MTBF: 95.000h • Warranty: 5 years

4047438040464	29,6 cm
85258900	20,0 cm
1.710 9	17,5 cm
	10,4 l


**Mx-VB3A-2-IR-VA****MOBOTIX MOVE VandalBullet VB3-2-IR-VA (Video Analytics)**

MOBOTIX MOVE Vandal Bullet Network Camera VB3-2-IR-VA (Video Analytics) • Weatherproof ONVIF S / G / T dome camera with integrated IR LEDs (up to 40 m) for day and night operation • Max. Image Resolution: 2MP (1920 x 1080), 1/2.7" Progressive CMOS • Automatic changeover from color to B / W image (mechanical IR cut filter) • Remote Zoom • Motor-controlled Varifocal lens (F1.6-F2.9: 2.7 to 12 mm, viewing angle H: 99°-31°, V: 53°-18°) with Auto Iris with automatic adaptation to changing light situations • 3-axis lens adjustment • IP67, IK10 • Ambient temperature -55 to 60°C, (heater on) humidity 10 to 90% non-condensing • Video codecs: H.264, H.265, MJPEG (up to 4 video-streams simultaneously) • True WDR (130 dB) • Max. Frame rate: H.265 / H.264: 1920x1080 @ 30 fps + 720x480 @ 30 fps; MJPEG: 1080p @ 30 fps • Power supply: PoE IEEE 802.3af or DC 12V (13W) or AC 24V; max 14 W • Hardened and "self-cleaning" anti-reflex Bullet front glass coating by MOBOTIX EverClear • MTBF: 95.000h • Warranty: 5 years


4047438040440	29,6 cm
85258900	20,0 cm
1.460 9	17,5 cm
	10,4 l

MOBOTIX MOVE Hemispheric Vandal Dome

MOBOTIX MOVE Hemispheric Vandal Dome Camera


	Article No. / Name / Description	EAN / HS / weight	dimen.
	Mx-VH1A-12-IR-VA	4047438038317	17,3 cm
	MOBOTIX MOVE 12MP Vandal Hemispheric	85258900	17,3 cm
	MOBOTIX MOVE Vandal Hemispheric Network Camera Mx-VH1A-12-IR-VA • Image sensor: 12MP (4072 x 3046), 1/1.7" Progressive CMOS • Indoor • ONVIF S/G/T/M • Hemispheric camera with built-in IR LED illumination (up to 10 m) for use with day and night • Automatic changeover from color to B / W image (mechanical IR cut filter) • focal length 1.65 mm • IK10 • Ambient temperature -10 to 55°C (14° to 131°F), humidity 10 to 90% • Video codecs: H.264, H.265, MJPEG (up to 4 streams simultaneously) • Max. Frame rate: 12MP@20 fps (Backend dewarping) 8.9MP@27 fps (Edge dewarping) • Power supply: PoE IEEE 802.3af • Warranty: 5 years • MTBF: 95,000h	640 g	10,7 cm 3,2 l

MOBOTIX MOVE Fixed Domes

	Article No. / Name / Description	EAN / HS / weight	dimen.
	Mx-MD1A-5-IR	4047438042475	16,5 cm
	MOBOTIX MOVE Indoor MicroDome Mx-MD-5-IR	85258900	16,5 cm
	MOBOTIX MOVE Indoor MicroDome Network Camera Mx-MD-5-IR • Max. Image Resolution: 5M (2720x1976), 1/2.7" Progressive CMOS • ONVIF S/G/T dome camera with integrated IR LEDs (up to 15 m) for day and night operation • Automatic changeover from color to B/W image (mechanical IR cut filter) • Fixed lens (F2.0: 2.8 mm), viewing angle H: 108.3°, V: - 76.5 °) • 3-axis lens adjustment • Indoor, IK8 • Ambient temperature -30 to 55°C, humidity 10 to 90% non-condensing • Video codecs: H.264, H.265, MJPEG (up to 4 video-streams simultaneously) • True WDR (120 dB) • Max. Frame rate: 5MP H.264, H.265 @ 30 fps; MJPEG: 1080p @ 30 fps • Power supply: PoE IEEE802.3af, max. 5.09 W • MTBF: 95.000h • Warranty: 5 years	450 g	13,5 cm 3,7 l

MOBOTIX MOVE Multi Sensor Cameras

MOBOTIX MOVE Multi Sensor Cameras

	Article No. / Name / Description	EAN / HS / weight	dimen.
	Mx-VM1A-20-IR-VA MOBOTIX MOVE Vandal Multisensor VM-20-IR-VA MOBOTIX MOVE Vandal Multisensor Network Camera Mx-VM1A-20-IR-VA • Image sensor: 4x5MP (2608x1964), 1/2.8" Progressive CMOS IMX 675 SONY STARVIS II • Up to 3x optical zoom • ONVIF S/G/T/M • 10 Integrated Video Analytic Function incl. DNN Face- and License-Plate Recognition • Auto Object Tracking • Multisensor camera with built-in IR LED illumination (up to 30 m) for use with day and night • Automatic changeover from color to B / W image (mechanical IR cut filter) • FIPS140-2 level 2-compliant IT-Secure TPM chipset • NEMA-4x compliant • M.2 SATA 3 SSD support • 2D & 3D Motion Compensated Noise Reduction (MCTF) • Motor-controlled Zoom lens (F1.6 x 4: 2,8mm to 8 mm, viewing angle HxV: 111,5° - 53,7° x 79° - 40,2°) with autofocus and P-Iris with automatic adaptation to changing light situations • IK10 / IP66 • Ambient temperature -40 to 60°C (22° to 122°F), humidity 10 to 90% • Video codecs: H.264, H.265, MJPEG (up to 9 Video-Streams simultaneously - 4x2 per sensor module + 1 quadview stream) • Wide Dynamic Range (130 dB) • Max. Frame rate: 5MP@30 fps (H.264, with and without WDR enabled); MJPEG: 1080p @ 30 fps • Power supply: PoE++ IEEE802.3bt, max. 51 W, AC24V max. 53,10 W / 74,80 VA • Opt. Integrated Microphone & Loudspeaker (bi-directional communication) • Hardened and "self-cleaning" anti-reflex camera front glass coating by MOBOTIX EverClear • MTBF: 95000h • Warranty: 5 years	4047438045063 85258900 3.740 g	32,3 cm 30,5 cm 15,6 cm 15,4 l
	Mx-VM1A-20-IR-VA MOBOTIX MOVE Vandal Multisensor PTZ Combo VM1A-20-IR-VA MOBOTIX MOVE Vandal Multisensor PTZ Combo Network Camera Mx-VM1A-20-IR-VA • Image sensor Multi: 4x5MP (2560x1920), 1/2.7" Progressive CMOS • Image sensor PTZ: 2MP (1920x1080), 1/2.8" Progressive CMOS • ONVIF S/G/T/M • Pre-Installed AI-VMD DNN based Video-Motion Detection • Auto Object Tracking by PTZ-Unit • Automatic changeover from color to B / W image (mechanical IR cut filter) • FIPS140 -2 level 3 certified IT-Security TPM chipset • Intelligent Encoding, "Smart Low Bitrate Control" • Multisensor: 4x Fixed Focal Lens 3.2mm (viewing angle HxV: 97° x 71° • PTZ: 21x Motorized Zoom /Focus Lens 4.0 – 84.6mm with Autofokus & P-Iris (Viewing angle HxV: 3.7° - 77° x 2.2° - 44°) • IK10 / IP66/ IP67 • NNDA conformant • NEMA-4x conformant • Ambient temperature -40 to 55°C (-4° to 131°F), humidity 10 to 100% • Video codecs: H.264, H.265, MJPEG • Wide Dynamic Range up to 108 dB for Multisensor / 144 dB for PTZ-Unit • 1 Micro SD/SDHC/SDXC Card support up to 512 GB on each Multisensor/ PTZ • Max. Frame rate Multisensor: 5MP@15 fps H.264, MJPEG: 1080p @ 15 fps, max. Frame rate PTZ: 2MP@60 fps H.264, MJPEG: 1080p @ 60 fps • Power supply: PoE++ IEEE802.3bt, DC 54 V max. 35.6 W • Audio Line In/Out • MTBF: 95000h • Warranty: 5 years	4047438047524 85258900 4.950 g	34,0 cm 28,7 cm 34,5 cm 33,7 l

Optics

BeyondHumanVision

MOBOTIX

Sensor Modules 4K for MOBOTIX 7

	Article No. / Name / Description	EAN / HS / weight	dimen.
	Mx-O-M7SA-12DN016 12MP Hemispheric Day & Night Sensor Module 12MP Hemispheric M73/S74 with IR cut filter for day and night use, max. resolution: 4K UHD 2880x2880, IP66, white	4047438040631 85299097 107 g	9,8 cm 7,5 cm 9,0 cm 0,7 l
	Mx-O-M7SA-12DN016-b 12MP Hemispheric Day & Night Sensor Module black 12MP Hemispheric M73/S74 with IR cut filter for day and night use, max. resolution: 4K UHD 2880x2880, IP66, black	4047438041379 85299097 107 g	9,8 cm 7,5 cm 9,0 cm 0,7 l
	Mx-O-M7SA-8D500 8° 4K Day Sensor mod. TELE M73/S74 sensor module with premium tele lens for day use, aperture: f/1.8, max. image angle (HxV): 8°x4,5°, max. resolution: 4K UHD (3840x2160), IP66, white	4047438047265 85299097 210 g	9,8 cm 7,5 cm 9,0 cm 0,7 l
	Mx-O-M7SA-8DN040-b 120° 4K IR Cut Day & Night Sensor Module WIDE black M73/S74 sensor module with premium wide-angle lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 120°x60°, max. resolution: 4K UHD (3840x2160), IP66, black	4047438041386 85299097 140 g	9,8 cm 7,5 cm 9,0 cm 0,7 l
	Mx-O-M7SA-8DN050-b 95° 4K IR Cut Day & Night Sensor Module WIDE black M73/S74 sensor module with premium wide-angle lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 95°x50°, max. resolution: 4K UHD (3840x2160), IP66, black	4047438041393 85299097 140 g	9,8 cm 7,5 cm 9,0 cm 0,7 l



Mx-O-M7SA-8DN080-b
60° 4K IR Cut Day & Night Sensor Module WIDE black
 M73/S74 sensor module with premium wide-angle lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 60°x33°, max. resolution: 4K UHD (3840x2160), IP66, black

4047438041409 9,8 cm
 85299097 7,5 cm
 140 g 9,0 cm
 0,7 l



Mx-O-M7SA-8DN100-b
45° 4K IR Cut Day & Night Sensor Module STANDARD black
 M73/S74 sensor module with premium normal lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 45°x25°, max. resolution: 4K UHD (3840x2160), IP66, black

4047438041416 9,8 cm
 85299097 7,5 cm
 140 g 9,0 cm
 0,7 l



Mx-O-M7SA-8DN150-b
30° 4K IR Cut Day & Night Sensor Module TELE black
 M73/S74 sensor module with premium tele lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 30°x17°, max. resolution: 4K UHD (3840x2160), IP66, black

4047438041423 9,8 cm
 85299097 7,5 cm
 140 g 9,0 cm
 0,7 l



Mx-O-M7SA-8DN280-b
15° 4K IR Cut Day & Night Sensor Module TELE black
 M73/S74 sensor module with premium tele lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 15°x8,5°, max. resolution: 4K UHD (3840x2160), IP66, black

4047438041430 9,8 cm
 85299097 7,5 cm
 140 g 9,0 cm
 0,7 l



Mx-O-M7SA-8L040
120° 4K LPF Sensor Module WIDE
 M73/S74 sensor module with premium wide-angle lens, LPF special lens, e.g., for license plate detection (with infrared), aperture: f/1.8, max. image angle (HxV): 120°x60°, max. resolution: 4K UHD (3840x2160), IP66, white

4047438040310 9,8 cm
 85299097 7,5 cm
 140 g 9,0 cm
 0,7 l



Mx-O-M7SA-8L500
8° 4K LPF Sensor mod. TELE
 M73/S74 sensor module with premium tele lens, LPF special lens, e.g., for license plate detection (with infrared), aperture: f/1.8, max. image angle (HxV): 8°x4,5°, max. resolution: 4K UHD (3840x2160), IP66, white

4047438044080 9,8 cm
 85299097 7,5 cm
 210 g 9,0 cm
 0,7 l



Mx-O-M7SA-8N040-b
120° 4K Night Sensor Module WIDE black

M73/S74 sensor module with premium wide-angle lens and for night use, aperture: f/1.8, max. image angle (HxV): 120°x60°, max. resolution: 4K UHD (3840x2160), IP66, black

4047438041447 9,8 cm
 85299097 7,5 cm
 140 g 9,0 cm
 0,7 l



Mx-O-M7SA-8N050-b
95° 4K Night Sensor Module WIDE black

M73/S74 sensor module with premium wide-angle lens for night use, aperture: f/1.8, max. image angle (HxV): 95°x50°, max. resolution: 4K UHD (3840x2160), IP66, black

4047438041454 9,8 cm
 85299097 7,5 cm
 140 g 9,0 cm
 0,7 l



Mx-O-M7SA-8N080-b
60° 4K Night Sensor Module WIDE black

M73/S74 sensor module with premium wide-angle lens for night use, aperture: f/1.8, max. image angle (HxV): 95°x50°, max. resolution: 4K UHD (3840x2160), IP66, black

4047438041461 9,8 cm
 85299097 7,5 cm
 140 g 9,0 cm
 0,7 l



Mx-O-M7SA-8N100-b
45° 4K Night Sensor Module STANDARD black

M73/S74 sensor module with premium standard-angle lens for night use, aperture: f/1.8, max. image angle (HxV): 45°x25°, max. resolution: 4K UHD (3840x2160), IP66, black

4047438041478 9,8 cm
 85299097 7,5 cm
 140 g 9,0 cm
 0,7 l



Mx-O-M7SA-8N150-b
30° 4K Night Sensor Module TELE black

M73/S74 sensor module with premium tele lens for night use, aperture: f/1.8, max. image angle (HxV): 30°x17°, max. resolution: 4K UHD (3840x2160), IP66, black

4047438041485 9,8 cm
 85299097 7,5 cm
 140 g 9,0 cm
 0,7 l



Mx-O-M7SA-8N280-b
15° 4K Night Sensor Module TELE black

M73/S74 sensor module with premium tele lens for night use, aperture: f/1.8, max. image angle (HxV): 15°x8,5°, max. resolution: 4K UHD (3840x2160), IP66, black

4047438041492 9,8 cm
 85299097 7,5 cm
 140 g 9,0 cm
 0,7 l

**Mx-O-M7SA-8N500****8° 4K Night Sensor mod. TELE**

M73/S74 sensor module with premium tele lens for night use, aperture: f/1.8, max. image angle (HxV): 8°x4,5°, max. resolution: 4K UHD (3840x2160), IP66, white

4047438047272	9,8 cm
85299097	7,5 cm
210 g	9,0 cm
	0,7 l

**Mx-O-M7SA-8DN040****120° 4K IR Cut Day & Night Sensor Module WIDE**

M73/S74 sensor module with premium wide-angle lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 120°x60°, max. resolution: 4K UHD (3840x2160), IP66, white

4047438034968	9,8 cm
85299097	7,5 cm
140 g	9,0 cm
	0,7 l

**Mx-O-M7SA-8DN050****95° 4K IR Cut Day & Night Sensor Module WIDE**

M73/S74 sensor module with premium wide-angle lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 95°x50°, max. resolution: 4K UHD (3840x2160), IP66, white

4047438034814	9,8 cm
85299097	7,5 cm
140 g	9,0 cm
	0,7 l

**Mx-O-M7SA-8DN080****60° 4K IR Cut Day & Night Sensor Module WIDE**

M73/S74 sensor module with premium wide-angle lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 60°x33°, max. resolution: 4K UHD (3840x2160), IP66, white

4047438035941	9,8 cm
85299097	7,5 cm
140 g	9,0 cm
	0,7 l

**Mx-O-M7SA-8DN100****45° 4K IR Cut Day & Night Sensor Module STANDARD**

M73/S74 sensor module with premium normal lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 45°x25°, max. resolution: 4K UHD (3840x2160), IP66, white

4047438034821	9,8 cm
85299097	7,5 cm
140 g	9,0 cm
	0,7 l

**Mx-O-M7SA-8DN150****30° 4K IR Cut Day & Night Sensor Module TELE**

M73/S74 sensor module with premium tele lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 30°x17°, max. resolution: 4K UHD (3840x2160), IP66, white

4047438035958	9,8 cm
85299097	7,5 cm
140 g	9,0 cm
	0,7 l



Mx-O-M7SA-8DN280
15° 4K IR Cut Day & Night Sensor Module TELE

M73/S74 sensor module with premium tele lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 15°x8,5°, max. resolution: 4K UHD (3840x2160), IP66, white

4047438034838 9,8 cm
 85299097 7,5 cm
 140 g 9,0 cm
 0,7 l



Mx-O-M7SA-8D040
120° 4K Day Sensor Module WIDE

M73/S74 sensor module with premium wide-angle lens for day use, aperture: f/1.8, max. image angle (HxV): 120°x60°, max. resolution: 4K UHD (3840x2160), IP66, white

4047438034944 9,8 cm
 85299097 7,5 cm
 140 g 9,0 cm
 0,7 l



Mx-O-M7SA-8D050
95° 4K Day Sensor Module WIDE

M73/S74 sensor module with premium wide-angle lens for day use, aperture: f/1.8, max. image angle (HxV): 95°x50°, max. resolution: 4K UHD (3840x2160), IP66, white

4047438034845 9,8 cm
 85299097 7,5 cm
 140 g 9,0 cm
 0,7 l



Mx-O-M7SA-8D080
60° 4K Day Sensor Module WIDE

M73/S74 sensor module with premium wide-angle lens for day use, aperture: f/1.8, max. image angle (HxV): 60°x33°, max. resolution: 4K UHD (3840x2160), IP66, white

4047438035989 9,8 cm
 85299097 7,5 cm
 140 g 9,0 cm
 0,7 l



Mx-O-M7SA-8D100
45° 4K Day Sensor Module STANDARD

M73/S74 sensor module with premium standard-angle lens for day, aperture: f/1.8, max. image angle (HxV): 45°x25°, max. resolution: 4K UHD (3840x2160), IP66, white

4047438034852 9,8 cm
 85299097 7,5 cm
 140 g 9,0 cm
 0,7 l



Mx-O-M7SA-8D150
30° 4K Day Sensor Module TELE

M73/S74 sensor module with premium tele lens for day use, aperture: f/1.8, max. image angle (HxV): 30°x17°, max. resolution: 4K UHD (3840x2160), IP66, white

4047438035996 9,8 cm
 85299097 7,5 cm
 140 g 9,0 cm
 0,7 l



Mx-O-M7SA-8D280
15° 4K Day Sensor Module TELE

M73/S74 sensor module with premium tele lens for day, aperture: f/1.8, max. image angle (HxV): 15°x8,5°, max. resolution: 4K UHD (3840x2160), IP66, white

4047438034869	9,8 cm
85299097	7,5 cm
140 G	9,0 cm
	0,7 l



Mx-O-M7SA-8N040
120° 4K Night Sensor Module WIDE

M73/S74 sensor module with premium wide-angle lens and for night use, aperture: f/1.8, max. image angle (HxV): 120°x60°, max. resolution: 4K UHD (3840x2160), IP66, white

4047438034951	9,8 cm
85299097	7,5 cm
140 G	9,0 cm
	0,7 l



Mx-O-M7SA-8N050
95° 4K Night Sensor Module WIDE

M73/S74 sensor module with premium wide-angle lens for night use, aperture: f/1.8, max. image angle (HxV): 95°x50°, max. resolution: 4K UHD (3840x2160), IP66, white

4047438034876	9,8 cm
85299097	7,5 cm
140 G	9,0 cm
	0,7 l



Mx-O-M7SA-8N080
60° 4K Night Sensor Module WIDE

M73/S74 sensor module with premium wide-angle lens for night use, aperture: f/1.8, max. image angle (HxV): 95°x50°, max. resolution: 4K UHD (3840x2160), IP66, white

4047438035965	9,8 cm
85299097	7,5 cm
140 G	9,0 cm
	0,7 l



Mx-O-M7SA-8N100
45° 4K Night Sensor Module STANDARD

M73/S74 sensor module with premium standard-angle lens for night use, aperture: f/1.8, max. image angle (HxV): 45°x25°, max. resolution: 4K UHD (3840x2160), IP66, white

4047438034883	9,8 cm
85299097	7,5 cm
140 G	9,0 cm
	0,7 l



Mx-O-M7SA-8N150
30° 4K Night Sensor Module TELE

M73/S74 sensor module with premium tele lens for night use, aperture: f/1.8, max. image angle (HxV): 30°x17°, max. resolution: 4K UHD (3840x2160), IP66, white

4047438035972	9,8 cm
85299097	7,5 cm
140 G	9,0 cm
	0,7 l



Mx-O-M7SA-8N280
15° 4K Night Sensor Module TELE

M73/S74 sensor module with premium tele lens for night use, aperture: f/1.8, max. image angle (HxV): 15°x8,5°, max. resolution: 4K UHD (3840x2160), IP66, white

4047438034890	9,8 cm
85299097	7,5 cm
140 g	9,0 cm
	0,7 l



Mx-O-M7SA-8L150
30° 4K LPF Sensor Module TELE

M73/S74 sensor module with premium tele lens, LPF special lens, e.g., for license plate detection (with infrared), aperture: f/1.8, max. image angle (HxV): 30°x17°, max. resolution: 4K UHD (3840x2160), IP66, white

4047438037730	9,8 cm
85299097	7,5 cm
140 g	9,0 cm
	0,7 l



Mx-O-M7SA-8L280
15° 4K LPF Sensor Module TELE

M73/S74 sensor module with premium tele lens, LPF special lens, e.g., for license plate detection (with infrared), aperture: f/1.8, max. image angle (HxV): 15°x8,5°, max. resolution: 4K UHD (3840x2160), IP66, white

4047438037723	9,8 cm
85299097	7,5 cm
140 g	9,0 cm
	0,7 l

Sensor Modules 4MP Low Light for MOBOTIX 7

	Article No. / Name / Description	EAN / HS / weight	dimen.
	Mx-O-M7SA-4D045-f1.0 109° f/1,0 4MP Day Sensor module M73/S74 sensor module with premium wide-angle lens for day use, aperture: f/1.0, max. image angle (HxV): 109° x 55°, max. resolution: 4MP (2688x1512), IP66, white	4047438044387 85299097 160 g	9,8 cm 7,5 cm 9,0 cm 0,7 l
	Mx-O-M7SA-4D050-f1.0 94° f/1,0 4MP Day Sensor module M73/S74 sensor module with premium wide-angle lens for day use, aperture: f/1.0, max. image angle (HxV): 94°x49,5°, max. resolution: 4MP (2688x1512), IP66, white	4047438044370 85299097 160 g	9,8 cm 7,5 cm 9,0 cm 0,7 l
	Mx-O-M7SA-4D080-f1.0 57° f/1,0 4MP Day Sensor module M73/S74 sensor module with premium wide-angle lens for day use, aperture: f/1.0, max. image angle (HxV): 57°x32°, max. resolution: 4MP (2688x1512), IP66, white	4047438044363 85299097 160 g	9,8 cm 7,5 cm 9,0 cm 0,7 l
	Mx-O-M7SA-4D115-f1.0 37° f/1,0 4MP Day Sensor module M73/S74 sensor module with premium normal lens for day use, aperture: f/1.0, max. image angle (HxV): 37,5°x22°, max. resolution: 4MP (2688x1512), IP66, white	4047438044356 85299097 160 g	9,8 cm 7,5 cm 9,0 cm 0,7 l
	Mx-O-M7SA-4DN040 120° 4MP IR Cut Day & Night Ultra LowLight Sensor Module M73/S74 sensor module with premium wide-angle lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 120° x 60°, max. resolution: 4MP (2688x1512), IP66, white	4047438037167 85299097 140 g	9,8 cm 7,5 cm 9,0 cm 0,7 l

**Mx-O-M7SA-4DN050****95° 4MP IR Cut Day & Night Ultra LowLight Sensor Module**

M73/S74 sensor module with premium wide-angle lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 95°x50°, max. resolution: 4MP (2688x1512), IP66, white

4047438037174	9,8 cm
85299097	7,5 cm
140 G	9,0 cm
	0,7 l

**Mx-O-M7SA-4DN080****60° 4MP IR Cut Day & Night Ultra LowLight Sensor Module**

M73/S74 sensor module with premium wide-angle lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 60°x33°, max. resolution: 4MP (2688x1512), IP66, white

4047438037181	9,8 cm
85299097	7,5 cm
140 G	9,0 cm
	0,7 l

**Mx-O-M7SA-4DN100****45° 4MP IR Cut Day & Night Ultra LowLight Sensor Module**

M73/S74 sensor module with premium normal lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 45°x25°, max. resolution: 4MP (2688x1512), IP66, white

4047438037198	9,8 cm
85299097	7,5 cm
140 G	9,0 cm
	0,7 l

**Mx-O-M7SA-4DN150****30° 4MP IR Cut Day & Night Ultra LowLight Sensor Module**

M73/S74 sensor module with premium tele lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 30°x17°, max. resolution: 4MP (2688x1512), IP66, white



4047438037204	9,8 cm
85299097	7,5 cm
140 G	9,0 cm
	0,7 l

**Mx-O-M7SA-4DN280****15° 4MP IR Cut Day & Night Low Light Sensor Module TELE**

M73/S74 sensor module with premium tele lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 15°x8,5°, max. resolution: 4MP (2688x1512), IP66, white

4047438037211	9,8 cm
85299097	7,5 cm
140 G	9,0 cm
	0,7 l

Sensor Modules 6MP For S16A/S16B And

	Article No. / Name / Description	EAN / HS / weight	dimen.
	Mx-O-SMA-S-6D016 Sensor Module 6MP, B016 (Day), White Sensor module S16/M16 with HD premium fisheye lens B016 (f/2.0, horiz. image angle 180°) and Moonlight sensor day, 6MP (3072 x 2048), IP66, white	4047438029100 85299097 144 g	9,8 cm 7,5 cm 9,0 cm 0,7 l
	Mx-O-SMA-S-6D036 Sensor Module 6MP, B036 (Day), White Sensor module S16/M16 with HD premium lens B036 (f/1.8, horiz. image angle 103°) and Moonlight sensor day, 6MP (3072 x 2048), IP66, white	4047438029117 85299097 144 g	9,8 cm 7,5 cm 9,0 cm 0,7 l
	Mx-O-SMA-S-6D041 Sensor Module 6MP, B041 (Day), White Sensor module S16/M16 with HD premium lens B041 (f/1.8, horiz. image angle 90°) and Moonlight sensor day, 6MP (3072 x 2048), IP66, white	4047438029124 85299097 144 g	9,8 cm 7,5 cm 9,0 cm 0,7 l
	Mx-O-SMA-S-6D061 Sensor Module 6MP, B061 (Day), White Sensor module S16/M16 with HD premium lens B061 (f/1.8, horiz. image angle 60°) and Moonlight sensor day, 6MP (3072 x 2048), IP66, white	4047438029131 85299097 144 g	9,8 cm 7,5 cm 9,0 cm 0,7 l
	Mx-O-SMA-S-6D079 Sensor Module 6MP, B079 (Day), White Sensor module S16/M16 with HD premium lens B079 (f/1.8, horiz. image angle 45°) and Moonlight sensor day, 6MP (3072 x 2048), IP66, white	4047438029148 85299097 144 g	9,8 cm 7,5 cm 9,0 cm 0,7 l

**Mx-O-SMA-S-6D119****Sensor Module 6MP, B119 (Day), White**

Sensor module S16/M16 with HD premium lens B119 (f/1.8, horiz. image angle 31°) and Moonlight sensor day, 6MP (3072 x 2048), IP66, white

4047438029155	9,8 cm
85299097	7,5 cm
144 g	9,0 cm
	0,7 l

**Mx-O-SMA-S-6D237****Sensor Module 6MP, B237 (Day), White**

Sensor module S16/M16 with HD premium lens B237 (f/1.8, horiz. image angle 15°) and Moonlight sensor day, 6MP (3072 x 2048), IP66, white

4047438029162	9,8 cm
85299097	7,5 cm
144 g	9,0 cm
	0,7 l

**Mx-O-SMA-S-6D500****Sensor Module 6MP, B500 (Day), White**

Sensor module S16/M16 with HD premium lens B500 (f/2.5, horiz. image angle 8°) and Moonlight sensor day, 6MP (3072 x 2048), IP66, white

4047438029179	9,8 cm
85299097	7,5 cm
144 g	9,0 cm
	0,7 l

**Mx-O-SMA-S-6DCSV****Sensor Module 6MP, CSVario 4,5-10 mm (Day), White**

Sensor module S16/M16 with CSVario Lens B045-100-CS focal length 4.5-10 mm, f/1.6-2.3, 39°-89° x 29°-65° • 6 Megapixel Moonlight Sensor, color (day) • Max. image size: 6MP (3072 x 2048) • IP66, -30 to 60°C / -22 to 140°F (only with lens protection cap), white

4047438030052	10,5 cm
85299097	6,8 cm
190 g	10,5 cm
	0,7 l

**Mx-O-SMA-S-6DCS****Sensor Module 6MP, CS-Mount (Day), White**

Sensor module S16/M16 for standard lenses with CS mount (e.g., for Vario lens MX-B045-100-CS) • 6 Megapixel Moonlight Sensor, color (day) • Max. image size: 6MP (3072 x 2048) • IP66, -30 to 60°C / -22 to 140°F (only with lens protection cap), white

4047438030076	10,5 cm
85299097	6,8 cm
146 g	10,5 cm
	0,7 l

**Mx-O-SMA-S-6N016****Sensor Module 6MP, B016 (Night), White**

Sensor module S16/M16 with HD premium fisheye lens B016 (f/2.0, horiz. image angle 180°) and Moonlight sensor night, 6MP (3072 x 2048), IP66, white

4047438029186	9,8 cm
85299097	7,5 cm
144 g	9,0 cm
	0,7 l

**Mx-O-SMA-S-6N036****Sensor Module 6MP, B036 (Night), White**

Sensor module S16/M16 with HD premium lens B036 (f/1.8, horiz. image angle 103°) and Moonlight sensor night, 6MP (3072 x 2048), IP66, white

4047438029193	9,8 cm
85299097	7,5 cm
170 g	9,0 cm
	0,7 l

**Mx-O-SMA-S-6N041****Sensor Module 6MP, B041 (Night), White**

Sensor module S16/M16 with HD premium lens B041 (f/1.8, horiz. image angle 90°) and Moonlight sensor night, 6MP (3072 x 2048), IP66, white

4047438029209	9,8 cm
85299097	7,5 cm
144 g	9,0 cm
	0,7 l

**Mx-O-SMA-S-6N061****Sensor Module 6MP, B061 (Night), White**

Sensor module S16/M16 with HD premium lens B061 (f/1.8, horiz. image angle 60°) and Moonlight sensor night, 6MP (3072 x 2048), IP66, white

4047438029216	9,8 cm
85299097	7,5 cm
144 g	9,0 cm
	0,7 l

**Mx-O-SMA-S-6N079****Sensor Module 6MP, B079 (Night), White**

Sensor module S16/M16 with HD premium lens B079 (f/1.8, horiz. image angle 45°) and Moonlight sensor night, 6MP (3072 x 2048), IP66, white

4047438029223	9,8 cm
85299097	7,5 cm
144 g	9,0 cm
	0,7 l

**Mx-O-SMA-S-6N119****Sensor Module 6MP, B119 (Night), White**

Sensor module S16/M16 with HD premium lens B119 (f/1.8, horiz. image angle 31°) and Moonlight sensor night, 6MP (3072 x 2048), IP66, white

4047438029230	9,8 cm
85299097	7,5 cm
144 g	9,0 cm
	0,7 l

**Mx-O-SMA-S-6N237****Sensor Module 6MP, B237 (Night), White**

Sensor module S16/M16 with HD premium lens B237 (f/1.8, horiz. image angle 15°) and Moonlight sensor night, 6MP (3072 x 2048), IP66, white

4047438029247	9,8 cm
85299097	7,5 cm
144 g	9,0 cm
	0,7 l

**Mx-O-SMA-S-6N500****Sensor Module 6MP, B500 (Night), White**

Sensor module S16/M16 with HD premium lens B500 (f/2.5, horiz. image angle 8°) and Moonlight sensor night, 6MP (3072 x 2048), IP66, white

4047438029254	9,8 cm
85299097	7,5 cm
144 G	9,0 cm
	0,7 l

**Mx-O-SMA-S-6NCSV****Sensor Module 6MP, CSVario 4,5-10 mm (Night), White**

Sensor module S16/M16 with CSVario Lens B045-100-CS (focal length 4.5-10 mm, f/1.6-2.3, 39°-89° x 29°-65°) • 6 Megapixel Moonlight Sensor, B/W (night) • Max. image size: 6MP (3072 x 2048) • IP66, -30 to 60°C / -22 to 140°F (only with lens protection cap), white

4047438030069	10,5 cm
85299097	6,8 cm
190 G	10,5 cm
	0,7 l

**Mx-O-SMA-S-6NCS****Sensor Module 6MP, CS-Mount (Night), White**

Sensor module S16/M16 for standard lenses with CS mount (e.g., for Vario lens MX-B045-100-CS) • 6 Megapixel Moonlight Sensor, B/W (night) • Max. image size: 6MP (3072 x 2048) • IP66, -30 to 60°C / -22 to 140°F (only with lens protection cap), white

4047438030083	10,5 cm
85299097	6,8 cm
146 G	10,5 cm
	0,7 l

**Mx-O-SMA-S-6L016****Sensor Module 6MP, B016 (Night LPF), White**

Sensor module S16/M16 with HD premium lens B016 (f/2.0, horiz. image angle 180°) and Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared), IP66, white

4047438029261	9,8 cm
85299097	7,5 cm
144 G	9,0 cm
	0,7 l

**Mx-O-SMA-S-6L036****Sensor Module 6MP, B036 (Night LPF), White**

Sensor module S16/M16 with HD premium lens B036 (f/1.8, horiz. image angle 103°) and Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared), IP66, white

4047438029278	9,8 cm
85299097	7,5 cm
144 G	9,0 cm
	0,7 l

**Mx-O-SMA-S-6L041****Sensor Module 6MP, B041 (Night LPF), White**

Sensor module S16/M16 with HD premium lens B041 (f/1.8, horiz. image angle 90°) and Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared), IP66, white

4047438029285	9,8 cm
85299097	7,5 cm
144 G	9,0 cm
	0,7 l

**Mx-O-SMA-S-6L061****Sensor Module 6MP, B061 (Night LPF), White**

Sensor module S16/M16 with HD premium lens B061 (f/1.8, horiz. image angle 60°) and Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared), IP66, white

4047438029292	9,8 cm
85299097	7,5 cm
144 G	9,0 cm
	0,7 l

**Mx-O-SMA-S-6L079****Sensor Module 6MP, B079 (Night LPF), White**

Sensor module S16/M16 with HD premium lens B079 (f/1.8, horiz. image angle 45°) and Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared), IP66, white

4047438029308	9,8 cm
85299097	7,5 cm
144 G	9,0 cm
	0,7 l

**Mx-O-SMA-S-6L119****Sensor Module 6MP, B119 (Night LPF), White**

Sensor module S16/M16 with HD premium lens B119 (f/1.8, horiz. image angle 31°) and Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared), IP66, white

4047438029315	9,8 cm
85299097	7,5 cm
144 G	9,0 cm
	0,7 l

**Mx-O-SMA-S-6L237****Sensor Module 6MP, B237 (Night LPF), White**

Sensor module S16/M16 with HD premium lens B237 (f/1.8, horiz. image angle 15°) and Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared), IP66, white

4047438029322	9,8 cm
85299097	7,5 cm
144 G	9,0 cm
	0,7 l

**Mx-O-SMA-S-6L500****Sensor Module 6MP, B500 (Night LPF), White**

Sensor module S16/M16 with HD premium lens B500 (f/2.5, horiz. image angle 8°) and Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared), IP66, white

4047438029339	9,8 cm
85299097	7,5 cm
144 G	9,0 cm
	0,7 l

**Mx-O-SMA-S-6D016-b****Sensor Module 6MP, B016 (Day), Black**

Sensor module S16/M16 with HD premium lens B016 (f/2.0, horiz. image angle 180°) and Moonlight sensor day, 6MP (3072 x 2048), IP66, black

4047438029346	9,8 cm
85299097	7,5 cm
144 G	9,0 cm
	0,7 l

**Mx-O-SMA-S-6D036-b****Sensor Module 6MP, B036 (Day), Black**

Sensor module S16/M16 with HD premium lens B036 (f/1.8, horiz. image angle 103°) and Moonlight sensor day, 6MP (3072 x 2048), IP66, black

4047438029353	9,8 cm
85299097	7,5 cm
144 G	9,0 cm
	0,7 l

**Mx-O-SMA-S-6D041-b****Sensor Module 6MP, B041 (Day), Black**

Sensor module S16/M16 with HD premium lens B041 (f/1.8, horiz. image angle 90°) and Moonlight sensor day, 6MP (3072 x 2048), IP66, black

4047438029360	9,8 cm
85299097	7,5 cm
144 G	9,0 cm
	0,7 l

**Mx-O-SMA-S-6D061-b****Sensor Module 6MP, B061 (Day), Black**

Sensor module S16/M16 with HD premium lens B061 (f/1.8, horiz. image angle 60°) and Moonlight sensor day, 6MP (3072 x 2048), IP66, black

4047438029377	9,8 cm
85299097	7,5 cm
144 G	9,0 cm
	0,7 l

**Mx-O-SMA-S-6D079-b****Sensor Module 6MP, B079 (Day), Black**

Sensor module S16/M16 with HD premium lens B079 (f/1.8, horiz. image angle 45°) and Moonlight sensor day, 6MP (3072 x 2048), IP66, black

4047438029384	9,8 cm
85299097	7,5 cm
144 G	9,0 cm
	0,7 l

**Mx-O-SMA-S-6D119-b****Sensor Module 6MP, B119 (Day), Black**

Sensor module S16/M16 with HD premium lens B119 (f/1.8, horiz. image angle 31°) and Moonlight sensor day, 6MP (3072 x 2048), IP66, black

4047438029391	9,8 cm
85299097	7,5 cm
144 G	9,0 cm
	0,7 l

**Mx-O-SMA-S-6D237-b****Sensor Module 6MP, B237 (Day), Black**

Sensor module S16/M16 with HD premium lens B237 (f/1.8, horiz. image angle 15°) and Moonlight sensor day, 6MP (3072 x 2048), IP66, black

4047438029407	9,8 cm
85299097	7,5 cm
144 G	9,0 cm
	0,7 l

**Mx-O-SMA-S-6D500-b****Sensor Module 6MP, B500 (Day), Black**

Sensor module S16/M16 with HD premium lens B500 (f/2.5, horiz. image angle 8°) and Moonlight sensor day, 6MP (3072 x 2048), IP66, black

4047438029414	9,8 cm
85299097	7,5 cm
144 G	9,0 cm
	0,7 l

**Mx-O-SMA-S-6N016-b****Sensor Module 6MP, B016 (Night), Black**

Sensor module S16/M16 with HD premium lens B016 (f/2.0, horiz. image angle 180°) and Moonlight sensor night, 6MP (3072 x 2048), IP66, black

4047438029421	9,8 cm
85299097	7,5 cm
144 G	9,0 cm
	0,7 l

**Mx-O-SMA-S-6N036-b****Sensor Module 6MP, B036 (Night), Black**

Sensor module S16/M16 with HD premium lens B036 (f/1.8, horiz. image angle 103°) and Moonlight sensor night, 6MP (3072 x 2048), IP66, black

4047438029438	9,8 cm
85299097	7,5 cm
144 G	9,0 cm
	0,7 l

**Mx-O-SMA-S-6N041-b****Sensor Module 6MP, B041 (Night), Black**

Sensor module S16/M16 with HD premium lens B041 (f/1.8, horiz. image angle 90°) and Moonlight sensor night, 6MP (3072 x 2048), IP66, black

4047438029445	9,8 cm
85299097	7,5 cm
144 G	9,0 cm
	0,7 l

**Mx-O-SMA-S-6N061-b****Sensor Module 6MP, B061 (Night), Black**

Sensor module S16/M16 with HD premium lens B061 (f/1.8, horiz. image angle 60°) and Moonlight sensor night, 6MP (3072 x 2048), IP66, black

4047438029452	9,8 cm
85299097	7,5 cm
144 G	9,0 cm
	0,7 l

**Mx-O-SMA-S-6N079-b****Sensor Module 6MP, B079 (Night), Black**

Sensor module S16/M16 with HD premium lens B079 (f/1.8, horiz. image angle 45°) and Moonlight sensor night, 6MP (3072 x 2048), IP66, black

4047438029469	9,8 cm
85299097	7,5 cm
144 G	9,0 cm
	0,7 l

**Mx-O-SMA-S-6N119-b****Sensor Module 6MP, B119 (Night), Black**

Sensor module S16/M16 with HD premium lens B119 (f/1.8, horiz. image angle 31°) and Moonlight sensor night, 6MP (3072 x 2048), IP66, black

4047438029476	9,8 cm
85299097	7,5 cm
144 G	9,0 cm
	0,7 l

**Mx-O-SMA-S-6N237-b****Sensor Module 6MP, B237 (Night), Black**

Sensor module S16/M16 with HD premium lens B237 (f/1.8, horiz. image angle 15°) and Moonlight sensor night, 6MP (3072 x 2048), IP66, black

4047438029483	9,8 cm
85299097	7,5 cm
144 G	9,0 cm
	0,7 l

**Mx-O-SMA-S-6N500-b****Sensor Module 6MP, B500 (Night), Black**

Sensor module S16/M16 with HD premium lens B500 (f/2.5, horiz. image angle 8°) and Moonlight sensor night, 6MP (3072 x 2048), IP66, black

4047438029490	9,8 cm
85299097	7,5 cm
144 G	9,0 cm
	0,7 l

**Mx-O-SMA-S-6L016-b****Sensor Module 6MP, B016 (Night LPF), Black**

Sensor module S16/M16 with HD premium lens B016 (f/2.0, horiz. image angle 180°) and Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared), IP66, black

4047438029506	9,8 cm
85299097	7,5 cm
144 G	9,0 cm
	0,7 l

**Mx-O-SMA-S-6L036-b****Sensor Module 6MP, B036 (Night LPF), Black**

Sensor module S16/M16 with HD premium lens B036 (f/1.8, horiz. image angle 103°) and Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared), IP66, black

4047438029513	9,8 cm
85299097	7,5 cm
144 G	9,0 cm
	0,7 l

**Mx-O-SMA-S-6L041-b****Sensor Module 6MP, B041 (Night LPF), Black**

Sensor module S16/M16 with HD premium lens B041 (f/1.8, horiz. image angle 90°) and Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared), IP66, black

4047438029520	9,8 cm
85299097	7,5 cm
144 G	9,0 cm
	0,7 l

**Mx-O-SMA-S-6L061-b****Sensor Module 6MP, B061 (Night LPF), Black**

Sensor module S16/M16 with HD premium lens B061 (f/1.8, horiz. image angle 60°) and Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared), IP66, black

4047438029537	9,8 cm
85299097	7,5 cm
144 G	9,0 cm
	0,7 l

**Mx-O-SMA-S-6L079-b****Sensor Module 6MP, B079 (Night LPF), Black**

Sensor module S16/M16 with HD premium lens B079 (f/1.8, horiz. image angle 45°) and Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared), IP66, black

4047438029544	9,8 cm
85299097	7,5 cm
144 G	9,0 cm
	0,7 l

**Mx-O-SMA-S-6L119-b****Sensor Module 6MP, B119 (Night LPF), Black**

Sensor module S16/M16 with HD premium lens B119 (f/1.8, horiz. image angle 31°) and Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared), IP66, black

4047438029551	9,8 cm
85299097	7,5 cm
144 G	9,0 cm
	0,7 l

**Mx-O-SMA-S-6L237-b****Sensor Module 6MP, B237 (Night LPF), Black**

Sensor module S16/M16 with HD premium lens B237 (f/1.8, horiz. image angle 15°) and Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared), IP66, black

4047438029568	9,8 cm
85299097	7,5 cm
144 G	9,0 cm
	0,7 l

**Mx-O-SMA-S-6L500-b****Sensor Module 6MP, B500 (Night LPF), Black**

Sensor module S16/M16 with HD premium lens B500 (f/2.5, horiz. image angle 8°) and Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared), IP66, black

4047438029575	9,8 cm
85299097	7,5 cm
144 G	9,0 cm
	0,7 l

BlockFlexMounts 12MP for S7x

Article No. / Name / Description

EAN / HS / weight dimen.



MX-O-M7SA-B-12DN016

BlockFlexMount 12MP IR Cut Day & Night Sensor Module,

Suitable for: S74 • 12MP Sensor module with premium hemispheric lens and IR cut filter for day and night use, max. resolution: 4K UHD (2880x2880) • Operating conditions: IP30, 0 to 50°C (32 to 122°F) • Integrated status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)

4047438047715 10,0 cm

85299097 7,5 cm

120 g 9,0 cm

0,7 l

BlockFlexMounts 4K for S7x

	Article No. / Name / Description	EAN / HS / weight	dimen.
	MX-O-M7SA-B-8DN040 BlockFlexMount 4K IR Cut Day & Night Sensor Module, incl. Suitable for: S74 • Sensor module with premium wide-angle lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 120°x60°, max. resolution: 4K UHD (3840x2160) • Operating conditions: IP30, 0 to 50°C (32 to 122°F) • Integrated status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)	4047438047722 85299097 125 g	10,0 cm 7,5 cm 9,0 cm 0,7 l
	MX-O-M7SA-B-8DN050 BlockFlexMount 4K IR Cut Day & Night Sensor Module, incl. Suitable for: S74 • Sensor module with premium wide-angle lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 95°x50°, max. resolution: 4K UHD (3840x2160) • Operating conditions: IP30, 0 to 50°C (32 to 122°F) • Integrated status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)	4047438047739 85299097 125 g	10,0 cm 7,5 cm 9,0 cm 0,7 l
	MX-O-M7SA-B-8DN080 BlockFlexMount 4K IR Cut Day & Night Sensor Module, incl. Suitable for: S74 • Sensor module with premium wide-angle lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 60°x33°, max. resolution: 4K UHD (3840x2160) • Operating conditions: IP30, 0 to 50°C (32 to 122°F) • Integrated status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)	4047438047746 85299097 125 g	10,0 cm 7,5 cm 9,0 cm 0,7 l
	MX-O-M7SA-B-8DN100 BlockFlexMount 4K IR Cut Day & Night Sensor Module, incl. Suitable for: S74 • Sensor module with premium wide-angle lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 45°x25°, max. resolution: 4K UHD (3840x2160) • Operating conditions: IP30, 0 to 50°C (32 to 122°F) • Integrated status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)	4047438047753 85299097 125 g	10,0 cm 7,5 cm 9,0 cm 0,7 l
	MX-O-M7SA-B-8DN150 BlockFlexMount 4K IR Cut Day & Night Sensor Module, incl. Suitable for: S74 • Sensor module with premium wide-angle lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 30°x17°, max. resolution: 4K UHD (3840x2160) • Operating conditions: IP30, 0 to 50°C (32 to 122°F) • Integrated status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)	4047438047760 85299097 125 g	10,0 cm 7,5 cm 9,0 cm 0,7 l

**MX-O-M7SA-B-8DN280****BlockFlexMount 4K IR Cut Day & Night Sensor Module, incl.**

Suitable for: S74 • Sensor module with premium wide-angle lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 15°x8.5°, max. resolution: 4K UHD (3840x2160) • Operating conditions: IP30, 0 to 50°C (32 to 122°F) • Integrated status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)

4047438047777	10,0 cm
85299097	7,5 cm
125 g	9,0 cm
	0,7 l

**MX-O-M7SA-B-8DN500****BlockFlexMount 4K IR Cut Day & Night Sensor Module, incl.**

Suitable for: S74 • Sensor module with premium wide-angle lens and IR cut filter for day and night use, aperture: f/1.8, max. image angle (HxV): 8°x4.5°, max. resolution: 4K UHD (3840x2160) • Operating conditions: IP30, 0 to 50°C (32 to 122°F) • Integrated status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)

4047438047784	10,0 cm
85299097	7,5 cm
180 g	9,0 cm
	0,7 l

BlockFlexMounts 6MP For S16A/S16B

	Article No. / Name / Description	EAN / HS / weight	dimen.
	Mx-O-SMA-B-6D016	4047438029797	9,8 cm
	BlockFlexMount 6MP, Incl. Hemispheric B016 (Day) Suitable for: S16 • HD premium lens B016 (f/2.0, horiz. image angle 180°) and Moonlight sensor day, 6MP (3072 x 2048) • Operating conditions: IP30, 0 to 50°C (32 to 122°F) • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)	85299097 155 g	7,5 cm 9,0 cm 0,7 l
	Mx-O-SMA-B-6D036	4047438029803	9,8 cm
	BlockFlexMount 6MP, Incl. B036 (Day) Suitable for: S16 • HD premium lens B036 (f/1.8, horiz. image angle 103°) and Moonlight sensor day, 6MP (3072 x 2048) • Operating conditions: IP30, 0 to 50°C (32 to 122°F) • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)	85299097 155 g	7,5 cm 9,0 cm 0,7 l
	Mx-O-SMA-B-6D041	4047438029810	10,0 cm
	BlockFlexMount 6MP, Incl. B041 (Day) Suitable for: S16 • HD premium lens B041 (f/1.8, horiz. image angle 90°) and Moonlight sensor day, 6MP (3072 x 2048) • Operating conditions: IP30, 0 to 50°C (32 to 122°F) • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)	85299097 134 g	7,5 cm 9,0 cm 0,7 l
	Mx-O-SMA-B-6D061	4047438029827	10,0 cm
	BlockFlexMount 6MP, Incl. B061 (Day) Suitable for: S16 • HD premium lens B061 (f/1.8, horiz. image angle 60°) and Moonlight sensor day, 6MP (3072 x 2048) • Operating conditions: IP30, 0 to 50°C (32 to 122°F) • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)	85299097 136 g	7,5 cm 9,0 cm 0,7 l
	Mx-O-SMA-B-6D079	4047438029834	10,0 cm
	BlockFlexMount 6MP, Incl. B079 (Day) Suitable for: S16 • HD premium lens B079 (f/1.8, horiz. image angle 45°) and Moonlight sensor day, 6MP (3072 x 2048) • Operating conditions: IP30, 0 to 50°C (32 to 122°F) • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)	85299097 134 g	7,5 cm 9,0 cm 0,7 l

**Mx-O-SMA-B-6D119****BlockFlexMount 6MP, Incl. B119 (Day)**


Suitable for: S16 • HD premium lens B119 (f/1.8, horiz. image angle 31°) and Moonlight sensor day, 6MP (3072 x 2048) • Operating conditions: IP30, 0 to 50°C (32 to 122°F) • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)

4047438029841	10,0 cm
85299097	7,5 cm
130 g	9,0 cm
	0,7 l

**Mx-O-SMA-B-6D237****BlockFlexMount 6MP, Incl. B237 (Day)**


Suitable for: S16 • HD premium lens B237 (f/1.8, horiz. image angle 15°) and Moonlight sensor day, 6MP (3072 x 2048) • Operating conditions: IP30, 0 to 50°C (32 to 122°F) • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)

4047438029858	10,0 cm
85299097	7,5 cm
134 g	9,0 cm
	0,7 l

**Mx-O-SMA-B-6D500****BlockFlexMount 6MP, incl. B500 (Day)**

Suitable for: S16 • HD premium lens B500 (f/2.5, horiz. image angle 8°) and Moonlight sensor day, 6MP (3072 x 2048) • Operating conditions: IP30, 0 to 50°C (32 to 122°F) • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)

4047438029865	10,0 cm
85299097	7,5 cm
150 g	9,0 cm
	0,7 l

**Mx-O-SMA-B-6DCS****BlockFlexMount 6MP, For CS Mount Lens (Day)**

Suitable for: S16 • For standard lenses with CS mount (e.g., MX-B045-100-CS), Moonlight sensor day, 6MP (3072 x 2048) • Operating conditions: IP30, 0 to 50°C (32 to 122°F) • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)

4047438029766	9,8 cm
85299097	7,5 cm
155 g	9,0 cm
	0,7 l

**Mx-O-SMA-B-6N016****BlockFlexMount 6MP, Incl. Hemispheric B016 (Night)**

Suitable for: S16 • HD premium lens B016 (f/2.0, horiz. image angle 180°) and Moonlight sensor night, 6MP (3072 x 2048) • Operating conditions: IP30, 0 to 50°C (32 to 122°F) • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)

4047438029872	9,8 cm
85299097	7,5 cm
155 g	9,0 cm
	0,7 l

**Mx-O-SMA-B-6N036****BlockFlexMount 6MP, Incl. B036 (Night)**

Suitable for: S16 • HD premium lens B036 (f/1.8, horiz. image angle 103°) and Moonlight sensor night, 6MP (3072 x 2048) • Operating conditions: IP30, 0 to 50°C (32 to 122°F) • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)

4047438029889	9,8 cm
85299097	7,5 cm
155 g	9,0 cm
	0,7 l

**Mx-O-SMA-B-6N041****BlockFlexMount 6MP, Incl. B041 (Night)**


Suitable for: S16 • HD premium lens B041 (f/1.8, horiz. image angle 90°) and Moonlight sensor night, 6MP (3072 x 2048) • Operating conditions: IP30, 0 to 50°C (32 to 122°F) • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)

4047438029896	9,8 cm
85299097	7,5 cm
155 9	9,0 cm
	0,7 l

**Mx-O-SMA-B-6N061****BlockFlexMount 6MP, Incl. B061 (Night)**

Suitable for: S16 • HD premium lens B061 (f/1.8, horiz. image angle 60°) and Moonlight sensor night, 6MP (3072 x 2048) • Operating conditions: IP30, 0 to 50°C (32 to 122°F) • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)

4047438029902	9,8 cm
85299097	7,5 cm
155 9	9,0 cm
	0,7 l

**Mx-O-SMA-B-6N079****BlockFlexMount 6MP, Incl. B079 (Night)**

Suitable for: S16 • HD premium lens B079 (f/1.8, horiz. image angle 45°) and Moonlight sensor night, 6MP (3072 x 2048) • Operating conditions: IP30, 0 to 50°C (32 to 122°F) • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)

4047438029919	10,0 cm
85299097	7,5 cm
134 9	9,0 cm
	0,7 l

**Mx-O-SMA-B-6N119****BlockFlexMount 6MP, Incl. B119 (Night)**


Suitable for: S16 • HD premium lens B119 (f/1.8, horiz. image angle 31°) and Moonlight sensor night, 6MP (3072 x 2048) • Operating conditions: IP30, 0 to 50°C (32 to 122°F) • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)

4047438029926	10,0 cm
85299097	7,5 cm
130 9	9,0 cm
	0,7 l

**Mx-O-SMA-B-6N237****BlockFlexMount 6MP, Incl. B237 (Night)**


Suitable for: S16 • HD premium lens B237 (f/1.8, horiz. image angle 15°) and Moonlight sensor night, 6MP (3072 x 2048) • Operating conditions: IP30, 0 to 50°C (32 to 122°F) • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)

4047438029933	10,0 cm
85299097	7,5 cm
134 9	9,0 cm
	0,7 l

**Mx-O-SMA-B-6N500****BlockFlexMount 6MP, Incl. B500 (Night)**

Suitable for: S16 • HD premium lens B500 (f/2.5, horiz. image angle 8°) and Moonlight sensor night, 6MP (3072 x 2048) • Operating conditions: IP30, 0 to 50°C (32 to 122°F) • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)

4047438029940	9,8 cm
85299097	7,5 cm
155 9	9,0 cm
	0,7 l

**Mx-O-SMA-B-6NCS****BlockFlexMount 6MP, For CS Mount Lens (Night)**

Suitable for: S16 • For standard lenses with CS mount (e.g., MX-B045-100-CS), Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared) • Operating conditions: IP30, 0 to 50°C (32 to 122°F) • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)

4047438029773	10,0 cm
85299097	7,5 cm
102 9	9,0 cm
	0,7 l

**Mx-O-SMA-B-6L036****BlockFlexMount 6MP, Incl. B036 (Night LPF)**

Suitable for: S16 • HD premium lens B036 (f/1.8, horiz. image angle 103°) and Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared) • Operating conditions: IP30, 0 to 50°C (32 to 122°F) • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)

4047438029957	10,0 cm
85299097	7,5 cm
136 9	9,0 cm
	0,7 l

**Mx-O-SMA-B-6L041****BlockFlexMount 6MP, Incl. B041 (Night LPF)**


Suitable for: S16, S15 • HD premium lens B041 (f/1.8, horiz. image angle 90°) and Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared) • Operating conditions: IP30, 0 to 50°C (32 to 122°F) • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)

4047438029964	10,0 cm
85299097	7,5 cm
132 9	9,0 cm
	0,7 l

**Mx-O-SMA-B-6L061****BlockFlexMount 6MP, Incl. B061 (Night LPF)**

Suitable for: S16, S15 • HD premium lens B061 (f/1.8, horiz. image angle 60°) and Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared) • Operating conditions: IP30, 0 to 50°C (32 to 122°F) • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)

4047438029971	10,0 cm
85299097	7,5 cm
134 9	9,0 cm
	0,7 l

**Mx-O-SMA-B-6L079****BlockFlexMount 6MP, Incl. B079 (Night LPF)**

Suitable for: S16 • HD premium lens B079 (f/1.8, horiz. image angle 45°) and Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared) • Operating conditions: IP30, 0 to 50°C (32 to 122°F) • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)

4047438029988	10,0 cm
85299097	7,5 cm
134 9	9,0 cm
	0,7 l

**Mx-O-SMA-B-6L119****BlockFlexMount 6MP, Incl. B119 (Night LPF)**


Suitable for: S16 • HD premium lens B119 (f/1.8, horiz. image angle 31°) and Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared) • Operating conditions: IP30, 0 to 50°C (32 to 122°F) • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)

4047438029995	10,0 cm
85299097	7,5 cm
130 9	9,0 cm
	0,7 l

**Mx-O-SMA-B-6L237****BlockFlexMount 6MP, Incl. B237 (Night LPF)**


Suitable for: S16 • HD premium lens B237 (f/1.8, horiz. image angle 15°) and Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared) • Operating conditions: IP30, 0 to 50°C (32 to 122°F) • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)

4047438030007	10,0 cm
85299097	7,5 cm
134 g	9,0 cm
	0,7 l

**Mx-O-SMA-B-6L500****BlockFlexMount 6MP, Incl. B500 (Night LPF)**

Suitable for: S16 • HD premium lens B500 (f/2.5, horiz. image angle 8°) and Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared) • Operating conditions: IP30, 0 to 50°C (32 to 122°F) • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)


4047438030014	10,0 cm
85299097	7,5 cm
150 g	9,0 cm
	0,7 l

**Mx-O-SMA-B-6LCS****BlockFlexMount 6MP, For CS Mount Lens (Night LPF)**

Suitable for: S16 • For standard lenses with CS mount (e.g., MX-B045-100-CS), Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared) • Operating conditions: IP30, 0 to 50°C (32 to 122°F) • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)

4047438029780	10,0 cm
85299097	7,5 cm
104 g	9,0 cm
	0,7 l

Sensor Modules 6MP For D16A/D16B

	Article No. / Name / Description	EAN / HS / weight	dimen.	
 	Mx-O-SDA-F-6D6N Sensor Bridge FIX For D16, 2x 6MP (Day & Night) Day & Night sensor bridge for D16 Body, including two parallel aligned 6MP sensors (1x Day, 1x Night) and a XL cover (MX-D15-DCT-XL) • Lenses not included (two lenses B036 to B237 possible, to be ordered separately)	4047438030182 85299097 346 g	19,6 cm 18,0 cm 14,8 cm 5,2 l	
	 	Mx-O-SDA-P-6D6D Sensor Bridge PAN/180° For D16, 2x 6MP (Day) Panorama/180° sensor bridge for D16 Body, including two day sensors 6MP and a XL cover (MX-D15-DCT-XL) • Lenses not included (two lenses B041 needed for 180° panoramic image, to be ordered separately)	4047438030199 85299097 346 g	19,6 cm 18,0 cm 14,8 cm 5,2 l
		 	Mx-O-SDA-P-6N6N Sensor Bridge PAN-N/180° for D16, 2x 6MP (Night) Panorama/180° sensor bridge for D16 Body, including two night sensors 6MP and a XL cover (MX-D15-DCT-XL) • Lenses not included (two lenses B041 needed for 180° panoramic image, to be ordered separately)	4047438030205 85299097 344 g
 			Mx-O-SDA-S-6D036 Sensor Module D16 6MP, Incl. B036 (Day) Sensor module D16 with HD premium lens B036 (f/1.8, horiz. image angle 103°) and Moonlight sensor day, 6MP (3072 x 2048)	4047438029582 85299097 68 g
	 		Mx-O-SDA-S-6D041 Sensor Module D16 6MP, Incl. B041 (Day) Sensor module D16 with HD premium lens B041 (f/1.8, horiz. image angle 90°) and Moonlight sensor day, 6MP (3072 x 2048)	4047438029599 85299097 66 g

**Mx-O-SDA-S-6D061****Sensor Module D16 6MP, Incl. B061 (Day)**

Sensor module D16 with HD premium lens B061 (f/1.8, horiz. image angle 60°) and Moonlight sensor day, 6MP (3072 x 2048)

4047438029605	9,0 cm
85299097	7,5 cm
68 g	5,0 cm
	0,3 l

**Mx-O-SDA-S-6D079****Sensor Module D16 6MP, Incl. B079 (Day)**

Sensor module D16 with HD premium lens B079 (f/1.8, horiz. image angle 45°) and Moonlight sensor day, 6MP (3072 x 2048)

4047438029612	9,0 cm
85299097	7,5 cm
68 g	5,0 cm
	0,3 l

**Mx-O-SDA-S-6D119****Sensor Module D16 6MP, Incl. B119 (Day)**

Sensor module D16 with HD premium lens B119 (f/1.8, horiz. image angle 31°) and Moonlight sensor day, 6MP (3072 x 2048)

4047438029629	9,0 cm
85299097	7,5 cm
68 g	5,0 cm
	0,3 l

**Mx-O-SDA-S-6N036****Sensor Module D16 6MP, Incl. B036 (Night)**

Sensor module D16 with HD premium lens B036 (f/1.8, horiz. image angle 103°) and Moonlight sensor day, 6MP (3072 x 2048)

4047438029643	9,0 cm
85299097	7,5 cm
68 g	5,0 cm
	0,3 l

**Mx-O-SDA-S-6N041****Sensor Module D16 6MP, Incl. B041 (Night)**

Sensor module D16 with HD premium lens B041 (f/1.8, horiz. image angle 90°) and Moonlight sensor night, 6MP (3072 x 2048)

4047438029650	9,0 cm
85299097	7,5 cm
66 g	5,0 cm
	0,3 l

**Mx-O-SDA-S-6N061****Sensor Module D16 6MP, Incl. B061 (Night)**

Sensor module D16 with HD premium lens B061 (f/1.8, horiz. image angle 60°) and Moonlight sensor night, 6MP (3072 x 2048)

4047438029667	9,0 cm
85299097	7,5 cm
68 g	5,0 cm
	0,3 l

**Mx-O-SDA-S-6N079****Sensor Module D16 6MP, Incl. B079 (Night)**

Sensor module D16 with HD premium lens B079 (f/1.8, horiz. image angle 45°) and Moonlight sensor night, 6MP (3072 x 2048)

4047438029674	9,0 cm
85299097	7,5 cm
68 g	5,0 cm
	0,3 l

**Mx-O-SDA-S-6N119****Sensor Module D16 6MP, Incl. B119 (Night)**

Sensor module D16 with HD premium lens B119 (f/1.8, horiz. image angle 31°) and Moonlight sensor night, 6MP (3072 x 2048)

4047438029681	9,0 cm
85299097	7,5 cm
64 g	5,0 cm
	0,3 l

**Mx-O-SDA-S-6L036****Sensor Module D16 6MP, Incl. B036 (Night LPF)**

Sensor module D16 with HD premium lens B036 (f/1.8, horiz. image angle 103°) and Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared)

4047438029704	7,5 cm
85299097	4,9 cm
64 g	9,0 cm
	0,3 l

**Mx-O-SDA-S-6L041****Sensor Module D16 6MP, Incl. B041 (Night LPF)**

Sensor module D16 with HD premium lens B041 (f/1.8, horiz. image angle 90°) and Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared)

4047438029711	7,5 cm
85299097	4,9 cm
64 g	9,0 cm
	0,3 l

**Mx-O-SDA-S-6L061****Sensor Module D16 6MP, Incl. B061 (Night LPF)**

Sensor module D16 with HD premium lens B061 (f/1.8, horiz. image angle 60°) and Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared)

4047438029728	7,5 cm
85299097	4,9 cm
64 g	9,0 cm
	0,3 l

**Mx-O-SDA-S-6L079****Sensor Module D16 6MP, Incl. B079 (Night LPF)**

Sensor module D16 with HD premium lens B079 (f/1.8, horiz. image angle 45°) and Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared)

4047438029735	7,5 cm
85299097	4,9 cm
64 g	9,0 cm
	0,3 l

**Mx-O-SDA-S-6L119****Sensor Module D16 6MP, Incl. B119 (Night LPF)**

Sensor module D16 with HD premium lens B119 (f/1.8, horiz. image angle 31°) and Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared)

4047438029742	7,5 cm
85299097	4,9 cm
64 9	9,0 cm
	0,3 l


Camera Accessories

BeyondHumanVision

MOBOTIX

Camera Mounts (M7)

	Article No. / Name / Description	EAN / HS / weight	dimen.
	Mx-M-CM-M73 Ceiling Mount for M73 models Suitable for: M73 cameras • Die-Casting, white incl. Mounting parts	4047438039819 90079100 631 g	19,6 cm 18,0 cm 14,8 cm 5,2 l
	Mx-M-IC-DQ In-Ceiling Set for MOBOTIX 7 Single Lens Models In-Ceiling Set for MOBOTIX 7 Single Lens Models	4047438040761 90079100 665 g	39,5 cm 29,6 cm 9,0 cm 10,5 l
	Mx-M-OW-DQ On-Wall Set for MOBOTIX 7 Single Lens Models On-Wall Set for MOBOTIX 7 Single Lens Models	4047438040662 90079100 410 g	29,6 cm 19,6 cm 9,0 cm 5,2 l
	Mx-M-OW-DQ-10DEG On-Wall Set 10° for MOBOTIX 7 Single Lens Models On-Wall Set 10° inclined for MOBOTIX 7 Single Lens Models	4047438043373 90079100 500 g	29,6 cm 19,6 cm 9,0 cm 5,2 l
	Mx-M-OW-M73 On-Wall Mount for M73 models Suitable for: M73 cameras • Die-Casting, white incl. Mounting parts	4047438039802 90079100 502 g	19,6 cm 18,0 cm 14,8 cm 5,2 l

**Mx-M-PM-M73****Pole mount for M73 models**

Suitable for: M73 Cameras • 2 mm stainless steel, white • Incl. mounting parts and 2 stainless steel straps for pole diameters of 60 to 180 mm

4047438035064	20,0 cm
90079100	18,2 cm
1.247 g	9,0 cm
	3,3 l

**Mx-M-WM-DQ****Wall Mount for MOBOTIX 7 Single Lens Models**

Wall Mount for MOBOTIX 7 Single Lens Models



4047438040778	29,6 cm
90079100	19,6 cm
835 g	18,0 cm
	10,4 l

**Mx-M-WPM-DQ****Wall & Pole/Corner Mount Set For D7x/Q7x**

Suitable for: D7x and Q7x • Set consisting of pole/corner mount (MX-OPT-MH) and wall mount (Mx-M-WM-DQ) • Pole/corner mount for fastening of wall mount: 3 mm stainless steel, white • Wall mount consists of shock-resistant fiberglass-reinforced plastic (PBT), white • Covers RJ45 wall outlets • Ample room inside for extras (e.g., interface boxes) • Incl. mounting parts and 2 stainless steel straps for pole diameters of 60 to 180 mm

4047438041348	41,0 cm
90079100	31,0 cm
3.380 g	20,0 cm
	25,4 l

Mounts For S74

	Article No. / Name / Description	EAN / HS / weight	dimen.
	Mx-M-DLMA	4047438036887	19,6 cm
	DualMount S7x, white For surveillance of one to two areas with two sensor modules • Suitable for all screwable sensor modules of the S7x (not included) • Concealed cabling, weatherproof from -30 to 60°C/-22 to 140°F • Suitable for ceiling installation, with a 25° tilt of the lenses • Color: white	90079100 450 g	15,0 cm 9,0 cm 2,6 l
	Mx-M-DLMA-b	4047438041553	19,6 cm
	DualMount S7x, black For surveillance of one to two areas with two sensor modules • Suitable for all screwable sensor modules of the S7x (not included) • Concealed cabling, weatherproof from -30 to 60°C/-22 to 140°F • Suitable for ceiling installation, with a 25° tilt of the lenses • Color: black	90079100 450 g	15,0 cm 9,0 cm 2,6 l
	Mx-M-PTMA	4047438036894	19,6 cm
	PTMount S7x, white Manually adjustable dome mount for one sensor module (not included) • Features three axes that allow it to compensate for sideways tilt and to re-align the image horizon horizontally when mounted to a wall • Suitable for all screwable sensor modules for S7x and S16B • Concealed cabling, weatherproof from -30 to 60°C/-22 to 140°F • Suitable for ceiling or wall installation • Color: white • Angled sensor cables are recommended (e.g. Mx-A-S7A-CBL01-AN)	90079100 620 g	18,0 cm 14,8 cm 5,2 l
	Mx-M-PTMA-b	4047438036900	19,6 cm
	PTMount S7x, black Manually adjustable dome mount for one sensor module (not included) • Features three axes that allow it to compensate for sideways tilt and to re-align the image horizon horizontally when mounted to a wall • Suitable for all screwable sensor modules for S7x • Concealed cabling, weatherproof from -30 to 60°C/-22 to 140°F • Suitable for ceiling or wall installation • Color: black	90079100 620 g	18,0 cm 14,8 cm 5,2 l
	Mx-M-PTMA-OW On-Wall Kit for PTMount S7x, white On-Wall Kit for PTMount S7x, white incl. Mounting parts	4047438039826 90079100 75 g	9,8 cm 7,5 cm 9,0 cm 0,7 l

**Mx-M-PTMA-OW-b****On-Wall Kit for PTMount S7x, black**

On-Wall Kit for PTMount S7x, black incl. Mounting parts

4047438039833	9,8 cm
90079100	7,5 cm
75 g	9,0 cm
	0,7 l

**Mx-M-SLMA****SingleMount S7x, white**

For surveillance of one area with one sensor module • Suitable for all screwable sensor modules of the S7x and S16B (not included) • Concealed cabling, weatherproof from -30 to 60°C/-22 to 140°F • Suitable for ceiling installation, with a 25° tilt of the lenses • Color: white

4047438036870	14,8 cm
90079100	9,8 cm
240 g	9,0 cm
	1,3 l

**Mx-M-SLMA-b****SingleMount S7x, black**

For surveillance of one area with one sensor module • Suitable for all screwable sensor modules of the S7x (not included) • Concealed cabling, weatherproof from -30 to 60°C/-22 to 140°F • Suitable for ceiling installation, with a 25° tilt of the lenses • Color: black

4047438037921	14,8 cm
90079100	9,8 cm
240 g	9,0 cm
	1,3 l

S7x Sensor Cables

	Article No. / Name / Description	EAN / HS / weight	dimen.
	<p>Mx-A-S7A-AUCBL05-AN S74 audio cable 5m Audio cable to connect a MOBOTIX 7 audio module Mx-F-AUDA to the IO board Mx-F-S7A-INT01 the S74, length 5m</p>	<p>4047438040501 85444210 155 g</p>	<p>14,0 cm 3,5 cm 15,0 cm 0,7 l</p>
	<p>Mx-A-S7A-CBL01 Sensor Cable 1m for S7x straight-straight Sensor cable straight-straight, length 1 m/3,3 ft • For connecting optical sensor modules and thermal sensor modules to the S7x camera body</p>	<p>4047438035583 85444210 70 g</p>	<p>14,0 cm 3,5 cm 15,0 cm 0,7 l</p>
	<p>Mx-A-S7A-CBL01-AN Sensor cable 1m for S7x straight-angled Sensor cable straight-angled, length 1 m/3,3 ft • For connecting optical sensor modules and thermal sensor modules to the S7x camera body • recommended for PTMounts</p>	<p>4047438035897 85444210 70 g</p>	<p>14,0 cm 3,5 cm 15,0 cm 0,7 l</p>
	<p>Mx-A-S7A-CBL02 Sensor Cable 2m for S7x straight-straight Sensor cable straight-straight, length 2 m/6,6 ft • For connecting optical sensor modules and thermal sensor modules to the S7x camera body</p>	<p>4047438035590 85444210 90 g</p>	<p>14,0 cm 3,5 cm 15,0 cm 0,7 l</p>
	<p>Mx-A-S7A-CBL02-AN Sensor cable 2m for S7x straight-angled Sensor cable straight-angled, length 2 m/6,6 ft • For connecting optical sensor modules and thermal sensor modules to the S7x camera body • recommended for PTMounts</p>	<p>4047438035903 85444210 90 g</p>	<p>14,0 cm 3,5 cm 15,0 cm 0,7 l</p>

**Mx-A-S7A-CBL03****Sensor Cable 3m for S7x straight-straight**


Sensor cable straight-straight, length 3 m/9,9 ft • For connecting optical sensor modules and thermal sensor modules to the S7x camera body

4047438035606	14,0 cm
85444210	3,5 cm
110 g	15,0 cm
	0,7 l

**Mx-A-S7A-CBL03-AN****Sensor cable 3m for S7x straight-angled**


Sensor cable straight-angled, length 3 m/9,9 ft • For connecting optical sensor modules and thermal sensor modules to the S7x camera body • recommended for PTMounts

4047438035910	14,0 cm
85444210	3,5 cm
110 g	15,0 cm
	0,7 l

**Mx-CBL-MUC-AB-1****S74 Cable MiniUSB-C to USB-A 1m**


MiniUSB-C straight > USB-A straight • Length 1 m /3,3 ft • For S74 • to connect ext. USB device (e.g. external harddrive)

4047438037129	10,0 cm
85444210	7,5 cm
102 g	9,0 cm
	0,7 l

**Mx-CBL-MUC-AB-5****S74 Cable MiniUSB-C to USB-A 5m**


MiniUSB-C straight > USB-A straight • Length 5 m /16,4 ft • For S74 • to connect ext. USB device (e.g. external harddrive)

4047438037136	14,8 cm
85444210	9,8 cm
220 g	9,0 cm
	1,3 l

**Mx-CBL-MUC-AN-AB-1****S7x Cable MiniUSB-C to USB-A angled-straight 1m**

MiniUSB-C angled > USB-A straight • Length 1 m /3,3 ft • For S7x • to connect ext. USB device (e.g. external harddrive)

4047438040556	10,0 cm
85444210	7,5 cm
102 g	9,0 cm
	0,7 l

**Mx-CBL-MUC-AN-AB-5****S7x Cable MiniUSB-C to USB-A angled-straight 5m**

MiniUSB-C angled > USB-A straight • Length 5 m /16,4 ft • For S7x • to connect ext. USB device (e.g. external harddrive)

4047438040563	14,8 cm
85444210	9,8 cm
220 g	9,0 cm
	1,3 l

**Mx-CBL-MUC-AN-MU-1****S7x Cable MiniUSB-C to MiniUSB angled-straight 1m**

MiniUSB-C angled > MiniUSB straight • Length 1 m /3,3 ft • For S7x • to connect ext. USB device (e.g. external harddrive)

4047438040532	10,0 cm
85444210	7,5 cm
102 9	9,0 cm
	0,7 l

**Mx-CBL-MUC-AN-MU-5****S7x Cable MiniUSB-C to MiniUSB angled-straight 5m**

MiniUSB-C angled > MiniUSB straight • Length 5 m /16,4 ft • For S7x • to connect ext. USB device (e.g. external harddrive)

4047438040549	14,8 cm
85444210	9,8 cm
220 9	9,0 cm
	1,3 l

**Mx-CBL-MUC-MU-1****S74 Cable MiniUSB-C to MiniUSB 1m**

MiniUSB-C straight > MiniUSB straight • Length 1 m /3,3 ft • For S74 • To connect RS232-IO-Box (MX-OPT-RS1-EXT)


4047438037143	10,0 cm
85444210	7,5 cm
102 9	9,0 cm
	0,7 l

**Mx-CBL-MUC-MU-5****S74 Cable MiniUSB-C to MiniUSB 5m**

MiniUSB-C straight > MiniUSB straight • Length 5 m /16,4 ft • For S74 • To connect RS232-IO-Box (MX-OPT-RS1-EXT)

4047438037150	14,8 cm
85444210	9,8 cm
220 9	9,0 cm
	1,3 l

Camera Mounts ONE

	Article No. / Name / Description	EAN / HS / weight	dimen.
	<p>Mx-M-CM-M1</p> <p>Ceiling Mount for M1 ONE Cameras</p> <p>Suitable for: M1 ONE Cameras • Mounting set to convert the VarioFlex wall mount into a ceiling mount • Incl. mount, M6x30 connection screw, washer, M6 nut and rubber seal • Turning/tilting (mechanically): 360° horizontally, -90° to +20° vertically • Suspended ceiling installation with additional MxTubeMount (MX-MT-TUBE)</p>	<p>4047438048415</p> <p>90079100</p> <p>160 g</p>	<p>15,0 cm</p> <p>9,5 cm</p> <p>9,0 cm</p> <p>1,3 l</p>

HD Premium Lenses

	Article No. / Name / Description	EAN / HS / weight	dimen.
	MX-B036 Ultra Wide Lens B036, Focal Length: 3.6 mm Ultra Wide lens B036 • HD premium quality • Focal length: 3.6 mm • Aperture: f/1.8 • Image angle (horizontal x vertical, on camera with 6MP sensor): 103° x 77° (up to 5MP resolution) and 122° x 80° (6MP resolution)	4047438026536 90021100 34 g	9,0 cm 7,5 cm 5,0 cm 0,3 l
	MX-B041 Super Wide Lens B041, Focal Length: 4.1 mm Super Wide lens B041 • HD premium quality • Focal length: 4.1 mm • Aperture: f/1.8 • Image angle (horizontal x vertical, on camera with 6MP sensor): 90° x 67° (up to 5MP resolution) and 110° x 70° (6MP resolution)	4047438026543 90021100 34 g	9,0 cm 7,5 cm 5,0 cm 0,3 l
	MX-B061 Wide Lens B061, Focal Length: 6.1 mm Wide lens B061 • HD premium quality • Focal length: 6.1 mm • Aperture: f/1.8 • Image angle (horizontal x vertical, on camera with 6MP sensor): 60° x 45° (up to 5MP resolution) and 70.5° x 46° (6MP resolution)	4047438026550 90021100 34 g	9,0 cm 7,5 cm 5,0 cm 0,3 l
	MX-B079 Standard Lens B079, Focal Length: 7.9 mm Standard lens B079 • HD premium quality • Focal length: 7.9 mm • Aperture: f/1.8 • Image angle (horizontal x vertical, on camera with 6MP sensor): 45° x 34° (up to 5MP resolution) and 54° x 36° (6MP resolution)	4047438026567 90021100 34 g	9,0 cm 7,5 cm 5,0 cm 0,3 l
	MX-B119 Tele Lens B119, Focal Length: 11.9 mm Tele lens B119 • HD premium quality • Focal length: 11.9 mm • Aperture: f/1.8 • Image angle (horizontal x vertical, on camera with 6MP sensor): 31° x 23° (up to 5MP resolution) and 36° x 24.5° (6MP resolution)	4047438026574 90021100 30 g	9,0 cm 7,5 cm 5,0 cm 0,3 l

**MX-B237****lens for D1x/M2x/D2x (HS code 90021900)**

Distant Tele lens B237 • HD premium quality • Focal length: 23.7 mm • Aperture: f/1.8
 • Image angle (horizontal x vertical, on camera with 6MP sensor): 15° x 11° (up to 5MP resolution) and 17° x 11.5° (6MP resolution)

4047438026581	9,0 cm
90021100	7,5 cm
34 g	5,0 cm
	0,3 l

**MX-B500****Super Tele Lens B500, Focal Length: 50 mm**

Super Tele lens B500 • HD premium quality • Focal length: 50 mm • Aperture: f/2.5 •
 Image angle (horizontal x vertical): 8° x 6° (up to 5MP resolution) and 9° x 6° (6MP resolution) • For mounting this lens on the M2x, the extended replacement lens cover is needed (MOBOTIX accessory: MX-M24M-OPT-LCGL)

4047438026598	9,0 cm
90021100	7,5 cm
52 g	5,0 cm
	0,3 l

**MX-B045-100-CS****CSVario Lens For Cameras With CS-Mount**

CS Vario lens B045-100-CS • HD premium quality • Variable focal length: 4,5-10 mm •
 Variable aperture: f/1.6-2.3 • Variable image angle (horizontal x vertical): 39°-89° x 29°-65°

4047438026604	9,0 cm
90021100	7,5 cm
66 g	5,0 cm
	0,3 l

**MX-SM-OPT-POL****Polarization Filter For Sensor Modules**

Suitable for all M1x/S1x sensor modules except with the lenses B016, B036, B500 and CSVario or CS Mount • Filter replaces the lens cover (made of glass) • Example: Recognition of people through the windshield of a car - the filter reduces the mirror reflection (and about 50 % of the sensor light sensitivity)

4047438019781	9,0 cm
90079100	7,5 cm
28 g	5,0 cm
	0,3 l

Domes & Housings

	Article No. / Name / Description	EAN / HS / weight	dimen.
	MX-M24M-OPT-LCSK Replacement Lens Cover M2x, Standard Suitable for: M2x (not CSVario, Hemispheric or super tele lens B500) and S1x/M1x sensor module with super tele lens B500 • Weather lens protection made of plastic (IP66)	4047438012980 90079100 32 g	9,0 cm 7,5 cm 5,0 cm 0,3 l
	MX-M24M-OPT-LCSG Replacement Lens Cover M2x, With Glass Pane Suitable for: M2x (not CSVario, Hemispheric or super tele lens B500) and S1x/M1x sensor module with super tele lens B500 • Lens protection made of scratch-proof glass for extreme weather conditions (IP66)	4047438012997 90079100 38 g	9,0 cm 7,5 cm 5,0 cm 0,3 l
	MX-M24M-OPT-LCGL Replacement Lens Cover M2x, Extended Suitable for: M2x and S1x/M1x sensor module with CSVario lens B045-100-CS or M2x with super tele lens B500 • Lens protection made of scratch-proof glass for extreme weather conditions (IP66)	4047438013000 90079100 44 g	9,0 cm 7,5 cm 5,0 cm 0,3 l
	MX-OPT-DK-L11 Replacement Cover Hemispheric Suitable for: Hemispheric sensor modules (for S1x/M1x), S26, S1xM, T2x and Q2x with Vanadlism Kit • Mounted with the blue MOBOTIX lens wrench (supplied with the Mx camera) • Polycarbonate (1.5 mm)	4047438016469 90079100 24 g	9,0 cm 7,5 cm 5,0 cm 0,3 l
	MX-D15-OPT-DCT Replacement Cover D1x/v2x, Standard Suitable for: D1x and v2x • Not for Pano/180° and DNight-Fix models (XL cover needed)	4047438018227 90079100 54 g	19,6 cm 14,8 cm 9,0 cm 2,6 l

**MX-D15-OPT-DCS****Replacement Cover D1x/v2x, Tinted**

Suitable for: D1x and v2x • Not for Pano/180° and DNight-Fix models (XL cover needed) • Tinted (50%) for especially bright environments

4047438018210	19,6 cm
90079100	14,8 cm
54 g	9,0 cm
	2,6 l

**MX-D15-DCT-XL****Replacement Cover D1x FIX/PAN, XL**

Suitable for: D1x PAN/180° and FIX/Day&Night models • Polycarbonate (1.5 mm)

4047438027519	19,6 cm
90079100	18,0 cm
281 g	14,8 cm
	5,2 l

**MX-D15-DCS-XL****Replacement Cover D1x PAN/FIX, XL Tinted**

Suitable for: D1x PAN/180° and FIX/Day&Night models • Tinted (50%) for especially bright environments • Polycarbonate (1.5 mm)

4047438027526	19,6 cm
90079100	18,0 cm
60 g	14,8 cm
	5,2 l

**MX-D24M-OPT-DCT****Replacement Cover D2x, Standard**

Suitable for: D2x • With sealing ring

4047438011419	19,6 cm
90079100	15,0 cm
150 g	9,0 cm
	2,6 l

**MX-D24M-OPT-DCS****Replacement Cover D2x, Tinted**

Suitable for: D2x • With sealing ring • Tinted (50%) for especially bright environments

4047438011402	19,6 cm
90079100	15,0 cm
150 g	9,0 cm
	2,6 l

**MX-D15-Vandal-ESMA****Vandalism Set For D1x, Matt**

Suitable for: D1x • Stainless steel vandalism ring with safety screws replaces the standard outer shell • Deletes the PIR and audio features (use ExtIO if necessary) • Raises camera protection class from IP54 to IP66 and IK10 • Reinforced Dome (3 mm) – not suitable for Pano and DNight-Fix models

4047438018173	39,5 cm
90079100	29,6 cm
1.012 g	9,0 cm
	10,5 l

**MX-D15-DCT-V****Replacement Cover D1x/v2x, Vandalism**

Reinforced replacement cover (polycarbonate, 3 mm) for D1x and v25 Vandalism Sets • Suitable for: D1x and v2x • Not for D1x PAN/180° and FIX/Day&Night models (XL cover needed)

4047438027533	19,6 cm
90079100	18,0 cm
278 g	14,8 cm
	5,2 l

**MX-D24M-Vandal-ESMA****Vandalism Set For D2x, Matt**

Suitable for: D2x Dome • Stainless steel vandalism ring with safety screws replaces the standard outer shell • Raises camera protection class to IP66 and IK10 • Reinforced Dome (3 mm)

4047438011143	30,5 cm
90079100	24,0 cm
672 g	12,0 cm
	8,8 l

**MX-D25-DCT-V****Replacement D2x, Vandalism**

Reinforced replacement cover (polycarbonate, 3 mm) for D2x Vandalism Kits • With sealing ring

4047438027700	19,6 cm
90079100	18,0 cm
60 g	14,8 cm
	5,2 l

**MX-Q24M-Vandal-ESMA****Vandalism Set For Q2x, Matt**

Suitable for: Q2x • Vandalism-proof housing with lens protection • Ideally suited for surveillance at extremely critical locations • Raises camera protection class to IP66 and IK10 • Stainless steel, finish matt • Incl. safety screws • Incl. 3 reinforced domes (3 mm polycarbonate) • Audio features still available

4047438011273	29,6 cm
90079100	19,6 cm
590 g	9,0 cm
	5,2 l

**MX-MT-v25-V****Vandalism Set For v2x**

Suitable for: v2x without On-Wall Mounting Set with Audio • Stainless steel vandalism ring (matt) with safety screws • Protects the camera housing (only without On-Wall Set) • Reinforced lens cover (polycarbonate, 3 mm) • IK10+

4047438027601	29,6 cm
90079100	19,6 cm
502 g	9,0 cm
	5,2 l

**MX-MT-v25-V-XL****Vandalism Set For v2x With On-Wall Mounting Set**

Suitable for: v2x with On-Wall Mounting Set with Audio • XL stainless steel vandalism ring (matt) with safety screws • Protects the camera housing (only with mounted On-Wall Set) • Reinforced lens cover (polycarbonate, 3 mm) • IK10+

4047438027625	29,6 cm
90079100	19,6 cm
680 g	9,0 cm
	5,2 l

Mounts For S16A/S16B

	Article No. / Name / Description	EAN / HS / weight	dimen.
	MX-FLEX-OPT-DM-PW DualMount S1x, White For surveillance of one area with two sensor modules (in particular, for day and night) • Suitable for all available sensor modules of the S1x (not included) • Concealed cabling, weatherproof from -30 to 60°C/-22 to 140°F • Suitable for ceiling installation, with a 25° tilt of the lenses • Color: White	4047438017626 90079100 414 g	19,6 cm 15,0 cm 9,0 cm 2,6 l
	MX-FLEX-OPT-SM-PW SurroundMount S1x, White For surveillance of long and narrow spaces (e.g., bus, train, hallway, etc.) without blind spots • Two sensor modules of the S1x can be integrated in the mount (not included) • For all GMP Sensor modules (B016 to B500 and CS Mount) • Concealed cabling, weatherproof from -30 to 60°C/-22 to 140°F • Suitable for ceiling installation, with a 25° tilt of the lenses • Color: White	4047438016407 90079100 392 g	19,6 cm 15,0 cm 9,0 cm 2,6 l
	MX-FLEX-OPT-DM-BL DualMount S1x, Black For surveillance of one area with two sensor modules (in particular, for day and night) • Suitable for all screwable sensor modules of the S1x (not included) • Concealed cabling, weatherproof from -30 to 60°C/-22 to 140°F • Suitable for ceiling installation, with a 25° tilt of the lenses • Color: black	4047438021869 90079100 414 g	19,6 cm 15,0 cm 9,0 cm 2,6 l
	MX-FLEX-OPT-SM-BL SurroundMount S1x, Black For surveillance of long and narrow spaces (e.g., bus, train, hallway, etc.) without blind spots • Two sensor modules of the S1x can be integrated in the mount (not included) • For all screwable sensor modules • Concealed cabling, weatherproof from -30 to 60°C/-22 to 140°F • Suitable for ceiling installation, with a 25° tilt of the lenses • Color: black	4047438021845 90079100 392 g	19,6 cm 15,0 cm 9,0 cm 2,6 l
	MX-HALO-EXT-PW HaloMount S7x/S1x, White Indoor installation mount for a sensor module (in-wall or in-ceiling) • Suitable for all available sensor modules S7x, S1x and Thermal module ECO 320 (not included) • Flexible setting of inner ring, sensor module can be tilted up to 20° • High-quality metal design • Also for lighting equipment (QR-CBC/MR16 LED Sharp Array 4/6 W)	4047438017664 90079100 175 g	13,5 cm 12,0 cm 4,5 cm 0,7 l

**MX-HALO-EXT-BL****HaloMount S7x/S1x, Black**

Indoor installation mount for a sensor module (in-wall or in-ceiling) • Suitable for all available sensor modules S7x, S1x and Thermal module ECO 320 (not included) • Flexible setting of inner ring, sensor module can be tilted up to 20° • High-quality metal design • Also for lighting equipment (QR-CBC/MR16 LED Sharp Array 4/6 W) •

4047438017671	13,5 cm
90079100	12,0 cm
175 g	4,5 cm
	0,7 l

**MX-HALO-EXT-CM****HaloMount S7x/S1x, Matt Chrome**

Indoor installation mount for a sensor module (in-wall or in-ceiling) • Suitable for all available sensor modules S7x, S1x and Thermal module ECO 320 (not included) • Flexible setting of inner ring, sensor module can be tilted up to 20° • High-quality metal design • Also for lighting equipment (QR-CBC/MR16 LED Sharp Array 4/6 W) •

4047438017633	13,5 cm
90079100	12,0 cm
175 g	4,5 cm
	0,7 l

**MX-HALO-EXT-CO****HaloMount S7x/S1x, Chrome**

Indoor installation mount for a sensor module (in-wall or in-ceiling) • Suitable for all available sensor modules S7x, S1x and Thermal module ECO 320 (not included) • Flexible setting of inner ring, sensor module can be tilted up to 20° • High-quality metal design • Also for lighting equipment (QR-CBC/MR16 LED Sharp Array 4/6 W) •

4047438017640	13,5 cm
90079100	12,0 cm
175 g	4,5 cm
	0,7 l

**MX-HALO-EXT-NG****HaloMount S7x/S1x, Brushed Nickel**

Indoor installation mount for a sensor module (in-wall or in-ceiling) • Suitable for all available sensor modules S7x, S1x and Thermal module ECO 320 (not included) • Flexible setting of inner ring, sensor module can be tilted up to 20° • High-quality metal design • Also for lighting equipment (QR-CBC/MR16 LED Sharp Array 4/6 W) •

4047438017657	13,5 cm
90079100	12,0 cm
175 g	4,5 cm
	0,7 l

**MX-HALO-SP-EXT-PW****SpeakerMount S1x, White**

Integrated speaker incl. mount, white • Suitable for the installation in ceilings or walls, indoor (IP20) • Compatible with all cameras S1x and V1x • Direct connection via two-wire cable, no additional power supply unit needed • Inner ring with speaker can be tilted up to 20° • Temperature range: -30 to 60°C/-22 to 140°F • IP code: IP20 • impedance: 8 ohm • Speaker material: metall with perforated plate covering • Connection type: two-wired strand, clamp included

4047438017688	13,5 cm
85182200	12,0 cm
273 g	4,5 cm
	0,7 l

**MX-HALO-SP-EXT-CM****SpeakerMount S1x, Matt Chrome**

Integrated speaker incl. mount, matt chrome • Suitable for the installation in ceilings or walls, indoor (IP20) • Compatible with all cameras S1x and V1x • Direct connection via two-wire cable, no additional power supply unit needed • Inner ring with speaker can be tilted up to 20° • Temperature range: -30 to 60°C/-22 to 140°F • IP code: IP20 • impedance: 8 ohm • Speaker material: metall with perforated plate covering • Connection type: two-wired strand, clamp included

4047438017695	13,5 cm
85182200	12,0 cm
273 g	4,5 cm
	0,7 l

**MX-S14-OPT-MK-CW****Extension Set Sensor Module, 40 mm and 15° wedges**

Complete set for wall or ceiling mounting of a sensor module using 15° wedges • Incl. extension to increase the installation depth • Suitable for all S1x and S7x sensor modules • 1x extension 40 mm/1.6 in • 2x 15° wedges (white and black) • 2x wedge sealing rings • 1x nut





4047438016384	10,0 cm
90079100	7,5 cm
96 9	9,0 cm
	0,7 l

**MX-S14-OPT-MK-EX****Extension Sensor Module, 40 mm**

1x extension 40 mm/1.6 inch, increases the installation depth • Suitable for all (screwable) S1x sensor modules • Can be mounted directly onto the sensor modules themselves or onto existing extensions

4047438016391	9,8 cm
90079100	7,5 cm
62 9	9,0 cm
	0,7 l

Camera Mounts

	Article No. / Name / Description	EAN / HS / weight	dimen.
	Mx-M-OWA-AU	4047438030328	19,6 cm
	On-Wall Mounting Set With Audio For v26, White On-Wall Set with Audio for v26 • Consists of on-wall mount, mounting parts, integrated speaker, microphone and camera plug-in connection cable • Enables on-wall cabling of the camera and integrates two additional Interface Box modules • Housing color: white	90079100 510 g	18,0 cm 14,8 cm 5,2 l
	Mx-M-OWA-AU-b	4047438030335	19,6 cm
	On-Wall Mounting Set With Audio For v26, Black On-Wall Set with Audio for v26 • Consists of on-wall mount, mounting parts, integrated speaker, microphone and camera plug-in connection cable • Enables on-wall cabling of the camera and integrates two additional Interface Box modules • Housing color: black	90079100 510 g	18,0 cm 14,8 cm 5,2 l
	MX-MT-OW2-AUD	4047438027632	19,6 cm
	On-Wall Mounting Set With Audio For v25, White Suitable for: v25 • Consists of on-wall mount, mounting parts, integrated speaker, microphone and camera plug-in connection cable • Enables on-wall cabling of the camera and integrates two additional Interface Box modules • Housing color: white	90079100 500 g	18,0 cm 14,8 cm 5,2 l
	MX-MT-OW2-AUD-b	4047438027670	19,6 cm
	On-Wall Mounting Set With Audio For v25, Black Suitable for: v25 • Consists of on-wall mount, mounting parts, integrated speaker, microphone and camera plug-in connection cable • Enables on-wall cabling of the camera and integrates two additional Interface Box modules • Housing color: black	90079100 500 g	18,0 cm 14,8 cm 5,2 l
	MX-MT-TUBE	4047438027557	29,6 cm
	MxTubeMount Ceiling Suspension System	90079100	19,6 cm
	For suspended ceiling installation of the cameras M1x/M2x/v2x/PTMount/PT-Mount-Thermal (each can be attached directly to the MxTubeMount) and of the cameras D2x/Q2x/c2x/p2x (each can only be attached to the MxTubeMount when using the optional on-wall mounting set of the camera) • Incl. drop down protection wire (length: 2.2 m/7.2 ft) • Additionally needed suspension tube MxTube with a length of 1m (3.3 ft) or 2 m (6.6 ft) to be ordered separately (MX-MT-TUBE100, MX-MT-TUBE200) • Alternative suspension with customary tubes: outer diameter 30 mm or 26.9 mm (R3/4" according to DIN 2440), max. length: 2 m (6.6 ft), max. weight: 2.5 kg (5.5 lb), color: white	870 g	9,0 cm 5,2 l

**MX-MT-TUBE100****MxTube, 1 m**

Suspension tube for MxTubeMount • Length: 1 m (3.3 ft) • Anodized aluminium • Outer diameter: 30 mm, wall thickness: 2 mm

4047438027687	106,0 cm
90079100	4,0 cm
700 9	4,0 cm
	1,7 l

**MX-MT-TUBE200****MxTube, 2 m**

Suspension tube for MxTubeMount • Length: 2 m (6.6 ft) • Anodized aluminium • Outer diameter: 30 mm, wall thickness: 2 mm

4047438027564	212,5 cm
90079100	4,0 cm
1.390 9	4,0 cm
	3,4 l

**MX-OPT-UP1****Cavity Wall Installation Set i2x**

Cavity Wall Installation Set for the i2x • With cavity wall socket, stainless steel mounting plate, 2 Allen screws with washers • For installing the camera directly on the mounting plate, no dowels required • Mounting plate is screwed onto the cavity wall socket • Recommended only for wall installations

4047438022118	14,8 cm
90079100	9,8 cm
158 9	9,0 cm
	1,3 l

**MX-OPT-AP2****On-Wall Mounting Set For i2x**

Suitable for: i25 • Consists of on-wall mount and mounting parts • Enables on-wall cabling of the camera • Camera distance from the wall: ca. 25 mm • Recommended only for wall installation • Color: white

4047438025898	14,8 cm
90079100	9,8 cm
136 9	9,0 cm
	1,3 l

**MX-MT-OW-1****On-Wall Mounting Set For c2x/p2x**

Suitable for: c2x und p2x • Consists of on-wall mount and mounting parts • Enables on-wall cabling of the camera and integrates additional modules (e.g. two Interface Boxes) • Camera distance from the wall: ca. 80 mm • Diameter: 140 mm • Recommended only for ceiling installation • Color: White

4047438027083	19,6 cm
90079100	18,0 cm
514 9	14,8 cm
	5,2 l

**MX-MT-CM-1****Corner Mounting Set For c2x**

Suitable for: c2x • Consists of on-wall mount and mounting parts • Mounting in a room corner • Mounting position plus 35° tilt angle enable one camera (e.g. c2x with 103° lens B036) to capture an entire room • Color: White

4047438027076	29,6 cm
90079100	19,6 cm
448 9	9,0 cm
	5,2 l

**MX-OPT-AP****On-Wall Mounting Set For Q2x/D2x/ExtIO**

Suitable for: Q2x, D2x, ExtIO • Consists of on-wall mount and mounting parts • Protects the cabling • Allows integrating additional modules • Dimensions: 165 mm x 37 mm

4047438011358	29,6 cm
90079100	19,6 cm
612 g	9,0 cm
	5,2 l

**MX-OPT-AP-10DEG****On-Wall Mounting Set For Q2x/D2x/ExtIO, 10°**


Suitable for: Q2x, D2x, ExtIO • Consists of on-wall mount and mounting parts • Camera can be mounted at a 10° tilt angle • Protects the cabling • Allows integrating additional modules • Dimensions: 165 mm x 37 mm

4047438010283	29,6 cm
90079100	19,6 cm
552 g	9,0 cm
	5,2 l

**MX-D15-OPT-WHMH-Set****Wall & Pole/Corner Mount Set For D1x**

Suitable for: D1x • Set consisting of pole/corner mount (MX-MH-Dome-ESWS) and wall mount (MX-WH-Dome) • Mounted to the corner, one camera can cover two sides of a building simultaneously • Pole/corner mount for fastening of wall mount: 3 mm stainless steel, white • Wall mount consists of shock-resistant fiberglass-reinforced plastic (PBT), white • Covers RJ45 wall outlets • Ample room inside for extras (e.g., interface boxes) • Wall mount raises camera protection class from IP54 to IP65 • Incl. mounting parts and 2 stainless steel straps for pole diameters of 60 to 180 mm

4047438018159	41,0 cm
90079100	31,0 cm
6.280 g	39,0 cm
	49,6 l

**MX-OPT-WHMH-Set****Wall & Pole/Corner Mount Set For Q2x/D2x/ExtIO**

Suitable for: Q2x, D2x, ExtIO • Set consisting of pole/corner mount (MX-OPT-MH) and wall mount (MX-OPT-WH) • Pole/corner mount for fastening of wall mount: 3 mm stainless steel, white • Wall mount consists of shock-resistant fiberglass-reinforced plastic (PBT), white • Covers RJ45 wall outlets • Ample room inside for extras (e.g., interface boxes) • Incl. mounting parts and 2 stainless steel straps for pole diameters of 60 to 180 mm

4047438011396	41,0 cm
90079100	31,0 cm
3.380 g	20,0 cm
	25,4 l

**MX-WH-Dome****Wall Mount For D1x**


Suitable for: D1x • Shock-resistant fiberglass-reinforced plastic (PBT), white • Covers RJ45 wall outlets • Ample room inside for extras (e.g., interface boxes) • Raises camera protection class from IP54 to IP66 • Incl. mounting parts

4047438002233	39,5 cm
90079100	29,6 cm
2.020 g	18,0 cm
	21,0 l

**MX-OPT-WH****Wall Mount For Q2x/D2x/ExtIO**

Suitable for: Q2x, D2x, ExtIO • Wall mount consists of shock-resistant fiberglass-reinforced plastic (PBT), white • Covers RJ45 wall outlets • Ample room inside for extras (e.g., interface boxes) • Incl. mounting parts

4047438011372	29,6 cm
90079100	19,6 cm
886 g	18,0 cm
	10,4 l

**MX-MH-Dome-ESWS****Pole/Corner Mount For MX-WH-Dome**


Suitable for: D1x • Pole/corner mount for fastening of wall mount MX-WH-Dome (to be ordered individually) • Made of 3 mm stainless steel, white • Incl. mounting parts and 2 stainless steel straps for pole diameters of 60 to 180 mm

4047438002240	34,0 cm
90079100	18,5 cm
3.000 g	11,5 cm
	7,2 l

**MX-MH-SecureFlex-ESWS****Pole Mount For M1x/M2x**

Suitable for: M1x, M2x • Mount for fastening the standard camera wall mount SecureFlex (M12/M10, M22) and VarioFlex (M15, M2x) • Made of 3 mm stainless steel, white • Incl. mounting parts and 2 stainless steel straps for pole diameters of 60 to 180 mm

4047438002226	20,0 cm
90079100	15,2 cm
1.230 g	8,0 cm
	2,4 l

**MX-OPT-MH****Pole/Corner Mount For MX-OPT-WH**

Suitable for: D7x, Q7x, Q2x, D2x, ExtIO • Mount for fastening the wall mount Mx-M-WM-DQ and MX-OPT-WH (to be ordered separately) • A set consisting of Pole/Corner Mount and Wall Mount is also available (MX-OPT-WHMH-Set) for the Q2x/D2x und ExtIO • Made of 3 mm stainless steel, white • Incl. mounting parts and 2 stainless steel straps for pole diameters of 60 to 180 mm • Wall mounts (Mx-M-WM-DQ or MX-OPT-WH) are not included in the scope of delivery and must be ordered separately

4047438011389	21,0 cm
90079100	20,0 cm
2.050 g	17,0 cm
	7,1 l

**MX-OPT-IC-ESMA****In-Ceiling Set For Q2x/D2x/ExtIO, Matt**

Suitable for: Q2x, D2x, ExtIO • Stainless steel ring (matt) • Consists of in-ceiling mount and mounting parts • Easy mounting from front • Provides optimum protection for the camera • Inconspicuous, as the visible profile is reduced to a minimum • Installation dimension (diameter): 150 mm

4047438011433	29,6 cm
90079100	19,6 cm
724 g	9,0 cm
	5,2 l

**MX-OPT-IC-ESPO****In-Ceiling Set For Q2x/D2x/ExtIO, Polished**

Suitable for: Q2x, D2x, ExtIO • Stainless steel ring (polished) • Consists of in-ceiling mount and mounting parts • Easy mounting from front • Provides optimum protection for the camera • Inconspicuous, as the visible profile is reduced to a minimum • Installation dimension (diameter): 150 mm

4047438011426	29,6 cm
90079100	19,6 cm
724 g	9,0 cm
	5,2 l

**MX-OPT-IC****In-Ceiling Set For Q2x/D2x/ExtIO, White**

Suitable for: Q2x, D2x, ExtIO • Consists of in-ceiling mount and mounting parts • Easy mounting from front • Provides optimum protection for the camera • Inconspicuous, as the visible profile is reduced to a minimum • Installation dimension (diameter): 150 mm

4047438011365	29,6 cm
90079100	19,6 cm
412 g	9,0 cm
	5,2 l



MX-DH-M24-SecureFlex
Ceiling Mount For M16/M26

Suitable for: M16, M26, M15, M25, M24 • Mounting set to convert the VarioFlex wall mount into a ceiling mount • Incl. mount, M6x30 connection screw, washer, M6 nut and rubber seal • Turning/tilting (mechanically): 360° horizontally, -90° to +20° vertically • Suspended ceiling installation with additional MxTubeMount (MX-MT-TUBE)

4047438015653	15,0 cm
90079100	9,5 cm
160 g	9,0 cm
	1,3 l



MX-OPT-TW-Demo-1
Demo Table/Wall Mount For Q2x/D2x

Useful mount for testing and for finding the optimum mounting position of the single lens cameras Q2x Hemispheric or D2x Dome. The set includes an Allen wrench and a Torx screw with dowel and the corresponding Torx wrench for installing as alternative wall mount for testing. The camera can be placed on a flat surface or can be mounted on a tripod (1/4" tripod thread at the bottom of the mount).

4047438013055	14,8 cm
90079100	9,8 cm
170 g	9,0 cm
	1,3 l

MOBOTIX Cables

	Article No. / Name / Description	EAN / HS / weight	dimen.
	MX-OPT-CBL-LAN-1-SP Ethernet Patch Cable for MOBOTIX 7, 1 m Ethernet Patch Cable for MOBOTIX systems • Lenght 1 m/3,3 ft • 2x RJ45 plug with special MOBOTIX sealing ring and sealing plug	4047438041591 85444210 40 g	23,5 cm 15,0 cm 2,0 cm 0,7 l
	MX-OPT-CBL-LAN-10-SP Ethernet Patch Cable for MOBOTIX 7, 10 m Ethernet Patch Cable for MOBOTIX systems • Lenght 10 m/32,8 ft • 2x RJ45 plug with special MOBOTIX sealing ring and sealing plug	4047438041560 85444210 465 g	27,0 cm 17,0 cm 4,0 cm 1,8 l
	MX-OPT-CBL-LAN-2-SP Ethernet Patch Cable for MOBOTIX 7, 2 m Ethernet Patch Cable for MOBOTIX systems • Lenght 2 m/6,6 ft • 2x RJ45 plug with special MOBOTIX sealing ring and sealing plug	4047438041584 85444210 65 g	23,5 cm 15,0 cm 2,0 cm 0,7 l
	MX-OPT-CBL-LAN-5-SP Ethernet Patch Cable for MOBOTIX 7, 5 m Ethernet Patch Cable for MOBOTIX systems • Lenght 5 m/16,4 ft • 2x RJ45 plug with special MOBOTIX sealing ring and sealing plug	4047438041577 85444210 240 g	23,5 cm 15,0 cm 4,0 cm 1,4 l
	MX-FLEX-OPT-CBL-015 Sensor Module Cable For M15/M16, 0.15 m Lenght: 0.15 m/0,5 ft, to connect one sensor module (inside camera housing), angled plugs, only for M15/M16	4047438019941 85444210 16 g	9,8 cm 7,5 cm 9,0 cm 0,7 l



MX-FLEX-OPT-CBL-05
Sensor Cable For S1x, 0.5 m

Sensor cable, length 0.5 m/1,6 ft • For connecting optical sensor modules, BlockFlexMounts and thermal sensor modules to the camera module

4047438018890	10,0 cm
85444210	7,5 cm
66 g	9,0 cm
	0,7 l



MX-FLEX-OPT-CBL-1
Sensor Cable For S1x, 1 m

Sensor cable, length 1 m/3,3 ft • For connecting optical sensor modules, BlockFlexMounts and thermal sensor modules to the camera module

4047438018883	10,0 cm
85444210	7,5 cm
80 g	9,0 cm
	0,7 l



MX-FLEX-OPT-CBL-2
Sensor Cable For S1x, 2 m

Sensor cable, length 2 m/6,6 ft • For connecting optical sensor modules, BlockFlexMounts and thermal sensor modules to the camera module

4047438018876	10,0 cm
85444210	7,5 cm
116 g	9,0 cm
	0,7 l



MX-FLEX-OPT-CBL-3
Sensor Cable For S1x (6MP/Thermal), 3 m

Sensor cable, length 3 m/9,8 ft • For connecting optical sensor modules and BlockFlexMounts with 6MP sensors and Thermal sensor modules to the S15/S16 camera module • Not compatible with PTMount-Thermal, S14D and 5MP modules

4047438024303	10,0 cm
85444210	7,5 cm
144 g	9,0 cm
	0,7 l



MX-CBL-MU-EN-AB-05
USB Device Cable For M/Q/T2x, 0.5 m

MiniUSB angled > USB-A straight • Length 0,5 m/1,6 ft • For M15/M16, M25/M26, Q25/Q26, T25 • To connect ext. USB device

4047438016728	9,8 cm
85444210	7,5 cm
52 g	9,0 cm
	0,7 l



MX-CBL-MU-EN-AB-2
USB Device Cable For M/Q/T2x, 2 m

MiniUSB angled > USB-A straight • Length 2 m/6,6 ft • For M15/M16, M25/M26, Q25/Q26, T25 • To connect ext. USB-Gerät

4047438016711	10,0 cm
85444210	7,5 cm
102 g	9,0 cm
	0,7 l

**MX-CBL-MU-EN-AB-5****USB Device Cable For M/Q/T2x, 5 m**

MiniUSB angled > USB-A straight • Length 5 m/16,4 ft • For M15/M16, M25/M26, Q25/Q26, T25 • To connect ext. USB device

4047438016704	9,8 cm
85444210	7,5 cm
194 9	9,0 cm
	0,7 l

**MX-CBL-MU-EN-EN-PG-05****ExtIO Cable For M/Q/T2x, 0,5 m**

MiniUSB angled > MiniUSB+ angled • Length 0,5 m/1,6 ft • For M15/M16, M25/M26, Q25/Q26, T25 • To connect MX-ExtIO

4047438020947	9,8 cm
85444210	7,5 cm
52 9	9,0 cm
	0,7 l

**MX-CBL-MU-EN-EN-PG-2****ExtIO Cable For M/Q/T2x, 2 m**

MiniUSB angled > MiniUSB+ angled • Length 2 m/6,6 ft • For M15/M16, M25/M26, Q25/Q26, T25 • To connect MX-ExtIO

4047438020930	9,8 cm
85444210	7,5 cm
102 9	9,0 cm
	0,7 l

**MX-CBL-MU-EN-EN-PG-5****ExtIO Cable for M/Q/T2x, 5 m**

MiniUSB angled > MiniUSB+ angled • Length 5 m/16,4 ft • For M15/M16, M25/M26, Q25/Q26, T25 • To connect MX-ExtIO

4047438020923	9,8 cm
85444210	7,5 cm
194 9	9,0 cm
	0,7 l

**MX-CBL-MU-EN-PG-AB-05****USB Device Cable For D25/D26, 0.5 m**

MiniUSB+ angled > USB-A straight • Length 0,5 m/1,6 ft • For D25/D26 • To connect ext. USB device

4047438020916	9,8 cm
85444210	7,5 cm
52 9	9,0 cm
	0,7 l

**MX-CBL-MU-EN-PG-AB-2****USB Device Cable For D25/D26, 2 m**

MiniUSB+ angled > USB-A straight • Length 2 m/6,6 ft • For D25/D26 • to connect ext. USB device

4047438020909	9,8 cm
85444210	7,5 cm
102 9	9,0 cm
	0,7 l

**MX-CBL-MU-EN-PG-AB-5****USB Device Cable For D25/D26, 5 m**

MiniUSB+ angled > USB-A straight • Length 5 m/16,4 ft • For D25/D26 • To connect ext. USB device

4047438020893	9,8 cm
85444210	7,5 cm
194 g	9,0 cm
	0,7 l

**MX-CBL-MU-EN-PG-EN-PG-05****ExtIO Cable For D25/D26, 0.5 m**

MiniUSB+ angled > MiniUSB+ angled • Length 0,5 m/1,6 ft • For D25/D26 • To connect MX-ExtIO

4047438020886	9,8 cm
85444210	7,5 cm
52 g	9,0 cm
	0,7 l

**MX-CBL-MU-EN-PG-EN-PG-2****ExtIO Cable For D25/D26, 2 m**

MiniUSB+ angled > MiniUSB+ angled • Length 2 m/6,6 ft • For D25/D26 • To connect MX-ExtIO

4047438020879	9,8 cm
85444210	7,5 cm
102 g	9,0 cm
	0,7 l

**MX-CBL-MU-EN-PG-EN-PG-5****ExtIO Cable For D25/D26, 5 m**

MiniUSB+ angled > MiniUSB+ angled • Length 5 m/16,4 ft • For D25/D26 • To connect MX-ExtIO

4047438020862	9,8 cm
85444210	7,5 cm
194 g	9,0 cm
	0,7 l

**MX-CBL-MU-EN-PG-STR-05****232-IO-Box Cable For D25/D26, 0.5 m**

MiniUSB+ angled > MiniUSB straight • Length 0,5 m/1,6 ft • For D25/D26 • To connect MX-232-IO-Box

4047438020855	9,8 cm
85444210	7,5 cm
52 g	9,0 cm
	0,7 l

**MX-CBL-MU-EN-PG-STR-2****232-IO-Box Cable For D25/D26, 2 m**

MiniUSB+ angled > MiniUSB straight • Length 2 m/6,6 ft • For D25/D26 • To connect MX-232-IO-Box

4047438020848	9,8 cm
85444210	7,5 cm
102 g	9,0 cm
	0,7 l

**MX-CBL-MU-EN-PG-STR-5****232-IO-Box Cable For D25/D26, 5 m**

MiniUSB+ angled > MiniUSB straight • Length 5 m/16,4 ft • For D25/D26 • To connect MX-232-IO-Box

4047438020831	9,8 cm
85444210	7,5 cm
194 g	9,0 cm
	0,7 l

**MX-CBL-MU-EN-STR-05****232-IO-Box Cable For M/Q/T2x, 0.5 m**

MiniUSB angled > MiniUSB straight • Length 0,5 m/1,6 ft • For M15/M16, M25/M26, Q25/Q26, T25 • To connect MX-232-IO-Box

4047438016667	10,0 cm
85444210	7,5 cm
48 g	9,0 cm
	0,7 l

**MX-CBL-MU-EN-STR-2****232-IO-Box Cable For M/Q/T2x, 2 m**

MiniUSB angled > MiniUSB straight • Length 2 m/6,6 ft • For M15/M16, M25/M26, Q25/Q26, T25 • To connect MX-232-IO-Box

4047438016650	10,0 cm
85444210	7,5 cm
94 g	9,0 cm
	0,7 l

**MX-CBL-MU-EN-STR-5****232-IO-Box Cable For M/Q/T2x, 5 m**

MiniUSB angled > MiniUSB straight • Length 5 m/16,4 ft • For M15/M16, M25/M26, Q25/Q26, T25 • To connect MX-232-IO-Box

4047438016643	10,0 cm
85444210	7,5 cm
188 g	9,0 cm
	0,7 l

**MX-CBL-MU-STR-05****232-IO-Box Cable For D/S/V1x, 0.5 m**

MiniUSB straight > MiniUSB straight • Length 0,5 m/1,6 ft • For D15/D16, S15D/S16, S15M/S26, V15/V16 • To connect MX-232-IO-Box

4047438016605	10,0 cm
85444210	7,5 cm
50 g	9,0 cm
	0,7 l

**MX-CBL-MU-STR-2****232-IO-Box Cable For D/S/V1x, 2 m**

MiniUSB straight > MiniUSB straight • Length 2 m/6,6 ft • For D15/D16, S15D/S16, S15M/S26, V15/V16 • To connect MX-232-IO-Box

4047438016599	10,0 cm
85444210	7,5 cm
94 g	9,0 cm
	0,7 l

**MX-CBL-MU-STR-5****232-IO-Box Cable For D/S/V1x, 5 m**

MiniUSB straight > MiniUSB straight • Length 5 m/16,4 ft • For D15/D16, S15D/S16, S15M/S26, V15/V16 • To connect MX-232-IO-Box

4047438016445	10,0 cm
85444210	7,5 cm
184 g	9,0 cm
	0,7 l

**MX-CBL-MU-STR-AB-05****USB Device Cable For D/S/V1x, 0.5 m**

MiniUSB straight > USB-A straight • Length 0,5 m/1,6 ft • For D15/D16, S15D/S16, S15M/S26, V15/V16 • To connect ext. USB device

4047438016698	10,0 cm
85444210	7,5 cm
56 g	9,0 cm
	0,7 l

**MX-CBL-MU-STR-AB-2****USB Device Cable For D/S/V1x, 0.2 m**

MiniUSB straight > USB-A straight • Length 2 m/6,6 ft • D15/D16, S15D/S16, S15M/S26, V15/V16 • To connect ext. USB device

4047438016681	10,0 cm
85444210	7,5 cm
102 g	9,0 cm
	0,7 l

**MX-CBL-MU-STR-AB-5****USB Device Cable For D/S/V1x, 5 m**

MiniUSB straight > USB-A straight • Length 5 m/16,4 ft • For D15/D16, S15D/S16, S15M/S26, V15/V16 • To connect ext. USB device

4047438016674	10,0 cm
85444210	7,5 cm
196 g	9,0 cm
	0,7 l

**MX-CBL-MU-STR-EN-PG-05****ExtIO Cable For D/S/V1x, 0.5 m**

MiniUSB straight > MiniUSB+ angled • Length 0,5 m/1,6 ft • For D15/D16, S15D/S16, S15M/S26, V15/V16 • To connect MX-ExtIO

4047438020978	9,8 cm
85444210	7,5 cm
52 g	9,0 cm
	0,7 l

**MX-CBL-MU-STR-EN-PG-2****ExtIO Cable For D/S/V1x, 0.2 m**

MiniUSB straight > MiniUSB+ angled • Length 2 m/6,6 ft • For D15/D16, S15D/S16, S15M/S26, V15/V16 • To connect MX-ExtIO

4047438020961	9,8 cm
85444210	7,5 cm
102 g	9,0 cm
	0,7 l

**MX-CBL-MU-STR-EN-PG-5****ExtIO Cable For D/S/V1x, 5 m**

MiniUSB straight > MiniUSB+ angled • Length 5 m/16,4 ft • For D15/D16, S15D/S16, S15M/S26, V15/V16 • To connect MX-ExtIO

4047438020954	9,8 cm
85444210	7,5 cm
194 g	9,0 cm
	0,7 l

**MX-OPT-CBL-LAN-1****Ethernet Patch Cable, 1 m**

Ethernet Patch Cable for MOBOTIX systems • Length 1 m/3,3 ft • 2x RJ45 plug with special MOBOTIX sealing ring

4047438012300	23,5 cm
85444210	15,0 cm
36 g	2,0 cm
	0,7 l

**MX-OPT-CBL-LAN-10****Ethernet Patch Cable, 10 m**

Ethernet Patch Cable for MOBOTIX systems • Length 10 m/32,8 ft • 2x RJ45 plug with special MOBOTIX sealing ring

4047438012331	27,0 cm
85444210	17,0 cm
462 g	4,0 cm
	1,8 l

**MX-OPT-CBL-LAN-2****Ethernet Patch Cable, 2 m**

Ethernet Patch Cable for MOBOTIX systems • Length 2 m/6,6 ft • 2x RJ45 plug with special MOBOTIX sealing ring

4047438012317	23,5 cm
85444210	15,0 cm
62 g	2,0 cm
	0,7 l

**MX-OPT-CBL-LAN-5****Ethernet Patch Cable, 5 m**

Ethernet Patch Cable for MOBOTIX systems • Length 5 m/16,4 ft • 2x RJ45 plug with special MOBOTIX sealing ring

4047438012324	23,5 cm
85444210	15,0 cm
237 g	4,0 cm
	1,4 l

**MX-FLEX-IO-CBL-015****IO Connection Cable For M15/M16, 0.15 m**

Length: 0.15 m/0,5 ft, IO cable to the front element of the camera, only for M15/M16 (inside camera housing)

4047438019958	13,5 cm
85444210	8,0 cm
10 g	2,0 cm
	0,2 l








MX-CBL-NPA-BAT-2
NPA Battery Cable, 2 m

NPA-PoE Battery Cable • Provides a power supply for the camera from car batteries or other power sources from 12 to 24 Volts • With self-resetting fuse • RJ45 connector to PoE injector, „+/-“ terminals for power source • Can only be used with Mx-NPA PoE injector • Length: 2 m/6.6 ft

4047438013949	10,0 cm
85444210	7,5 cm
68 9	9,0 cm
	0,7 l

Other Camera Accessories

	Article No. / Name / Description	EAN / HS / weight	dimen.
	<p>Mx-M-SEC-SCREWS-SET Security Screw Set With Allen Bit For M73 Triple set of anti-theft screws (1 pcs M6x65, 4 pcs M6x16, 2 pcs M6x13) to securely attach the M73. Incl. Allen bit for power screwdrivers (1/4" in drive with hole for security pin)</p>	<p>4047438045209 90079100 68 g</p>	<p>9,0 cm 7,5 cm 4,6 cm 0,3 l</p>
	<p>Mx-O-M7SA-Blind Blind Module M73 For M73 • When operating the camera, it needs to be fitted either with sensor or blind modules. This closes off the front element and protects the camera against foreign objects, insects and water.</p>	<p>4047438035415 90079100 50 g</p>	<p>9,0 cm 7,5 cm 5,0 cm 0,3 l</p>
	<p>MX-OPT-Ring-L10-L12-BL Sealing Ring For Hemispheric Sensor Modules, Black Enables weather resistance when removing the plastic dome of black hemispheric sensor modules (S1x/M1x) • To avoid burns by the hot lens, the dome must not be removed within the reach of persons • Color: black</p>	<p>4047438021241 90079100 16 g</p>	<p>7,5 cm 4,9 cm 9,0 cm 0,3 l</p>
	<p>MX-OPT-Ring-L10-L12-PW Sealing Ring For Hemispheric Sensor Modules, White Enables weather resistance when removing the plastic dome of white hemispheric sensor modules (S1x/M1x) • To avoid burns by the hot lens, the dome must not be removed within the reach of persons • Color: white</p>	<p>4047438021234 90079100 16 g</p>	<p>7,5 cm 4,9 cm 9,0 cm 0,3 l</p>
	<p>MX-OPT-SEC-SCREWS-SET Security Screw Set With Allen Bit For M1x/M2x Triple set of anti-theft screws for plugs (4 pcs 6x50) and for machine threads (4 pcs M6x15, 4 pcs M6x30) to securely attach the VarioFlex wall mount • Incl. Allen bit for power screwdrivers (1/4" in drive with hole for security pin)</p>	<p>4047438021265 90079100 120 g</p>	<p>7,5 cm 4,9 cm 9,0 cm 0,3 l</p>

**MX-SM-Blind-PW****Blind Module M1x**

For M1x and M1x Thermal • When operating the camera, it needs to be fitted either with sensor or blind modules. This closes off the front element and protects the camera against foreign objects, insects and water.

4047438019965 9,0 cm






90079100 7,5 cm

46 g 5,0 cm

0,3 l

MOBOTIX MOVE Accessories

MOBOTIX MOVE Accessories

	Article No. / Name / Description	EAN / HS / weight	dimen.
	Mx-A-SD-DBC-EC Dome-Bubble EverClear (Clear) for MOBOTIX MOVE SD Dome Bubble EverClear (Clear) for MOBOTIX MOVE PTZ SD-230/330	4047438041508 90079100 580 g	26,0 cm 25,5 cm 17,0 cm 11,3 l
	MX-A-SD-DBT-EC Dome Bubble EverClear (Tinted) for MOBOTIX MOVE SD Dome Bubble EverClear (Tinted) for MOBOTIX MOVE PTZ SD-230/330	4047438041515 90079100 580 g	26,0 cm 25,5 cm 17,0 cm 11,3 l
	Mx-A-SD-DCS Tinted Dome For MOBOTIX MOVE SD-330 Tinted replacement dome suitable for MOBOTIX MOVE SpeedDome SD-330 • For particularly bright environments	4047438031776 90079100 300 g	26,0 cm 25,5 cm 17,0 cm 11,3 l
	Mx-A-SD-DCT Dome (Standard) For MOBOTIX MOVE SD-330 Standard replacement dome suitable for MOBOTIX MOVE SpeedDome SD-330	4047438031783 90079100 300 g	26,0 cm 25,5 cm 17,0 cm 11,3 l
	Mx-A-VB-FGK-EC Frontglass Kit EverClear for MOBOTIX MOVE VandalBullet - Frontglass Kit EverClear for MOBOTIX MOVE VB VandalBullet VB (model > Nov. 21)	4047438041546 90079100 33 g	12,0 cm 11,0 cm 3,0 cm 0,4 l



Mx-A-VD-DBC-EC
Dome Bubble EverClear (Clear) For MOBOTIX MOVE
 Dome Bubble EverClear (Clear) For MOBOTIX MOVE VD VandalDomes

4047438041522	17,0 cm
90079100	17,0 cm
240 g	13,0 cm
	3,8 l



Mx-A-VD-DBT-EC
Dome -Bubble EverClear (Tinted) For MOBOTIX MOVE
 Dome Bubble EverClear (Tinted) For MOBOTIX MOVE VD VandalDomes

4047438041539	17,0 cm
90079100	17,0 cm
240 g	13,0 cm
	3,8 l




Mx-A-VD-DCS
Tinted Dome For MOBOTIX MOVE VandalDome
 Tinted replacement dome for particularly bright environments • Suitable for all MOBOTIX MOVE VandalDome cameras

4047438031714	16,1 cm
90079100	16,1 cm
210 g	11,5 cm
	3,0 l




Mx-A-VD-DCT
Dome (Standard) For MOBOTIX MOVE VandalDome
 VD Standard replacement dome • Suitable for all MOBOTIX MOVE VandalDome cameras

4047438031721	16,1 cm
90079100	16,1 cm
250 g	11,5 cm
	3,0 l




Mx-A-VM-DBC
Dome-Bubble (Clear) for MOBOTIX MOVE Vandal
 VM Standard replacement dome • Suitable for MOBOTIX MOVE Vandal Multisensor camera Mx-VM1A-20-IR-VA

4047438047685	26,6 cm
90079100	25,0 cm
530 g	8,5 cm
	5,7 l




Mx-A-VM-DBT
Dome-Bubble (Tinted) For MOBOTIX MOVE Vandal
 Tinted replacement dome for particularly bright environments • Suitable for MOBOTIX MOVE Vandal Multiisensor camera Mx-VM1A-20-IR-VA

4047438047692	26,6 cm
90079100	25,0 cm
530 g	8,5 cm
	5,7 l

**Mx-M-BC-P****Pole Mount For MOBOTIX MOVE BulletCamera**


BC Pole Mount suitable for all MOBOTIX MOVE BulletCameras (except Mx-BC1A-2-IR)

4047438031677	17,3 cm
90079100	17,3 cm
1.000 g	16,7 cm
	5,0 l

**Mx-M-BC-W****Wall Mount For MOBOTIX MOVE BulletCamera**


BC Wall Mount suitable for MOBOTIX MOVE BulletCamera (except Mx-BC1A-2-IR)

4047438031660	17,3 cm
90079100	17,3 cm
840 g	10,7 cm
	3,2 l

**Mx-M-NVR16-RM****19" Rack Mounting Brackets for MOVE NVR 16CH**


2x metal mounting brackets for installing MOBOTIX MOVE NVR 16CH in a 19" rack

4047438037075	14,5 cm
85299097	11,0 cm
447 g	6,0 cm
	1,0 l

**Mx-M-NVR8-RM****19" Rack Mounting Brackets for MOVE NVR 8CH**

2x metal mounting brackets for installing MOBOTIX MOVE NVR 8CH in a 19" rack

4047438037068	14,5 cm
85299097	11,0 cm
544 g	6,0 cm
	1,0 l

**Mx-M-SD-C****Corner Mount For MOBOTIX MOVE SD-330/SD-340-IR**

SD Corner Mount suitable for MOBOTIX MOVE SpeedDome SD-330 and SD-340-IR • Installation only in combination with SD Wall Mount (Mx-M-SD-W)

4047438031769	21,0 cm
90079100	12,5 cm
2.170 g	25,0 cm
	6,6 l

**Mx-M-SD-GN****MOBOTIX MOVE SD Parapet Mount**

MOBOTIX MOVE SD Parapet Mount(Gooseneck) with integrated junction Box for MOBOTIX MOVE SpeedDome Mx-SD1A-330 and Mx-SD1A-340-IR

4047438038997	90,0 cm
90079100	57,0 cm
14.800 g	20,0 cm
	102,6 l

**Mx-M-SD-P****Pole Mount For MOBOTIX MOVE SD-330/SD-340-IR**

SD Pole Mount suitable for MOBOTIX MOVE SpeedDome SD-330 und SD-340-IR • Installation only in combination with SD Wall Mount (Mx-M-SD-W)

4047438031752	31,0 cm
90079100	15,5 cm
1.580 g	26,0 cm
	12,5 l

**Mx-M-SD-PM****MOBOTIX MOVE SD Pendant Mount Kit**

MOBOTIX MOVE SD Pendant Mount Kit 25 cm incl. Base-Mount, 25 cm pendant pipe, installation material and safety wires 50cm & 1m. Max. extendable pendant mount length 1m by usage of additional pendant mount extension Mx-M-SD-PMEXT

4047438039000	64,0 cm
90079100	22,0 cm
2.295 g	22,0 cm
	31,0 l

**Mx-M-SD-PMEXT****MOBOTIX MOVE SD PM Extension**

MOBOTIX MOVE SD Pendant Mount 25cm extension for Mx-M-SD-PM

4047438039017	14,4 cm
90079100	14,5 cm
800 g	28,0 cm
	5,8 l

**Mx-M-SD-W****Wall Mount For MOBOTIX MOVE SD-330/SD-340-IR**

SD Wall Mount suitable for MOBOTIX MOVE SpeedDome SD-330 and SD-340-IR • Can be combined with SD Pole Mount (Mx-M-SD-P) und SD-Corner Mount (Mx-M-SD-C)

4047438031745	21,6 cm
90079100	12,7 cm
840 g	14,8 cm
	4,1 l

**Mx-M-SD-WL****Wall Mount long for MOBOTIX MOVE Speeddomes SD and Multisensor VMxx**

Wall Mount long for MOBOTIX MOVE Speeddomes SD and Multisensor VMxx • Can be combined with SD Pole Mount (Mx-M-SD-P) und SD-Corner Mount (Mx-M-SD-C)

4047438048194	34,8 cm
90079100	10,4 cm
1.500 g	13,8 cm
	5,0 l

**Mx-M-SD-WM****Wall Mount For MOBOTIX MOVE SpeedDome**


MOBOTIX MOVE SD Wall Mount supporting optional Junction Box Mx-M-SD-WMJB, suitable for MOBOTIX MOVE SpeedDome Mx-SD1A-330 and Mx-SD1A-340-IR

4047438038973	33,0 cm
90079100	15,0 cm
1.300 g	23,0 cm
	11,4 l

**Mx-M-SD-WMJB****MOBOTIX MOVE SD Junction Box**

MOBOTIX MOVE SD Wall Mount Junction Box for use with Wall Mount Mx-M-SD-WM

4047438038980	29,0 cm
90079100	32,0 cm
4.800 g	19,0 cm
	17,6 l

**Mx-M-VD-C****Corner Mount For MOBOTIX MOVE VandalDome**

VD Corner Mount suitable for all MOBOTIX MOVE VandalDome cameras

4047438031738	21,0 cm
90079100	12,5 cm
2.170 g	25,0 cm
	6,6 l

**Mx-M-VD-IC****In-Ceiling Set For MOBOTIX MOVE VandalDome**

VD In-Ceiling Set suitable for all MOBOTIX MOVE VandalDome cameras

4047438031684	23,4 cm
90079100	23,4 cm
800 g	12,8 cm
	7,0 l

**Mx-M-VD-P****Pole Mount For MOBOTIX MOVE VandalDome**

VD-Pole Mount suitable for all MOBOTIX MOVE VandalDome cameras

4047438031707	31,0 cm
90079100	15,5 cm
1.580 g	26,0 cm
	12,5 l

**Mx-M-VD-W****Wall Mount For MOBOTIX MOVE VandalDome**

VD Wall Mount Set (2-piece) suitable for all MOBOTIX MOVE VandalDome cameras

4047438031691	31,0 cm
90079100	22,0 cm
1.400 g	18,0 cm
	12,3 l

**Mx-M-VM-AP****Adapter Mounting Plate for MOBOTIX MOVE Vandal**

Adaptor Mounting Plate suitable for MOBOTIX MOVE Vandal Multisensor camera Mx-VM1A-20-IR-VA

4047438047678	36,4 cm
90079100	34,5 cm
1.950 g	12,8 cm
	16,1 l



Mx-M-VM-IC

In-Ceiling Set For MOBOTIX MOVE Vandal Multisensor

In-Ceiling Set suitable for MOBOTIX MOVE Vandal Multisensor camera Mx-VM1A-20-IR-VA

4047438047661	31,6 cm
90079100	34,5 cm
965 g	12,8 cm
	14,0 l



Mx-M-VMSD-AP

Adapter Mounting-Plate for MOBOTIX MOVE Vandal

VMSD Adaptor Mounting -Plate suitable for MOBOTIX MOVE Vandal Multisensor PTZ Combo camera Mx-VMSD1A-2021-VA

4047438047517	32,2 cm
90079100	32,2 cm
1.570 g	11,9 cm
	12,3 l



Mx-M-VMSD-IC

In-Ceiling Set For MOBOTIX MOVE Vandal Multisensor PTZ

VMSD In-Ceiling Set suitable for MOBOTIX MOVE Vandal Multisensor PTZ Combo camera Mx-VMSD1A-2021-VA

4047438047708	40,9 cm
90079100	38,9 cm
3.500 g	22,6 cm
	36,0 l



Mx-M-VT-AP

Adapter Mounting-Plate for MOBOTIX MOVE Vandal Turret

Adapter Mounting Plate suitable for MOBOTIX MOVE Vandal Turret Cameras VT-2-IR, VT-5-IR, VT-203-IR, VT-503-IR

4047438049009	16,2 cm
90079100	17,2 cm
600 g	14,3 cm
	4,0 l



Mx-M-VT-JB

Junction Box for MOBOTIX MOVE Vandal Turret Camera

Junction Box suitable for MOBOTIX MOVE Vandal Turret Cameras VT-2-IR, VT-5-IR, VT-203-IR, VT-503-IR

4047438049016	17,3 cm
90079100	17,1 cm
950 g	13,4 cm
	4,0 l



Mx-M-VT-WM

Wall Mount for MOBOTIX MOVE Vandal Turret Camera

Wall Mount suitable for MOBOTIX MOVE Vandal Turret Cameras VT-2-IR, VT-5-IR, VT-203-IR, VT-503-IR

4047438048996	22,6 cm
90079100	10,3 cm
600 g	15,5 cm
	3,6 l

MOVE Other Accessories






	Article No. / Name / Description	EAN / HS / weight	dimen.
	Mx-A-ETP1A-2601-POW Plug-type Power-supply for Mx-A-ETP1A-2601-SET Plug-type power supply for Mx-A-ETP1A-2601-SET • Output: 57V DC +/-3% / 1.2 A • Input: 90-260V AC (47-63Hz) • 68,4 Watt • Operating Temperature: 0-40 °C	4047438042581 85365019 490 g	19,4 cm 14,2 cm 4,0 cm 1,1 l
	Mx-A-ETP1A-2601-SET Media converter set Ethernet(PoE+) – Twisted-Pair Mx-ETP1A-2601-SET Complete set consisting of two two-wire transmitting and receiving units for realising an Ethernet transmission path via Twisted Pair cable. • Transmission of Ethernet and PoE+ power supply via two-wire line according to IEEE1901. • Simple connection of 10/100 Mbps Ethernet end devices • Max. 95 Mbps transmission bandwidth, range up to 600m for data / 300m for PoE depending on the quality of the Twisted-Pair link • 128 bit AES network data encryption • Power supply 2-wire transmitter (Tx) and receiver (Rx) as well as end device via PoE+ network switch or external power supply 56VDC / 1.2A (not included!) • Connected end devices are supplied via PoE switch IEEE802.3af(PoE), IEEE802.3at (PoE+), UPoE up to 60W (requires ext. power supply unit). • Status LEDs (data, power supply, data link, PoE) • Integrated Overvoltage protection (IEC 61000-4-5 4kV(1.2 / 50us), 2kA(8 / 20us)) • Power Supply: TX: T-Linx or DC12V-57V, RX: PoE Switch or DC48V-57V • Operational temperature: -20 to 60 °C • Dimensions: 80.4(L) x 61.6(W) x 24(H)mm • Weight: RX/TX: 102g • Warranty: 2 years	4047438041317 85299065 368 g	20,7 cm 12,5 cm 7,0 cm 1,8 l
	Mx-A-KBD1A-PTZ-JOG MOBOTIX USB Keyboard with PTZ Joystick & Jog-Shuttle USB control panel for operating MOBOTIX MxMC 2.6 and higher and MOBOTIX HUB incl. Control of software PTZ and motorized PTZ cameras and pan/tilt devices • Integrated 3-axis joystick • Integrated jog shuttle • 38 control keys with backlight predefined for MxMC functions or freely definable for MOBOTIX HUB • Integrated alarm buzzer • Suitable for operation as HID device on MOBOTIX VMS with Windows and MAC based operating systems via USB2.0 • Suitable for right- and left-handed users • Power supply: USB, max. 350 mA • Operating temperature: 0° - 45 °C (32 °F- 113 °F)	4047438040754 85299065 1.900 g	42,5 cm 27,0 cm 17,5 cm 20,1 l


System Components

BeyondHumanVision

MOBOTIX

Functional Modules for MOBOTIX 7 Cameras


	Article No. / Name / Description	EAN / HS / weight	dimen.
	<p>Mx-F-AUDA M73/S74 Audio Module equipped with microphone / Weatherproof audio module (IP66, -30 to 65 °C, IK07) with integrated microphone and speaker for connection to the MOBOTIX M73 camera, no camera removal required • In connection with the audio cable Mx-A-S7A-AUCBL05-AN and the IO plug-in board Mx-F-S7A-INT01, the audio module can also be operated at the S74 (compatible with S74 module mounts)</p>	4047438034937 85299065 150 g	9,8 cm 7,5 cm 9,0 cm 0,7 l
	<p>Mx-F-IRA-S M73/S74 IR Light Module for Standard Lens (45° - 60°) Infrared illuminator module for MOBOTIX M73/S74 camera night sensor modules with 45°-60° illumination angle (horizontal) • 850 nm • IP66 • Range in connection with the Ultra LowLight sensor modules: Standard lenses: up to 70 m</p>	4047438034913 85299065 145 g	9,8 cm 7,5 cm 9,0 cm 0,7 l
	<p>Mx-F-IRA-T M73/S74 IR Light Module for Tele Lens (15° - 30°) Infrared illuminator module for MOBOTIX M73/S74 cameras night sensor modules with 15°-30° illumination angle (horizontal) • 850 nm • IP66 • Range in connection with the Ultra LowLight sensor modules: Tele lenses up to 100 m</p>	4047438034920 85299065 145 g	9,8 cm 7,5 cm 9,0 cm 0,7 l
	<p>Mx-F-IRA-W M73/S74 IR Light Module for Wide Lens (95°) Infrared illuminator module for MOBOTIX M73/S74 camera night sensor modules with 95° illumination angle (horizontal) • 850 nm • IP66 • Range in connection with the Ultra LowLight sensor modules: Wide-angle lenses with W-IR illuminator: up to 40 m</p>	4047438034906 85299065 145 g	9,8 cm 7,5 cm 9,0 cm 0,7 l
	<p>Mx-F-MSA MOBOTIX 7 MultiSense Outdoor Weatherproof multi-sensor module with four environmental sensors: passive infrared sensor PIR, brightness sensor, temperature sensor (max ±0.4°C / 0.72°F) and microphone • Camera connection and supply via MOBOTIX 7 sensor cable (up to 3m): power consumption approx. 100 mW • Status LED • Compact device using a screwable sensor module housing • Easy installation without accessories (e.g., in suspended ceilings) • Protection class IP66 • IK05 • Housing color: white</p>	4047438035545 85299065 100 g	9,8 cm 7,5 cm 9,0 cm 0,7 l



Mx-F-S7A-INT01
S74 IO Slide in Board

S74 IO slide in board with 1x input / output, 1x line in / out and 1x mic in / speaker out functionality • Connection option for audio module Mx-F-AUDA with audio cable Mx-A-S7A-AUCBL05-AN

4047438035576	14,8 cm
85299065	9,8 cm
110 9	9,0 cm
	1,3 l



Mx-F-S7A-LSA
S74 network slide in board with LSA terminal

S74 network slide in board with LSA terminal

4047438037051	14,8 cm
85299065	9,8 cm
110 9	9,0 cm
	1,3 l



Mx-F-S7A-RJ45
S74 Network slide in board with RJ45 socket

S74 Network slide in board with RJ45 socket

4047438035569	14,8 cm
85299065	9,8 cm
110 9	9,0 cm
	1,3 l



Mx-F-S7A-RJ45-VDC
S74 RJ45 Network slide in board with 12/24 VDC Power

S74 Network slide in board with RJ45 socket and 12/24V DC Power Supply

4047438039680	14,8 cm
85299065	9,8 cm
110 9	9,0 cm
	1,3 l



Mx-F-WLA-S
M73/S74 White Light for Standard lens 45-60°

White light illuminator module for MOBOTIX M73/S74 cameras with an angle of view 45-60° (horizontal) • IP66 • Range in connection with the Ultra LowLight sensor modules: Standard lenses with illuminator: up to 60 m

4047438042529	9,8 cm
85395200	7,5 cm
145 9	9,0 cm
	0,7 l



Mx-F-WLA-T
M73/S74 White Light for tele lens 15-30°

White light illuminator module for MOBOTIX M73/S74 cameras with an angle of view 15-30° (horizontal) • IP66 • Range in connection with the Ultra LowLight sensor modules: Tele lenses with illuminator: up to 80 m

4047438042536	9,8 cm
85395200	7,5 cm
145 9	9,0 cm
	0,7 l

**Mx-F-WLA-W****M73/S74 White Light for Wide Lens 95°**

White light illuminator module for MOBOTIX M73/S74 cameras with an angle of view 95° (horizontal) • IP66 • Range in connection with the Ultra LowLight sensor modules: Wide-angle lenses with illuminator: up to 40 m






4047438042512 9,8 cm


85395200 7,5 cm

145 g 9,0 cm

0,7 l

Interface Boxes

	Article No. / Name / Description	EAN / HS / weight	dimen.
	<p>Mx-A-GPSA MX-GPS-Box Weatherproof GPS time base for MOBOTIX systems • GPS and Glonass support • Includes outdoor temperature and illumination sensors • Connects via MxBus 2-wire cable • Protection class IP66/IK08, -30 to 60°C / -22 to +140°F • Box can be mounted safely out of reach in the wall mounts of M1x, M2x, D1x and D2x</p>	<p>4047438035507 85299065 120 g</p>	<p>10,5 cm 6,8 cm 10,5 cm 0,7 l</p>
	<p>Mx-F-4IOA Input/Output Box for MOBOTIX 7 and MOBOTIX ONE Weatherproof connection of external sensors and switching of external devices via MOBOTIX cameras • Connection to camera using USB-C • 4 galvanically isolated inputs, 4 relay output • Protection class IP66/IK08, -30 to 60°C / -22 to 140°F</p>	<p>4047438048309 85299065 130 g</p>	<p>10,0 cm 7,5 cm 9,0 cm 0,7 l</p>
	<p>Mx-F-NPAA POE Power Adapter for MOBOTIX cameras Weatherproof PoE Injector and network connector • Needs external power supply units and batteries from 12 to 24V DC • Protection class IP66/IK08, -30 to 50°C / -22 to 122°F • Important: only use with original MOBOTIX patch cables</p>	<p>4047438048323 85299065 140 g</p>	<p>10,0 cm 7,5 cm 9,0 cm 0,7 l</p>
	<p>MX-Overvoltage-Protection-Box-LSA Network Connector with Surge Protection, LSA Version Weatherproof connection of one MOBOTIX patch cable (RJ45, from camera) and the network installation cable • Protects one MOBOTIX camera against surges of up to 4 kV on the PoE network cabling • Complete set including mounting supplies • Protection class IP66/IK08, -30 to 60°C / -22 to 140°F • Box can be mounted safely out of reach in the wall mounts of M1x, M2x, D1x, D2x</p>	<p>4047438018470 85299065 146 g</p>	<p>10,0 cm 7,5 cm 9,0 cm 0,7 l</p>
	<p>MX-Overvoltage-Protection-Box-RJ45 Network Connector with Surge Protection, RJ45 Version Weatherproof connection of two MOBOTIX patch cables (RJ45, one from the camera) • Protects one MOBOTIX camera against surges of up to 4 kV on the PoE network cabling • Complete set including mounting supplies • Protection class IP66/IK08, -30 to 60°C / -22 to 140°F • Box can be mounted safely out of reach in the wall mounts of M1x, M2x, D1x, D2x</p>	<p>4047438018463 85299065 150 g</p>	<p>10,0 cm 7,5 cm 9,0 cm 0,7 l</p>

**MX-OPT-RS1-EXT****MX-232-IO-Box**

Weatherproof connection of external sensors and switching of external devices via MOBOTIX cameras • Connection to camera using USB or MxBus • 2 self-powered inputs for connecting sensors • 2 outputs: 1 powered output, 1 isolated relay output (can be switched to second powered output) • RS232 interface when using MOBOTIX USB cable to connect to camera • Protection class IP66/IK08, -30 to 60°C / -22 to 140°F • Box can be mounted safely out of reach in the wall mounts of M1x, M2x, D1x and D2x

4047438015417 10,5 cm

85299065 6,8 cm

120 g 10,5 cm

0,7 l

Functional Enhancement & IR Illuminators

	Article No. / Name / Description	EAN / HS / weight	dimen.
	<p>MX-MULTISENSE1-EXT MxMultiSense Outdoor (HS code 85299065) Weatherproof multi-sensor module with four environmental sensors: passive infrared sensor PIR, brightness sensor, temperature sensor ($\pm 0.3^{\circ}\text{C}$ / 0.18°F) and acoustic sensor (level of sound waves) • Camera connection and supply via MxBus: power consumption approx. 0.3 W, MxBus cable length up to 100 m / 330 ft. • Status LED • Compact device using a screwable sensor module housing • Easy installation without accessories (e.g., in suspended ceilings) • Compatible with all MOBOTIX mounts for sensor modules and standard mounts for recessed spotlights • Protection class IP66 • IK05 • Ambient temperature -20 to 60°C / -4 to 140°F • Housing color: white</p>	<p>4047438028905 85299065 110 g</p>	<p>9,8 cm 7,5 cm 9,0 cm 0,7 l</p>
	<p>MX-OPT-IO3-INT Extension Module For c25, i25, p25 And v25 Extension module for the indoor cameras x25 (to be mounted on the backside) • Not compatible with x26 indoor cameras • For the connection of external sensors (e.g., door or window • contacts) and switching of external devices (e.g., relays with lamps and motors) • Two input lines (galvanically isolated, 0 to 48 V AC/DC) • Two output lines: 2x • isolated (contact load max.30 W or 1 A or 48 V AC/DC) or 2x 12 V DC (max. 50 mA • per output line) • MxBus terminal (1x2) • Ambient temperature: 0 to 4°C (32 to 104°F) • Power consumption: 1 W</p>	<p>4047438025928 85299065 45 g</p>	<p>10,7 cm 5,2 cm 8,7 cm 0,5 l</p>
	<p>MX-A-IOA-IC Extension Module For All Indoor Cameras x26A/x26B Expansion module for Indoor Cameras c26A/B, i26A/B, p26A/B and v26A/B (installed on the back) • Not suitable for x25 indoor cameras • For connecting external sensors (e.g., door and window contacts) and switches of external devices (e.g., relays with lamps and motors) • Two inputs (galvanically separated): 0 V to 48 V AC/DC • Two outputs: 2x floating (load per contact max. 30 W or 1 A or 48 V AC/DC) or 2x 12 V DC (max. 50 mA per output) • 2x MxBus terminal connector (MxBus will be supported only by the x26B Indoor Cameras) • Ambient temperature: 0°C to 40°C (32°F to 104°F) • Power consumption: 1 W</p>	<p>4047438029032 85299065 45 g</p>	<p>10,7 cm 5,2 cm 8,7 cm 0,5 l</p>
	<p>Mx-A-SPA MxSplitProtect Installation Box, IP66 Weatherproof installation box with integrated 4-kV surge protection (Type 2 P4) for connecting two IP cameras/PoE devices using one Ethernet cable • Interfaces (weatherproof): 1 LSA (with shield clip) for Ethernet 2 100Base-T, 2 MxRJ45 for Ethernet 100Base-T with PoE Mode A, 1 protective earth terminal • IP66 and IK08, ambient temperature: -30°C to 60°C (-22°F to 140°F) • Accessories (available separately): MxSplitProtectHR Hat Rail module (Mx-A-SPA-HR), cover with camera mount in three versions (Mx-A-SPCA-M/-H/-V), pole mount (MX-MH-SecureFlex-ESWS) • Housing color: white</p>	<p>4047438030229 85299065 1.184 g</p>	<p>30,5 cm 24,0 cm 16,0 cm 11,7 l</p>
	<p>Mx-A-SPA-HR MxSplitProtectHR Hat Rail Module Compatible with MxSplitProtect Installation Box (Mx-A-SPA): Hat rail module (for 35 mm DIN rails) with integrated 4-kV surge protection (Type 2 P4) for connecting two IP cameras/PoE devices using one Ethernet cable • Interfaces: 3x RJ45 for Ethernet 100Base-T, 1x protective earth terminal • Only use in indoor areas, ambient temperature: 0°C to 40°C (32°F to 104°F) • Accessories (available separately): MxSwitch (MX-SWITCH1) • Housing color: gray</p>	<p>4047438030236 85299065 130 g</p>	<p>10,0 cm 7,5 cm 9,0 cm 0,7 l</p>

**Mx-A-SPCA-M****MxSplitProtect Cover, M-Cameras**

Cover/mounting option with camera mount • Accessories for the MxSplitProtect Installation Box (Mx-A-SPA) • Also possible to install the standard VarioFlex wall mount of an M15/M16/M25/M26 camera directly to the cover • Color: white

4047438028820	19,6 cm
85299065	18,0 cm
514 g	14,8 cm
	5,2 l

**Mx-A-SPCA-H****MxSplitProtect Cover, Horizontal**

Cover/mounting option with camera mount • Accessories for the MxSplitProtect Installation Box (Mx-A-SPA) • Also possible to (vertically) install a Q2x (orD2x) camera with a 15° tilt angle without an additional mount directly to the cover • Color: white

4047438028837	19,6 cm
85299065	18,0 cm
570 g	14,8 cm
	5,2 l

**Mx-A-SPCA-V****MxSplitProtect Cover, Vertical**

Cover/mounting option with camera mount • Accessories for the MxSplitProtect Installation Box (Mx-A-SPA) • Also possible to (horizontally) install a Q2x/D2x camera without an additional mount directly to the cover • Color: white

4047438028844	19,6 cm
85299065	18,0 cm
482 g	14,8 cm
	5,2 l

**Mx-A-IRA-120****MxIRLight Infrared Illuminator (860 nm), 120°x120°**


Infrared illuminator with 120° illumination angle (horizontal and vertical), aluminum housing • 860 nm • IP67 • Range: up to 20 m (66 ft.) • PoE+ power supply via network cable (IEEE 802.3at), 19 W (max.) power consumption • Photosensor for automatic switching on/off (threshold value: 3 lux, delay for switching off: 150 s) • Including standard mount for installing on wall and ceiling, screws, preassembled 0.9 m patch cable with RJ45 connector and MOBOTIX special sealing ring • Optional accessories: mounting brackets for M1x/M2x (Mx-M-IRA-ML/Mx-M-IRA-M) • Housing color: white

4047438030342	20,5 cm
85394900	17,5 cm
1.098 g	12,5 cm
	4,5 l

**Mx-A-IRA-90****MxIRLight Infrared Illuminator (860 nm), 90°x90°**


Infrared illuminator with 90° illumination angle (horizontal and vertical), aluminum housing • 860 nm • IP67 • Range: up to 35 m (115 ft.) • PoE+ power supply via network cable (IEEE 802.3at), 19 W (max.) power consumption • Photosensor for automatic switching on/off (threshold value: 3 lux, delay for switching off: 150 s) • Including standard mount for installing on wall and ceiling, screws, preassembled 0.9 m patch cable with RJ45 connector and MOBOTIX special sealing ring • Optional accessories: mounting brackets for M1x/M2x (Mx-M-IRA-ML/Mx-M-IRA-M) • Housing color: white

4047438030359	20,5 cm
85394900	17,5 cm
1.112 g	12,5 cm
	4,5 l

**Mx-A-IRA-60****MxIRLight Infrared Illuminator (860 nm), 60°x60°**


Infrared illuminator with 60° illumination angle (horizontal and vertical), aluminum housing • 860 nm • IP67 • Range: up to 50 m (165 ft.) • PoE+ power supply via network cable (IEEE 802.3at), 19 W (max.) power consumption • Photosensor for automatic switching on/off (threshold value: 3 lux, delay for switching off: 150 s) • Including standard mount for installing on wall and ceiling, screws, preassembled 0.9 m patch cable with RJ45 connector and MOBOTIX special sealing ring • Optional accessories: mounting brackets for M1x/M2x (Mx-M-IRA-ML/Mx-M-IRA-M) • Housing color: white

4047438030366	20,5 cm
85394900	17,5 cm
1.116 g	12,5 cm
	4,5 l

**Mx-A-IRA-45****MxIRLight Infrared Illuminator (860 nm), 45°x45°**


Infrared illuminator with 45° illumination angle (horizontal and vertical), aluminum housing • 860 nm • IP67 • Range: up to 80 m (262 ft.) • PoE+ power supply via network cable (IEEE 802.3at), 19 W (max.) power consumption • Photosensor for automatic switching on/off (threshold value: 3 lux, delay for switching off: 150 s) • Including standard mount for installing on wall and ceiling, screws, preassembled 0.9 m patch cable with RJ45 connector and MOBOTIX special sealing ring • Optional accessories: mounting brackets for M1x/M2x (Mx-M-IRA-ML/Mx-M-IRA-M) • Housing color: white

4047438030373	20,5 cm
85394900	17,5 cm
1.124 9	12,5 cm
	4,5 l

**Mx-A-IRA-30****MxIRLight Infrared Illuminator (860 nm), 30°x30°**

Infrared illuminator with 30° illumination angle (horizontal and vertical), aluminum housing • 860 nm • IP67 • Range: up to 120 m (394 ft.) • PoE+ power supply via network cable (IEEE 802.3at), 19 W (max.) power consumption • Photosensor for automatic switching on/off (threshold value: 3 lux, delay for switching off: 150 s) • Including standard mount for installing on wall and ceiling, screws, preassembled 0.9 m patch cable with RJ45 connector and MOBOTIX special sealing ring • Optional accessories: mounting brackets for M1x/M2x (Mx-M-IRA-ML/Mx-M-IRA-M) • Housing color: white

4047438030380	20,5 cm
85394900	17,5 cm
1.096 9	12,5 cm
	4,5 l

**Mx-A-IRA-15****MxIRLight Infrared Illuminator (860 nm), 15°x15°**

Infrared illuminator with 15° illumination angle (horizontal and vertical), aluminum housing • 860 nm • IP67 • Range: up to 160 m (525 ft.) • PoE+ power supply via network cable (IEEE 802.3at), 19 W (max.) power consumption • Photosensor for automatic switching on/off (threshold value: 3 lux, delay for switching off: 150 s) • Including standard mount for installing on wall and ceiling, screws, preassembled 0.9 m patch cable with RJ45 connector and MOBOTIX special sealing ring • Optional accessories: mounting brackets for M1x/M2x (Mx-M-IRA-ML/Mx-M-IRA-M) • Housing color: white

4047438030397	20,5 cm
85394900	17,5 cm
1.090 9	12,5 cm
	4,5 l

**Mx-M-IRA-ML****MxIRLight Mounting Brackets For M1x**

Mounting brackets „Large“ for the MOBOTIX M15/M16 AllroundDual cameras • Accessories for the MxIRLight Infrared Illuminator • Material: aluminum • Color: white

4047438030403	19,6 cm
85399010	5,5 cm
216 9	3,5 cm
	0,4 l

**Mx-M-IRA-M****MxIRLight Mounting Brackets For M2x**

Mounting brackets for the MOBOTIX M25/M26 Allround cameras • Accessories for the MxIRLight Infrared Illuminator • Material: aluminum • Color: white

4047438030410	14,0 cm
85399010	5,5 cm
150 9	3,5 cm
	0,3 l

PoE Power Supply

	Article No. / Name / Description	EAN / HS / weight	dimen.
	Mx-NPA-PoE1A-60W-BT PoE++ Power Network Injektor 60 Watt PoE++ 60W Network Power injector • AC Input Voltage: 100 to 240 VAC (50 to 60Hz) • AC Input Current: 1.5A @100-240 VAC • Operating Ambient Temperature: • -10° to 40°C @60W • -10° to 50°C, humidity 10 to 90% @30W • IEEE 802.3bt compliant • Output power of 60W over 4-pairs • Supports 10/100/1000Base-T applications • Plug-and-play installation • Full Protection OVP, OCP • Additional required power cord C14-type not included • Warranty: 1 year	4047438047531 85043180 318 g	17,0 cm 7,0 cm 4,7 cm 0,6 l
	Mx-NPA-UPoE1A-60W UPoE Power Injektor 60W UPoE (PoE++) 60W Network Power injector • AC Input Voltage: 100 to 240 VAC (50 to 60Hz) • AC Input Current: 1.5A @100-240 VAC • Operating Ambient Temperature: • 14° to 113°F @60W • 14° to 131°F @30W • IEEE 802.3at compliant with 2-event classification • IEEE 802.3af backward compatible • Output power of 60W over 4-pairs • Supports 10/100/1000Base-T applications • Plug-and-play installation	4047438039024 85043180 450 g	20,5 cm 11,5 cm 6,5 cm 1,5 l
	MX-SWITCH1 MxSwitch For DIN Rail Mounting PoE+ Switch for the top-hat rail • 5x RJ45 port with 100 MBit/s (1x uplink, 4x PoE+ with max. 75 W) • Supply: 48 V DC, max. 75 W • Simplified cabling for door stations due to available connectivity for anti-theft protection, door opener and MxBus • MxBus, anti-theft protection, door and lock contact can be connected via separate wires of the ethernet cable	4047438028882 85176200 310 g	14,8 cm 9,8 cm 9,0 cm 1,3 l
	Mx-NPA-PoE-EU-Set PoE Power Adapter Set, EU PoE injector incl. crossover function for direct connection to the PC • With power plug for Europe • For all MOBOTIX cameras (except for M1 und M10), Mx2wire+ and all PoE devices • Provides compliant PoE power supply (IEEE 802.3af) for direct connection to PC and camera • Kit includes blue adapter with 3 sockets RJ45 and universal power supply with RJ45 plug	4047438012249 85043180 268 g	14,8 cm 9,8 cm 9,0 cm 1,3 l
	Mx-NPA-PoE-INT-Set PoE Power Adapter Set, INT PoE injector incl. crossover function for direct connection to the PC • With 4 exchangeable power plugs for Europe, United Kingdom, USA and Australia • For all MOBOTIX cameras (except for M1 und M10), Mx2wire+ and all PoE devices • Provides compliant PoE power supply (IEEE 802.3af) for direct connection to PC and camera • Kit includes blue adapter with 3 sockets RJ45 and universal power supply with RJ45 plug	4047438012256 85043180 314 g	14,8 cm 9,8 cm 9,0 cm 1,3 l



MX-NPA-PoE-RJ
PoE Power Adapter

PoE injector (IEEE 802.3af) incl. crossover function for direct connection to the PC • Blue adapter with 3 sockets RJ45 and universal power supply with RJ45 plug • Without power plug, additional power supply (12 to 57 V DC) and connection cable needed

4047438013932	9,0 cm
85043180	7,5 cm
60 g	5,0 cm
	0,3 l






MX-SNT-INT-PoE
Universal Power Supply With 4 Power Plugs

For international use thanks to broad input voltage range and interchangeable power plugs (no tools required) • With 4 power plugs for Europe, United Kingdom, USA and Australia • Connections: 1x RJ45 (for adapter), 1x network (up to 4x interchangeable adapter) • Nominal data input: 100 V to 240 V, 50 to 60 Hz/400 mA • Nominal data output: DC 24 V/750 mA • Ambient temperature: 0 to 40°C / 32 to 104 °F

4047438013925	9,8 cm
85043180	7,5 cm
160 g	9,0 cm
	0,7 l

MOBOTIX Storage & Recording Solutions


	Article No. / Name / Description	EAN / HS / weight	dimen.
	<p>Mx-S-NVR1A-64-POE24</p> <p>MOBOTIX MOVE NVR Network Video Recorder 64 Channels</p> <p>MOBOTIX MOVE NVR Network Video Recorder for recording and Display up to 64 IP Cameras (Resolution up to 12MP) • 24 integrated PoE+ Ports for centralized powering of connected IP-Cameras • 8x 3.5" SATA3 locklable HDD cartridge-slots (Delivery without hard disks (not available via MOBOTIX) • Harddrives "Hot-Swappable" • RAID 0/1/5/10 Support for Data recovering in case of HDD Failure • Optional Failover-Server functionality withing MOVE NVR System • IP-Data-Throughput (Live & Recording): avrg.: 480 Mbps, peak 2upt to 540 Mbps • Video-Codecs : H.264 / H.265 • Support of ONVIF S conformant 3rd Party cameras • APP remote access (IOS / Android), Live, Playback • iSCSI NAS Storage support • 19"-Rack mount kit included. • Environmental Temperature 0 to 40°C • Power Supply: AC AC 100-240V, ATX 520W (53V/360W for PoE; 12V/160W for HDD/System) • Incl. Power cable with EU plug (cable with US / GB / AU plug available on request) • Warranty: 5 Years (excl. HDD's)</p>	<p>4047438040365</p> <p>85255000</p> <p>12.510 g</p>	<p>58,0 cm</p> <p>58,0 cm</p> <p>25,0 cm</p> <p>84,1 l</p>
	<p>Mx-S-NVR1B-16-POE</p> <p>MOBOTIX MOVE NVR Network Video Recorder 16 Channels</p> <p>MOBOTIX MOVE NVR Network Video Recorder with 16 integrated PoE IP camera channels (support of up to 24 IP cameras in total) • 8GB RAM integrated • Max. Storage capacity net: 28 TB (2x 3.5" SATA3) • Supplied without hard disks (not available via MOBOTIX) • IP data throughput (live & recording): max. 240 Mbps • Recording compression: H.264 / H.265 • Supports ONVIF S compliant third-party cameras • APP remote access (IOS / Android), live, playback • CMS (Central Monitoring Software) Remote Zugriff • Integrierated in MOBOTIX HUB VMS • iSCSI NAS storage support • Incl. power connection cable with EU plug (cable with US/GB/AU plug available on request) • Warranty: 5 Years (excl. HDD's)</p>	<p>4047438047623</p> <p>85255000</p> <p>8.500 g</p>	<p>49,5 cm</p> <p>34,5 cm</p> <p>18,1 cm</p> <p>30,9 l</p>
	<p>Mx-S-NVR1B-8-POE</p> <p>MOBOTIX MOVE NVR Network Video Recorder 8 Channels</p> <p>MOBOTIX MOVE NVR Network Video Recorder with 8 integrated PoE IP camera channels (support of up to 12 IP cameras in total) • 4GB RAM integrated • Max. Storage capacity net: 20 TB (2x 3.5" SATA3) Supplied without hard disks (not available via MOBOTIX) • IP data throughput (live & recording): max. 160 Mbps • Recording & playback: H.264 / H.265 • Supports ONVIF S compliant third-party cameras • APP remote access (IOS / Android), live, playback • CMS (Central Monitoring Software) Remote Zugriff • Integrierated in MOBOTIX HUB VMS • iSCSI NAS storage support • Incl. power connection cable with EU plug (cable with US/GB/AU plug available on request) • Warranty: 5 Years (excl. HDD's)</p>	<p>4047438047616</p> <p>85255000</p> <p>4.200 g</p>	<p>42,6 cm</p> <p>37,9 cm</p> <p>11,0 cm</p> <p>17,8 l</p>

MOBOTIX Cloud






BeyondHumanVision







MOBOTIX

MOBOTIX Cloud Bridge

	Article No. / Name / Description	EAN / HS / weight	dimen.
	<p>Mx-S-BRIDGEB-DT-20</p> <p>MOBOTIX CLOUD Bridge 304+ for up to 20 IP Cameras</p> <p>High-security connection box for the MOBOTIX CLOUD VMS • Locally connected to the Internet and up to 20 ONVIF IP cameras at 4MP resolution • Cybersecure connection to regionally available MOBOTIX CLOUD data centers • Secure end-to-end encryption of all data stored and transferred in the system • No data loss in case of up to 2-day Internet outage: Integrated hard disk as a memory buffer in case of interrupted connection to the cloud • No data loss due to Internet bandwidth fluctuations: Automatic data buffering in the BRIDGE • Ultra flexible cloud data storage with individually selectable retention period (max. 5 years) • Compact, robust metal housing with an extended temperature range and fanless device design for maximum reliability thanks to SSD memory • Dimensions (LxWxH): 127 x 127 x 45 mm (5" x 5" x 1.75") • Connections: AC power supply (adapter included), 2x ETH (1x for PoE switch for local cameras, 1x for internet router), monitor and keyboard (optional) • Integrated display for status display such as the IP</p>	<p>4047438043588</p> <p>85299065</p> <p>1.980 g</p>	<p>29,6 cm</p> <p>19,6 cm</p> <p>9,0 cm</p> <p>5,2 l</p>

MOBOTIX Cloud Subscriptions

	Article No. / Name / Description	EAN / HS / weight	dimen.
	Mx-CL-Sub-ANA-001-12 MOBOTIX CLOUD Yearly Analytics Subscription, Line Cross Yearly subscription for using the MOBOTIX CLOUD Analytics: Line Cross • Cancellation possible at any time at the end of the subscription period.	4047438042062	cm cm g cm l
	Mx-CL-Sub-ANA-001-36 MOBOTIX CLOUD 3 Yearly Analytics Subscription, Line Cross 3 Yearly subscription for using the MOBOTIX CLOUD Analytics: Line Cross • Cancellation possible at any time at the end of the subscription period.	4047438046701	cm cm g cm l
	Mx-CL-Sub-ANA-001-60 MOBOTIX CLOUD 5 Yearly Analytics Subscription, Line Cross 5 Yearly subscription for using the MOBOTIX CLOUD Analytics: Line Cross • Cancellation possible at any time at the end of the subscription period.	4047438046718	cm cm g cm l
	Mx-CL-Sub-ANA-002-12 MOBOTIX CLOUD Yearly Analytics Subscription, Counting Yearly subscription for using the MOBOTIX CLOUD Analytics: Counting • Cancellation possible at any time at the end of the subscription period.	4047438042079	cm cm g cm l
	Mx-CL-Sub-ANA-002-36 MOBOTIX CLOUD 3 Yearly Analytics Subscription, Counting 3 Yearly subscription for using the MOBOTIX CLOUD Analytics: Counting • Cancellation possible at any time at the end of the subscription period.	4047438046725	cm cm g cm l

	<p>Mx-CL-Sub-ANA-002-60 MOBOTIX CLOUD 5 Yearly Analytics Subscription, Counting 5 Yearly subscription for using the MOBOTIX CLOUD Analytics: Counting • Cancellation possible at any time at the end of the subscription period.</p>	4047438046732	cm cm cm l
	<p>Mx-CL-Sub-ANA-003-12 MOBOTIX CLOUD Yearly Analytics Subscription, Area Yearly subscription for using the MOBOTIX CLOUD Analytics: Area Intrusion • Cancellation possible at any time at the end of the subscription period.</p>	4047438042086	cm cm cm l
	<p>Mx-CL-Sub-ANA-003-36 MOBOTIX CLOUD 3 Yearly Analytics Subscription, Area 3 Yearly subscription for using the MOBOTIX CLOUD Analytics: Area Intrusion • Cancellation possible at any time at the end of the subscription period.</p>	4047438046749	cm cm cm l
	<p>Mx-CL-Sub-ANA-003-60 MOBOTIX CLOUD 5 Yearly Analytics Subscription, Area 5 Yearly subscription for using the MOBOTIX CLOUD Analytics: Area Intrusion • Cancellation possible at any time at the end of the subscription period.</p>	4047438046756	cm cm cm l
	<p>Mx-CL-Sub-ANA-004-12 MOBOTIX CLOUD Yearly Analytics Subscription, Camera Yearly subscription for using the MOBOTIX CLOUD Analytics: Camera Tamper Detect • Cancellation possible at any time at the end of the subscription period.</p>	4047438042093	cm cm cm l
	<p>Mx-CL-Sub-ANA-004-36 MOBOTIX CLOUD 3 Yearly Analytics Subscription, Camera 3 Yearly subscription for using the MOBOTIX CLOUD Analytics: Camera Tamper Detect • Cancellation possible at any time at the end of the subscription period.</p>	4047438046763	cm cm cm l

**Mx-CL-Sub-ANA-004-60****MOBOTIX CLOUD 5Y Analytics Subscription, Camera Tamper**

5 Yearly subscription for using the MOBOTIX CLOUD Analytics: Camera Tamper Detect • Cancellation possible at any time at the end of the subscription period.

4047438046770

g

cm

cm

cm

l

**Mx-CL-Sub-ANA-005-12****MOBOTIX CLOUD Yearly Analytics Subscription, Loitering**

Yearly subscription for using the MOBOTIX CLOUD Analytics: Loitering • Cancellation possible at any time at the end of the subscription period.

4047438042109

g

cm

cm

cm

l

**Mx-CL-Sub-ANA-005-36****MOBOTIX CLOUD 3 Yearly Analytics Subscription, Loitering**

3 Yearly subscription for using the MOBOTIX CLOUD Analytics: Loitering • Cancellation possible at any time at the end of the subscription period.

4047438046787

g

cm

cm

cm

l

**Mx-CL-Sub-ANA-005-60****MOBOTIX CLOUD 5 Yearly Analytics Subscription, Loitering**

5 Yearly subscription for using the MOBOTIX CLOUD Analytics: Loitering • Cancellation possible at any time at the end of the subscription period.

4047438046794

g

cm

cm

cm

l

**Mx-CL-Sub-ED001-1****1 Month MOBOTIX CLOUD Subscription, update to**

1 Month subscription for using the Account function of the Professional Edition in the MOBOTIX CLOUD • Independently from the amount of cameras • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment of subscription possible at any time at the end of the month

4047438048002

g

cm

cm

cm

l

**Mx-CL-Sub-ED001-12****MOBOTIX CLOUD Yearly Subscription, update to**

Yearly subscription for using the Account function of the Professional Edition in the MOBOTIX CLOUD • Independently from the amount of cameras • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

4047438048019







g







cm

cm

cm

l







	<p>Mx-CL-Sub-ED001-36</p> <p>3 Years MOBOTIX CLOUD Subscription, update to</p> <p>3 Years subscription for using the Account function of the Professional Edition in the MOBOTIX CLOUD • Independently from the amount of cameras • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	4047438048026	cm cm g cm l
	<p>Mx-CL-Sub-ED001-60</p> <p>5 Years MOBOTIX CLOUD Subscription, update to</p> <p>5 Years subscription for using the Account function of the Professional Edition in the MOBOTIX CLOUD • Independently from the amount of cameras • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	4047438048033	cm cm g cm l
	<p>Mx-CL-Sub-ED002-1</p> <p>1 Month MOBOTIX CLOUD Subscription, update to</p> <p>1 Month subscription for using the Account function of the Enterprise Edition in the MOBOTIX CLOUD • Independently from the amount of cameras • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment of subscription possible at any time at the end of the month.</p>	4047438048040	cm cm g cm l
	<p>Mx-CL-Sub-ED002-12</p> <p>MOBOTIX CLOUD Yearly Subscription, update to Enterprise</p> <p>Yearly subscription for using the Account function of the Enterprise Edition in the MOBOTIX CLOUD • Independently from the amount of cameras • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	4047438048057	cm cm g cm l
	<p>Mx-CL-Sub-ED002-36</p> <p>3 Years MOBOTIX CLOUD Subscription, update to Enterprise</p> <p>3 Years subscription for using the Account function of the Enterprise Edition in the MOBOTIX CLOUD • Independently from the amount of cameras • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	4047438048064	cm cm g cm l
	<p>Mx-CL-Sub-ED002-60</p> <p>5 Years MOBOTIX CLOUD Subscription, update to Enterprise</p> <p>5 Years subscription for using the Account function of the Enterprise Edition in the MOBOTIX CLOUD • Independently from the amount of cameras • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	4047438048071	cm cm g cm l







	<p>Mx-CL-Sub-HD1-D1095-12 MOBOTIX CLOUD Yearly Camera Subscription, 720p/1095 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 1095 days (automatic deletion afterwards) • Max. Resolution: 720p • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	<p>4047438041744</p>	<p>cm cm cm l</p>
	<p>Mx-CL-Sub-HD1-D1095-36 MOBOTIX CLOUD 3 Yearly Camera Subscription, 720p/1095 3 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 1095 days (automatic deletion afterwards) • Max. Resolution: 720p • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	<p>4047438045667</p>	<p>cm cm cm l</p>
	<p>Mx-CL-Sub-HD1-D1095-60 MOBOTIX CLOUD 5 Yearly Camera Subscription, 720p/1095 5 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 1095 days (automatic deletion afterwards) • Max. Resolution: 720p • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	<p>4047438045674</p>	<p>cm cm cm l</p>
	<p>Mx-CL-Sub-HD1-D14-12 MOBOTIX CLOUD Yearly Camera Subscription, 720p/14 Days Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 14 days (automatic deletion afterwards) • Max. Resolution: 720p • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	<p>4047438041676</p>	<p>cm cm cm l</p>
	<p>Mx-CL-Sub-HD1-D14-36 MOBOTIX CLOUD 3 Yearly Camera Subscription, 720p/14 3 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 14 days (automatic deletion afterwards) • Max. Resolution: 720p • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	<p>4047438045520</p>	<p>cm cm cm l</p>
	<p>Mx-CL-Sub-HD1-D14-60 MOBOTIX CLOUD 5 Yearly Camera Subscription, 720p/14 5 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 14 days (automatic deletion afterwards) • Max. Resolution: 720p • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	<p>4047438045537</p>	<p>cm cm cm l</p>







	<p>Mx-CL-Sub-HD1-D180-12</p> <p>MOBOTIX CLOUD Yearly Camera Subscription, 720p/180</p> <p>Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 180 days (automatic deletion afterwards) • Max. Resolution: 720p • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	4047438041713	cm cm cm l
	<p>Mx-CL-Sub-HD1-D180-36</p> <p>MOBOTIX CLOUD 3 Yearly Camera Subscription, 720p/180</p> <p>3 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 180 days (automatic deletion afterwards) • Max. Resolution: 720p • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	4047438045605	cm cm cm l
	<p>Mx-CL-Sub-HD1-D180-60</p> <p>MOBOTIX CLOUD 5 Yearly Camera Subscription, 720p/180</p> <p>5 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 180 days (automatic deletion afterwards) • Max. Resolution: 720p • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	4047438045612	cm cm cm l
	<p>Mx-CL-Sub-HD1-D1825-12</p> <p>MOBOTIX CLOUD Yearly Camera Subscription, 720p/1825</p> <p>Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 1825 days (automatic deletion afterwards) • Max. Resolution: 720p • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	4047438041751	cm cm cm l
	<p>Mx-CL-Sub-HD1-D1825-36</p> <p>MOBOTIX CLOUD 3 Yearly Camera Subscription, 720p/1825</p> <p>3 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 1825 days (automatic deletion afterwards) • Max. Resolution: 720p • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	4047438045681	cm cm cm l
	<p>Mx-CL-Sub-HD1-D1825-60</p> <p>MOBOTIX CLOUD 5 Yearly Camera Subscription, 720p/1825</p> <p>5 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 1825 days (automatic deletion afterwards) • Max. Resolution: 720p • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	4047438045698	cm cm cm l







	<p>Mx-CL-Sub-HD1-D30-12</p> <p>MOBOTIX CLOUD Yearly Camera Subscription, 720p/30 Days</p> <p>Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 30 days (automatic deletion afterwards) • Max. Resolution: 720p • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	4047438041683	cm cm cm l
	<p>Mx-CL-Sub-HD1-D30-36</p> <p>MOBOTIX CLOUD 3 Yearly Camera Subscription, 720p/30</p> <p>3 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 30 days (automatic deletion afterwards) • Max. Resolution: 720p • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	4047438045544	cm cm cm l
	<p>Mx-CL-Sub-HD1-D30-60</p> <p>MOBOTIX CLOUD 5 Yearly Camera Subscription, 720p/30</p> <p>5 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 30 days (automatic deletion afterwards) • Max. Resolution: 720p • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	4047438045551	cm cm cm l
	<p>Mx-CL-Sub-HD1-D365-12</p> <p>MOBOTIX CLOUD Yearly Camera Subscription, 720p/365</p> <p>Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 365 days (automatic deletion afterwards) • Max. Resolution: 720p • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	4047438041720	cm cm cm l
	<p>Mx-CL-Sub-HD1-D365-36</p> <p>MOBOTIX CLOUD 3 Yearly Camera Subscription, 720p/365</p> <p>3 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 365 days (automatic deletion afterwards) • Max. Resolution: 720p • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	4047438045629	cm cm cm l
	<p>Mx-CL-Sub-HD1-D365-60</p> <p>MOBOTIX CLOUD 5 Yearly Camera Subscription, 720p/365</p> <p>5 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 365 days (automatic deletion afterwards) • Max. Resolution: 720p • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	4047438045636	cm cm cm l

	<p>Mx-CL-Sub-HD1-D60-12 MOBOTIX CLOUD Yearly Camera Subscription, 720p/60 Days Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 60 days (automatic deletion afterwards) • Max. Resolution: 720p • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	4047438041690	cm cm cm l
	<p>Mx-CL-Sub-HD1-D60-36 MOBOTIX CLOUD 3 Yearly Camera Subscription, 720p/60 3 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 60 days (automatic deletion afterwards) • Max. Resolution: 720p • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	4047438045568	cm cm cm l
	<p>Mx-CL-Sub-HD1-D60-60 MOBOTIX CLOUD 5 Yearly Camera Subscription, 720p/60 5 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 60 days (automatic deletion afterwards) • Max. Resolution: 720p • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	4047438045575	cm cm cm l
	<p>Mx-CL-Sub-HD1-D7-12 MOBOTIX CLOUD Yearly Camera Subscription, 720p/7 Days Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 2/3/5 up to 7 days (automatic deletion afterwards) • Max. Resolution: 720p • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	4047438041669	cm cm cm l
	<p>Mx-CL-Sub-HD1-D7-36 MOBOTIX CLOUD 3 Yearly Camera Subscription, 720p/7 3 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 2/3/5 up to 7 days (automatic deletion afterwards) • Max. Resolution: 720p • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	4047438045506	cm cm cm l
	<p>Mx-CL-Sub-HD1-D7-60 MOBOTIX CLOUD 5 Yearly Camera Subscription, 720p/7 5 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 2/3/5 up to 7 days (automatic deletion afterwards) • Max. Resolution: 720p • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	4047438045513	cm cm cm l







	<p>Mx-CL-Sub-HD1-D730-12 MOBOTIX CLOUD Yearly Camera Subscription, 720p/730 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 730 days (automatic deletion afterwards) • Max. Resolution: 720p • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	<p>4047438041737</p>	<p>cm cm cm l</p>
	<p>Mx-CL-Sub-HD1-D730-36 MOBOTIX CLOUD 3 Yearly Camera Subscription, 720p/730 3 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 730 days (automatic deletion afterwards) • Max. Resolution: 720p • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	<p>4047438045643</p>	<p>cm cm cm l</p>
	<p>Mx-CL-Sub-HD1-D730-60 MOBOTIX CLOUD 5 Yearly Camera Subscription, 720p/730 5 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 730 days (automatic deletion afterwards) • Max. Resolution: 720p • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	<p>4047438045650</p>	<p>cm cm cm l</p>
	<p>Mx-CL-Sub-HD1-D90-12 MOBOTIX CLOUD Yearly Camera Subscription, 720p/90 Days Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 90 days (automatic deletion afterwards) • Max. Resolution: 720p • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	<p>4047438041706</p>	<p>cm cm cm l</p>
	<p>Mx-CL-Sub-HD1-D90-36 MOBOTIX CLOUD 3 Yearly Camera Subscription, 720p/90 3 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 90 days (automatic deletion afterwards) • Max. Resolution: 720p • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	<p>4047438045582</p>	<p>cm cm cm l</p>
	<p>Mx-CL-Sub-HD1-D90-60 MOBOTIX CLOUD 5 Yearly Camera Subscription, 720p/90 5 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 90 days (automatic deletion afterwards) • Max. Resolution: 720p • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	<p>4047438045599</p>	<p>cm cm cm l</p>







	<p>Mx-CL-Sub-HD10-D1095-12 MOBOTIX CLOUD Yearly Camera Subscription, 10MP/1095 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 1095 days (automatic deletion afterwards) • Max. Resolution: 10MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	<p>4047438042390</p>	<p>cm cm cm l</p>
	<p>Mx-CL-Sub-HD10-D1095-36 MOBOTIX CLOUD 3 Yearly Camera Subscription, 10MP/1095 3 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 1095 days (automatic deletion afterwards) • Max. Resolution: 10MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	<p>4047438046664</p>	<p>cm cm cm l</p>
	<p>Mx-CL-Sub-HD10-D1095-60 MOBOTIX CLOUD 5 Yearly Camera Subscription, 10MP/1095 5 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 1095 days (automatic deletion afterwards) • Max. Resolution: 10MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	<p>4047438046671</p>	<p>cm cm cm l</p>
	<p>Mx-CL-Sub-HD10-D14-12 MOBOTIX CLOUD Yearly Camera Subscription, 10MP/14 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 14 days (automatic deletion afterwards) • Max. Resolution: 10MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	<p>4047438042321</p>	<p>cm cm cm l</p>
	<p>Mx-CL-Sub-HD10-D14-36 MOBOTIX CLOUD 3 Yearly Camera Subscription, 10MP/14 3 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 14 days (automatic deletion afterwards) • Max. Resolution: 10MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	<p>4047438046527</p>	<p>cm cm cm l</p>
	<p>Mx-CL-Sub-HD10-D14-60 MOBOTIX CLOUD 5 Yearly Camera Subscription, 10MP/14 5 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 14 days (automatic deletion afterwards) • Max. Resolution: 10MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	<p>4047438046534</p>	<p>cm cm cm l</p>

	<p>Mx-CL-Sub-HD10-D180-12</p> <p>MOBOTIX CLOUD Yearly Camera Subscription, 10MP/180</p> <p>Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 180 days (automatic deletion afterwards) • Max. Resolution: 10MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	4047438042369	cm cm cm l
	<p>Mx-CL-Sub-HD10-D180-36</p> <p>MOBOTIX CLOUD 3 Yearly Camera Subscription, 10MP/180</p> <p>3 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 180 days (automatic deletion afterwards) • Max. Resolution: 10MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	4047438046602	cm cm cm l
	<p>Mx-CL-Sub-HD10-D180-60</p> <p>MOBOTIX CLOUD 5 Yearly Camera Subscription, 10MP/180</p> <p>5 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 180 days (automatic deletion afterwards) • Max. Resolution: 10MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	4047438046619	cm cm cm l
	<p>Mx-CL-Sub-HD10-D1825-12</p> <p>MOBOTIX CLOUD Yearly Camera Subscription, 10MP/1825</p> <p>Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 1825 days (automatic deletion afterwards) • Max. Resolution: 10MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	4047438042406	cm cm cm l
	<p>Mx-CL-Sub-HD10-D1825-36</p> <p>MOBOTIX CLOUD 3 Yearly Camera Subscription, 10MP/1825</p> <p>3 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 1825 days (automatic deletion afterwards) • Max. Resolution: 10MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	4047438046688	cm cm cm l
	<p>Mx-CL-Sub-HD10-D1825-60</p> <p>MOBOTIX CLOUD 5 Yearly Camera Subscription, 10MP/1825</p> <p>5 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 1825 days (automatic deletion afterwards) • Max. Resolution: 10MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	4047438046695	cm cm cm l

	<p>Mx-CL-Sub-HD10-D30-12 MOBOTIX CLOUD Yearly Camera Subscription, 10MP/30 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 30 days (automatic deletion afterwards) • Max. Resolution: 10MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	<p>4047438042338</p>	<p>cm cm cm l</p>
	<p>Mx-CL-Sub-HD10-D30-36 MOBOTIX CLOUD 3 Yearly Camera Subscription, 10MP/30 3 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 30 days (automatic deletion afterwards) • Max. Resolution: 10MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	<p>4047438046541</p>	<p>cm cm cm l</p>
	<p>Mx-CL-Sub-HD10-D30-60 MOBOTIX CLOUD 5 Yearly Camera Subscription, 10MP/30 5 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 30 days (automatic deletion afterwards) • Max. Resolution: 10MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	<p>4047438046558</p>	<p>cm cm cm l</p>
	<p>Mx-CL-Sub-HD10-D365-12 MOBOTIX CLOUD Yearly Camera Subscription, 10MP/365 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 365 days (automatic deletion afterwards) • Max. Resolution: 10MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	<p>4047438042376</p>	<p>cm cm cm l</p>
	<p>Mx-CL-Sub-HD10-D365-36 MOBOTIX CLOUD 3 Yearly Camera Subscription, 10MP/365 3 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 365 days (automatic deletion afterwards) • Max. Resolution: 10MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	<p>4047438046626</p>	<p>cm cm cm l</p>
	<p>Mx-CL-Sub-HD10-D365-60 MOBOTIX CLOUD 5 Yearly Camera Subscription, 10MP/365 5 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 365 days (automatic deletion afterwards) • Max. Resolution: 10MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	<p>4047438046633</p>	<p>cm cm cm l</p>

	<p>Mx-CL-Sub-HD10-D60-12</p> <p>MOBOTIX CLOUD Yearly Camera Subscription, 10MP/60</p> <p>Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 60 days (automatic deletion afterwards) • Max. Resolution: 10MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	4047438042345	cm cm cm l
	<p>Mx-CL-Sub-HD10-D60-36</p> <p>MOBOTIX CLOUD 3 Yearly Camera Subscription, 10MP/60</p> <p>3 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 60 days (automatic deletion afterwards) • Max. Resolution: 10MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	4047438046565	cm cm cm l
	<p>Mx-CL-Sub-HD10-D60-60</p> <p>MOBOTIX CLOUD 5 Yearly Camera Subscription, 10MP/60</p> <p>5 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 60 days (automatic deletion afterwards) • Max. Resolution: 10MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	4047438046572	cm cm cm l
	<p>Mx-CL-Sub-HD10-D7-12</p> <p>MOBOTIX CLOUD Yearly Camera Subscription, 10MP/7 Days</p> <p>Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 2/3/5 up to 7 days (automatic deletion afterwards) • Max. Resolution: 10MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	4047438042314	cm cm cm l
	<p>Mx-CL-Sub-HD10-D7-36</p> <p>MOBOTIX CLOUD 3 Yearly Camera Subscription, 10MP/7</p> <p>3 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 2/3/5 up to 7 days (automatic deletion afterwards) • Max. Resolution: 10MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	4047438046503	cm cm cm l
	<p>Mx-CL-Sub-HD10-D7-60</p> <p>MOBOTIX CLOUD 5 Yearly Camera Subscription, 10MP/7</p> <p>5 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 2/3/5 up to 7 days (automatic deletion afterwards) • Max. Resolution: 10MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	4047438046510	cm cm cm l

	<p>Mx-CL-Sub-HD10-D730-12 MOBOTIX CLOUD Yearly Camera Subscription, 10MP/730 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 730 days (automatic deletion afterwards) • Max. Resolution: 10MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	<p>4047438042383</p>	<p>cm cm cm l</p>
	<p>Mx-CL-Sub-HD10-D730-36 MOBOTIX CLOUD 3 Yearly Camera Subscription, 10MP/730 3 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 730 days (automatic deletion afterwards) • Max. Resolution: 10MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	<p>4047438046640</p>	<p>cm cm cm l</p>
	<p>Mx-CL-Sub-HD10-D730-60 MOBOTIX CLOUD 5 Yearly Camera Subscription, 10MP/730 5 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 730 days (automatic deletion afterwards) • Max. Resolution: 10MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	<p>4047438046657</p>	<p>cm cm cm l</p>
	<p>Mx-CL-Sub-HD10-D90-12 MOBOTIX CLOUD Yearly Camera Subscription, 10MP/90 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 90 days (automatic deletion afterwards) • Max. Resolution: 10MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	<p>4047438042352</p>	<p>cm cm cm l</p>
	<p>Mx-CL-Sub-HD10-D90-36 MOBOTIX CLOUD 3 Yearly Camera Subscription, 10MP/90 3 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 90 days (automatic deletion afterwards) • Max. Resolution: 10MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	<p>4047438046589</p>	<p>cm cm cm l</p>
	<p>Mx-CL-Sub-HD10-D90-60 MOBOTIX CLOUD 5 Yearly Camera Subscription, 10MP/90 5 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 90 days (automatic deletion afterwards) • Max. Resolution: 10MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	<p>4047438046596</p>	<p>cm cm cm l</p>

	<p>Mx-CL-Sub-HD15-D1095-1 MOBOTIX CLOUD Monthly Camera Subscription, 15MP/1095 Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 1095 days (automatic deletion afterwards) • Max. Resolution: 15MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	<p>4047438047128</p>	<p>cm cm cm l</p>
	<p>Mx-CL-Sub-HD15-D1095-12 MOBOTIX CLOUD 1 Yearly Camera Subscription, 15MP/1095 1 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 1095 days (automatic deletion afterwards) • Max. Resolution: 15MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	<p>4047438047135</p>	<p>cm cm cm l</p>
	<p>Mx-CL-Sub-HD15-D1095-36 MOBOTIX CLOUD 3 Yearly Camera Subscription, 15MP/1095 3 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 1095 days (automatic deletion afterwards) • Max. Resolution: 15MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	<p>4047438047142</p>	<p>cm cm cm l</p>
	<p>Mx-CL-Sub-HD15-D1095-60 MOBOTIX CLOUD 5 Yearly Camera Subscription, 15MP/1095 5 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 1095 days (automatic deletion afterwards) • Max. Resolution: 15MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	<p>4047438047159</p>	<p>cm cm cm l</p>
	<p>Mx-CL-Sub-HD15-D14-1 MOBOTIX CLOUD Monthly Camera Subscription, 15MP/14 Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 14 days (automatic deletion afterwards) • Max. Resolution: 15MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	<p>4047438046848</p>	<p>cm cm cm l</p>
	<p>Mx-CL-Sub-HD15-D14-12 MOBOTIX CLOUD 1 Yearly Camera Subscription, 15MP/14 1 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 14 days (automatic deletion afterwards) • Max. Resolution: 15MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	<p>4047438046855</p>	<p>cm cm cm l</p>

**Mx-CL-Sub-HD15-D14-36**

4047438046862 cm

MOBOTIX CLOUD 3 Yearly Camera Subscription, 15MP/14

3 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 14 days (automatic deletion afterwards) • Max. Resolution: 15MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g cm l

**Mx-CL-Sub-HD15-D14-60**

4047438046879 cm

MOBOTIX CLOUD 5 Yearly Camera Subscription, 15MP/14

5 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 14 days (automatic deletion afterwards) • Max. Resolution: 15MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g cm l

**Mx-CL-Sub-HD15-D180-1**

4047438047005 cm

MOBOTIX CLOUD Monthly Camera Subscription, 15MP/180

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 180 days (automatic deletion afterwards) • Max. Resolution: 15MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g cm l

**Mx-CL-Sub-HD15-D180-12**

4047438047012 cm

MOBOTIX CLOUD 1 Yearly Camera Subscription, 15MP/180

1 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 180 days (automatic deletion afterwards) • Max. Resolution: 15MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g cm l

**Mx-CL-Sub-HD15-D180-36**

4047438047029 cm

MOBOTIX CLOUD 3 Yearly Camera Subscription, 15MP/180

3 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 180 days (automatic deletion afterwards) • Max. Resolution: 15MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g cm l







**Mx-CL-Sub-HD15-D180-60**







4047438047036 cm







MOBOTIX CLOUD 5 Yearly Camera Subscription, 15MP/180







5 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 180 days (automatic deletion afterwards) • Max. Resolution: 15MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g cm l







	<p>Mx-CL-Sub-HD15-D1825-1 MOBOTIX CLOUD Monthly Camera Subscription, 15MP/1825 Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 1825 days (automatic deletion afterwards) • Max. Resolution: 15MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	<p>4047438047166</p>	<p>cm cm cm l</p>
	<p>Mx-CL-Sub-HD15-D1825-12 MOBOTIX CLOUD 1 Yearly Camera Subscription, 15MP/1825 1 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 1825 days (automatic deletion afterwards) • Max. Resolution: 15MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	<p>4047438047173</p>	<p>cm cm cm l</p>
	<p>Mx-CL-Sub-HD15-D1825-36 MOBOTIX CLOUD 3 Yearly Camera Subscription, 15MP/1825 3 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 1825 days (automatic deletion afterwards) • Max. Resolution: 15MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	<p>4047438047180</p>	<p>cm cm cm l</p>
	<p>Mx-CL-Sub-HD15-D1825-60 MOBOTIX CLOUD 5 Yearly Camera Subscription, 15MP/1825 5 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 1825 days (automatic deletion afterwards) • Max. Resolution: 15MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	<p>4047438047197</p>	<p>cm cm cm l</p>
	<p>Mx-CL-Sub-HD15-D30-1 MOBOTIX CLOUD Monthly Camera Subscription, 15MP/30 Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 30 days (automatic deletion afterwards) • Max. Resolution: 15MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	<p>4047438046886</p>	<p>cm cm cm l</p>
	<p>Mx-CL-Sub-HD15-D30-12 MOBOTIX CLOUD 1 Yearly Camera Subscription, 15MP/30 1 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 30 days (automatic deletion afterwards) • Max. Resolution: 15MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	<p>4047438046893</p>	<p>cm cm cm l</p>

	<p>Mx-CL-Sub-HD15-D30-36 MOBOTIX CLOUD 3 Yearly Camera Subscription, 15MP/30 3 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 30 days (automatic deletion afterwards) • Max. Resolution: 15MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	4047438046909	cm cm cm l
	<p>Mx-CL-Sub-HD15-D30-60 MOBOTIX CLOUD 5 Yearly Camera Subscription, 15MP/30 5 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 30 days (automatic deletion afterwards) • Max. Resolution: 15MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	4047438046916	cm cm cm l
	<p>Mx-CL-Sub-HD15-D365-1 MOBOTIX CLOUD Monthly Camera Subscription, 15MP/365 Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 365 days (automatic deletion afterwards) • Max. Resolution: 15MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	4047438047043	cm cm cm l
	<p>Mx-CL-Sub-HD15-D365-12 MOBOTIX CLOUD 1 Yearly Camera Subscription, 15MP/365 1 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 365 days (automatic deletion afterwards) • Max. Resolution: 15MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	4047438047050	cm cm cm l
	<p>Mx-CL-Sub-HD15-D365-36 MOBOTIX CLOUD 3 Yearly Camera Subscription, 15MP/365 3 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 365 days (automatic deletion afterwards) • Max. Resolution: 15MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	4047438047067	cm cm cm l
	<p>Mx-CL-Sub-HD15-D365-60 MOBOTIX CLOUD 5 Yearly Camera Subscription, 15MP/365 5 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 365 days (automatic deletion afterwards) • Max. Resolution: 15MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	4047438047074	cm cm cm l







	<p>Mx-CL-Sub-HD15-D60-1 MOBOTIX CLOUD Monthly Camera Subscription, 15MP/60 Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 60 days (automatic deletion afterwards) • Max. Resolution: 15MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	<p>4047438046923</p>	<p>cm cm cm l</p>
	<p>Mx-CL-Sub-HD15-D60-12 MOBOTIX CLOUD 1 Yearly Camera Subscription, 15MP/60 1 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 60 days (automatic deletion afterwards) • Max. Resolution: 15MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	<p>4047438046930</p>	<p>cm cm cm l</p>
	<p>Mx-CL-Sub-HD15-D60-36 MOBOTIX CLOUD 3 Yearly Camera Subscription, 15MP/60 3 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 60 days (automatic deletion afterwards) • Max. Resolution: 15MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	<p>4047438046947</p>	<p>cm cm cm l</p>
	<p>Mx-CL-Sub-HD15-D60-60 MOBOTIX CLOUD 5 Yearly Camera Subscription, 15MP/60 5 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 60 days (automatic deletion afterwards) • Max. Resolution: 15MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	<p>4047438046954</p>	<p>cm cm cm l</p>
	<p>Mx-CL-Sub-HD15-D7-1 MOBOTIX CLOUD Monthly Camera Subscription, 15MP/7 Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 2/3/5 up to 7 days (automatic deletion afterwards) • Max. Resolution: 15MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	<p>4047438046800</p>	<p>cm cm cm l</p>
	<p>Mx-CL-Sub-HD15-D7-12 MOBOTIX CLOUD 1 Yearly Camera Subscription, 15MP/7 1 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 2/3/5 up to 7 days (automatic deletion afterwards) • Max. Resolution: 15MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	<p>4047438046817</p>	<p>cm cm cm l</p>







	<p>Mx-CL-Sub-HD15-D7-36</p> <p>MOBOTIX CLOUD 3 Yearly Camera Subscription, 15MP/7</p> <p>3 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 2/3/5 up to 7 days (automatic deletion afterwards) • Max. Resolution: 15MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	4047438046824	cm cm cm l
	<p>Mx-CL-Sub-HD15-D7-60</p> <p>MOBOTIX CLOUD 5 Yearly Camera Subscription, 15MP/7</p> <p>5 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 2/3/5 up to 7 days (automatic deletion afterwards) • Max. Resolution: 15MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	4047438046831	cm cm cm l
	<p>Mx-CL-Sub-HD15-D730-1</p> <p>MOBOTIX CLOUD Monthly Camera Subscription, 15MP/730</p> <p>Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 730 days (automatic deletion afterwards) • Max. Resolution: 15MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	4047438047081	cm cm cm l
	<p>Mx-CL-Sub-HD15-D730-12</p> <p>MOBOTIX CLOUD 1 Yearly Camera Subscription, 15MP/730</p> <p>1 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 730 days (automatic deletion afterwards) • Max. Resolution: 15MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	4047438047098	cm cm cm l
	<p>Mx-CL-Sub-HD15-D730-36</p> <p>MOBOTIX CLOUD 3 Yearly Camera Subscription, 15MP/730</p> <p>3 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 730 days (automatic deletion afterwards) • Max. Resolution: 15MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	4047438047104	cm cm cm l
	<p>Mx-CL-Sub-HD15-D730-60</p> <p>MOBOTIX CLOUD 5 Yearly Camera Subscription, 15MP/730</p> <p>5 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 730 days (automatic deletion afterwards) • Max. Resolution: 15MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	4047438047111	cm cm cm l

	<p>Mx-CL-Sub-HD15-D90-1</p> <p>MOBOTIX CLOUD Monthly Camera Subscription, 15MP/90</p> <p>Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 90 days (automatic deletion afterwards) • Max. Resolution: 15MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	4047438046961	cm cm cm l
	<p>Mx-CL-Sub-HD15-D90-12</p> <p>MOBOTIX CLOUD 1 Yearly Camera Subscription, 15MP/90</p> <p>1 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 90 days (automatic deletion afterwards) • Max. Resolution: 15MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	4047438046978	cm cm cm l
	<p>Mx-CL-Sub-HD15-D90-36</p> <p>MOBOTIX CLOUD 3 Yearly Camera Subscription, 15MP/90</p> <p>3 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 90 days (automatic deletion afterwards) • Max. Resolution: 15MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	4047438046985	cm cm cm l
	<p>Mx-CL-Sub-HD15-D90-60</p> <p>MOBOTIX CLOUD 5 Yearly Camera Subscription, 15MP/90</p> <p>5 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 90 days (automatic deletion afterwards) • Max. Resolution: 15MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	4047438046992	cm cm cm l
	<p>Mx-CL-Sub-HD2-D1095-12</p> <p>MOBOTIX CLOUD Yearly Camera Subscription, 1080p/1095</p> <p>Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 1095 days (automatic deletion afterwards) • Max. Resolution: 1080p • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	4047438041843	cm cm cm l
	<p>Mx-CL-Sub-HD2-D1095-36</p> <p>MOBOTIX CLOUD 3 Yearly Camera Subscription, 1080p/1095</p> <p>3 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 1095 days (automatic deletion afterwards) • Max. Resolution: 1080p • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	4047438045865	cm cm cm l







	<p>Mx-CL-Sub-HD2-D1095-60 MOBOTIX CLOUD 5 Yearly Camera Subscription, 1080p/1095 5 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 1095 days (automatic deletion afterwards) • Max. Resolution: 1080p • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	4047438045872	cm
		g	cm
			l
	<p>Mx-CL-Sub-HD2-D14-12 MOBOTIX CLOUD Yearly Camera Subscription, 1080p/14 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 14 days (automatic deletion afterwards) • Max. Resolution: 1080p • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	4047438041775	cm
		g	cm
			l
	<p>Mx-CL-Sub-HD2-D14-36 MOBOTIX CLOUD 3 Yearly Camera Subscription, 1080p/14 3 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 14 days (automatic deletion afterwards) • Max. Resolution: 1080p • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	4047438045728	cm
		g	cm
			l
	<p>Mx-CL-Sub-HD2-D14-60 MOBOTIX CLOUD 5 Yearly Camera Subscription, 1080p/14 5 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 14 days (automatic deletion afterwards) • Max. Resolution: 1080p • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	4047438045735	cm
		g	cm
			l
	<p>Mx-CL-Sub-HD2-D180-12 MOBOTIX CLOUD Yearly Camera Subscription, 1080p/180 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 180 days (automatic deletion afterwards) • Max. Resolution: 1080p • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	4047438041812	cm
		g	cm
			l
	<p>Mx-CL-Sub-HD2-D180-36 MOBOTIX CLOUD 3 Yearly Camera Subscription, 1080p/180 3 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 180 days (automatic deletion afterwards) • Max. Resolution: 1080p • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	4047438045803	cm
		g	cm
			l







	<p>Mx-CL-Sub-HD2-D180-60</p> <p>MOBOTIX CLOUD 5 Yearly Camera Subscription, 1080p/180</p> <p>5 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 180 days (automatic deletion afterwards) • Max. Resolution: 1080p • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	4047438045810	cm cm cm l
	<p>Mx-CL-Sub-HD2-D1825-12</p> <p>MOBOTIX CLOUD Yearly Camera Subscription, 1080p/1825</p> <p>Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 1825 days (automatic deletion afterwards) • Max. Resolution: 1080p • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	4047438041850	cm cm cm l
	<p>Mx-CL-Sub-HD2-D1825-36</p> <p>MOBOTIX CLOUD 3 Yearly Camera Subscription, 1080p/1825</p> <p>3 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 1825 days (automatic deletion afterwards) • Max. Resolution: 1080p • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	4047438045889	cm cm cm l
	<p>Mx-CL-Sub-HD2-D1825-60</p> <p>MOBOTIX CLOUD 5 Yearly Camera Subscription, 1080p/1825</p> <p>5 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 1825 days (automatic deletion afterwards) • Max. Resolution: 1080p • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	4047438045896	cm cm cm l
	<p>Mx-CL-Sub-HD2-D30-12</p> <p>MOBOTIX CLOUD Yearly Camera Subscription, 1080p/30</p> <p>Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 30 days (automatic deletion afterwards) • Max. Resolution: 1080p • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	4047438041782	cm cm cm l
	<p>Mx-CL-Sub-HD2-D30-36</p> <p>MOBOTIX CLOUD 3 Yearly Camera Subscription, 1080p/30</p> <p>3 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 30 days (automatic deletion afterwards) • Max. Resolution: 1080p • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	4047438045742	cm cm cm l







	<p>Mx-CL-Sub-HD2-D30-60 MOBOTIX CLOUD 5 Yearly Camera Subscription, 1080p/30 5 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 30 days (automatic deletion afterwards) • Max. Resolution: 1080p • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	4047438045759	cm cm cm l
	<p>Mx-CL-Sub-HD2-D365-12 MOBOTIX CLOUD Yearly Camera Subscription, 1080p/365 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 365 days (automatic deletion afterwards) • Max. Resolution: 1080p • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	4047438041829	cm cm cm l
	<p>Mx-CL-Sub-HD2-D365-36 MOBOTIX CLOUD 3 Yearly Camera Subscription, 1080p/365 3 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 365 days (automatic deletion afterwards) • Max. Resolution: 1080p • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	4047438045827	cm cm cm l
	<p>Mx-CL-Sub-HD2-D365-60 MOBOTIX CLOUD 5 Yearly Camera Subscription, 1080p/365 5 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 365 days (automatic deletion afterwards) • Max. Resolution: 1080p • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	4047438045834	cm cm cm l
	<p>Mx-CL-Sub-HD2-D60-12 MOBOTIX CLOUD Yearly Camera Subscription, 1080p/60 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 60 days (automatic deletion afterwards) • Max. Resolution: 1080p • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	4047438041799	cm cm cm l
	<p>Mx-CL-Sub-HD2-D60-36 MOBOTIX CLOUD 3 Yearly Camera Subscription, 1080p/60 3 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 60 days (automatic deletion afterwards) • Max. Resolution: 1080p • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	4047438045766	cm cm cm l







	<p>Mx-CL-Sub-HD2-D60-60 MOBOTIX CLOUD 5 Yearly Camera Subscription, 1080p/60 5 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 60 days (automatic deletion afterwards) • Max. Resolution: 1080p • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	<p>4047438045773</p>	<p>cm cm g cm l</p>
	<p>Mx-CL-Sub-HD2-D7-12 MOBOTIX CLOUD Yearly Camera Subscription, 1080p/7 Days Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 2/3/5 up to 7 days (automatic deletion afterwards) • Max. Resolution: 1080p • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	<p>4047438041768</p>	<p>cm cm g cm l</p>
	<p>Mx-CL-Sub-HD2-D7-36 MOBOTIX CLOUD 3 Yearly Camera Subscription, 1080p/7 3 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 2/3/5 up to 7 days (automatic deletion afterwards) • Max. Resolution: 1080p • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	<p>4047438045704</p>	<p>cm cm g cm l</p>
	<p>Mx-CL-Sub-HD2-D7-60 MOBOTIX CLOUD 5 Yearly Camera Subscription, 1080p/7 5 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 2/3/5 up to 7 days (automatic deletion afterwards) • Max. Resolution: 1080p • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	<p>4047438045711</p>	<p>cm cm g cm l</p>
	<p>Mx-CL-Sub-HD2-D730-12 MOBOTIX CLOUD Yearly Camera Subscription, 1080p/730 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 730 days (automatic deletion afterwards) • Max. Resolution: 1080p • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	<p>4047438041836</p>	<p>cm cm g cm l</p>
	<p>Mx-CL-Sub-HD2-D730-36 MOBOTIX CLOUD 3 Yearly Camera Subscription, 1080p/730 3 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 730 days (automatic deletion afterwards) • Max. Resolution: 1080p • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	<p>4047438045841</p>	<p>cm cm g cm l</p>







	<p>Mx-CL-Sub-HD2-D730-60</p> <p>MOBOTIX CLOUD 5 Yearly Camera Subscription, 1080p/730</p> <p>5 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 730 days (automatic deletion afterwards) • Max. Resolution: 1080p • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	4047438045858	cm
		g	cm
			l
	<p>Mx-CL-Sub-HD2-D90-12</p> <p>MOBOTIX CLOUD Yearly Camera Subscription, 1080p/90</p> <p>Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 90 days (automatic deletion afterwards) • Max. Resolution: 1080p • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	4047438041805	cm
		g	cm
			l
	<p>Mx-CL-Sub-HD2-D90-36</p> <p>MOBOTIX CLOUD 3 Yearly Camera Subscription, 1080p/90</p> <p>3 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 90 days (automatic deletion afterwards) • Max. Resolution: 1080p • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	4047438045780	cm
		g	cm
			l
	<p>Mx-CL-Sub-HD2-D90-60</p> <p>MOBOTIX CLOUD 5 Yearly Camera Subscription, 1080p/90</p> <p>5 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 90 days (automatic deletion afterwards) • Max. Resolution: 1080p • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	4047438045797	cm
		g	cm
			l
	<p>Mx-CL-Sub-HD3-D1095-12</p> <p>MOBOTIX CLOUD Yearly Camera Subscription, 3MP/1095</p> <p>Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 1095 days (automatic deletion afterwards) • Max. Resolution: 3MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	4047438041942	cm
		g	cm
			l
	<p>Mx-CL-Sub-HD3-D1095-36</p> <p>MOBOTIX CLOUD 3 Yearly Camera Subscription, 3MP/1095</p> <p>3 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 1095 days (automatic deletion afterwards) • Max. Resolution: 3MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	4047438046060	cm
		g	cm
			l







	<p>Mx-CL-Sub-HD3-D1095-60 MOBOTIX CLOUD 5 Yearly Camera Subscription, 3MP/1095 5 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 1095 days (automatic deletion afterwards) • Max. Resolution: 3MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	4047438046077	cm cm cm l
	<p>Mx-CL-Sub-HD3-D14-12 MOBOTIX CLOUD Yearly Camera Subscription, 3MP/14 Days Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 14 days (automatic deletion afterwards) • Max. Resolution: 3MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	4047438041874	cm cm cm l
	<p>Mx-CL-Sub-HD3-D14-36 MOBOTIX CLOUD 3 Yearly Camera Subscription, 3MP/14 3 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 14 days (automatic deletion afterwards) • Max. Resolution: 3MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	4047438045926	cm cm cm l
	<p>Mx-CL-Sub-HD3-D14-60 MOBOTIX CLOUD 5 Yearly Camera Subscription, 3MP/14 5 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 14 days (automatic deletion afterwards) • Max. Resolution: 3MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	4047438045933	cm cm cm l
	<p>Mx-CL-Sub-HD3-D180-12 MOBOTIX CLOUD Yearly Camera Subscription, 3MP/180 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 180 days (automatic deletion afterwards) • Max. Resolution: 3MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	4047438041911	cm cm cm l
	<p>Mx-CL-Sub-HD3-D180-36 MOBOTIX CLOUD 3 Yearly Camera Subscription, 3MP/180 3 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 180 days (automatic deletion afterwards) • Max. Resolution: 3MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	4047438046008	cm cm cm l







	<p>Mx-CL-Sub-HD3-D180-60 MOBOTIX CLOUD 5 Yearly Camera Subscription, 3MP/180 5 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 180 days (automatic deletion afterwards) • Max. Resolution: 3MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	4047438046015	cm
		g	cm
			l
	<p>Mx-CL-Sub-HD3-D1825-12 MOBOTIX CLOUD Yearly Camera Subscription, 3MP/1825 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 1825 days (automatic deletion afterwards) • Max. Resolution: 3MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	4047438041959	cm
		g	cm
			l
	<p>Mx-CL-Sub-HD3-D1825-36 MOBOTIX CLOUD 3 Yearly Camera Subscription, 3MP/1825 3 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 1825 days (automatic deletion afterwards) • Max. Resolution: 3MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	4047438046084	cm
		g	cm
			l
	<p>Mx-CL-Sub-HD3-D1825-60 MOBOTIX CLOUD 5 Yearly Camera Subscription, 3MP/1825 5 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 1825 days (automatic deletion afterwards) • Max. Resolution: 3MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	4047438046091	cm
		g	cm
			l
	<p>Mx-CL-Sub-HD3-D30-12 MOBOTIX CLOUD Yearly Camera Subscription, 3MP/30 Days Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 30 days (automatic deletion afterwards) • Max. Resolution: 3MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	4047438041881	cm
		g	cm
			l
	<p>Mx-CL-Sub-HD3-D30-36 MOBOTIX CLOUD 3 Yearly Camera Subscription, 3MP/30 3 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 30 days (automatic deletion afterwards) • Max. Resolution: 3MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	4047438045940	cm
		g	cm
			l







	<p>Mx-CL-Sub-HD3-D30-60</p> <p>MOBOTIX CLOUD 5 Yearly Camera Subscription, 3MP/30</p> <p>5 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 30 days (automatic deletion afterwards) • Max. Resolution: 3MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	4047438045957	cm cm cm l
	<p>Mx-CL-Sub-HD3-D365-12</p> <p>MOBOTIX CLOUD Yearly Camera Subscription, 3MP/365</p> <p>Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 365 days (automatic deletion afterwards) • Max. Resolution: 3MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	4047438041928	cm cm cm l
	<p>Mx-CL-Sub-HD3-D365-36</p> <p>MOBOTIX CLOUD 3 Yearly Camera Subscription, 3MP/365</p> <p>3 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 365 days (automatic deletion afterwards) • Max. Resolution: 3MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	4047438046022	cm cm cm l
	<p>Mx-CL-Sub-HD3-D365-60</p> <p>MOBOTIX CLOUD 5 Yearly Camera Subscription, 3MP/365</p> <p>5 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 365 days (automatic deletion afterwards) • Max. Resolution: 3MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	4047438046039	cm cm cm l
	<p>Mx-CL-Sub-HD3-D60-12</p> <p>MOBOTIX CLOUD Yearly Camera Subscription, 3MP/60 Days</p> <p>Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 60 days (automatic deletion afterwards) • Max. Resolution: 3MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	4047438041898	cm cm cm l
	<p>Mx-CL-Sub-HD3-D60-36</p> <p>MOBOTIX CLOUD 3 Yearly Camera Subscription, 3MP/60</p> <p>3 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 60 days (automatic deletion afterwards) • Max. Resolution: 3MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	4047438045964	cm cm cm l







	<p>Mx-CL-Sub-HD3-D60-60</p> <p>MOBOTIX CLOUD 5 Yearly Camera Subscription, 3MP/60</p> <p>5 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 60 days (automatic deletion afterwards) • Max. Resolution: 3MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	4047438045971	cm cm cm l
	<p>Mx-CL-Sub-HD3-D7-12</p> <p>MOBOTIX CLOUD Yearly Camera Subscription, 3MP/7 Days</p> <p>Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 2/3/5 up to 7 days (automatic deletion afterwards) • Max. Resolution: 3MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	4047438041867	cm cm cm l
	<p>Mx-CL-Sub-HD3-D7-36</p> <p>MOBOTIX CLOUD 3 Yearly Camera Subscription, 3MP/7 Days</p> <p>3 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 2/3/5 up to 7 days (automatic deletion afterwards) • Max. Resolution: 3MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	4047438045902	cm cm cm l
	<p>Mx-CL-Sub-HD3-D7-60</p> <p>MOBOTIX CLOUD 5 Yearly Camera Subscription, 3MP/7 Days</p> <p>5 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 2/3/5 up to 7 days (automatic deletion afterwards) • Max. Resolution: 3MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	4047438045919	cm cm cm l
	<p>Mx-CL-Sub-HD3-D730-12</p> <p>MOBOTIX CLOUD Yearly Camera Subscription, 3MP/730</p> <p>Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 730 days (automatic deletion afterwards) • Max. Resolution: 3MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	4047438041935	cm cm cm l
	<p>Mx-CL-Sub-HD3-D730-36</p> <p>MOBOTIX CLOUD 3 Yearly Camera Subscription, 3MP/730</p> <p>3 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 730 days (automatic deletion afterwards) • Max. Resolution: 3MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	4047438046046	cm cm cm l







	<p>Mx-CL-Sub-HD3-D730-60 MOBOTIX CLOUD 5 Yearly Camera Subscription, 3MP/730 5 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 730 days (automatic deletion afterwards) • Max. Resolution: 3MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	4047438046053	cm cm g cm l
	<p>Mx-CL-Sub-HD3-D90-12 MOBOTIX CLOUD Yearly Camera Subscription, 3MP/90 Days Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 90 days (automatic deletion afterwards) • Max. Resolution: 3MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	4047438041904	cm cm g cm l
	<p>Mx-CL-Sub-HD3-D90-36 MOBOTIX CLOUD 3 Yearly Camera Subscription, 3MP/90 3 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 90 days (automatic deletion afterwards) • Max. Resolution: 3MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	4047438045988	cm cm g cm l
	<p>Mx-CL-Sub-HD3-D90-60 MOBOTIX CLOUD 5 Yearly Camera Subscription, 3MP/90 5 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 90 days (automatic deletion afterwards) • Max. Resolution: 3MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	4047438045995	cm cm g cm l
	<p>Mx-CL-Sub-HD4-D1095-12 MOBOTIX CLOUD Yearly Camera Subscription, 4MP/1095 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 1095 days (automatic deletion afterwards) • Max. Resolution: 4MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	4047438042192	cm cm g cm l
	<p>Mx-CL-Sub-HD4-D1095-36 MOBOTIX CLOUD 3 Yearly Camera Subscription, 4MP/1095 3 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 1095 days (automatic deletion afterwards) • Max. Resolution: 4MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	4047438046268	cm cm g cm l

	<p>Mx-CL-Sub-HD4-D1095-60 MOBOTIX CLOUD 5 Yearly Camera Subscription, 4MP/1095 5 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 1095 days (automatic deletion afterwards) • Max. Resolution: 4MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	4047438046275	cm cm cm l
	<p>Mx-CL-Sub-HD4-D14-12 MOBOTIX CLOUD Yearly Camera Subscription, 4MP/14 Days Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 14 days (automatic deletion afterwards) • Max. Resolution: 4MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	4047438042123	cm cm cm l
	<p>Mx-CL-Sub-HD4-D14-36 MOBOTIX CLOUD 3 Yearly Camera Subscription, 4MP/14 3 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 14 days (automatic deletion afterwards) • Max. Resolution: 4MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	4047438046121	cm cm cm l
	<p>Mx-CL-Sub-HD4-D14-60 MOBOTIX CLOUD 5 Yearly Camera Subscription, 4MP/14 5 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 14 days (automatic deletion afterwards) • Max. Resolution: 4MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	4047438046138	cm cm cm l
	<p>Mx-CL-Sub-HD4-D180-12 MOBOTIX CLOUD Yearly Camera Subscription, 4MP/180 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 180 days (automatic deletion afterwards) • Max. Resolution: 4MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	4047438042161	cm cm cm l
	<p>Mx-CL-Sub-HD4-D180-36 MOBOTIX CLOUD 3 Yearly Camera Subscription, 4MP/180 3 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 180 days (automatic deletion afterwards) • Max. Resolution: 4MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	4047438046206	cm cm cm l







	<p>Mx-CL-Sub-HD4-D180-60</p> <p>MOBOTIX CLOUD 5 Yearly Camera Subscription, 4MP/180</p> <p>5 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 180 days (automatic deletion afterwards) • Max. Resolution: 4MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	4047438046213	cm cm cm l
	<p>Mx-CL-Sub-HD4-D1825-12</p> <p>MOBOTIX CLOUD Yearly Camera Subscription, 4MP/1825</p> <p>Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 1825 days (automatic deletion afterwards) • Max. Resolution: 4MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	4047438042208	cm cm cm l
	<p>Mx-CL-Sub-HD4-D1825-36</p> <p>MOBOTIX CLOUD 3 Yearly Camera Subscription, 4MP/1825</p> <p>3 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 1825 days (automatic deletion afterwards) • Max. Resolution: 4MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	4047438046282	cm cm cm l
	<p>Mx-CL-Sub-HD4-D1825-60</p> <p>MOBOTIX CLOUD 5 Yearly Camera Subscription, 4MP/1825</p> <p>5 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 1825 days (automatic deletion afterwards) • Max. Resolution: 4MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	4047438046299	cm cm cm l
	<p>Mx-CL-Sub-HD4-D30-12</p> <p>MOBOTIX CLOUD Yearly Camera Subscription, 4MP/30 Days</p> <p>Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 30 days (automatic deletion afterwards) • Max. Resolution: 4MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	4047438042130	cm cm cm l
	<p>Mx-CL-Sub-HD4-D30-36</p> <p>MOBOTIX CLOUD 3 Yearly Camera Subscription, 4MP/30</p> <p>3 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 30 days (automatic deletion afterwards) • Max. Resolution: 4MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	4047438046145	cm cm cm l







	<p>Mx-CL-Sub-HD4-D30-60</p> <p>MOBOTIX CLOUD 5 Yearly Camera Subscription, 4MP/30</p> <p>5 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 30 days (automatic deletion afterwards) • Max. Resolution: 4MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	4047438046152	cm cm cm l
	<p>Mx-CL-Sub-HD4-D365-12</p> <p>MOBOTIX CLOUD Yearly Camera Subscription, 4MP/365</p> <p>Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 365 days (automatic deletion afterwards) • Max. Resolution: 4MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	4047438042178	cm cm cm l
	<p>Mx-CL-Sub-HD4-D365-36</p> <p>MOBOTIX CLOUD 3 Yearly Camera Subscription, 4MP/365</p> <p>3 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 365 days (automatic deletion afterwards) • Max. Resolution: 4MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	4047438046220	cm cm cm l
	<p>Mx-CL-Sub-HD4-D365-60</p> <p>MOBOTIX CLOUD 5 Yearly Camera Subscription, 4MP/365</p> <p>5 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 365 days (automatic deletion afterwards) • Max. Resolution: 4MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	4047438046237	cm cm cm l
	<p>Mx-CL-Sub-HD4-D60-12</p> <p>MOBOTIX CLOUD Yearly Camera Subscription, 4MP/60 Days</p> <p>Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 60 days (automatic deletion afterwards) • Max. Resolution: 4MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	4047438042147	cm cm cm l
	<p>Mx-CL-Sub-HD4-D60-36</p> <p>MOBOTIX CLOUD 3 Yearly Camera Subscription, 4MP/60</p> <p>3 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 60 days (automatic deletion afterwards) • Max. Resolution: 4MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	4047438046169	cm cm cm l







	<p>Mx-CL-Sub-HD4-D60-60</p> <p>MOBOTIX CLOUD 5 Yearly Camera Subscription, 4MP/60</p> <p>5 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 60 days (automatic deletion afterwards) • Max. Resolution: 4MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	4047438046176	cm cm cm l
	<p>Mx-CL-Sub-HD4-D7-12</p> <p>MOBOTIX CLOUD Yearly Camera Subscription, 4MP/7 Days</p> <p>Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 2/3/5 up to 7 days (automatic deletion afterwards) • Max. Resolution: 4MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	4047438042116	cm cm cm l
	<p>Mx-CL-Sub-HD4-D7-36</p> <p>MOBOTIX CLOUD 3 Yearly Camera Subscription, 4MP/7 Days</p> <p>3 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 2/3/5 up to 7 days (automatic deletion afterwards) • Max. Resolution: 4MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	4047438046107	cm cm cm l
	<p>Mx-CL-Sub-HD4-D7-60</p> <p>MOBOTIX CLOUD 5 Yearly Camera Subscription, 4MP/7 Days</p> <p>5 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 2/3/5 up to 7 days (automatic deletion afterwards) • Max. Resolution: 4MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	4047438046114	cm cm cm l
	<p>Mx-CL-Sub-HD4-D730-12</p> <p>MOBOTIX CLOUD Yearly Camera Subscription, 4MP/730</p> <p>Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 730 days (automatic deletion afterwards) • Max. Resolution: 4MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	4047438042185	cm cm cm l
	<p>Mx-CL-Sub-HD4-D730-36</p> <p>MOBOTIX CLOUD 3 Yearly Camera Subscription, 4MP/730</p> <p>3 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 730 days (automatic deletion afterwards) • Max. Resolution: 4MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	4047438046244	cm cm cm l







	<p>Mx-CL-Sub-HD4-D730-60</p> <p>MOBOTIX CLOUD 5 Yearly Camera Subscription, 4MP/730</p> <p>5 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 730 days (automatic deletion afterwards) • Max. Resolution: 4MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	4047438046251	cm
		g	cm
			l
	<p>Mx-CL-Sub-HD4-D90-12</p> <p>MOBOTIX CLOUD Yearly Camera Subscription, 4MP/90 Days</p> <p>Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 90 days (automatic deletion afterwards) • Max. Resolution: 4MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	4047438042154	cm
		g	cm
			l
	<p>Mx-CL-Sub-HD4-D90-36</p> <p>MOBOTIX CLOUD 3 Yearly Camera Subscription, 4MP/90</p> <p>3 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 90 days (automatic deletion afterwards) • Max. Resolution: 4MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	4047438046183	cm
		g	cm
			l
	<p>Mx-CL-Sub-HD4-D90-60</p> <p>MOBOTIX CLOUD 5 Yearly Camera Subscription, 4MP/90</p> <p>5 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 90 days (automatic deletion afterwards) • Max. Resolution: 4MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	4047438046190	cm
		g	cm
			l
	<p>Mx-CL-Sub-HD5-D1095-12</p> <p>MOBOTIX CLOUD Yearly Camera Subscription, 5MP/1095</p> <p>Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 1095 days (automatic deletion afterwards) • Max. Resolution: 5MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	4047438042291	cm
		g	cm
			l
	<p>Mx-CL-Sub-HD5-D1095-36</p> <p>MOBOTIX CLOUD 3 Yearly Camera Subscription, 5MP/1095</p> <p>3 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 1095 days (automatic deletion afterwards) • Max. Resolution: 5MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	4047438046466	cm
		g	cm
			l







	<p>Mx-CL-Sub-HD5-D1095-60</p> <p>MOBOTIX CLOUD 5 Yearly Camera Subscription, 5MP/1095</p> <p>5 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 1095 days (automatic deletion afterwards) • Max. Resolution: 5MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	4047438046473	cm
		g	cm
			l
	<p>Mx-CL-Sub-HD5-D14-12</p> <p>MOBOTIX CLOUD Yearly Camera Subscription, 5MP/14 Days</p> <p>Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 14 days (automatic deletion afterwards) • Max. Resolution: 5MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	4047438042222	cm
		g	cm
			l
	<p>Mx-CL-Sub-HD5-D14-36</p> <p>MOBOTIX CLOUD 3 Yearly Camera Subscription, 5MP/14</p> <p>3 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 14 days (automatic deletion afterwards) • Max. Resolution: 5MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	4047438046329	cm
		g	cm
			l
	<p>Mx-CL-Sub-HD5-D14-60</p> <p>MOBOTIX CLOUD 5 Yearly Camera Subscription, 5MP/14</p> <p>5 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 14 days (automatic deletion afterwards) • Max. Resolution: 5MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	4047438046336	cm
		g	cm
			l
	<p>Mx-CL-Sub-HD5-D180-12</p> <p>MOBOTIX CLOUD Yearly Camera Subscription, 5MP/180</p> <p>Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 180 days (automatic deletion afterwards) • Max. Resolution: 5MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	4047438042260	cm
		g	cm
			l
	<p>Mx-CL-Sub-HD5-D180-36</p> <p>MOBOTIX CLOUD 3 Yearly Camera Subscription, 5MP/180</p> <p>3 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 180 days (automatic deletion afterwards) • Max. Resolution: 5MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	4047438046404	cm
		g	cm
			l







	<p>Mx-CL-Sub-HD5-D180-60</p> <p>MOBOTIX CLOUD 5 Yearly Camera Subscription, 5MP/180</p> <p>5 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 180 days (automatic deletion afterwards) • Max. Resolution: 5MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	4047438046411	cm cm cm l
	<p>Mx-CL-Sub-HD5-D1825-12</p> <p>MOBOTIX CLOUD Yearly Camera Subscription, 5MP/1825</p> <p>Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 1825 days (automatic deletion afterwards) • Max. Resolution: 5MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	4047438042307	cm cm cm l
	<p>Mx-CL-Sub-HD5-D1825-36</p> <p>MOBOTIX CLOUD 3 Yearly Camera Subscription, 5MP/1825</p> <p>3 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 1825 days (automatic deletion afterwards) • Max. Resolution: 5MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	4047438046480	cm cm cm l
	<p>Mx-CL-Sub-HD5-D1825-60</p> <p>MOBOTIX CLOUD 5 Yearly Camera Subscription, 5MP/1825</p> <p>5 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 1825 days (automatic deletion afterwards) • Max. Resolution: 5MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	4047438046497	cm cm cm l
	<p>Mx-CL-Sub-HD5-D30-12</p> <p>MOBOTIX CLOUD Yearly Camera Subscription, 5MP/30 Days</p> <p>Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 30 days (automatic deletion afterwards) • Max. Resolution: 5MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	4047438042239	cm cm cm l
	<p>Mx-CL-Sub-HD5-D30-36</p> <p>MOBOTIX CLOUD 3 Yearly Camera Subscription, 5MP/30</p> <p>3 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 30 days (automatic deletion afterwards) • Max. Resolution: 5MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	4047438046343	cm cm cm l







	<p>Mx-CL-Sub-HD5-D30-60</p> <p>MOBOTIX CLOUD 5 Yearly Camera Subscription, 5MP/30</p> <p>5 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 30 days (automatic deletion afterwards) • Max. Resolution: 5MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	4047438046350	cm cm cm l
	<p>Mx-CL-Sub-HD5-D365-12</p> <p>MOBOTIX CLOUD Yearly Camera Subscription, 5MP/365</p> <p>Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 365 days (automatic deletion afterwards) • Max. Resolution: 5MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	4047438042277	cm cm cm l
	<p>Mx-CL-Sub-HD5-D365-36</p> <p>MOBOTIX CLOUD 3 Yearly Camera Subscription, 5MP/365</p> <p>3 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 365 days (automatic deletion afterwards) • Max. Resolution: 5MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	4047438046428	cm cm cm l
	<p>Mx-CL-Sub-HD5-D365-60</p> <p>MOBOTIX CLOUD 5 Yearly Camera Subscription, 5MP/365</p> <p>5 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 365 days (automatic deletion afterwards) • Max. Resolution: 5MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	4047438046435	cm cm cm l
	<p>Mx-CL-Sub-HD5-D60-12</p> <p>MOBOTIX CLOUD Yearly Camera Subscription, 5MP/60 Days</p> <p>Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 60 days (automatic deletion afterwards) • Max. Resolution: 5MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	4047438042246	cm cm cm l
	<p>Mx-CL-Sub-HD5-D60-36</p> <p>MOBOTIX CLOUD 3 Yearly Camera Subscription, 5MP/60</p> <p>3 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 60 days (automatic deletion afterwards) • Max. Resolution: 5MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	4047438046367	cm cm cm l







	<p>Mx-CL-Sub-HD5-D60-60</p> <p>MOBOTIX CLOUD 5 Yearly Camera Subscription, 5MP/60</p> <p>5 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 60 days (automatic deletion afterwards) • Max. Resolution: 5MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	4047438046374	cm
		g	cm
			l
	<p>Mx-CL-Sub-HD5-D7-12</p> <p>MOBOTIX CLOUD Yearly Camera Subscription, 5MP/7 Days</p> <p>Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 2/3/5 up to 7 days (automatic deletion afterwards) • Max. Resolution: 5MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	4047438042215	cm
		g	cm
			l
	<p>Mx-CL-Sub-HD5-D7-36</p> <p>MOBOTIX CLOUD 3 Yearly Camera Subscription, 5MP/7 Days</p> <p>3 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 2/3/5 up to 7 days (automatic deletion afterwards) • Max. Resolution: 5MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	4047438046305	cm
		g	cm
			l
	<p>Mx-CL-Sub-HD5-D7-60</p> <p>MOBOTIX CLOUD 5 Yearly Camera Subscription, 5MP/7 Days</p> <p>5 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 2/3/5 up to 7 days (automatic deletion afterwards) • Max. Resolution: 5MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	4047438046312	cm
		g	cm
			l
	<p>Mx-CL-Sub-HD5-D730-12</p> <p>MOBOTIX CLOUD Yearly Camera Subscription, 5MP/730</p> <p>Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 730 days (automatic deletion afterwards) • Max. Resolution: 5MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	4047438042284	cm
		g	cm
			l
	<p>Mx-CL-Sub-HD5-D730-36</p> <p>MOBOTIX CLOUD 3 Yearly Camera Subscription, 5MP/730</p> <p>3 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 730 days (automatic deletion afterwards) • Max. Resolution: 5MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	4047438046442	cm
		g	cm
			l







	<p>Mx-CL-Sub-HD5-D730-60 MOBOTIX CLOUD 5 Yearly Camera Subscription, 5MP/730 5 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 730 days (automatic deletion afterwards) • Max. Resolution: 5MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	4047438046459	cm cm cm l
	<p>Mx-CL-Sub-HD5-D90-12 MOBOTIX CLOUD Yearly Camera Subscription, 5MP/90 Days Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 90 days (automatic deletion afterwards) • Max. Resolution: 5MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	4047438042253	cm cm cm l
	<p>Mx-CL-Sub-HD5-D90-36 MOBOTIX CLOUD 3 Yearly Camera Subscription, 5MP/90 3 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 90 days (automatic deletion afterwards) • Max. Resolution: 5MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	4047438046381	cm cm cm l
	<p>Mx-CL-Sub-HD5-D90-60 MOBOTIX CLOUD 5 Yearly Camera Subscription, 5MP/90 5 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 90 days (automatic deletion afterwards) • Max. Resolution: 5MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	4047438046398	cm cm cm l
	<p>Mx-CL-Sub-M10-1 MOBOTIX CLOUD Camera license, only live stream, NO Monthly subscription for using a single camera in the MOBOTIX CLOUD • Only for Live streaming • Recording duration (retention period): 0 days (No recording) • Max. Resolution: freely selectable • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment of subscription possible at any time at the end of the month</p>	4047438040327	cm cm cm l
	<p>Mx-CL-Sub-M10-12 MOBOTIX CLOUD 1Y Camera Subscription, only Live, NO Yearly subscription for using a single camera in the MOBOTIX CLOUD • Only for Live streaming • Recording duration (retention period): 0 days (No recording) • Max. Resolution: freely selectable • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment of subscription possible at any time at the end of the year</p>	4047438042482	cm cm cm l

	<p>Mx-CL-Sub-M10-36 MOBOTIX CLOUD 3Y Camera Subscription, only Live, NO 3 Years subscription for using a single camera in the MOBOTIX CLOUD • Only for Live streaming • Recording duration (retention period): 0 days (No recording) • Max. Resolution: freely selectable • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment of subscription possible at any time at the end of the year</p>	4047438045278	cm cm cm l
	<p>Mx-CL-Sub-M10-60 MOBOTIX CLOUD 5Y Camera Subscription, only Live, NO 5 Years subscription for using a single camera in the MOBOTIX CLOUD • Only for Live streaming • Recording duration (retention period): 0 days (No recording) • Max. Resolution: freely selectable • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment of subscription possible at any time at the end of the year</p>	4047438045285	cm cm cm l
	<p>Mx-CL-Sub-PR1-D180-1 MOBOTIX CLOUD monthly Camera Subscription,for preview Monthly subscription for recording the Preview Stream with 1 fps from a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 180 days (automatic deletion afterwards) • Max. Resolution: Preview setting in the Cloud • Requires a Cloud Managed Video Recorder (CMVR) • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	4047438049146	cm cm cm l
	<p>Mx-CL-Sub-PR1-D180-12 MOBOTIX CLOUD 1 Yearly Camera Subscription, for preview 1 Yearly subscription for recording the Preview Stream with 1 fps from a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 180 days (automatic deletion afterwards) • Max. Resolution: Preview setting in the Cloud • Requires a Cloud Managed Video Recorder (CMVR) • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	4047438049153	cm cm cm l
	<p>Mx-CL-Sub-PR1-D180-36 MOBOTIX CLOUD 3 Yearly Camera Subscription, for preview 3 Yearly subscription for recording the Preview Stream with 1 fps from a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 180 days (automatic deletion afterwards) • Max. Resolution: Preview setting in the Cloud • Requires a Cloud Managed Video Recorder (CMVR) • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	4047438049160	cm cm cm l
	<p>Mx-CL-Sub-PR1-D180-60 MOBOTIX CLOUD 5 Yearly Camera Subscription, for preview 5 Yearly subscription for recording the Preview Stream with 1 fps from a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 180 days (automatic deletion afterwards) • Max. Resolution: Preview setting in the Cloud • Requires a Cloud Managed Video Recorder (CMVR) • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	4047438049177	cm cm cm l

	<p>Mx-CL-Sub-PR1-D30-1</p> <p>MOBOTIX CLOUD monthly Camera Subscription for preview</p> <p>Monthly subscription for recording the Preview Stream with 1 fps from a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 30 days (automatic deletion afterwards) • Max. Resolution: Preview setting in the Cloud • Requires a Cloud Managed Video Recorder (CMVR) • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	4047438049023	cm cm g cm l
	<p>Mx-CL-Sub-PR1-D30-12</p> <p>MOBOTIX CLOUD 1 Yearly Camera Subscription, for preview</p> <p>1 Yearly subscription for recording the Preview Stream with 1 fps from a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 30 days (automatic deletion afterwards) • Max. Resolution: Preview setting in the Cloud • Requires a Cloud Managed Video Recorder (CMVR) • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	4047438049030	cm cm g cm l
	<p>Mx-CL-Sub-PR1-D30-36</p> <p>MOBOTIX CLOUD 3 Yearly Camera Subscription, for preview</p> <p>3 Yearly subscription for recording the Preview Stream with 1 fps from a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 30 days (automatic deletion afterwards) • Max. Resolution: Preview setting in the Cloud • Requires a Cloud Managed Video Recorder (CMVR) • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	4047438049047	cm cm g cm l
	<p>Mx-CL-Sub-PR1-D30-60</p> <p>MOBOTIX CLOUD 5 Yearly Camera Subscription, for preview</p> <p>5 Yearly subscription for recording the Preview Stream with 1 fps from a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 30 days (automatic deletion afterwards) • Max. Resolution: Preview setting in the Cloud • Requires a Cloud Managed Video Recorder (CMVR) • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	4047438049054	cm cm g cm l
	<p>Mx-CL-Sub-PR1-D365-1</p> <p>MOBOTIX CLOUD monthly Camera Subscription,for preview</p> <p>Monthly subscription for recording the Preview Stream with 1 fps from a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 365 days (automatic deletion afterwards) • Max. Resolution: Preview setting in the Cloud • Requires a Cloud Managed Video Recorder (CMVR) • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	4047438049184	cm cm g cm l
	<p>Mx-CL-Sub-PR1-D365-12</p> <p>MOBOTIX CLOUD 1 Yearly Camera Subscription, for preview</p> <p>1 Yearly subscription for recording the Preview Stream with 1 fps from a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 365 days (automatic deletion afterwards) • Max. Resolution: Preview setting in the Cloud • Requires a Cloud Managed Video Recorder (CMVR) • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	4047438049191	cm cm g cm l

	<p>Mx-CL-Sub-PR1-D365-36</p> <p>MOBOTIX CLOUD 3 Yearly Camera Subscription, for preview</p> <p>3 Yearly subscription for recording the Preview Stream with 1 fps from a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 365 days (automatic deletion afterwards) • Max. Resolution: Preview setting in the Cloud • Requires a Cloud Managed Video Recorder (CMVR) • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	4047438049207	cm
		g	cm
			l
	<p>Mx-CL-Sub-PR1-D365-60</p> <p>MOBOTIX CLOUD 5 Yearly Camera Subscription, for preview</p> <p>5 Yearly subscription for recording the Preview Stream with 1 fps from a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 365 days (automatic deletion afterwards) • Max. Resolution: Preview setting in the Cloud • Requires a Cloud Managed Video Recorder (CMVR) • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	4047438049214	cm
		g	cm
			l
	<p>Mx-CL-Sub-PR1-D60-1</p> <p>MOBOTIX CLOUD monthly Camera Subscription,for preview</p> <p>Monthly subscription for recording the Preview Stream with 1 fps from a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 60 days (automatic deletion afterwards) • Max. Resolution: Preview setting in the Cloud • Requires a Cloud Managed Video Recorder (CMVR) • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	4047438049061	cm
		g	cm
			l
	<p>Mx-CL-Sub-PR1-D60-12</p> <p>MOBOTIX CLOUD 1 Yearly Camera Subscription, for preview</p> <p>1 Yearly subscription for recording the Preview Stream with 1 fps from a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 60 days (automatic deletion afterwards) • Max. Resolution: Preview setting in the Cloud • Requires a Cloud Managed Video Recorder (CMVR) • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	4047438049078	cm
		g	cm
			l
	<p>Mx-CL-Sub-PR1-D60-36</p> <p>MOBOTIX CLOUD 3 Yearly Camera Subscription, for preview</p> <p>3 Yearly subscription for recording the Preview Stream with 1 fps from a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 60 days (automatic deletion afterwards) • Max. Resolution: Preview setting in the Cloud • Requires a Cloud Managed Video Recorder (CMVR) • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	4047438049085	cm
		g	cm
			l
	<p>Mx-CL-Sub-PR1-D60-60</p> <p>MOBOTIX CLOUD 5 Yearly Camera Subscription, for preview</p> <p>5 Yearly subscription for recording the Preview Stream with 1 fps from a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 60 days (automatic deletion afterwards) • Max. Resolution: Preview setting in the Cloud • Requires a Cloud Managed Video Recorder (CMVR) • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	4047438049092	cm
		g	cm
			l







	<p>Mx-CL-Sub-PR1-D730-1 MOBOTIX CLOUD monthly Camera Subscription,for preview Monthly subscription for recording the Preview Stream with 1 fps from a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 730 days (automatic deletion afterwards) • Max. Resolution: Preview setting in the Cloud • Requires a Cloud Managed Video Recorder (CMVR) • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	4047438049221	cm cm g l
	<p>Mx-CL-Sub-PR1-D730-12 MOBOTIX CLOUD 1 Yearly Camera Subscription, for preview 1 Yearly subscription for recording the Preview Stream with 1 fps from a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 730 days (automatic deletion afterwards) • Max. Resolution: Preview setting in the Cloud • Requires a Cloud Managed Video Recorder (CMVR) • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	4047438049238	cm cm g l
	<p>Mx-CL-Sub-PR1-D730-36 MOBOTIX CLOUD 3 Yearly Camera Subscription, for preview 3 Yearly subscription for recording the Preview Stream with 1 fps from a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 730 days (automatic deletion afterwards) • Max. Resolution: Preview setting in the Cloud • Requires a Cloud Managed Video Recorder (CMVR) • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	4047438049245	cm cm g l
	<p>Mx-CL-Sub-PR1-D730-60 MOBOTIX CLOUD 5 Yearly Camera Subscription, for preview 5 Yearly subscription for recording the Preview Stream with 1 fps from a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 730 days (automatic deletion afterwards) • Max. Resolution: Preview setting in the Cloud • Requires a Cloud Managed Video Recorder (CMVR) • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	4047438049252	cm cm g l
	<p>Mx-CL-Sub-PR1-D90-1 MOBOTIX CLOUD monthly Camera Subscription,for preview Monthly subscription for recording the Preview Stream with 1 fps from a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 90 days (automatic deletion afterwards) • Max. Resolution: Preview setting in the Cloud • Requires a Cloud Managed Video Recorder (CMVR) • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	4047438049108	cm cm g l
	<p>Mx-CL-Sub-PR1-D90-12 MOBOTIX CLOUD 1 Yearly Camera Subscription, for preview 1 Yearly subscription for recording the Preview Stream with 1 fps from a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 90 days (automatic deletion afterwards) • Max. Resolution: Preview setting in the Cloud • Requires a Cloud Managed Video Recorder (CMVR) • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	4047438049115	cm cm g l

	<p>Mx-CL-Sub-PR1-D90-36</p> <p>MOBOTIX CLOUD 3 Yearly Camera Subscription, for preview</p> <p>3 Yearly subscription for recording the Preview Stream with 1 fps from a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 90 days (automatic deletion afterwards) • Max. Resolution: Preview setting in the Cloud • Requires a Cloud Managed Video Recorder (CMVR) • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	4047438049122	cm cm cm l
	<p>Mx-CL-Sub-PR1-D90-60</p> <p>MOBOTIX CLOUD 5 Yearly Camera Subscription, for preview</p> <p>5 Yearly subscription for recording the Preview Stream with 1 fps from a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 90 days (automatic deletion afterwards) • Max. Resolution: Preview setting in the Cloud • Requires a Cloud Managed Video Recorder (CMVR) • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	4047438049139	cm cm cm l
	<p>Mx-CL-Sub-SD1-D1095-12</p> <p>MOBOTIX CLOUD Yearly Camera Subscription, VGA/1095</p> <p>Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 1095 days (automatic deletion afterwards) • Max. Resolution: VGA • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	4047438042048	cm cm cm l
	<p>Mx-CL-Sub-SD1-D1095-36</p> <p>MOBOTIX CLOUD 3 Yearly Camera Subscription, VGA/1095</p> <p>3 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 1095 days (automatic deletion afterwards) • Max. Resolution: VGA • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	4047438045469	cm cm cm l
	<p>Mx-CL-Sub-SD1-D1095-60</p> <p>MOBOTIX CLOUD 5 Yearly Camera Subscription, VGA/1095</p> <p>5 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 1095 days (automatic deletion afterwards) • Max. Resolution: VGA • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	4047438045476	cm cm cm l
	<p>Mx-CL-Sub-SD1-D14-12</p> <p>MOBOTIX CLOUD Yearly Camera Subscription, VGA/14 Days</p> <p>Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 14 days (automatic deletion afterwards) • Max. Resolution: VGA • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	4047438041973	cm cm cm l

	<p>Mx-CL-Sub-SD1-D14-36</p> <p>MOBOTIX CLOUD 3 Yearly Camera Subscription, VGA/14</p> <p>3 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 14 days (automatic deletion afterwards) • Max. Resolution: VGA • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	4047438045315	cm cm cm l
	<p>Mx-CL-Sub-SD1-D14-60</p> <p>MOBOTIX CLOUD 5 Yearly Camera Subscription, VGA/14</p> <p>5 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 14 days (automatic deletion afterwards) • Max. Resolution: VGA • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	4047438045322	cm cm cm l
	<p>Mx-CL-Sub-SD1-D180-12</p> <p>MOBOTIX CLOUD Yearly Camera Subscription, VGA/180 Days</p> <p>Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 180 days (automatic deletion afterwards) • Max. Resolution: VGA • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	4047438042017	cm cm cm l
	<p>Mx-CL-Sub-SD1-D180-36</p> <p>MOBOTIX CLOUD 3 Yearly Camera Subscription, VGA/180</p> <p>3 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 180 days (automatic deletion afterwards) • Max. Resolution: VGA • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	4047438045407	cm cm cm l
	<p>Mx-CL-Sub-SD1-D180-60</p> <p>MOBOTIX CLOUD 5 Yearly Camera Subscription, VGA/180</p> <p>5 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 180 days (automatic deletion afterwards) • Max. Resolution: VGA • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	4047438045414	cm cm cm l
	<p>Mx-CL-Sub-SD1-D1825-12</p> <p>MOBOTIX CLOUD Yearly Camera Subscription, VGA/1825</p> <p>Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 1825 days (automatic deletion afterwards) • Max. Resolution: VGA • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	4047438042055	cm cm cm l

	<p>Mx-CL-Sub-SD1-D1825-36</p> <p>MOBOTIX CLOUD 3 Yearly Camera Subscription, VGA/1825</p> <p>3 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 1825 days (automatic deletion afterwards) • Max. Resolution: VGA • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	4047438045483	cm cm cm l
	<p>Mx-CL-Sub-SD1-D1825-60</p> <p>MOBOTIX CLOUD 5 Yearly Camera Subscription, VGA/1825</p> <p>5 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 1825 days (automatic deletion afterwards) • Max. Resolution: VGA • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	4047438045490	cm cm cm l
	<p>Mx-CL-Sub-SD1-D30-12</p> <p>MOBOTIX CLOUD Yearly Camera Subscription, VGA/30 Days</p> <p>Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 30 days (automatic deletion afterwards) • Max. Resolution: VGA • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	4047438041980	cm cm cm l
	<p>Mx-CL-Sub-SD1-D30-36</p> <p>MOBOTIX CLOUD 3 Yearly Camera Subscription, VGA/30</p> <p>3 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 30 days (automatic deletion afterwards) • Max. Resolution: VGA • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	4047438045339	cm cm cm l
	<p>Mx-CL-Sub-SD1-D30-60</p> <p>MOBOTIX CLOUD 5 Yearly Camera Subscription, VGA/30</p> <p>5 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 30 days (automatic deletion afterwards) • Max. Resolution: VGA • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	4047438045346	cm cm cm l
	<p>Mx-CL-Sub-SD1-D365-12</p> <p>MOBOTIX CLOUD Yearly Camera Subscription, VGA/365 Days</p> <p>Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 365 days (automatic deletion afterwards) • Max. Resolution: VGA • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	4047438042024	cm cm cm l

	<p>Mx-CL-Sub-SD1-D365-36</p> <p>MOBOTIX CLOUD 3 Yearly Camera Subscription, VGA/365</p> <p>3 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 365 days (automatic deletion afterwards) • Max. Resolution: VGA • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	4047438045421	cm cm cm l
	<p>Mx-CL-Sub-SD1-D365-60</p> <p>MOBOTIX CLOUD 5 Yearly Camera Subscription, VGA/365</p> <p>5 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 365 days (automatic deletion afterwards) • Max. Resolution: VGA • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	4047438045438	cm cm cm l
	<p>Mx-CL-Sub-SD1-D60-12</p> <p>MOBOTIX CLOUD Yearly Camera Subscription, VGA/60 Days</p> <p>Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 60 days (automatic deletion afterwards) • Max. Resolution: VGA • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	4047438041997	cm cm cm l
	<p>Mx-CL-Sub-SD1-D60-36</p> <p>MOBOTIX CLOUD 3 Yearly Camera Subscription, VGA/60</p> <p>3 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 60 days (automatic deletion afterwards) • Max. Resolution: VGA • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	4047438045360	cm cm cm l
	<p>Mx-CL-Sub-SD1-D60-60</p> <p>MOBOTIX CLOUD 5 Yearly Camera Subscription, VGA/60</p> <p>5 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 60 days (automatic deletion afterwards) • Max. Resolution: VGA • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	4047438045377	cm cm cm l
	<p>Mx-CL-Sub-SD1-D7-12</p> <p>MOBOTIX CLOUD Yearly Camera Subscription, VGA/7 Days</p> <p>Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 2/3/5 up to 7 days (automatic deletion afterwards) • Max. Resolution: VGA • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	4047438041966	cm cm cm l

	<p>Mx-CL-Sub-SD1-D7-36 MOBOTIX CLOUD 3 Years Camera Subscription, VGA/7 Days 3 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 2/3/5 up to 7 days (automatic deletion afterwards) • Max. Resolution: VGA • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	<p>4047438045292</p>	<p>cm cm cm l</p>
	<p>Mx-CL-Sub-SD1-D7-60 MOBOTIX CLOUD 5 Years Camera Subscription, VGA/7 Days 5 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 2/3/5 up to 7 days (automatic deletion afterwards) • Max. Resolution: VGA • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	<p>4047438045308</p>	<p>cm cm cm l</p>
	<p>Mx-CL-Sub-SD1-D730-12 MOBOTIX CLOUD Yearly Camera Subscription, VGA/730 Days Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 730 days (automatic deletion afterwards) • Max. Resolution: VGA • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	<p>4047438042031</p>	<p>cm cm cm l</p>
	<p>Mx-CL-Sub-SD1-D730-36 MOBOTIX CLOUD 3 Yearly Camera Subscription, VGA/730 3 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 730 days (automatic deletion afterwards) • Max. Resolution: VGA • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	<p>4047438045445</p>	<p>cm cm cm l</p>
	<p>Mx-CL-Sub-SD1-D730-60 MOBOTIX CLOUD 5 Yearly Camera Subscription, VGA/730 5 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 730 days (automatic deletion afterwards) • Max. Resolution: VGA • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	<p>4047438045452</p>	<p>cm cm cm l</p>
	<p>Mx-CL-Sub-SD1-D90-12 MOBOTIX CLOUD Yearly Camera Subscription, VGA/90 Days Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 90 days (automatic deletion afterwards) • Max. Resolution: VGA • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment possible at any time at the end of the subscription period.</p>	<p>4047438042000</p>	<p>cm cm cm l</p>

**Mx-CL-Sub-SD1-D90-36**

4047438045384

cm

MOBOTIX CLOUD 3 Yearly Camera Subscription, VGA/90

3 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 90 days (automatic deletion afterwards) • Max. Resolution: VGA • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

l

**Mx-CL-Sub-SD1-D90-60**

4047438045391

cm

MOBOTIX CLOUD 5 Yearly Camera Subscription, VGA/90

5 Yearly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 90 days (automatic deletion afterwards) • Max. Resolution: VGA • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

cm

l

**Mx-CL-Sub-SP01-M30-1**

4047438047203

cm

MOBOTIX CLOUD Monthly SIP Audio-Support Subscription

Monthly Subscription for using a single IP SIP based speaker/Intercom in the MOBOTIX CLOUD • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

cm

l

**Mx-CL-Sub-SP01-M30-12**

4047438047210

cm

MOBOTIX CLOUD Yearly SIP Audio-Support Subscription

Yearly subscription for using a single IP SIP based speaker/Intercom in the MOBOTIX CLOUD • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

cm

l

**Mx-CL-Sub-SP01-M30-36**

4047438047227

cm

MOBOTIX CLOUD 3 Yearly SIP Audio-Support Subscription

3 Yearly subscription for using a single IP SIP based speaker/Intercom in the MOBOTIX CLOUD • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.

g

cm

cm

l

**Mx-CL-Sub-SP01-M30-60**

4047438047234

cm

MOBOTIX CLOUD 5 Yearly SIP Audio-Support Subscription







5 Yearly subscription for using a single IP SIP based speaker/Intercom in the MOBOTIX CLOUD • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment possible at any time at the end of the subscription period.







g







cm







cm

l

	<p>Mx-CL-Sub-SD1-D7-1 MOBOTIX CLOUD Camera Subscription, VGA/7 Days Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 2/3/5 up to 7 days (automatic deletion afterwards) • Max. Resolution: VGA • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment of subscription possible at any time at the end of the month</p>	4047438036375	cm cm cm l
	<p>Mx-CL-Sub-SD1-D14-1 MOBOTIX CLOUD Camera Subscription, VGA/14 Days Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 14 days (automatic deletion afterwards) • Max. Resolution: VGA • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • MOBOTIX Cloud access portal: https://mobotixcloud.com • Cancellation/adjustment of subscription possible at any time at the end of the month</p>	4047438036382	cm cm cm l
	<p>Mx-CL-Sub-SD1-D30-1 MOBOTIX CLOUD Camera Subscription, VGA/30 Days Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 30 days (automatic deletion afterwards) • Max. Resolution: VGA • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment of subscription possible at any time at the end of the month</p>	4047438036399	cm cm cm l
	<p>Mx-CL-Sub-SD1-D60-1 MOBOTIX CLOUD Camera Subscription, VGA/60 Days Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 60 days (automatic deletion afterwards) • Max. Resolution: VGA • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment of subscription possible at any time at the end of the month</p>	4047438036405	cm cm cm l
	<p>Mx-CL-Sub-SD1-D90-1 MOBOTIX CLOUD Camera Subscription, VGA/90 Days Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 90 days (automatic deletion afterwards) • Max. Resolution: VGA • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment of subscription possible at any time at the end of the month</p>	4047438036412	cm cm cm l
	<p>Mx-CL-Sub-SD1-D180-1 MOBOTIX CLOUD Camera Subscription, VGA/180 Days Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 180 days (automatic deletion afterwards) • Max. Resolution: VGA • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment of subscription possible at any time at the end of the month</p>	4047438036429	cm cm cm l

	<p>Mx-CL-Sub-SD1-D365-1</p> <p>MOBOTIX CLOUD Camera Subscription, VGA/365 Days</p> <p>Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 365 days (automatic deletion afterwards) • Max. Resolution: VGA • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment of subscription possible at any time at the end of the month</p>	4047438036436	cm cm cm l
	<p>Mx-CL-Sub-SD1-D730-1</p> <p>MOBOTIX CLOUD Camera Subscription, VGA/730 Days</p> <p>Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 730 days (automatic deletion afterwards) • Max. Resolution: VGA • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment of subscription possible at any time at the end of the month</p>	4047438036443	cm cm cm l
	<p>Mx-CL-Sub-SD1-D1095-1</p> <p>MOBOTIX CLOUD Camera Subscription, VGA/1095 Days</p> <p>Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 1095 days (automatic deletion afterwards) • Max. Resolution: VGA • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment of subscription possible at any time at the end of the month</p>	4047438036450	cm cm cm l
	<p>Mx-CL-Sub-SD1-D1825-1</p> <p>MOBOTIX CLOUD Camera Subscription, VGA/1825 Days</p> <p>Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 1825 days (automatic deletion afterwards) • Max. Resolution: VGA • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment of subscription possible at any time at the end of the month</p>	4047438036467	cm cm cm l
	<p>Mx-CL-Sub-HD1-D7-1</p> <p>MOBOTIX CLOUD Camera Subscription, 720p/7 Days</p> <p>Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 2/3/5 up to 7 days (automatic deletion afterwards) • Max. Resolution: 720 pixels • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment of subscription possible at any time at the end of the month</p>	4047438036023	cm cm cm l
	<p>Mx-CL-Sub-HD1-D14-1</p> <p>MOBOTIX CLOUD Camera Subscription, 720p/14 Days</p> <p>Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 14 days (automatic deletion afterwards) • Max. Resolution: 720 pixels • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment of subscription possible at any time at the end of the month</p>	4047438036030	cm cm cm l

	<p>Mx-CL-Sub-HD1-D30-1</p> <p>MOBOTIX CLOUD Camera Subscription, 720p/30 Days</p> <p>Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 30 days (automatic deletion afterwards) • Max. Resolution: 720 pixels • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment of subscription possible at any time at the end of the month</p>	4047438036047	cm cm cm l
	<p>Mx-CL-Sub-HD1-D60-1</p> <p>MOBOTIX CLOUD Camera Subscription, 720p/60 Days</p> <p>Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 60 days (automatic deletion afterwards) • Max. Resolution: 720 pixels • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment of subscription possible at any time at the end of the month</p>	4047438036054	cm cm cm l
	<p>Mx-CL-Sub-HD1-D90-1</p> <p>MOBOTIX CLOUD Camera Subscription, 720p/90 Days</p> <p>Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 90 days (automatic deletion afterwards) • Max. Resolution: 720 pixels • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment of subscription possible at any time at the end of the month</p>	4047438036061	cm cm cm l
	<p>Mx-CL-Sub-HD1-D180-1</p> <p>MOBOTIX CLOUD Camera Subscription, 720p/180 Days</p> <p>Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 180 days (automatic deletion afterwards) • Max. Resolution: 720 pixels • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment of subscription possible at any time at the end of the month</p>	4047438036078	cm cm cm l
	<p>Mx-CL-Sub-HD1-D365-1</p> <p>MOBOTIX CLOUD Camera Subscription, 720p/365 Days</p> <p>Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 365 days (automatic deletion afterwards) • Max. Resolution: 720 pixels • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment of subscription possible at any time at the end of the month</p>	4047438036085	cm cm cm l
	<p>Mx-CL-Sub-HD1-D730-1</p> <p>MOBOTIX CLOUD Camera Subscription, 720p/730 Days</p> <p>Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 730 days (automatic deletion afterwards) • Max. Resolution: 720 pixels • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment of subscription possible at any time at the end of the month</p>	4047438036092	cm cm cm l

	<p>Mx-CL-Sub-HD1-D1095-1</p> <p>MOBOTIX CLOUD Camera Subscription, 720p/1095 Days</p> <p>Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 1095 days (automatic deletion afterwards) • Max. Resolution: 720 pixels • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment of subscription possible at any time at the end of the month</p>	4047438036108	cm cm cm l
	<p>Mx-CL-Sub-HD1-D1825-1</p> <p>MOBOTIX CLOUD Camera Subscription, 720p/1825 Days</p> <p>Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 1825 days (automatic deletion afterwards) • Max. Resolution: 720 pixels • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment of subscription possible at any time at the end of the month</p>	4047438036115	cm cm cm l
	<p>Mx-CL-Sub-HD2-D7-1</p> <p>MOBOTIX CLOUD Camera Subscription, 1080p/7 Days</p> <p>Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 2/3/5 up to 7 days (automatic deletion afterwards) • Max. Resolution: 1080 pixels • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment of subscription possible at any time at the end of the month</p>	4047438036122	cm cm cm l
	<p>Mx-CL-Sub-HD2-D14-1</p> <p>MOBOTIX CLOUD Camera Subscription, 1080p/14 Days</p> <p>Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 14 days (automatic deletion afterwards) • Max. Resolution: 1080 pixels • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment of subscription possible at any time at the end of the month</p>	4047438036139	cm cm cm l
	<p>Mx-CL-Sub-HD2-D30-1</p> <p>MOBOTIX CLOUD Camera Subscription, 1080p/30 Days</p> <p>Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 30 days (automatic deletion afterwards) • Max. Resolution: 1080 pixels • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment of subscription possible at any time at the end of the month</p>	4047438036146	cm cm cm l
	<p>Mx-CL-Sub-HD2-D60-1</p> <p>MOBOTIX CLOUD Camera Subscription, 1080p/60 Days</p> <p>Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 60 days (automatic deletion afterwards) • Max. Resolution: 1080 pixels • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment of subscription possible at any time at the end of the month</p>	4047438036153	cm cm cm l

**Mx-CL-Sub-HD2-D90-1****MOBOTIX CLOUD Camera Subscription, 1080p/90 Days**

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 90 days (automatic deletion afterwards) • Max. Resolution: 1080 pixels • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment of subscription possible at any time at the end of the month

4047438036160

cm

g

cm

l

**Mx-CL-Sub-HD2-D180-1****MOBOTIX CLOUD Camera Subscription, 1080p/180 Days**

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 180 days (automatic deletion afterwards) • Max. Resolution: 1080 pixels • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment of subscription possible at any time at the end of the month

4047438036177

cm

g

cm

cm

l

**Mx-CL-Sub-HD2-D365-1****MOBOTIX CLOUD Camera Subscription, 1080p/365 Days**

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 365 days (automatic deletion afterwards) • Max. Resolution: 1080 pixels • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment of subscription possible at any time at the end of the month

4047438036184

cm

g

cm

cm

l

**Mx-CL-Sub-HD2-D730-1****MOBOTIX CLOUD Camera Subscription, 1080p/730 Days**

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 730 days (automatic deletion afterwards) • Max. Resolution: 1080 pixels • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment of subscription possible at any time at the end of the month

4047438036191

cm

g

cm

cm

l

**Mx-CL-Sub-HD2-D1095-1****MOBOTIX CLOUD Camera Subscription, 1080p/1095 Days**

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 1095 days (automatic deletion afterwards) • Max. Resolution: 1080 pixels • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment of subscription possible at any time at the end of the month

4047438036207

cm

g

cm

cm

l

**Mx-CL-Sub-HD2-D1825-1****MOBOTIX CLOUD Camera Subscription, 1080p/1825 Days**

Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 1825 days (automatic deletion afterwards) • Max. Resolution: 1080 pixels • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: <https://mobotixcloud.com> • Cancellation/adjustment of subscription possible at any time at the end of the month

4047438036214







cm







g







cm







cm







l







	<p>Mx-CL-Sub-HD3-D7-1</p> <p>MOBOTIX CLOUD Camera Subscription, 3MP/7 Days</p> <p>Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 2/3/5 up to 7 days (automatic deletion afterwards) • Max. Resolution: 3MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment of subscription possible at any time at the end of the month</p>	4047438036221	cm cm cm l
	<p>Mx-CL-Sub-HD3-D14-1</p> <p>MOBOTIX CLOUD Camera Subscription, 3MP/14 Days</p> <p>Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 14 days (automatic deletion afterwards) • Max. Resolution: 3MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment of subscription possible at any time at the end of the month</p>	4047438036238	cm cm cm l
	<p>Mx-CL-Sub-HD3-D30-1</p> <p>MOBOTIX CLOUD Camera Subscription, 3MP/30 Days</p> <p>Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 30 days (automatic deletion afterwards) • Max. Resolution: 3MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment of subscription possible at any time at the end of the month</p>	4047438036245	cm cm cm l
	<p>Mx-CL-Sub-HD3-D60-1</p> <p>MOBOTIX CLOUD Camera Subscription, 3MP/60 Days</p> <p>Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 60 days (automatic deletion afterwards) • Max. Resolution: 3MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment of subscription possible at any time at the end of the month</p>	4047438036252	cm cm cm l
	<p>Mx-CL-Sub-HD3-D90-1</p> <p>MOBOTIX CLOUD Camera Subscription, 3MP/90 Days</p> <p>Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 90 days (automatic deletion afterwards) • Max. Resolution: 3MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment of subscription possible at any time at the end of the month</p>	4047438036269	cm cm cm l
	<p>Mx-CL-Sub-HD3-D180-1</p> <p>MOBOTIX CLOUD Camera Subscription, 3MP/180 Days</p> <p>Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 180 days (automatic deletion afterwards) • Max. Resolution: 3MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment of subscription possible at any time at the end of the month</p>	4047438036276	cm cm cm l







	<p>Mx-CL-Sub-HD3-D365-1 MOBOTIX CLOUD Camera Subscription, 3MP/365 Days Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 365 days (automatic deletion afterwards) • Max. Resolution: 3MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment of subscription possible at any time at the end of the month</p>	4047438036283	cm cm cm l
	<p>Mx-CL-Sub-HD3-D730-1 MOBOTIX CLOUD Camera Subscription, 3MP/730 Days Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 730 days (automatic deletion afterwards) • Max. Resolution: 3MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • MOBOTIX Cloud access portal: https://mobotixcloud.com • Cancellation/adjustment of subscription possible at any time at the end of the month</p>	4047438036290	cm cm cm l
	<p>Mx-CL-Sub-HD3-D1095-1 MOBOTIX CLOUD Camera Subscription, 3MP/1095 Days Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 1095 days (automatic deletion afterwards) • Max. Resolution: 3MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment of subscription possible at any time at the end of the month</p>	4047438036306	cm cm cm l
	<p>Mx-CL-Sub-HD3-D1825-1 MOBOTIX CLOUD Camera Subscription, 3MP/1825 Days Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 1825 days (automatic deletion afterwards) • Max. Resolution: 3MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment of subscription possible at any time at the end of the month</p>	4047438036313	cm cm cm l
	<p>Mx-CL-Sub-HD4-D7-1 MOBOTIX CLOUD Camera Subscription, 4MP/7 days Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 2/3/5 up to 7 days (automatic deletion afterwards) • Max. Resolution: 4MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment of subscription possible at any time at the end of the month</p>	4047438036481	cm cm cm l
	<p>Mx-CL-Sub-HD4-D14-1 MOBOTIX CLOUD Camera Subscription, 4MP/14 days Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 14 days (automatic deletion afterwards) • Max. Resolution: 4MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment of subscription possible at any time at the end of the month</p>	4047438036498	cm cm cm l

	<p>Mx-CL-Sub-HD4-D30-1</p> <p>MOBOTIX CLOUD Camera Subscription, 4MP/30 days</p> <p>Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 30 days (automatic deletion afterwards) • Max. Resolution: 4MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment of subscription possible at any time at the end of the month</p>	4047438036504	cm cm cm l
	<p>Mx-CL-Sub-HD4-D60-1</p> <p>MOBOTIX CLOUD Camera Subscription, 4MP/60 days</p> <p>Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 60 days (automatic deletion afterwards) • Max. Resolution: 4MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment of subscription possible at any time at the end of the month</p>	4047438036511	cm cm cm l
	<p>Mx-CL-Sub-HD4-D90-1</p> <p>MOBOTIX CLOUD Camera Subscription, 4MP/90 days</p> <p>Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 90 days (automatic deletion afterwards) • Max. Resolution: 4MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment of subscription possible at any time at the end of the month</p>	4047438036528	cm cm cm l
	<p>Mx-CL-Sub-HD4-D180-1</p> <p>MOBOTIX CLOUD Camera Subscription, 4MP/180 days</p> <p>Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 180 days (automatic deletion afterwards) • Max. Resolution: 4MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment of subscription possible at any time at the end of the month</p>	4047438036535	cm cm cm l
	<p>Mx-CL-Sub-HD4-D365-1</p> <p>MOBOTIX CLOUD Camera Subscription, 4MP/365 days</p> <p>Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 365 days (automatic deletion afterwards) • Max. Resolution: 4MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment of subscription possible at any time at the end of the month</p>	4047438036542	cm cm cm l
	<p>Mx-CL-Sub-HD4-D730-1</p> <p>MOBOTIX CLOUD Camera Subscription, 4MP/730 days</p> <p>Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 730 days (automatic deletion afterwards) • Max. Resolution: 4MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment of subscription possible at any time at the end of the month</p>	4047438036559	cm cm cm l

	<p>Mx-CL-Sub-HD4-D1095-1</p> <p>MOBOTIX CLOUD Camera Subscription, 4MP/1095 days</p> <p>Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 1095 days (automatic deletion afterwards) • Max. Resolution: 4MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment of subscription possible at any time at the end of the month</p>	4047438036566	cm cm cm l
	<p>Mx-CL-Sub-HD4-D1825-1</p> <p>MOBOTIX CLOUD Camera Subscription, 4MP/1825 days</p> <p>Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 1825 days (automatic deletion afterwards) • Max. Resolution: 4MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment of subscription possible at any time at the end of the month</p>	4047438036573	cm cm cm l
	<p>Mx-CL-Sub-HD5-D7-1</p> <p>MOBOTIX CLOUD Camera Subscription, 5MP/7 days</p> <p>Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 2/3/5 up to 7 days (automatic deletion afterwards) • Max. Resolution: 5MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment of subscription possible at any time at the end of the month</p>	4047438036580	cm cm cm l
	<p>Mx-CL-Sub-HD5-D14-1</p> <p>MOBOTIX CLOUD Camera Subscription, 5MP/14 days</p> <p>Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 14 days (automatic deletion afterwards) • Max. Resolution: 5MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment of subscription possible at any time at the end of the month</p>	4047438036597	cm cm cm l
	<p>Mx-CL-Sub-HD5-D30-1</p> <p>MOBOTIX CLOUD Camera Subscription, 5MP/30 days</p> <p>Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 30 days (automatic deletion afterwards) • Max. Resolution: 5MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment of subscription possible at any time at the end of the month</p>	4047438036603	cm cm cm l
	<p>Mx-CL-Sub-HD5-D60-1</p> <p>MOBOTIX CLOUD Camera Subscription, 5MP/60 days</p> <p>Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 60 days (automatic deletion afterwards) • Max. Resolution: 5MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment of subscription possible at any time at the end of the month</p>	4047438036610	cm cm cm l

	<p>Mx-CL-Sub-HD5-D90-1</p> <p>MOBOTIX CLOUD Camera Subscription, 5MP/90 days</p> <p>Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 90 days (automatic deletion afterwards) • Max. Resolution: 5MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment of subscription possible at any time at the end of the month</p>	4047438036627	cm cm cm l
	<p>Mx-CL-Sub-HD5-D180-1</p> <p>MOBOTIX CLOUD Camera Subscription, 5MP/180 days</p> <p>Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 180 days (automatic deletion afterwards) • Max. Resolution: 5MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment of subscription possible at any time at the end of the month</p>	4047438036634	cm cm cm l
	<p>Mx-CL-Sub-HD5-D365-1</p> <p>MOBOTIX CLOUD Camera Subscription, 5MP/365 days</p> <p>Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 365 days (automatic deletion afterwards) • Max. Resolution: 5MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment of subscription possible at any time at the end of the month</p>	4047438036641	cm cm cm l
	<p>Mx-CL-Sub-HD5-D730-1</p> <p>MOBOTIX CLOUD Camera Subscription, 5MP/730 days</p> <p>Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 730 days (automatic deletion afterwards) • Max. Resolution: 5MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment of subscription possible at any time at the end of the month</p>	4047438036658	cm cm cm l
	<p>Mx-CL-Sub-HD5-D1095-1</p> <p>MOBOTIX CLOUD Camera Subscription, 5MP/1095 days</p> <p>Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 1095 days (automatic deletion afterwards) • Max. Resolution: 5MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment of subscription possible at any time at the end of the month</p>	4047438036665	cm cm cm l
	<p>Mx-CL-Sub-HD5-D1825-1</p> <p>MOBOTIX CLOUD Camera Subscription, 5MP/1825 days</p> <p>Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 1825 days (automatic deletion afterwards) • Max. Resolution: 5MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment of subscription possible at any time at the end of the month</p>	4047438036672	cm cm cm l

	<p>Mx-CL-Sub-HD10-D7-1</p> <p>MOBOTIX CLOUD Camera Subscription, 10MP/7 days</p> <p>Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 2/3/5 up to 7 days (automatic deletion afterwards) • Max. Resolution: 10MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment of subscription possible at any time at the end of the month</p>	4047438036689	cm cm cm l
	<p>Mx-CL-Sub-HD10-D14-1</p> <p>MOBOTIX CLOUD Camera Subscription, 10MP/14 days</p> <p>Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 14 days (automatic deletion afterwards) • Max. Resolution: 10MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment of subscription possible at any time at the end of the month</p>	4047438036696	cm cm cm l
	<p>Mx-CL-Sub-HD10-D30-1</p> <p>MOBOTIX CLOUD Camera Subscription, 10MP/30 days</p> <p>Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 30 days (automatic deletion afterwards) • Max. Resolution: 10MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment of subscription possible at any time at the end of the month</p>	4047438036702	cm cm cm l
	<p>Mx-CL-Sub-HD10-D60-1</p> <p>MOBOTIX CLOUD Camera Subscription, 10MP/60 days</p> <p>Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 60 days (automatic deletion afterwards) • Max. Resolution: 10MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment of subscription possible at any time at the end of the month</p>	4047438036719	cm cm cm l
	<p>Mx-CL-Sub-HD10-D90-1</p> <p>MOBOTIX CLOUD Camera Subscription, 10MP/90 days</p> <p>Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 90 days (automatic deletion afterwards) • Max. Resolution: 10MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment of subscription possible at any time at the end of the month</p>	4047438036726	cm cm cm l
	<p>Mx-CL-Sub-HD10-D180-1</p> <p>MOBOTIX CLOUD Camera Subscription, 10MP/180 days</p> <p>Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 180 days (automatic deletion afterwards) • Max. Resolution: 10MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment of subscription possible at any time at the end of the month</p>	4047438036733	cm cm cm l

	<p>Mx-CL-Sub-HD10-D365-1 MOBOTIX CLOUD Camera Subscription, 10MP/365 days Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 365 days (automatic deletion afterwards) • Max. Resolution: 10MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment of subscription possible at any time at the end of the month</p>	4047438036740	cm cm cm l
	<p>Mx-CL-Sub-HD10-D730-1 MOBOTIX CLOUD Camera Subscription, 10MP/730 days Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 730 days (automatic deletion afterwards) • Max. Resolution: 10MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment of subscription possible at any time at the end of the month</p>	4047438036757	cm cm cm l
	<p>Mx-CL-Sub-HD10-D1095-1 MOBOTIX CLOUD Camera Subscription, 10MP/1095 days Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 1095 days (automatic deletion afterwards) • Max. Resolution: 10MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment of subscription possible at any time at the end of the month</p>	4047438036764	cm cm cm l
	<p>Mx-CL-Sub-HD10-D1825-1 MOBOTIX CLOUD Camera Subscription, 10MP/1825 days Monthly subscription for using a single camera in the MOBOTIX CLOUD • Recording duration (retention period): 1825 days (automatic deletion afterwards) • Max. Resolution: 10MP • Free use of the MOBOTIX CLOUD app for desktop PC and mobile devices (Android and iOS) • Access portal: https://mobotixcloud.com • Cancellation/adjustment of subscription possible at any time at the end of the month</p>	4047438036771	cm cm cm l
	<p>Mx-CL-Sub-ANA-001-1 MOBOTIX CLOUD Analytics Subscription, Line Cross Monthly subscription for using the MOBOTIX CLOUD Analytics: Line Cross • Cancellation of subscription possible at any time at the end of the month</p>	4047438036320	cm cm cm l
	<p>Mx-CL-Sub-ANA-002-1 MOBOTIX CLOUD Analytics Subscription, Counting Monthly subscription for using the MOBOTIX CLOUD Analytics: Counting • Cancellation of subscription possible at any time at the end of the month</p>	4047438036337	cm cm cm l

**Mx-CL-Sub-ANA-003-1****MOBOTIX CLOUD Analytics Subscription, Area Intrusion**

Monthly subscription for using the MOBOTIX CLOUD Analytics: Area Intrusion •
Cancellation of subscription possible at any time at the end of the month

4047438036344

g

cm

cm

cm

l

**Mx-CL-Sub-ANA-004-1****MOBOTIX CLOUD Analytics Subscription, Camera Tamper**

Monthly subscription for using the MOBOTIX CLOUD Analytics: Camera Tamper
Detect • Cancellation of subscription possible at any time at the end of the month

4047438036351

g

cm

cm

cm

l

**Mx-CL-Sub-ANA-005-1****MOBOTIX CLOUD Analytics Subscription, Loitering**

Monthly subscription for using the MOBOTIX CLOUD Analytics: Loitering •
Cancellation of subscription possible at any time at the end of the month

4047438036368

g

cm

cm

cm






l

Access Control

BeyondHumanVision

MOBOTIX

T26B Camera Module

	Article No. / Name / Description	EAN / HS / weight	dimen.
	Mx-T26B-6D016	4047438032025	19,6 cm
	T26 CamCore, 6MP, B016, Day, White	85258900	14,8 cm
	Hemispheric IP door station camera with 6 Megapixel Moonlight Sensor, color (day) • ONVIF S compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • HD premium fisheye lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • Max. image size: 6MP (3072 x 2048) • IP65, -30 to 50°C (-22 to 122°F) • Internal DVR: 4 GB microSD • LED lighting strips, two buttons (doorbell, outdoor light), temperature sensor, shock • detector, MxActivitySensor, MxAnalytics, ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45 and LSA), MxBus, USB • Color: White	400 g	9,0 cm
	Mx-T26B-6N016	4047438032032	19,6 cm
	T26 CamCore, 6MP, B016, Night, White	85258900	14,8 cm
	Hemispheric IP door station camera with 6 Megapixel Moonlight Sensor, B/W (night) • ONVIF S compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • HD premium fisheye lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • Max. image size: 6MP (3072 x 2048) • IP65, -30 to 50°C (-22 to 122°F) • Internal DVR: 4 GB microSD • LED lighting strips, two buttons (doorbell, outdoor light), temperature sensor, shock • detector, MxActivitySensor, MxAnalytics, ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45 and LSA), MxBus, USB • Color: White	400 g	9,0 cm
	Mx-T26B-6D016-s	4047438032063	19,6 cm
	T26 CamCore, 6MP, B016, Day, Silver	85258900	14,8 cm
	Hemispheric IP door station camera with 6 Megapixel Moonlight Sensor, color (day) • ONVIF S compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • HD premium fisheye lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • Max. image size: 6MP (3072 x 2048) • IP65, -30 to 50°C (-22 to 122°F) • Internal DVR: 4 GB microSD • LED lighting strips, two buttons (doorbell, outdoor light), temperature sensor, shock • detector, MxActivitySensor, MxAnalytics, ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45 and LSA), MxBus, USB • Color: Silver	400 g	9,0 cm
	Mx-T26B-6N016-s	4047438032070	19,6 cm
	T26 CamCore, 6MP, B016, Night, Silver	85258900	14,8 cm
	Hemispheric IP door station camera with 6 Megapixel Moonlight Sensor, B/W (night) • ONVIF S compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • HD premium fisheye lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • Max. image size: 6MP (3072 x 2048) • IP65, -30 to 50°C (-22 to 122°F) • Internal DVR: 4 GB microSD • LED lighting strips, two buttons (doorbell, outdoor light), temperature sensor, shock • detector, MxActivitySensor, MxAnalytics, ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45 and LSA), MxBus, USB • Color: Silver	400 g	9,0 cm
	Mx-T26B-6D016-d	4047438032087	19,6 cm
	T26 CamCore, 6MP, B016, Day, Dark Gray	85258900	14,8 cm
	Hemispheric IP door station camera with 6 Megapixel Moonlight Sensor, color (day) • ONVIF S compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • HD premium fisheye lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • Max. image size: 6MP (3072 x 2048) • IP65, -30 to 50°C (-22 to 122°F) • Internal DVR: 4 GB microSD • LED lighting strips, two buttons (doorbell, outdoor light), temperature sensor, shock • detector, MxActivitySensor, MxAnalytics, ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45 and LSA), MxBus, USB • Color: Dark Gray	400 g	9,0 cm

**Mx-T26B-6N016-d****T26 CamCore, 6MP, B016, Night, Dark Gray**

Hemispheric IP door station camera with 6 Megapixel Moonlight Sensor, B/W (night)
• ONVIF S compliant Mx6 system platform (2nd generation) with H.264, MxPEG+ and M-JPEG • HD premium fisheye lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • Max. image size: 6MP (3072 x 2048) • IP65, -30 to 50°C (-22 to 122°F) • Internal DVR: 4 GB microSD • LED lighting strips, two buttons (doorbell, outdoor light), temperature sensor, shock • detector, MxActivitySensor, MxAnalytics, ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45 and LSA), MxBus, USB • Color: Dark Gray




4047438032094 19,6 cm

85258900 14,8 cm


400 g 9,0 cm

2,6 l





Info Module

	Article No. / Name / Description	EAN / HS / weight	dimen.
	MX-Info1-EXT-PW	4047438014991	19,6 cm
	Info Module With LEDs, White Standard info module for MOBOTIX IP Video Door Stations • To attach the house number and/or name • With backlighting using energy-saving and long-lasting LED technology • Powered by the door camera via MxBus • Printing service free of charge: www.mobotix.com > Support • Protection class IP65, -30 to 50°C / -22 to 122°F • Color: White	85414900 282 g	15,0 cm 9,0 cm 2,6 l
	MX-Info1-EXT-SV	4047438015035	19,6 cm
	Info Module With LEDs, Silver Standard info module for MOBOTIX IP Video Door Stations • To attach the house number and/or name • With backlighting using energy-saving and long-lasting LED technology • Powered by the door camera via MxBus • Printing service free of charge: www.mobotix.com > Support • Protection class IP65, -30 to 50°C / -22 to 122°F • Color: Silver	85414900 282 g	15,0 cm 9,0 cm 2,6 l
	MX-Info1-EXT-DG	4047438015028	19,6 cm
	Info Module With LEDs, Dark Gray Standard info module for MOBOTIX IP Video Door Stations • To attach the house number and/or name • With backlighting using energy-saving and long-lasting LED technology • Powered by the door camera via MxBus • Printing service free of charge: www.mobotix.com > Support • Protection class IP65, -30 to 50°C / -22 to 122°F • Color: Dark Gray	85414900 282 g	15,0 cm 9,0 cm 2,6 l

Access Control Accessories


	Article No. / Name / Description	EAN / HS / weight	dimen.
	Mx-A-FrogDisplay	4047438041324	14,0 cm
	frogblue Display Indoor Station	85285291	13,0 cm
	frogblue Display for MOBOTIX Doorstation T26	220 g	6,0 cm
			1,1 l

Building Automation Accessories

	Article No. / Name / Description	EAN / HS / weight	dimen.
	MX-AdminCard1 Admin RFID Transponder Card (Red) For system configuration IP Video Door Station via KeypadRFID and BellRFID • Type/encryption: MIFARE DESFire EV1 3K3DES/AES	4047438015288 85235200 2 g	8,5 cm 5,5 cm 0,1 cm 0,0 l
	MX-UserCard1 User RFID Transponder Card (Blue) For keyless entry via with KeypadRFID or BellRFID (IP video door station) • Type/encryption: MIFARE DESFire EV1 3K3DES/AES	4047438015295 85235200 2 g	8,5 cm 5,5 cm 0,1 cm 0,0 l
	MX-OPT-IO1 Extended Terminal Board (IO Module) Suitable for: T2x, delivers extended connection options for the door station (e.g., doorbell buttons, light, garage door opener, etc.) • Connect the IO Module to the camera module via MxBus, which connects it to the network. It has eight physical signal inputs that allow it to distinguish in AC operation between a pending full-wave and half-wave. This makes it possible to connect two switches to each signal input terminal so that 16 button inputs are made available. The inputs can be used for, e.g., bell buttons. The outputs can be used for external devices such as a doorbell, or for outdoor lights or garage door openers (via a power relay).	4047438013307 85299065 86 g	9,8 cm 7,5 cm 9,0 cm 0,7 l
	MX-OPT-IO2 Ethernet Terminal Board Suitable for: T2x • The Ethernet terminal board is used to connect the door station for the versions without Mx2wire+ technology. It securely connects the camera module with the 8 connected wires of the network patch cable via RJ45 connector. The Ethernet terminal board is screwed on to the housing (on-wall or in-wall) behind the camera module	4047438014786 85299065 60 g	9,8 cm 7,5 cm 9,0 cm 0,7 l

Frames & Housings

	Article No. / Name / Description	EAN / HS / weight	dimen.
	Mx-OPT-Box-1-EXT-IN-US Single In-Wall-Housing (USA version)	4047438034463	14,5 cm
	Suitable for: 1 module, outdoors • The blue housing is firmly connected to the subsurface or brick work. It can also be used to ensure easy installation in cavities: Drill opening, position housing and screw tightly in place; the retaining wings, which automatically swing out, secure the housing, while the plastic bars at the edge of the housing prevent it from sliding into the cavity. • Required flushmounting opening: 117 x 129 mm (width x height) • Permissible wall thickness for cavity installation: 7 to 27 mm	90079100	13,5 cm
		186 g	3,5 cm
			0,7 l
	Mx-OPT-Box-2-EXT-IN-US Double In-Wall-Housing (USA version)	4047438034470	23,5 cm
	Suitable for: 2 modules, outdoors • The blue housing is firmly connected to the subsurface or brick work. It can also be used to ensure easy installation in cavities: Drill opening, position housing and screw tightly in place; the retaining wings, which automatically swing out, secure the housing, while the plastic bars at the edge of the housing prevent it from sliding into the cavity. • Required flushmounting opening: 117 x 218 mm (width x height) • Permissible wall thickness for cavity installation: 7 to 27 mm	90079100	13,5 cm
		270 g	3,5 cm
			1,1 l
	Mx-OPT-Box-3-EXT-IN-US Triple In-Wall-Housing (USA version)	4047438034487	33,5 cm
	Suitable for: 3 modules, outdoors • The blue housing is firmly connected to the subsurface or brick work. It can also be used to ensure easy installation in cavities: Drill opening, position housing and screw tightly in place; the retaining wings, which automatically swing out, secure the housing, while the plastic bars at the edge of the housing prevent it from sliding into the cavity. • Required flushmounting opening: 117 x 318 mm (width x height) • Permissible wall thickness for cavity installation: 7 to 27 mm	90079100	13,5 cm
		362 g	3,5 cm
			1,6 l
	MX-OPT-Frame-1-EXT-PW Single Frame, White	4047438014892	13,5 cm
	Suitable for: 1 module, outdoors • Integrated electromagnetic theft protection • Includes special key for module unlocking, housing gasket and installation material • Dimensions: 131 x 143 x 18 mm (W x H x D) • Color: White	90079100	14,5 cm
		268 g	5,5 cm
			1,1 l
	MX-OPT-Frame-1-EXT-SV Single Frame, Silver	4047438014939	13,5 cm
	Suitable for: 1 module, outdoors • Integrated electromagnetic anti-theft protection • Includes special key for module unlocking, housing gasket and installation material • Dimensions: 131 x 143 x 18 mm (W x H x D) • Color: Silver	90079100	14,5 cm
		268 g	5,5 cm
			1,1 l

**MX-OPT-Frame-1-EXT-DG****Single Frame, Dark Gray**

Suitable for: 1 module, outdoors • Integrated electromagnetic theft protection • Includes special key for module unlocking, housing gasket and installation material • Dimensions: 131 x 143 x 18 mm (W x H x D) • Color: Dark Gray

4047438014922	13,5 cm
90079100	14,5 cm
268 g	5,5 cm
	1,1 l

**MX-OPT-Box-1-EXT-ON-PW****Single On-Wall-Housing, White**

Suitable for: 1 module, outdoors • Metal-reinforced housing: 126 x 138 x 31 mm (W x H x D) • Color: White

4047438015202	14,5 cm
90079100	13,5 cm
286 g	3,5 cm
	0,7 l

**MX-OPT-Box-1-EXT-ON-SV****Single On-Wall-Housing, Silver**

Suitable for: 1 module, outdoors • Metal-reinforced housing: 126 x 138 x 31 mm (W x H x D) • Color: Silver

4047438015240	14,5 cm
90079100	13,5 cm
286 g	3,5 cm
	0,7 l

**MX-OPT-Box-1-EXT-ON-DG****Single On-Wall-Housing, Dark Gray**


Suitable for: 1 module, outdoors • Metal-reinforced housing: 126 x 138 x 31 mm (W x H x D) • Color: Dark Gray

4047438015233	14,5 cm
90079100	13,5 cm
286 g	5,0 cm
	1,0 l

**MX-OPT-Box-1-EXT-IN****Single In-Wall-Housing**


Suitable for: 1 module, outdoors • The blue housing is firmly connected to the subsurface or brick work. It can also be used to ensure easy installation in cavities: Drill opening, position housing and screw tightly in place; the retaining wings, which automatically swing out, secure the housing, while the plastic bars at the edge of the housing prevent it from sliding into the cavity. • Required flushmounting opening: 117 x 129 mm (width x height) • Permissible wall thickness for cavity installation: 7 to 27 mm

4047438015271	14,5 cm
90079100	13,5 cm
186 g	3,5 cm
	0,7 l

**MX-OPT-Frame-2-EXT-PW****Double Frame, White**


Suitable for: 2 modules, outdoors • Integrated electromagnetic theft protection • Includes special key for module unlocking, housing gasket and installation material • Dimensions: 131 x 233 x 18 mm (W x H x D) • Color: White

4047438014847	23,5 cm
90079100	13,5 cm
333 g	3,5 cm
	1,1 l

**MX-OPT-Frame-2-EXT-SV****Double Frame, Silver**

Suitable for: 2 modules, outdoors • Integrated electromagnetic anti-theft protection
 • Includes special key for module unlocking, housing gasket and installation material
 • Dimensions: 131 x 233 x 18 mm (W x H x D) • Color: Silver

4047438014885	23,5 cm
90079100	13,5 cm
333 g	3,5 cm
	1,1 l

**MX-OPT-Frame-2-EXT-DG****Double Frame, Dark Gray**

Suitable for: 2 modules, outdoors • Integrated electromagnetic theft protection •
 Includes special key for module unlocking, housing gasket and installation material •
 Dimensions: 131 x 233 x 18 mm (W x H x D) • Color: Dark Gray

4047438014878	23,5 cm
90079100	13,5 cm
333 g	5,0 cm
	1,6 l

**MX-OPT-Box-2-EXT-ON-PW****Double On-Wall-Housing, White**

Suitable for: 2 modules, outdoors • Metal-reinforced housing: 126 x 327 x 31 mm (W x H x D) • Color: White

4047438015158	23,5 cm
90079100	13,5 cm
430 g	3,5 cm
	1,1 l

**MX-OPT-Box-2-EXT-ON-SV****Double On-Wall-Housing, Silver**


Suitable for: 2 modules, outdoors • Metal-reinforced housing: 126 x 327 x 31 mm (W x H x D) • Color: Silver

4047438015196	23,5 cm
90079100	13,5 cm
430 g	3,5 cm
	1,1 l

**MX-OPT-Box-2-EXT-ON-DG****Double On-Wall-Housing, Dark Gray**

Suitable for: 2 modules, outdoors • Metal-reinforced housing: 126 x 327 x 31 mm (W x H x D) • Color: Dark Gray

4047438015189	23,5 cm
90079100	13,5 cm
430 g	3,0 cm
	1,0 l

**MX-OPT-Box-2-EXT-IN****Double In-Wall-Housing**


Suitable for: 2 modules, outdoors • The blue housing is firmly connected to the subsurface or brick work. It can also be used to ensure easy installation in cavities: Drill opening, position housing and screw tightly in place; the retaining wings, which automatically swing out, secure the housing, while the plastic bars at the edge of the housing prevent it from sliding into the cavity. • Required flushmounting opening: 117 x 218 mm (width x height) • Permissible wall thickness for cavity installation: 7 to 27 mm

4047438015264	23,5 cm
90079100	13,5 cm
270 g	3,5 cm
	1,1 l

**MX-OPT-Frame-3-EXT-PW****Triple Frame, White**


Suitable for: 3 modules, outdoors • Integrated electromagnetic theft protection • Includes special key for module unlocking, housing gasket and installation material • Dimensions: 131 x 333 x 18 mm (W x H x D) • Color: White

4047438014793	33,5 cm
90079100	13,5 cm
426 g	5,5 cm
	2,5 l

**MX-OPT-Frame-3-EXT-SV****Triple Frame, Silver**

Suitable for: 3 modules, outdoors • Integrated electromagnetic anti-theft protection • Includes special key for module unlocking, housing gasket and installation material • Dimensions: 131 x 333 x 18 mm (W x H x D) • Color: Silver

4047438014830	33,5 cm
90079100	13,5 cm
426 g	5,5 cm
	2,5 l

**MX-OPT-Frame-3-EXT-DG****Triple Frame, Dark Gray**

Suitable for: 3 modules, outdoors • Integrated electromagnetic theft protection • Includes special key for module unlocking, housing gasket and installation material • Dimensions: 131 x 333 x 18 mm (W x H x D) • Color: Dark Gray

4047438014823	33,5 cm
90079100	13,5 cm
426 g	5,0 cm
	2,3 l

**MX-OPT-Box-3-EXT-ON-PW****Triple On-Wall-Housing, White**

Suitable for: 3 modules, outdoors • Metal-reinforced housing: 126 x 327 x 31 mm (W x H x D) • Color: White

4047438015103	33,5 cm
90079100	13,5 cm
574 g	3,5 cm
	1,6 l

**MX-OPT-Box-3-EXT-ON-SV****Triple On-Wall-Housing, Silver**

Suitable for: 3 modules, outdoors • Metal-reinforced housing: 126 x 327 x 31 mm (W x H x D) • Color: Silver

4047438015141	33,5 cm
90079100	13,5 cm
574 g	3,5 cm
	1,6 l

**MX-OPT-Box-3-EXT-ON-DG****Triple On-Wall-Housing, Dark Gray**

Suitable for: 3 modules, outdoors • Metal-reinforced housing: 126 x 327 x 31 mm (W x H x D) • Color: Dark Gray

4047438015134	33,5 cm
90079100	13,5 cm
574 g	3,0 cm
	1,4 l

**MX-OPT-Box-3-EXT-IN****Triple In-Wall-Housing**


Suitable for: 3 modules, outdoors • The blue housing is firmly connected to the subsurface or brick work. It can also be used to ensure easy installation in cavities: Drill opening, position housing and screw tightly in place; the retaining wings, which automatically swing out, secure the housing, while the plastic bars at the edge of the housing prevent it from sliding into the cavity. • Required flushmounting opening: 117 x 318 mm (width x height) • Permissible wall thickness for cavity installation: 7 to 27 mm

4047438015257	33,5 cm
90079100	13,5 cm
362 g	3,5 cm
	1,6 l

**MX-OPT-FlatMount-EXT-PW****FlatMount Frame, white**

For flush-mounting of MxDisplay and door station modules in wall cavities • Integrated electromagnetic theft protection • W x H: 124 x 124 mm • Color: white

4047438019811	14,7 cm
90079100	13,7 cm
190 g	5,5 cm
	1,1 l

**MX-OPT-FlatMount-Box-EXT-IN****FlatMount Frame In-Wall Housing**

In-wall housing for FlatMount Frame • To be affixed securely with the subsurface or brick work • Size of cavity for flush-mounting (W x H x D): 112 x 112 x 60 mm

4047438019866	13,8 cm
90079100	6,5 cm
130 g	13,8 cm
	1,2 l






Software & Services







BeyondHumanVision







MOBOTIX

MOBOTIX HUB Video Management System

MOBOTIX HUB

	Article No. / Name / Description	EAN / HS / weight	dimen.
	Mx-HUB-L1-BAS L1 Base License (8 Device Licenses incl) MOBOTIX HUB L1 is available as a free version. The license includes the basic license and device license with the support of up to eight cameras	4047438039208 g	cm cm cm l
	Mx-HUB-L2-BAS MOBOTIX HUB L2 Base License (BL) MOBOTIX HUB L2 for smaller companies with one location manages up to 48 surveillance cameras	4047438038584 g	cm cm cm l
	Mx-HUB-L2-DEV MOBOTIX HUB L2 Device License (DL) Device licenses for MOBOTIX HUB L2. Up to 48 device licenses can be linked to the HUB L2	4047438038591 g	cm cm cm l
	Mx-HUB-L2-1MDEV 1 Month Advanced Services for MOBOTIX HUB L2 Device 1 month MOBOTIX HUB L2 Advanced Services (Device license). For monthly extension of the MOBOTIX HUB L2 Advanced Service for 1, 2, 3 and 5 years.	4047438039215 g	cm cm cm l
	Mx-HUB-L2-1YDEV One year MOBOTIX HUB Advanced Services for L2 Device 1 Year MOBOTIX HUB L2 Advanced Service provides one year of scheduled product updates that make the product more secure, efficient and powerful, and also provides the greatest possible return on your original HUB investment when upgrading to a more advanced HUB solution.	4047438038607 g	cm cm cm l

	<p>Mx-HUB-L2-2YDEV</p> <p>Two years MOBOTIX HUB Advanced Services for L2 Device</p> <p>2 Year MOBOTIX HUB L2 Advanced Service provides two years of scheduled product updates that make the product more secure, efficient and powerful, and also provides the greatest possible return on your original HUB investment when upgrading to a more advanced HUB solution.</p>	4047438038614	cm
		g	cm
			l
	<p>Mx-HUB-L2-3YDEV</p> <p>Three years MOBOTIX HUB Advanced Services for L2 Device</p> <p>3 Year MOBOTIX HUB L2 Advanced Service provides three years of scheduled product updates that make the product more secure, efficient and powerful, and also provides the greatest possible return on your original HUB investment when upgrading to a more advanced HUB solution.</p>	4047438038621	cm
		g	cm
			l
	<p>Mx-HUB-L2-5YDEV</p> <p>Five years MOBOTIX HUB Advanced Services for L2 Device</p> <p>5 Year MOBOTIX HUB L2 Advanced Service provides five years of scheduled product updates that make the product more secure, efficient and powerful, and also provides the greatest possible return on your original HUB investment when upgrading to a more advanced HUB solution.</p>	4047438038638	cm
		g	cm
			l
	<p>Mx-HUB-L2-3YOPT-DEV</p> <p>Three years opt-in MOBOTIX HUB Advanced Services for L2</p> <p>The MOBOTIX HUB Advanced Service Opt-In for HUB L2 device licenses, provides three years of access to firmware updates and trade-in options for MOBOTIX HUB L2 software if the previous Advanced Service has expired or has not been purchased within 30 days after ordering a HUB product.</p>	4047438039031	cm
		g	cm
			l
	<p>Mx-HUB-L2-UP-BASWO</p> <p>Version Upgrade HUB L2 BL w/o ASP</p> <p>Software update for MOBOTIX HUB L2 base licenses that are not in possession of an Advanced Service Product.</p>	4047438039277	cm
		g	cm
			l
	<p>Mx-HUB-L2-UP-DEVWO</p> <p>Version Upgrade HUB L2 DL w/o ASP</p> <p>Software update for MOBOTIX HUB L2 device licenses that are not in possession of an Advanced Service Product.</p>	4047438039284	cm
		g	cm
			l

	<p>Mx-HUB-L3-BAS MOBOTIX HUB L3 Base License (BL) MOBOTIX HUB L3 is the solution for medium-sized companies. The number of cameras is unlimited and can be distributed across multiple locations.</p>	4047438038645	cm cm cm l
	<p>Mx-HUB-L3-DEV MOBOTIX HUB L3 Device License (DL) Device licenses for MOBOTIX HUB L3. Unlimited number of devices can be integrated into one L3 installation.</p>	4047438038652	cm cm cm l
	<p>Mx-HUB-L3-1MDEV 1 Month Advanced Services for MOBOTIX HUB L3 Device 1 month MOBOTIX HUB L3 Advanced Services (Device license). For monthly extension of the MOBOTIX HUB L3 Advanced Service for 1, 2, 3 and 5 years.</p>	4047438039222	cm cm cm l
	<p>Mx-HUB-L3-1YDEV One year MOBOTIX HUB Advanced Services for L3 Device 1 Year MOBOTIX HUB L3 Advanced Service provides one year of scheduled product updates that make the product more secure, efficient and powerful, and also provides the greatest possible return on your original HUB investment when upgrading to a more advanced HUB solution.</p>	4047438038669	cm cm cm l
	<p>Mx-HUB-L3-2YDEV Two years MOBOTIX HUB Advanced Services for L3 Device 2 Year MOBOTIX HUB L3 Advanced Service provides two years of scheduled product updates that make the product more secure, efficient and powerful, and also provides the greatest possible return on your original HUB investment when upgrading to a more advanced HUB solution.</p>	4047438038676	cm cm cm l
	<p>Mx-HUB-L3-3YDEV Three years MOBOTIX HUB Advanced Services for L3 Device 3 Year MOBOTIX HUB L3 Advanced Service provides three years of scheduled product updates that make the product more secure, efficient and powerful, and also provides the greatest possible return on your original HUB investment when upgrading to a more advanced HUB solution.</p>	4047438038683	cm cm cm l



Mx-HUB-L3-5YDEV

Five years MOBOTIX HUB Advanced Services for L3 Device

5 Year MOBOTIX HUB L3 Advanced Service provides five years of scheduled product updates that make the product more secure, efficient and powerful, and also provides the greatest possible return on your original HUB investment when upgrading to a more advanced HUB solution.

4047438038690

g

cm
cm
cm
l



Mx-HUB-L3-3YOPT-DEV

Three years opt-in MOBOTIX HUB Advanced Services for L3

The MOBOTIX HUB Advanced Service Opt-In for HUB L3 device licenses, provides three years of access to firmware updates and trade-in options for MOBOTIX HUB L3 software if the previous Advanced Service has expired or has not been purchased within 30 days after ordering a HUB product.

4047438039048

g

cm
cm
cm
l



Mx-HUB-TRAD-BAS-L2-L3-W

Trade-in BL L2->L3 w/ ASP

Product Upgrade of the base license from MOBOTIX HUB L2 to MOBOTIX HUB L3, which are in possession of an Advanced Service Product (ASP).

4047438039369

g

cm
cm
cm
l



Mx-HUB-TRAD-DEV-L2-L3-W

Trade-in DL L2->L3 w/ ASP

Product Upgrade of the device license from MOBOTIX HUB L2 to MOBOTIX HUB L3, which are in possession of an Advanced Service Product (ASP).

4047438039376

g

cm
cm
cm
l



Mx-HUB-TRAD-BAS-L2-L3-WO

Trade-in BL L2->L3 w/o ASP

Product Upgrade of the base license from MOBOTIX HUB L2 to MOBOTIX HUB L3, which are not in possession of an Advanced Service Product (ASP).

4047438039383

g

cm
cm
cm
l



Mx-HUB-TRAD-DEV-L2-L3-WO







Trade-in DL L2->L3 w/o ASP






Product Upgrade of the device license from MOBOTIX HUB L2 to MOBOTIX HUB L3, which are not in possession of an Advanced Service Product (ASP).







4047438039390







g







cm
cm
cm
l







	<p>Mx-HUB-L3-UP-BASWO Version Upgrade HUB L3 BL w/o ASP Software update for MOBOTIX HUB L3 base licenses that are not in possession of an Advanced Service Product.</p>	4047438039291	cm cm cm l
	<p>Mx-HUB-L3-UP-DEVWO Version Upgrade HUB L3 DL w/o ASP Software update for MOBOTIX HUB L3 device licenses that are not in possession of an Advanced Service Product.</p>	4047438039307	cm cm cm l
	<p>Mx-HUB-L4-BAS MOBOTIX HUB L4 Base License (BL) MOBOTIX HUB L4 is made for medium and large installations. In addition to the features of MOBOTIX HUB L3, L4 provides access to failover recording servers in case of server failure. The use of MOBOTIX HUB L4 requires an Advanced Service (base + devices) of at least one year.</p>	4047438038706	cm cm cm l
	<p>Mx-HUB-L4-DEV MOBOTIX HUB L4 Device License (DL) Device licenses for MOBOTIX HUB L4. Unlimited number of devices can be integrated into one L4 installation. The use of MOBOTIX HUB L4 requires an Advanced Service (base + devices) of at least one year.</p>	4047438038713	cm cm cm l
	<p>Mx-HUB-L4-1MBAS 1 Month Advanced Services for MOBOTIX HUB L4 Base 1 month MOBOTIX HUB L4 Advanced Services (basic license). For monthly extension of the MOBOTIX HUB L4 Advanced Service for 1, 2, 3 and 5 years.</p>	4047438039239	cm cm cm l
	<p>Mx-HUB-L4-1YBAS One year MOBOTIX HUB Advanced Services for L4 Base 1 year MOBOTIX HUB L4 Advanced Service (base license) provides regular product updates over one year, making the product more secure, efficient and powerful, and also offers the greatest possible return on your original HUB investment when upgrading to a more advanced HUB solution.</p>	4047438038720	cm cm cm l







	<p>Mx-HUB-L4-2YBAS</p> <p>Two years MOBOTIX HUB Advanced Services for L4 Base</p> <p>2 years MOBOTIX HUB L4 Advanced Service (base license) provides periodic product updates over 2 years that make the product more secure, efficient and powerful, and also provides the greatest possible return on your original HUB investment when upgrading to a more advanced HUB solution.</p>	<p>4047438038737</p> <p>g</p>	<p>cm</p> <p>cm</p> <p>cm</p> <p>l</p>
	<p>Mx-HUB-L4-3YBAS</p> <p>Three years MOBOTIX HUB Advanced Services for L4 Base</p> <p>3 years MOBOTIX HUB L4 Advanced Service (base license) provides periodic product updates over 3 years that make the product more secure, efficient and powerful, and also provides the greatest possible return on your original HUB investment when upgrading to a more advanced HUB solution.</p>	<p>4047438038744</p> <p>g</p>	<p>cm</p> <p>cm</p> <p>cm</p> <p>l</p>
	<p>Mx-HUB-L4-5YBAS</p> <p>Five years MOBOTIX HUB Advanced Services for L4 Base</p> <p>5-year MOBOTIX HUB L4 Advanced Service (base license) provides 5-year periodic product updates that make the product more secure, efficient and powerful, and also provides the greatest possible return on your original HUB investment when upgrading to a more advanced HUB solution.</p>	<p>4047438038751</p> <p>g</p>	<p>cm</p> <p>cm</p> <p>cm</p> <p>l</p>
	<p>Mx-HUB-L4-3YOPT-BAS</p> <p>Three years opt-in MOBOTIX HUB Advanced Services for L4</p> <p>The MOBOTIX HUB Advanced Service Opt-In for HUB L4 base licenses, provides three years of access to firmware updates and trade-in options for MOBOTIX HUB L4 software if the previous Advanced Service has expired or has not been purchased within 30 days after ordering a HUB product.</p>	<p>4047438039055</p> <p>g</p>	<p>cm</p> <p>cm</p> <p>cm</p> <p>l</p>
	<p>Mx-HUB-L4-1MDEV</p> <p>1 Month Advanced Services for MOBOTIX HUB L4 Device</p> <p>1 month MOBOTIX HUB L4 Advanced Services (Device license). For monthly extension of the MOBOTIX HUB L4 Advanced Service for 1, 2, 3 and 5 years.</p>	<p>4047438039246</p> <p>g</p>	<p>cm</p> <p>cm</p> <p>cm</p> <p>l</p>
	<p>Mx-HUB-L4-1YDEV</p> <p>One year MOBOTIX HUB Advanced Services for L4 Device</p> <p>1 year MOBOTIX HUB L4 Advanced Service (Device license) provides regular product updates over one year, making the product more secure, efficient and powerful, and also offers the greatest possible return on your original HUB investment when upgrading to a more advanced HUB solution</p>	<p>4047438038768</p> <p>g</p>	<p>cm</p> <p>cm</p> <p>cm</p> <p>l</p>

	<p>Mx-HUB-L4-2YDEV Two years MOBOTIX HUB Advanced Services for L4 Device 2 years MOBOTIX HUB L4 Advanced Service (Device license) provides periodic product updates over 2 years that make the product more secure, efficient and powerful, and also provides the greatest possible return on your original HUB investment when upgrading to a more advanced HUB solution.</p>	4047438038775	cm cm g cm l
	<p>Mx-HUB-L4-3YDEV Three years MOBOTIX HUB Advanced Services for L4 Device 3 years MOBOTIX HUB L4 Advanced Service (Device license) provides periodic product updates over 3 years that make the product more secure, efficient and powerful, and also provides the greatest possible return on your original HUB investment when upgrading to a more advanced HUB solution.</p>	4047438038782	cm cm g cm l
	<p>Mx-HUB-L4-5YDEV Five years MOBOTIX HUB Advanced Services for L4 Device 5-year MOBOTIX HUB L4 Advanced Service (Device license) provides 5-year periodic product updates that make the product more secure, efficient and powerful, and also provides the greatest possible return on your original HUB investment when upgrading to a more advanced HUB solution.</p>	4047438038799	cm cm g cm l
	<p>Mx-HUB-L4-3YOPT-DEV Three years opt-in MOBOTIX HUB Advanced Services for L4 The MOBOTIX HUB Advanced Service Opt-In for HUB L4 device licenses, provides three years of access to firmware updates and trade-in options for MOBOTIX HUB L4 software if the previous Advanced Service has expired or has not been purchased within 30 days after ordering a HUB product.</p>	4047438039062	cm cm g cm l
	<p>Mx-HUB-TRAD-BAS-L2-L4-W Trade-in BL L2->L4 w/ ASP Product Upgrade of the base license from MOBOTIX HUB L2 to MOBOTIX HUB L4, which are in possession of an Advanced Service Product (ASP).</p>	4047438039406	cm cm g cm l
	<p>Mx-HUB-TRAD-DEV-L2-L4-W Trade-in DL L2->L4 w/ ASP Product Upgrade of the device license from MOBOTIX HUB L2 to MOBOTIX HUB L4, which are in possession of an Advanced Service Product (ASP).</p>	4047438039413	cm cm g cm l

	<p>Mx-HUB-TRAD-BAS-L2-L4-WO Trade-in BL L2->L4 w/o ASP Product Upgrade of the base license from MOBOTIX HUB L2 to MOBOTIX HUB L4, which are not in possession of an Advanced Service Product (ASP).</p>	4047438039420	cm cm cm l
	<p>Mx-HUB-TRAD-DEV-L2-L4-WO Trade-in DL L2->L4 w/o ASP Product Upgrade of the device license from MOBOTIX HUB L2 to MOBOTIX HUB L4, which are not in possession of an Advanced Service Product (ASP).</p>	4047438039437	cm cm cm l
	<p>Mx-HUB-TRAD-BAS-L3-L4-W Trade-in BL L3->L4 w/ ASP Product Upgrade of the base license from MOBOTIX HUB L3 to MOBOTIX HUB L4, which are in possession of an Advanced Service Product (ASP).</p>	4047438039444	cm cm cm l
	<p>Mx-HUB-TRAD-DEV-L3-L4-W Trade-in DL L3->L4 w/ ASP Product Upgrade of the device license from MOBOTIX HUB L3 to MOBOTIX HUB L4, which are in possession of an Advanced Service Product (ASP).</p>	4047438039451	cm cm cm l
	<p>Mx-HUB-TRAD-BAS-L3-L4-WO Trade-in BL L3->L4 w/o ASP Product Upgrade of the base license from MOBOTIX HUB L3 to MOBOTIX HUB L4, which are not in possession of an Advanced Service Product (ASP).</p>	4047438039468	cm cm cm l
	<p>Mx-HUB-TRAD-DEV-L3-L4-WO Trade-in DL L3->L4 w/o ASP Product Upgrade of the device license from MOBOTIX HUB L3 to MOBOTIX HUB L4, which are not in possession of an Advanced Service Product (ASP).</p>	4047438039475	cm cm cm l

	<p>Mx-HUB-L4-UP-BASWO Version Upgrade HUB L4 BL w/o ASP Software update for MOBOTIX HUB L4 base licenses that are not in possession of an Advanced Service Product.</p>	4047438039314	cm cm cm l
	<p>Mx-HUB-L4-UP-DEVWO Version Upgrade HUB L4 DL w/o ASP Software update for MOBOTIX HUB L4 device licenses that are not in possession of an Advanced Service Product.</p>	4047438039321	cm cm cm l
	<p>Mx-HUB-L5-BAS MOBOTIX HUB L5 Base License (BL) MOBOTIX HUB L5 is the video management platform for large and extremely security-oriented applications. In addition to centralized management of all servers, cameras and users across multiple sites, L5 also includes control for a professional video wall as standard. The use of MOBOTIX HUB L5 requires an Advanced Service (base + devices) of at least one year.</p>	4047438038805	cm cm cm l
	<p>Mx-HUB-L5-DEV MOBOTIX HUB L5 Device License (DL) Device licenses for MOBOTIX HUB L5. Unlimited number of devices can be integrated into one L5 installation.</p>	4047438038812	cm cm cm l
	<p>Mx-HUB-L5-INTCON MOBOTIX HUB Interconnect Device License (DL) Interconnect licenses for MOBOTIX HUB L5. Unlimited number of Interconnect licenses can be used into one L5 installation.</p>	4047438038829	cm cm cm l
	<p>Mx-HUB-L5-1MBAS 1 Month Advanced Services for MOBOTIX HUB L5 Base 1 month MOBOTIX HUB L5 Advanced Services (basic license). For monthly extension of the MOBOTIX HUB L5 Advanced Service for 1, 2, 3 and 5 years.</p>	4047438039253	cm cm cm l

	<p>Mx-HUB-L5-1YBAS</p> <p>One year MOBOTIX HUB Advanced Services for L5 Base</p> <p>1 year MOBOTIX HUB L5 Advanced Service (base license) provides regular product updates over one year, making the product more secure, efficient and powerful, and also offers the greatest possible return on your original HUB investment when upgrading to a more advanced HUB solution.</p>	4047438038836	cm
		g	cm
			l
	<p>Mx-HUB-L5-2YBAS</p> <p>Two years MOBOTIX HUB Advanced Services for L5 Base</p> <p>2 years MOBOTIX HUB L5 Advanced Service (base license) provides periodic product updates over 2 years that make the product more secure, efficient and powerful, and also provides the greatest possible return on your original HUB investment when upgrading to a more advanced HUB solution.</p>	4047438038843	cm
		g	cm
			l
	<p>Mx-HUB-L5-3YBAS</p> <p>Three years MOBOTIX HUB Advanced Services for L5 Base</p> <p>3 years MOBOTIX HUB L5 Advanced Service (base license) provides periodic product updates over 3 years that make the product more secure, efficient and powerful, and also provides the greatest possible return on your original HUB investment when upgrading to a more advanced HUB solution.</p>	4047438038850	cm
		g	cm
			l
	<p>Mx-HUB-L5-5YBAS</p> <p>Five years MOBOTIX HUB Advanced Services for L5 Base</p> <p>5-year MOBOTIX HUB L5 Advanced Service (base license) provides 5-year periodic product updates that make the product more secure, efficient and powerful, and also provides the greatest possible return on your original HUB investment when upgrading to a more advanced HUB solution.</p>	4047438038867	cm
		g	cm
			l
	<p>Mx-HUB-L5-3YOPT-BAS</p> <p>Three years opt-in MOBOTIX HUB Advanced Services for L5</p> <p>The MOBOTIX HUB Advanced Service Opt-In for HUB L5 base licenses, provides three years of access to firmware updates and trade-in options for MOBOTIX HUB L5 software if the previous Advanced Service has expired or has not been purchased within 30 days after ordering a HUB product.</p>	4047438039079	cm
		g	cm
			l
	<p>Mx-HUB-L5-1MDEV</p> <p>1 Month Advanced Services for MOBOTIX HUB L5 Device</p> <p>1 month MOBOTIX HUB L5 Advanced Services (Device license). For monthly extension of the MOBOTIX HUB L5 Advanced Service for 1, 2, 3 and 5 years.</p>	4047438039260	cm
		g	cm
			l

	<p>Mx-HUB-L5-1YDEV</p> <p>One year MOBOTIX HUB Advanced Services for L5 Device</p> <p>1 year MOBOTIX HUB L5 Advanced Service (Device license) provides regular product updates over one year, making the product more secure, efficient and powerful, and also offers the greatest possible return on your original HUB investment when upgrading to a more advanced HUB solution</p>	4047438038874	cm
		g	cm
			l
	<p>Mx-HUB-L5-2YDEV</p> <p>Two years MOBOTIX HUB Advanced Services for L5 Device</p> <p>2 years MOBOTIX HUB L5 Advanced Service (Device license) provides periodic product updates over 2 years that make the product more secure, efficient and powerful, and also provides the greatest possible return on your original HUB investment when upgrading to a more advanced HUB solution</p>	4047438038881	cm
		g	cm
			l
	<p>Mx-HUB-L5-3YDEV</p> <p>Three years MOBOTIX HUB Advanced Services for L5 Device</p> <p>3 years MOBOTIX HUB L5 Advanced Service (Device license) provides periodic product updates over 3 years that make the product more secure, efficient and powerful, and also provides the greatest possible return on your original HUB investment when upgrading to a more advanced HUB solution</p>	4047438038898	cm
		g	cm
			l
	<p>Mx-HUB-L5-5YDEV</p> <p>Five years MOBOTIX HUB Advanced Services for L5 Device</p> <p>5-year MOBOTIX HUB L5 Advanced Service (Device license) provides 5-year periodic product updates that make the product more secure, efficient and powerful, and also provides the greatest possible return on your original HUB investment when upgrading to a more advanced HUB solution</p>	4047438038904	cm
		g	cm
			l
	<p>Mx-HUB-L5-3YOPT-DEV</p> <p>Three years opt-in MOBOTIX HUB Advanced Services for L5</p> <p>The MOBOTIX HUB Advanced Service Opt-In for HUB L5 device licenses, provides three years of access to firmware updates and trade-in options for MOBOTIX HUB L5 software if the previous Advanced Service has expired or has not been purchased within 30 days after ordering a HUB product.</p>	4047438039086	cm
		g	cm
			l
	<p>Mx-HUB-TRAD-BAS-L2-L5-W</p> <p>Trade-in BL L2->L5 w/ ASP</p> <p>Product Upgrade of the base license from MOBOTIX HUB L2 to MOBOTIX HUB L5, which are in possession of an Advanced Service Product (ASP).</p>	4047438039482	cm
		g	cm
			l

**Mx-HUB-TRAD-DEV-L2-L5-W**

4047438039499

cm

Trade-in DL L2->L5 w/ ASP

Product Upgrade of the device license from MOBOTIX HUB L2 to MOBOTIX HUB L5, which are in possession of an Advanced Service Product (ASP).

g

cm

cm
l**Mx-HUB-TRAD-BAS-L2-L5-WO**

4047438039505

cm

Trade-in BL L2->L5 w/o ASP

Product Upgrade of the base license from MOBOTIX HUB L2 to MOBOTIX HUB L5, which are not in possession of an Advanced Service Product (ASP).

g

cm

cm
l**Mx-HUB-TRAD-DEV-L2-L5-WO**

4047438039512

cm

Trade-in DL L2->L5 w/o ASP

Product Upgrade of the device license from MOBOTIX HUB L2 to MOBOTIX HUB L5, which are not in possession of an Advanced Service Product (ASP).

g

cm

cm
l**Mx-HUB-TRAD-BAS-L3-L5-W**

4047438039529

cm

Trade-in BL L3->L5 w/ ASP

Product Upgrade of the base license from MOBOTIX HUB L3 to MOBOTIX HUB L5, which are in possession of an Advanced Service Product (ASP).

g

cm

cm
l**Mx-HUB-TRAD-DEV-L3-L5-W**

4047438039536

cm

Trade-in DL L3->L5 w/ ASP

Product Upgrade of the device license from MOBOTIX HUB L3 to MOBOTIX HUB L5, which are in possession of an Advanced Service Product (ASP).

g

cm

cm
l**Mx-HUB-TRAD-BAS-L3-L5-WO**

4047438039543

cm

Trade-in BL L3->L5 w/o ASP

Product Upgrade of the base license from MOBOTIX HUB L3 to MOBOTIX HUB L5, which are not in possession of an Advanced Service Product (ASP).

g

cm

cm
l

**Mx-HUB-TRAD-DEV-L3-L5-WO****Trade-in DL L3->L5 w/o ASP**

Product Upgrade of the device license from MOBOTIX HUB L3 to MOBOTIX HUB L5, which not are in possession of an Advanced Service Product (ASP).

4047438039550

g

cm

cm

cm

l

**Mx-HUB-TRAD-BAS-L4-L5-W****Trade-in BL L4->L5 w/ ASP**

Product Upgrade of the base license from MOBOTIX HUB L4 to MOBOTIX HUB L5, which are in possession of an Advanced Service Product (ASP).

4047438039567

g

cm

cm

cm

l

**Mx-HUB-TRAD-DEV-L4-L5-W****Trade-in DL L4->L5 w/ ASP**

Product Upgrade of the device license from MOBOTIX HUB L4 to MOBOTIX HUB L5, which are in possession of an Advanced Service Product (ASP).

4047438039574

g

cm

cm

cm

l

**Mx-HUB-TRAD-BAS-L4-L5-WO****Trade-in BL L4->L5 w/o ASP**

Product Upgrade of the base license from MOBOTIX HUB L4 to MOBOTIX HUB L5, which are not in possession of an Advanced Service Product (ASP).

4047438039581

g

cm

cm

cm

l

**Mx-HUB-TRAD-DEV-L4-L5-WO****Trade-in DL L4->L5 w/o ASP**

Product Upgrade of the device license from MOBOTIX HUB L4 to MOBOTIX HUB L5, which not are in possession of an Advanced Service Product (ASP).

4047438039598

g

cm

cm

cm

l

**Mx-HUB-L5-UP-BASWO****Version Upgrade HUB L5 BL w/o ASP**

Software update for MOBOTIX HUB L5 base licenses that are not in possession of an Advanced Service Product

4047438039338

g

cm

cm

cm

l

**Mx-HUB-L5-UP-DEVWO****Version Upgrade HUB L5 DL w/o ASP**

Software update for MOBOTIX HUB L5 device licenses that are not in possession of an Advanced Service Product

4047438039345

g

cm

cm

cm

l

**Mx-HUB-L5-UP-INTWO****Version Upgrade HUB L5 Intercon. DL w/o ASP**

Software update for MOBOTIX HUB L5 interconnect licenses that are not in possession of an Advanced Service Product

4047438039352


g

cm

cm

cm

l

**Mx-HUB-ACC-WALL****MOBOTIX HUB Video Wall Base License (BL)**

MOBOTIX HUB Video Wall is an advanced add-on video wall product that improves response time by displaying all the video data in your installation and giving a complete overview of large surveillance centers.

4047438039116


g

cm

cm

cm

l

**Mx-HUB-ACC-WALL-UP****Version Upgrade HUB Video Wall BL w/o ASP**

Software update for MOBOTIX HUB Video Wall license that are not in possession of an Advanced Service Product

4047438039604


g

cm

cm

cm

l

**Mx-HUB-ACS-BASE****MOBOTIX HUB Access Base License (BL)**

MOBOTIX HUB Access is an Add-on product that video enables physical security through integration of access control and intrusion systems

4047438039178


g

cm

cm

cm

l

**Mx-HUB-ACS-BASE-UP****Version Upgrade HUB Access BL w/o ASP**

Software update for MOBOTIX HUB Access Basic license, which are not in possession of an Advanced Service product.

4047438039611







g







cm

cm

cm

l

	Mx-HUB-ACS-DOOR MOBOTIX HUB Access Door License (DL) Device license for MOBOTIX HUB Access.	4047438039185	cm cm cm l
	Mx-HUB-ACS-DOOR-UP Version Upgrade HUB Access DL w/o ASP Software Update for MOBOTIX HUB Access Devices License, which are not in possession of an Advanced Service Product.	4047438039628	cm cm cm l
	Mx-HUB-XP-TRA-BAS Xprotect Transaction Base License Server incl. 1 Connection XProtect Transact Base Server incl. 1 Connection License. XProtect Transact video enables different types of transaction-based processes. Combining transaction data from point of sales systems, scanners, cash point machines, or similar systems with corresponding video, XProtect Transact enables real-time monitoring, exception handling and documentation of transactions.	4047438039154	cm cm cm l
	Mx-HUB-XP-TRA-BAS-UP Version Upgrade Xprotect Transaction BL w/o ASP Software Update for XProtect Transaction Base License, which are not in possession of an Advanced Service Product.	4047438039635	cm cm cm l
	Mx-HUB-XP-TRA-CON Xprotect Transaction Connection License Connection licence for Xprotect Transact.	4047438039161	cm cm cm l
	Mx-HUB-XP-TRA-CON-UP Version Upgrade Xprotect Transaction CL w/o ASP Software update for XProtect Transaction Connection license, which are not in possession of an Advanced Service Product	4047438039642	cm cm cm l

	<p>Mx-HUB-XP-LPR-BAS Xprotect LPR Base License incl. 5 Country Modules XProtect LPR Base License, incl. 5 Country Modules. XProtect LPR is license plate recognition (LPR) software that detects license plate information from any vehicle around the world and links the license plate number with video.</p>	4047438039123	cm cm g cm l
	<p>Mx-HUB-XP-LPR-BAS-UP Version Upgrade Xprotect LPR BL w/o ASP Software update for XProtect LPR Basic license, which are not in possession of an Advanced Service Product.</p>	4047438039659	cm cm g cm l
	<p>Mx-HUB-XP-LPR-DEV XProtect LPR Device License (DL) Device licence for Xprotect LPR.</p>	4047438039130	cm cm g cm l
	<p>Mx-HUB-XP-LPR-DEV-UP Version Upgrade Xprotect LPR DL w/o ASP Software update for XProtect LPR devices license, which are not in possession of an Advanced Service Product.</p>	4047438039666	cm cm g cm l
	<p>Mx-HUB-XP-LPR-CTY Xprotect LPR Country Modul Country modul for Xprotect LPR.</p>	4047438039147	cm cm g cm l
	<p>Mx-HUB-XP-LPR-CTY-UP Version Upgrade Xprotect LPR CM w/o ASP Software update for XProtect LPR Country Module not in possession of an Advanced Service Product.</p>	4047438039673	cm cm g cm l


MxManagementCenter and Additional Licences

ONVIF-compliant Video Management System

MxManagementCenter (MxMC) is a powerful, intuitive video management system for Windows and macOS systems. MxMC can be utilized for projects and security installations of all sizes and with any number of cameras or storage media. It was designed to be user-friendly, high-performing and secure.


Please follow this link for further license-related informations: <https://www.mobotix.com/de/support/download-center/software-downloads/licenz-portal>

	Article No. / Name / Description	EAN / HS / weight	dimen.
	Mx-SW-MC-ADCON-VM MxMC Advanced Config License for virtual machines (VM) Free-of-charge MOBOTIX license for using the advanced configuration with a MxMC workstation (as of MxMC 2.0) • No time limit for use, unlimited number of users per workstation • Download via external license portal (access data required) • released for virtual machines (VM)	4047438035071	0,0 cm 0,0 cm 0 9 0,0 cm 0,0 l
	Mx-SW-MC MxManagementCenter VMS For Windows/macOS Free-of-charge MOBOTIX video management software MxManagementCenter (MxMC) • Certified ONVIF conformity (Profile S) • Versions 2.2 for Windows (Windows 8 or later) or macOS (10.12 or higher) • Language packs: English, German, French, Spanish, Italian, Russian, Turkish, Portuguese, Japanese • System requirements: 2 GHz processor (min.), at least 2 GB RAM, video card with support for OpenGL V2.1 • Download free of charge: www.mobotix.com > Support > Download Center > Software Downloads > Cameras > MxManagementCenter	4047438034456	0,0 cm 0,0 cm 0 9 0,0 cm 0,0 l
	Mx-SW-MC-ADCON MxMC Advanced Config License Free-of-charge MOBOTIX license for using the advanced configuration with a MxMC workstation (as of MxMC 2.0) • No time limit for use, unlimited number of users per workstation • Download via external license portal (access data required)	4047438034197	0,0 cm 0,0 cm 0 9 0,0 cm 0,0 l
	Mx-SW-MC-STARTER MxMC Integration Starter License MOBOTIX license for the general use of H.264 with a MxMC workstation (as of MxMC 2.0) for live images, playback and/or export • Unlimited number of users per workstation • No time limit for use • One additional video channel for a third-party ONVIF-S camera included • Download via external license portal (access data required)	4047438034142	0,0 cm 0,0 cm 0 9 0,0 cm 0,0 l
	Mx-SW-MC-CHAN MxMC Integration Channel License MOBOTIX license for using an additional video channel from an external ONVIF S compliant IP camera with a MxMC workstation (as of MxMC 2.0) • No time limit for use, unlimited number of users per workstation • Download via external license portal (access data required)	4047438034159	0,0 cm 0,0 cm 0 9 0,0 cm 0,0 l

**Mx-SW-MC-SDATA****MxMC Smart Data License**

MOBOTIX license for connecting an external data source (Smart Data Source) to a MxMC workstation (as of MxMC 2.1) • No time limit for use, unlimited number of users per workstation • Download via external license portal (access data required)

4047438034449 0,0 cm
0,0 cm
0 9 0,0 cm
0,0 l

**Mx-SW-MC-POS****MxMC POS Single Cash Point License**

MOBOTIX license for connecting a cash register to a MxMC workstation (as of MxMC 1.7) • No time limit for use, unlimited number of users per workstation • Download via external license portal (access data required)

4047438031615 0,0 cm
0,0 cm
0 9 0,0 cm
0,0 l

**Mx-SW-MC-AS-1****MxMC Advanced Service License, 1 Year**

MOBOTIX license for using the advanced system service and the MxMC Health Check with a MxMC workstation (as of MxMC 2.0) • Valid for up to 64 MOBOTIX devices • Validity: 1 year/12 months • Unlimited number of users per workstation • Download via external license portal (access data required)

4047438034166 0,0 cm
0,0 cm
0 9 0,0 cm
0,0 l

**Mx-SW-MC-AS-2****MxMC Advanced Service License, 2 Years**

MOBOTIX license for using the advanced system service and the MxMC Health Check with a MxMC workstation (as of MxMC 2.0) • Valid for up to 64 MOBOTIX devices • Validity: 2 years/24 months • Unlimited number of users per workstation • Download via external license portal (access data required)

4047438034173 0,0 cm
0,0 cm
0 9 0,0 cm
0,0 l

**Mx-SW-MC-AS-5****MxMC Advanced Service License, 5 Years**

MOBOTIX license for using the advanced system service and the MxMC Health Check with a MxMC workstation (as of MxMC 2.0) • Valid for up to 64 MOBOTIX devices • Validity: 5 years/60 months • Unlimited number of users per workstation • Download via external license portal (access data required)

4047438034180 0,0 cm
0,0 cm
0 9 0,0 cm
0,0 l

Certified Apps for MOBOTIX 7

Certified Apps for MOBOTIX 7

	Article No. / Name / Description	EAN / HS / weight	dimen.
	Mx-APP-IRIS-ANO Irisity Iris Anonymization App Irisity Iris Anonymization App including the following features: • patented dynamic pixelation of people in the camera's field of view • designed to address GDPR and privacy regulations • Configurable option to force switch to black/white image to ensure maximum privacy • applicable in indoor and outdoor camera operation • pixelation of persons from a minimum height of 20 pixels	4047438045230	cm cm g cm l
	<hr/>		
	Mx-APP-IRIS-C-INT Irisity Iris Core Intrusion App Irisity Iris Core Intrusion App including the following features: • Detects the intrusion of objects of interest into user-defined detection zones / areas • Designed for reliable detection of people and vehicles covering only small portions of the field of view • Reduction of false alarms to a minimum by filtering out non-critical motion (e.g. trees, clouds, etc.) • simultaneous detection on one or more image sensors • MOBOTIX events via MxMessageSystem • Consolidated event search via MxManagementCenter Smart Data Interface and / or MOBOTIX HUB	4047438040693	cm cm g cm l
	<hr/>		
	Mx-APP-MX-ARA MOBOTIX Advanced Radiometry App MOBOTIX Advanced Radiometry App including the following features: • Extension of the temperature measurement functions of MOBOTIX Thermal Radiometry cameras (CNPP 19005 compliant) • Definition of up to 20 temperature measurement areas within the field of view of the camera • individual calibration of each temperature measurement area (e.g. emissivity values) • Temperature events when defined temperature thresholds are exceeded • Detection of physical manipulation of the thermal sensor (e.g. sensor covered) • MOBOTIX events via MxMessageSystem • Reporting of temperature data and threshold status of each area via MODBUS/TCP and JSON	4047438044998	cm cm g cm l
	<hr/>		
	Mx-APP-MX-BAR MOBOTIX Barcode Reader App MOBOTIX Barcode Reader App including the following features: • Reader supports more than 40 common 1D, 2D and Stacked barcode types (e.g. QR Code, Data Matrix Code, Dot Code, etc.) • Optimized for difficult barcode reads (e.g. damaged, faded or distorted barcodes, barcodes on difficult surfaces, DPM codes) • Quick reading of one or multiple barcodes in motion • Definition of up to 20 detection areas within the camera's field of view • MOBOTIX events via MxMessageSystem • reporting of barcode reads via generic XML, JSON and MODBUS/TCP	4047438044981	cm cm g cm l
	<hr/>		
	Mx-APP-MX-COR MOBOTIX Color Recognition App MOBOTIX Color Recognition including the following features: • Detection of user-specified color values within customized detection areas • Definition of up to 20 detection areas within the camera's field of view • Supports the recognition of all RGB color values • Set sensitivity, required percentage within the defined detection area and duration of the associated condition • MOBOTIX events via MxMessageSystem	4047438042567	cm cm g cm l
	<hr/>		

**Mx-APP-MX-THD****MOBOTIX Thermal Heat Detection App**

MOBOTIX Thermal Heat Detection App including the following features: • Extension of the temperature measurement functions of MOBOTIX Thermal Radiometry cameras (according to CNPP France 19005 certification) • Definition of up to 20 temperature measurement areas within the field of view of the camera • individual calibration of each temperature measurement area (e.g. emissivity values) • Temperature events when defined temperature thresholds are exceeded • Detection of physical manipulation of the thermal sensor (e.g. sensor covered) • MOBOTIX events via MxMessageSystem • the MOBOTIX Thermal Heat Detection App is required in any case to fulfill the requirements for CNPP France 19005 certification (Thermal Camera Heat Detection Systems)

4047438045087

cm

g

cm

l

**Mx-APP-MX-TVA****MOBOTIX Thermal Validation App**

MOBOTIX Thermal Validation App including the following features: • App optimizes MOBOTIX Thermal Radiometry cameras for use in the fields of waste management and logistics • Enables filtering of vehicles (e.g. construction vehicles and forklifts) as a non-critical source of high temperatures (e.g. by measuring hot body parts such as the exhaust or engine cover) • Extension of the temperature measurement functions of MOBOTIX Thermal Radiometry cameras (CNPP 19005 compliant) • Definition of up to 20 temperature measurement areas within the field of view of the camera • individual calibration of each temperature measurement area (e.g. emissivity values) • Temperature events when defined temperature thresholds are exceeded • Detection of physical manipulation of the thermal sensor (e.g. sensor covered) • MOBOTIX events via MxMessageSystem • Reporting of temperature data and threshold status of each area via MODBUS/TCP and JSON / XML via HTTP(S)

4047438045216

cm

g

cm

cm

l

**Mx-APP-VX-ADR****Vaxtor App License Plate and Dangerous Goods Recognition**

Vaxtor App for License Plate and Dangerous Goods Recognition including the following features: • License plate recognition of one- and two-line license plates • read conventional and dangerous good plates simultaneously • support of latin, hebrew and arabic characters for global application • recognition log (Smart Data / Event Search via MxManagementCenter) • MOBOTIX events via MxMessageSystem • Two lists for individual actions (e.g. access granted/denied, alarm, etc.) • Free flow and trigger mode for LPR/ADR

4047438037815

cm

g

cm

cm

l

**Mx-APP-VX-AIN****Vaxtor Aircraft Identification Number Recognition App**

Vaxtor Aircraft Identification Number Recognition App including the following features: • Recognition of ICAO- and FAA-issued identification numbers • Operations up to a speed of 50 km/h • Real-time results: Aircraft ID, Aircraft Type, Country, etc. • MOBOTIX events via MxMessageSystem • Consolidated event search via MxManagementCenter Smart Data Interface and / or MOBOTIX HUB • meta data transfer through generic transmission protocols and / or pre-defined 3rd party interfaces • Two lists for individual actions (e.g. access granted/denied, alarm, etc.)

4047438040518

cm

g

cm

cm

l

**Mx-APP-VX-CON****Vaxtor App for Cargo Container Code Recognition**

Vaxtor App for Container Code Recognition including the following features: • Recognition of cargo container codes according to ISO 6346 • Real time results: • Container Code • Property Code • Owner • Container Type • Container Dimensions • Control Digit • Control Digit Validation • Recognition log (Smart Data / Event Search via MxManagementCenter) • MOBOTIX events via MxMessageSystem • Two lists for individual actions (e.g. access granted/denied, alarm, etc.) • Free flow and Signaled mode

4047438037938

cm

g

cm

cm

l

	<p>Mx-APP-VX-GEN Vaxtor Generic Optical Character Recognition App Vaxtor Generic Optical Character Recognition App including the following features: • generic optical character recognition to read any combination of uppercase Latin characters and/or numbers • reads characters arranged in up to three lines • user-defined specification of the required code format • recognition log • MOBOTIX events via MxMessageSystem • numerous integration options for further processing of the generated metadata (generic as well as native reporting interfaces) • Two lists for individual actions (e.g. access granted/denied, alarm, etc.) • Free flow and Signaled mode</p>	4047438042543	cm cm cm l
	<p>Mx-APP-VX-LPR Vaxtor License Plate Recognition App Vaxtor License Plate Recognition App including the following features: • License plate recognition of one- and two-line license plates • Recognition log • MOBOTIX events via MxMessageSystem • Global country coverage</p>	4047438037358	cm cm cm l
	<p>Mx-APP-VX-LPR-M Vaxtor License Plate Recognition App (multi-lens) Vaxtor License Plate Recognition App (multi-lens application) for S74 with two optical sensor modules including the following features: • License plate recognition of one- and two-line license plates • simultaneous recognition on both image sensors • monitoring the dwell time of license plates in the detection area • support of latin, hebrew and arabic characters for global application • Recognition log • MOBOTIX events via MxMessageSystem • Two lists for individual actions (e.g. access granted/denied, alarm, etc.) • Free flow and Signaled mode</p>	4047438040402	cm cm cm l
	<p>Mx-APP-VX-MMC Vaxtor License Plate Recognition App incl. Vehicle Make, Vaxtor License Plate Recognition App including the following features: • License plate recognition of one- and two-line license plates • support of latin, hebrew and arabic characters for global application • Additional recognition of vehicle make, model, color and class • Recognition log (Smart Data / Event Search via MxManagementCenter) • MOBOTIX events via MxMessageSystem • Two lists for individual actions (e.g. access granted/denied, alarm, etc.) • Free flow and Signaled mode</p>	4047438038324	cm cm cm l
	<p>Mx-APP-VX-UIC Vaxtor App for UIC Railway Code Recognition Vaxtor App for UIC Railway Code Recognition including the following features: • Recognition of the International Union of Railways Wagon and Coach numbers (UIC Codes) • Real time results: UIC Code, Country Code, Vehicle Type, Control Digit, Direction of travel • Stop / Go and slow speed (<10 km/h) applications (depending on installation and module selection) • MOBOTIX events via MxMessageSystem • Consolidated event search via MxManagementCenter Smart Data Interface and / or MOBOTIX HUB • meta data transfer through generic transmission protocols and / or pre-defined 3rd party interfaces • Two lists for individual actions (e.g. access granted/denied, alarm, etc.) • Free flow and Signaled mode</p>	4047438040266	cm cm cm l
	<p>Mx-APP-VX-USD Vaxtor USDOT Number Recognition App Vaxtor USDOT Number Recognition App including the following features: • Recognition of USDOT identification numbers • Operations up to a vehicle speed of 50 km/h • MOBOTIX events via MxMessageSystem • Consolidated event search via MxManagementCenter Smart Data Interface and / or MOBOTIX HUB • meta data transfer through generic transmission protocols and / or pre-defined 3rd party interfaces • Two lists for individual actions (e.g. access granted/denied, alarm, etc.) • Free flow and Signaled operation mode</p>	4047438041638	cm cm cm l

Desktop Apps

	Article No. / Name / Description	EAN / HS / weight	dimen.
	<p>Mx-SW-MC-QNAP</p> <p>QNAP QVR Pro license for activation of MxMC Playback</p> <p>Enables MxMC playback support in the QVR Pro recording software on a QNAP NAS with QTS operating system. • Supports MxMC playback from ONVIF cameras such as the MOVE camera series. • Optimal combination on a QNAP NAS • IOT cameras store independently on the NAS via file sharing (SMB) and record the integrated MOVE or ONVIF cameras in parallel with the QVR Pro Recording Software. The output is done with the MxMC. • The license is activated on the QNAP NAS via the QNAP License Manager. • License is not transferable • one license per QNAP NAS with QVR Pro is required! • For camera recordings, QNAP requires additional camera channel licenses per channel, which must be obtained from QNAP!</p>	4047438047791	cm cm g cm l
	<p>Mx-SW-MC-Th-DB-Bas</p> <p>MOBOTIX MxMC Feature - ThermalDashboard Base License</p> <p>Activates the MOBOTIX Thermal Dashboard in the MxMC and supports the MOBOTIX Thermal Camera functions • Main applications are: • Live monitoring and surveillance of temperature-critical processes • Subsequent analysis of the temperature curve • Supports MOBOTIX Thermal Cameras P3, P6 and P7 • Restriction of the P3 to temperature graphs no hot spot areas • License is activated via the MOBOTIX License Portal. • License is not transferable • One license per MxMC is required. • With one license, thermal graphs from 4 thermal cameras can be integrated in the layout • Additional thermal cameras require one MOBOTIX MxMC Device license per camera - Permanent license</p>	4047438048217	cm cm g cm l
	<p>Mx-SW-MC-Th-DB-Dev</p> <p>MOBOTIX MxMC Feature - ThermalDashboard Device</p> <p>Activates another camera in the MOBOTIX Thermal Dashboard in the MxMC and supports the MOBOTIX Thermal Camera functions • Supports MOBOTIX Thermal Cameras P3, P6 and P7 • Restriction of the P3 to temperature graphs no hot spot areas • License is activated via the MOBOTIX License Portal. • License is not transferable • One license per MxMC is required. • Requires a MOBOTIX Thermal Dashboard Base license • With one license, thermal graphs from 4 thermal cameras can be integrated in the layout • Additional thermal cameras require one MOBOTIX Device license per camera - Permanent license</p>	4047438048224	cm cm g cm l
	<p>Mx-SW-XPro-CLOUD-Bas</p> <p>MOBOTIX HUB Plug In - MOBOTIX CLOUD Base License for</p> <p>Activates the MOBOTIX CLOUD support in Milestone XProtect • Main application features in the Smart Client are • Integrating cloud cameras in the desk client layout • Additional CLOUD tab in the application • License is activated via the MOBOTIX License Portal. • License is not transferable • One license per Milestone XProtect VMS is required. • 4 cameras are included in the Base license • Additional cameras require a device licence per camera • Permanent License</p>	4047438047876	cm cm g cm l
	<p>Mx-SW-XPro-CLOUD-Dev</p> <p>MOBOTIX HUB Plug In - MOBOTIX CLOUD Device License for</p> <p>Activates another camera in the MOBOTIX CLOUD support in Milestone XProtect • License is activated via the MOBOTIX License Portal. • License is not transferable • One license per Milestone XProtect VMS is required. • Requires a MOBOTIX CLOUD Base license • 4 cameras are included in the Base license • Additional cameras require a device licence per camera • Permanent License</p>	4047438048125	cm cm g cm l

	<p>Mx-SW-XPro-Config</p> <p>MOBOTIX HUB Plug In - MOBOTIX camera Configuration for</p> <p>Activates the configuration settings for MOBOTIX cameras in Milestone XProtect - Management Client offers camera specific configuration tabs for P3/P6/P7 and MOVE cameras - License is activated via the MOBOTIX License Portal. - License is non-transferable - One license per Milestone • Activates the function for all MOBOTIX cameras registered in the system.</p>	4047438047890	cm cm g cm l
	<p>Mx-SW-XPro-ForSe</p> <p>MOBOTIX HUB Plug In - ForensicSearch for Milestone</p> <p>Activates the MOBOTIX ForensicSearch filters in Milestone XProtect Smart Client and supports the MOBOTIX event and app meta data for the forensic search - Intelligent search filter reduces the search in the playback to the essential - Search filter for camera apps as well as for MOBOTIX events - Support for camera models P6 / P7 and MOVE LPR models - License is activated via the MOBOTIX License Portal. - License is not transferable - One license per Milestone XProtect VMS is required. - Activates the function for all MOBOTIX cameras registered in the system.</p>	4047438047913	cm cm g cm l
	<p>Mx-SW-XPro-Nurse-DB-Bas</p> <p>MOBOTIX HUB Plug In - NurseAssist Dashboard Base License</p> <p>Activates the MOBOTIX NurseAssist Dashboard in Milestone XProtect and supports the MOBOTIX C71 NurseAssist Camera functions • Main applications are • Live monitoring of patient conditions such as fall detection in a dashboard as a status tableau • Patient information • Virtual Patrol • Live image activation with intercom support • Slider too blurred the live image • Activity Log Book • Activity report for statistical analysis • Supports MOBOTIX C71 NurseAssist Kameras • License is activated via the MOBOTIX License Portal. • License is not transferable • One license per Milestone XProtect VMS is required. • With one license, Status Tableau from 4 NurseAssist cameras can be integrated in the layout • Additional NurseAssist cameras require one MOBOTIX Device license per camera - Permanent license</p>	4047438049306	cm cm g cm l
	<p>Mx-SW-XPro-Nurse-DB-Dev</p> <p>MOBOTIX HUB Plug In - NurseAssist Dashboard Device</p> <p>Activates an additional camera for the MOBOTIX NurseAssist Dashboard in Milestone XProtect • Supports MOBOTIX C71 NurseAssist camera functions • Main application areas are • Live monitoring of patient conditions such as Fall detection in a dashboard as a status tableau • Patient information • Virtual tour • Live image activation with intercom support • Slider for live image blurring • Activity log book • Activity report for statistical evaluation • Supports MOBOTIX C71 NurseAssist cameras • Licence is activated via the MOBOTIX licence portal. • Licence is not transferable • One licence per NurseAssist camera required. • Requires a MOBOTIX NurseAssist Dashboard Base licence • With a MOBOTIX NurseAssist Dashboard Base licence, 4 NurseAssist cameras can be integrated in the Status Tableau • Additional NurseAssist cameras require a MOBOTIX Device licence per camera • Permanent licence</p>	4047438049320	cm cm g cm l
	<p>Mx-SW-XPro-SYNC-DB-Bas</p> <p>MOBOTIX HUB Plug In - MOBOTIX SYNC Base License for</p> <p>Activates the MOBOTIX SYNC Dashboard in Milestone XProtect Smart Client • Main applications are - Display of statistical values in diagrams • Display of lists of detected number plates • Support for MOBOTIX SYNC and Helix Vaxtor • License is activated via the MOBOTIX License Portal. • License is non-transferable • One license per Milestone XProtect VMS is required. • With one licence, 4 Grafana dashboards can be integrated in the layout • Additional Grafana dashboards require a MOBOTIX Sync Device license per dashboard. • Permanent licence</p>	4047438047852	cm cm g cm l

	<p>Mx-SW-XPro-SYNC-DB-Dev</p> <p>MOBOTIX HUB Plug In - MOBOTIX SYNC Device License for</p> <p>Activates another MOBOTIX SYNC Grafana Dashboard in the Milestone XProtect Smart Client. • License is activated via the MOBOTIX License Portal. • License is non-transferable. • One license per Milestone XProtect VMS is required. • Requires a MOBOTIX SYNC Base license • With one licence, 4 Grafana dashboards can be integrated in the layout • Additional Grafana dashboards require a MOBOTIX Sync Device license per dashboard. • Permanent licence</p>	4047438048101	cm
		g	cm
			l
	<p>Mx-SW-XPro-Th-DB-Bas</p> <p>MOBOTIX HUB Plug In - ThermalDashboard Base License for</p> <p>Activates the MOBOTIX Thermal Dashboard in Milestone XProtect and supports the MOBOTIX Thermal Camera functions • Main applications are • Live monitoring and surveillance of temperature-critical processes • Subsequent analysis of the temperature curve • Supports MOBOTIX Thermal Cameras P3, P6 and P7 • Restriction of the P3 to temperature graphs no hot spot areas • License is activated via the MOBOTIX License Portal. • License is not transferable • One license per Milestone XProtect VMS is required. • With one license, thermal graphs from 4 thermal cameras can be integrated in the layout • Additional thermal cameras require one MOBOTIX Device license per camera - Permanent license</p>	4047438047838	cm
		g	cm
			l
	<p>Mx-SW-XPro-Th-DB-Dev</p> <p>MOBOTIX HUB Plug In - ThermalDashboard Device License</p> <p>Activates another camera in the MOBOTIX Thermal Dashboard in Milestone XProtect and supports the MOBOTIX Thermal Camera functions • Supports MOBOTIX Thermal Cameras P3, P6 and P7 • Restriction of the P3 to temperature graphs no hot spot areas • License is activated via the MOBOTIX License Portal. • License is not transferable • One license per Milestone XProtect VMS is required. • Requires a MOBOTIX Thermal Dashboard Base license • With one license, thermal graphs from 4 thermal cameras can be integrated in the layout • Additional thermal cameras require one MOBOTIX Device license per camera - Permanent license</p>	4047438048088	cm
		g	cm
			l
	<p>Mx-SYNC-S-BAS</p> <p>MOBOTIX SYNC Server</p> <p>Store metadata and attached images generated by MOBOTIX Certified Apps (e.g. Vaxtor ALPR / OCR Apps) or other compatible data sources • 4 camera device licenses included • additional camera device licenses via additional license on demand • Monitor incoming license plates / metadata (e.g. plate reads) in real time • Search and filter existing license plates / metadata based on content such as Plate, Country, Camera, Zone, Make, Model, Color, Direction, etc. • Download and export customized license plate lists and search results • Management of cameras includes: • camera zones • manage and synchronize denied & granted license plate list • assign actuators (incl. camera I/Os) • manage data retention policies separately for images and metadata • supports GDPR measures with dedicated reports and data deletion • granular user and group permissions • login management including LDAP integration • audit trail of all interactions on the system including actions made by cameras • Send notifications (e.g. via E-Mail) • SYNC server license with runtime of 3 years after activation</p>	4047438047548	cm
		g	cm
			l
	<p>Mx-SYNC-S-DEV</p> <p>MOBOTIX SYNC Camera Device License</p> <p>1 camera device license per additional camera device • Enables adding camera devices to the server/client on demand • *4 camera device licenses included in the server base license</p>	4047438047562	cm
		g	cm
			l

**Mx-SYNC-S-CLI**

4047438047579

cm

MOBOTIX SYNC Client

Redundant operation and data storage for applications with discontinuous connection to the server (e.g. mobile applications) • active server connection enables continuous data synchronization

g

cm

cm
l**Mx-SYNC-P-GRA**

4047438047593

cm

MOBOTIX SYNC Grafana Plug-In

Visualization and consolidation of incoming metadata in customized dashboards including: • statistic insights • data queries • annotations • create and manage alerts / post-actions • exports




g

cm

cm
l

Warranty Extensions

Warranty Extensions

	Article No. / Name / Description	EAN / HS / weight	dimen.
	Mx-WE-DTVS-1 1 Year Warranty Extension For Dual Thermal Systems S74 5+1 Years warranty for MOBOTIX 7 and Mx6 Dual Thermal video systems • Notes: The warranty extension applies to a S74 or S16 DualFlex with two attached thermal sensor modules. The warranty extension can only be granted if the serial numbers of the camera and the connected thermal sensor modules are forwarded to MOBOTIX.	4047438031974 g	cm cm cm l
	Mx-WE-DTVS-2 2 Years Warranty Extension For Dual Thermal Systems S74 5+2 Years warranty for MOBOTIX 7 and Mx6 Dual Thermal video systems • Notes: The warranty extension applies to a S74 or S16 DualFlex with two attached thermal sensor modules. The warranty extension can only be granted if the serial numbers of the camera and the connected thermal sensor modules are forwarded to MOBOTIX.	4047438031981 g	cm cm cm l
	Mx-WE-DTVS-3 3 Years Warranty Extension For Dual Thermal Systems S74 5+3 Years warranty for MOBOTIX 7 and Mx6 Dual Thermal video systems • Notes: The warranty extension applies to a S74 or S16 DualFlex with two attached thermal sensor modules. The warranty extension can only be granted if the serial numbers of the camera and the connected thermal sensor modules are forwarded to MOBOTIX.	4047438031998 g	cm cm cm l
	Mx-WE-IVS-1 1 Year Warranty Extension For Indoor Video Systems 5+1 Years Warranty For Indoor Video Systems (MOBOTIX 7, Mx6 Indoor series, MxThinClient, MxSwitch) • Note: The warranty can be granted only if the serial number of the product is provided to MOBOTIX.	4047438031820 g	cm cm cm l
	Mx-WE-IVS-2 2 Years Warranty Extension For Indoor Video Systems 5+2 Years Warranty For Indoor Video Systems (MOBOTIX 7, Mx6 Indoor series, MxThinClient, MxSwitch) • Note: The warranty can be granted only if the serial number of the product is provided to MOBOTIX.	4047438031837 g	cm cm cm l



Mx-WE-IVS-3

3 Years Warranty Extension For Indoor Video Systems

5+3 Years Warranty For Indoor Video Systems (MOBOTIX 7, Mx6 Indoor series, MxThinClient, MxSwitch) • Note: The warranty can be granted only if the serial number of the product is provided to MOBOTIX.

4047438031844

g

cm
cm
cm
l



Mx-WE-OVS-1

1 Year Warranty Extension For Outdoor Video Systems

5+1 Year Warranty For Outdoor Video Systems (MOBOTIX 7, Mx6 Outdoor series, MxDisplay) • Note: The warranty can be granted only if the serial number of the product is provided to MOBOTIX.

4047438031875

g

cm
cm
cm
l



Mx-WE-OVS-2

2 Years Warranty Extension For Outdoor Video Systems

5+2 Years Warranty For Outdoor Video Systems (MOBOTIX 7, Mx6 Outdoor series, MxDisplay) • Note: The warranty can be granted only if the serial number of the product is provided to MOBOTIX.

4047438031882

g

cm
cm
cm
l



Mx-WE-OVS-3

3 Years Warranty Extension For Outdoor Video Systems

5+3 Years Warranty For Outdoor Video Systems (MOBOTIX 7, Mx6 Outdoor series, MxDisplay) • Note: The warranty can be granted only if the serial number of the product is provided to MOBOTIX.

4047438031899

g

cm
cm
cm
l



Mx-WE-STVS-1

1 Year Warranty Extension For Single Thermal Systems

5+1 Years warranty for MOBOTIX 7 and Mx6 thermal video systems • Notes: The warranty extension covers a S74 or S16 DualFlex with a maximum of one connected thermal sensor module or an M73 or M16 Thermal / Thermal TR. The warranty extension includes an additional optical sensor module used with the camera, but can only be granted if the serial numbers of the camera and the connected modules are passed to MOBOTIX.

4047438031929

g

cm
cm
cm
l



Mx-WE-STVS-2

2 Years Warranty Extension For Single Thermal Systems

5+2 Years warranty for MOBOTIX 7 and Mx6 thermal video systems • Notes: The warranty extension covers a S74 or S16 DualFlex with a maximum of one connected thermal sensor module or an M73 or M16 Thermal / Thermal TR. The warranty extension includes an additional optical sensor module used with the camera, but can only be granted if the serial numbers of the camera and the connected modules are passed to MOBOTIX.

4047438031936

g

cm
cm
cm
l



Mx-WE-STVS-3

3 Years Warranty Extension For Single Thermal Systems

5+3 Years warranty for MOBOTIX 7 and Mx6 thermal video systems • Notes: The warranty extension covers a S74 or S16 DualFlex with a maximum of one connected thermal sensor module or an M73 or M16 Thermal / Thermal TR. The warranty extension includes an additional optical sensor module used with the camera, but can only be granted if the serial numbers of the camera and the connected modules are passed to MOBOTIX.

4047438031943

g

cm

cm

cm

l

Other

BeyondHumanVision

MOBOTIX

Professional Services

	Article No. / Name / Description	EAN / HS / weight	dimen.
	Password-Reset-Software Professional Services Password Reset Software This password reset is an encrypted, time limited (will expire after 30 days) software file, specific for the factory IP of the camera directly on-site at your customers location.	4047438035392	cm cm g cm l
	PS-Field-Service-Day Professional Services Field Engineering & On-Site Support, Available for MOBOTIX systems of any size and for all MOBOTIX hardware and software products; fixed price flat rate for one working day. • Field Engineering: System configuration, commissioning and user training directly on site. Complete configuration and customization. • On-site Support: One working day for on-site support and troubleshooting directly at the project site. Professional health and storage check, troubleshooting through reconfiguration and re-configuration, on-site user training.	4047438035347	cm cm g cm l
	PS-Field-Service-Day-100 Professional Services Onsite Field Engineering / Project Onsite Field Engineering / Project Commissioning for projects of over 100+ MOBOTIX cameras (excludes travel costs)	4047438048149	cm cm g cm l
	PS-Field-Service-Half-Day Professional Services Field Engineering & On-Site Support, Available for MOBOTIX systems of any size and for all MOBOTIX hardware and software products; fixed price flat rate for half a working day. • Field Engineering: System configuration, commissioning and user training directly on site. Complete configuration and customization. • On-site Support: One working day for on-site support and troubleshooting directly at the project site. Professional health and storage check, troubleshooting through reconfiguration and re-configuration, on-site user training.	4047438035354	cm cm g cm l
	PS-PreConfig-9plus1free Professional Services Every 10th Pre-Configuration per PO Every 10th Pre-Configuration per PO is free (Buy 9 get 1 Free)	4047438048163	cm cm g cm l

	<p>PS-PreConfig-IoT Professional Services Pre-Configuration per IoT-Camera Pre-Configuration of all MOBOTIX IoT Cameras incl. Function Guarantee direct from production</p>	4047438035316	cm cm cm l
	<p>PS-PreConfig-IoT-Doorstation Professional Services Pre-Configuration per Doorstation Pre-Configuration of all MOBOTIX DoorStations incl. Function Guarantee direct from production</p>	4047438035323	cm cm cm l
	<p>PS-PreConfig-MxMove Professional Services Pre-Configuration per MOVE-Camera Pre-Configuration of all MOBOTIX MOVE Cameras incl. Function Guarantee direct from production</p>	4047438035330	cm cm cm l
	<p>PS-Remote-Service-Half-Hour Professional Services Remote Support Half-Hourly Rate Half Hour professional troubleshooting, rectification and system optimization via secure IP remote connection by MOBOTIX specialists</p>	4047438035385	cm cm cm l
	<p>PS-Remote-Service-Hour Professional Services Remote Support Hourly Rate One Hour professional troubleshooting, rectification and system optimization via secure IP remote connection by MOBOTIX specialists</p>	4047438035378	cm cm cm l
	<p>PS-Remote-Support-Opt Professional Services Remote Support System Optimization Remote Support System Optimization • 1 hr Remote Support free for every 20 Pre-Configurations per PO</p>	4047438048156	cm cm cm l

**PS-Travelcost**

4047438035361

cm

Professional Services Travel & Accommodation Costs

cm

Costs for travel expenses of the MOBOTIX specialist. Maximum 2000€.

g

cm

l

**PS-Travelcost-plus**

4047438048170

cm

Professional Services Increased Travel & Accommodation

cm

Increase the maximum chargeable for travel costs to €3000

g

cm

l