

GKB 5008 Analog Camera

Weatherproof High Resolution Analog Camera with Infrared and board lens

GKB 5008 is an analog camera for use in outdoor surveillance systems. With 3-Axis bracket, GKB 5008 features easy installation and flexible adjustment for preferred angles.

Features:

- **Built-in Infrared**

Infrared sensors inside the camera's housing provide the ability to capture images during night and low-light conditions.

- **Weatherproof Housing**

Weatherproof housing allows GKB 5008 to be installed in most applications and environments, including in summer, winter, sunny day or rainy day; making it an ideal camera for outdoor surveillance.

- **3-Axis Bracket**

3-Axis bracket smart design features easy installation and flexible adjustment for preferred angles which allows a rotation of 180° vertically and 360° horizontally.

- **Separated Protective Glass**

GKB 5008 features separated protective glass which avoid LED light reflection problem or image gone blur.



Alternate Views



GKB 5008 Analog Camera

Video	Image Sensor	1/3" Sony CCD
	Total Number of Pixels	NTSC: 811(H) * 508(V) / PAL: 795(H) * 596(V)
	Number of Effective Pixels	NTSC: 768(H) * 494(V) / PAL: 752(H) * 582(V)
	Resolution	550 TV Lines
	Min. Illumination	0.3 Lux, F1.2
	Gamma	0.45
	S/N Ratio	>48 dB
	Sync. Mode	Internal Sync
	Scanning System	2:1 Interlace
	Horizontal Sync. Frequency	NTSC: 15.734 KHz / PAL: 15.625 KHz
	Shutter Control	NTSC: 1/60 ~ 1/100,000 sec / PAL: 1/50 ~ 1/100,000 sec
	BNC Video Output	1.0Vp-p.75ohm
	Night Mode	Auto
	Auto Electronics Shutter	ON-OFF
	Auto Gain Control	ON-OFF
	Back Light Compensation	ON-OFF
	White Balance	ATW
Infrared LED	Quantity	28
	Peak Wavelength	850 mm
	Radiant Distance	20 meter
Power	Power Supply	12V DC
	Power Consumption	4.2 W
Lens	6 mm board lens (standard); 4mm/ 8 mm board lens (optional)	
Dimension	118 (L) * 78 (Ø) mm	
Weight	0.3 kg	
Ingress Protection Rating	IP66	
Operating Temperature	-10°C ~ 60°C	

Dimensions

